

**ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT  
EQUIPMENT AND PROCUREMENT DIVISION  
BID INVITATION**

Bid Number:                     M-12-020A                    

**BID OPENING LOCATION:**  
AHTD Equipment &  
Procurement Division  
11302 West Baseline Road  
Little Rock, AR 72209

**MAIL TO:**  
AHTD Equipment and  
Procurement Div.  
P.O. Box 2261  
Little Rock, AR 72203

**DELIVER TO:**  
AHTD Equipment &  
Procurement Division  
11302 West Baseline Road  
Little Rock, AR 72209

Bid Opening Date: September 7, 2011 Time: 11:00 a.m.

Sealed bids for furnishing the commodities and/or services described below, subject to the Conditions on Page 2 of This Bid Invitation will be received at the above-noted mail and delivery locations until the above-noted bid opening date and time, and then publicly opened at the above-noted bid opening location. **Bids must be submitted on this form, with attachments when appropriate, or bids will be rejected. Late bids and unsigned bids will not be considered.**

In compliance with this Bid Invitation and subject to all the Conditions thereof, the undersigned offers and agrees to furnish any and all items upon which prices are quoted, at the price set opposite each item.

Company Name: \_\_\_\_\_

Name (Type or Print): \_\_\_\_\_

Address: \_\_\_\_\_

Title: \_\_\_\_\_

Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_

E-mail Address: \_\_\_\_\_

Federal Tax ID or Social Security No.: \_\_\_\_\_

**Signature:** \_\_\_\_\_

Signature must be original (not photocopied) and in ink. Unsigned bids will be rejected.

Item No.	Description	Quantity	Unit	Unit Price	Amount
1.	Four Post Surface Mounted Car And Truck Lift, 30,000 Pounds Capacity. 235" W/B Capacity. 36' Overall Length.	1	ea		
2.	Four Post Surface Mounted Car And Truck Lift, 30,000 Pounds Capacity. 271" W/B Capacity. 39' Overall Length.	1	ea		
<p>To meet the requirements of Arkansas State Highway and Transportation Department Specifications attached to and made a part of this bid.            FOB: AHTD – 808 Frontier Rd., Barling, AR                      Attn: John Sharum (479) 452-1301</p> <p>1. Car and Truck Lift proposed to furnish:            Brand _____ No. _____</p> <p>2. Car and Truck Lift proposed to furnish:            Brand _____ No. _____</p> <p>If any literature and/or specifications of items conflict with AHTD specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.</p> <p><b>Bid Bond</b> in the amount of 5% of total bid price required of all bidders at time of bid opening or bid will be rejected. <b><u>Personal and company checks are not acceptable as Bid Bonds.</u></b> See Condition 3 on page 2 of bid invitation.</p> <p><b>Performance Bond</b> in the amount of 5% of total bid price will be required of successful bidder prior to providing goods/services. <b><u>Personal and company checks are not acceptable as Performance Bonds.</u></b> See Condition 3 page 2 of bid invitation.</p> <p>The successful bidder will be required to complete delivery within 30 days after award.</p> <p>Bids and Specifications are available on-line by going to the AHTD Web Site – <a href="http://www.arkansashighways.com">www.arkansashighways.com</a> and clicking on “Commodities and Services Bids/Contracts Information”. Tabulations will also be available at this site within 72 hours after bid opening. If you have any questions, call this office at 501-569-2667.</p> <p>(34-0290)    26-06</p>					
				TOTAL BID	

## STANDARD BID CONDITIONS

M-12-020A

1. **ACCEPTANCE AND REJECTION:** The Arkansas State Highway and Transportation Department (AHTD) reserves the right to reject any or all bids, to accept bids in whole or in part (unless otherwise indicated by bidder), to waive any informalities in bids received, to accept bids on materials or equipment with variations from specifications where efficiency of operation will not be impaired, and to award bids to best serve the interest of the State.
2. **PRICES:** Unless otherwise stated in the Bid Invitation, the following will apply: (1) unit prices shall be bid, (2) prices should be stated in units of quantity specified (feet, each, lbs., etc.), (3) prices must be F.O.B. destination specified in bid, (4) prices must be firm and not subject to escalation, (5) bid must be firm for acceptance for 30 days from bid opening date. In case of errors in extension, unit prices shall govern. Discounts from bid price will not be considered in making awards.
3. **BID BONDS AND PERFORMANCE BONDS:** If required, a **Bid Bond** in the form of a cashier's check, certified check, or surety bond issued by a surety company, in an amount stated in the Bid Invitation, must accompany bid. **Personal and company checks are not acceptable as Bid Bonds.** Failure to submit a Bid Bond as required will cause a bid to be rejected. The Bid Bond will be forfeited as liquidated damages if the successful bidder fails to provide a required Performance Bond within the period stipulated by AHTD or fails to honor their bid. Cashier's checks and certified checks submitted as Bid Bonds will be returned to unsuccessful bidders; surety bonds will be retained. The successful bidder will be required to furnish a **Performance Bond** in an amount stated in the Bid Invitation and in the form of a cashier's check, certified check, or surety bond issued by a surety company, unless otherwise stated in the Bid Invitation, as a guarantee of delivery of goods/services in accordance with the specifications and within the time established in the bid. **Personal and company checks are not acceptable as Performance Bonds.** In some cases, a cashier's check or certified check submitted as a Bid Bond will be held as the Performance Bond of the successful bidder. Cashier's checks or certified checks submitted as Performance Bonds will be refunded shortly after payment has been made to the successful bidder for completion of all terms of the bid; surety bonds will be retained. Surety bonds must be issued by a surety company authorized to do business in Arkansas, and must be signed by a Resident Local Agent licensed by the Arkansas State Insurance Commissioner to represent that surety company. Resident Agent's Power-of-Attorney must accompany the surety bond. Certain bids involving labor will require Performance Bonds in the form of surety bonds only (no checks of any kind allowed). In such cases, the company issuing the surety bond must comply with all stipulations herein and must be named in the U. S. Treasury listing of companies holding Certificates of Authority as acceptable sureties on Federal Bonds and as acceptable reinsuring companies. Any excess between the face amount of the bond and the underwriting limitation of the bonding company shall be protected by reinsurance provided by an acceptable reinsuring company. Annual Bid and Performance Bonds on file with E & P Division must have sufficient unencumbered funds to meet current bonding requirements, or the bid will be rejected, unless the balance is submitted as set forth above, prior to bid opening.
4. **TAXES:** The AHTD is not exempt from Arkansas State Sales and Use Taxes, or local option city/county sales taxes, when applicable, and bidders are responsible to the State Revenue Department for such taxes. These taxes should not be included in bid prices, but where required by law, will be paid by the AHTD as an addition thereto, and should be added to the billing to the AHTD. The AHTD is exempt from Federal Excise Taxes on all commodities except motor fuels; and excise taxes should not be included in bid prices except for motor fuels. Where applicable, tax exemption certificates will be furnished by the AHTD.
5. **"ALL OR NONE" BIDS:** Bidders who wish to bid "All or None" on two or more items shall so stipulate on the face of bid sheet; otherwise, bid may be awarded on an individual item basis.
6. **SPECIFICATIONS:** Complete specifications should be attached for any substitution or alternate offered, or where amplification is necessary. Bidder's name must be placed on all attachments to the bid.
7. **EXCEPTIONS TO SPECIFICATIONS:** Any exceptions to the bid specifications must be stated in the bid. Any exceptions to manufacturer's published literature must be stated in the bid, or it will be assumed that bidder is bidding exactly as stated in the literature.
8. **BRAND NAME REFERENCES:** All brand name references in bid specifications refer to that commodity or its equivalent, unless otherwise stated in Bid Invitation. Bidder should state brand or trade name of item being bid, if such name exists.
9. **FREIGHT:** All freight charges should be included in bid price. Any change in common carrier rates authorized by the Interstate Commerce Commission will be adjusted if such change occurs after the bid opening date. Receipted common carrier bills that reflect ICC authorized rate changes must be furnished.
10. **SAMPLES, LITERATURE, DEMONSTRATIONS:** Samples and technical literature must be provided free of any charge within 14 days of AHTD request, and free demonstrations within 30 days, unless AHTD extends time. Failure to provide as requested within this period may cause bid to be rejected. Samples, literature and demonstrations must be substantially the same as the item(s) being bid, unless otherwise agreed to by AHTD. Samples that are not destroyed will be returned upon request at bidders expense. Samples from successful bidders may be retained for comparison with items actually furnished.
11. **GUARANTY:** Unless otherwise indicated in Bid Invitation, it is understood and agreed that any item offered or shipped on this bid shall be newly manufactured, latest model and design, and in first class condition; and that all containers shall be new, suitable for storage or shipment and in compliance with all applicable laws relating to construction, packaging, labeling and registration.
12. **BACKORDERS OR DELAY IN DELIVERY:** Backorders or failure to deliver within the time required may constitute default. Vendor must give written notice to the AHTD, as soon as possible, of the reason for any delay and the expected delivery date. The AHTD has the right to extend delivery if reasons appear valid. If reason or delivery date is not acceptable, vendor is in default.
13. **DEFAULT:** All commodities furnished will be subject to inspection and acceptance by AHTD after delivery. Default in promised delivery or failure to meet specifications authorizes the AHTD to cancel award or any portion of same, to reasonably purchase commodities or services elsewhere and to charge full increase, if any, in cost and handling to defaulting vendor. Applicable bonds may be forfeited.
14. **ETHICS:** *"It shall be a breach of ethical standards for a person to be retained, or to retain a person, to solicit or secure a State contract upon an agreement of understanding for a commission, percentage, brokerage, or contingent fee, except for retention of bona fide employees or bona fide established commercial selling agencies maintained by the contractor for the purpose of securing business."* (Arkansas Code, Annotated, Section 19-11-708).

**ARKANSAS STATE HIGHWAY  
AND TRANSPORTATION DEPARTMENT**

**NOTICE OF NONDISCRIMINATION**

The Arkansas State Highway and Transportation (Department) complies with the Americans with Disabilities Act of 1990, Section 504 of the Rehabilitation Act of 1973, Title VI of the Civil Rights Act of 1964 and other federal equal opportunity laws and therefore does not discriminate on the basis of race, sex, color, age, national origin, religion or disability, in admission or access to and treatment in Department programs and activities, as well as the Department's hiring or employment practices. Complaints of alleged discrimination and inquiries regarding the Department's nondiscrimination policies may be directed to James B. Moore, Jr., Section Head - EEO/DBE (ADA/504/Title VI Coordinator), P. O. Box 2261, Little Rock, AR 72203, (501) 569-2298, (Voice/TTY 711), or the following email address: [james.moore@arkansashighways.com](mailto:james.moore@arkansashighways.com).

This notice is available from the ADA/504/Title VI Coordinator in large print, on audiotape and in Braille.

**ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT**

**SPECIFICATION 12-271-34-0290**

**FOR**

**FOUR POST SURFACE MOUNTED CAR AND TRUCK LIFT**

**30,000 POUNDS CAPACITY (271" WHEELBASE)**

**WITH DRIVE-THROUGH APPROACH RAMPS**

**AND**

**TWO ROLLING JACKS**

1. **General:** Heavy duty four post surface mounted lift with drive on type runways. Shall be electric-hydraulic operated and have a minimum capacity of 30,000 pounds. Shall be designed to accommodate passenger cars, light trucks and heavy trucks, including tandem axle dump trucks. Shall comply with applicable ANSI regulations.
2. **Lifting Columns:** Four (4) steel columns equipped with adjustable cables, chains and sheaves or direct drive pistons for lift synchronization.
  - A. **Lift Height (Rise):** 60", minimum.
  - B. **Overall Width:** 12', minimum.
  - C. **Width Inside Columns:** 10' 5", minimum.
3. **Mechanical Locks:** Each column shall be equipped with a ladder type mechanical locking system that automatically latches at intervals as the lift is raised. The locks shall be released by means of air or hydraulic cylinders with one (1) cylinder activating each lock (total of four (4) cylinders). The lock release cylinders shall be activated by a single point lock release located on the lift control panel.
4. **Runways and Approach Ramps:** Shall have two (2) runways with approach ramps located on each end to allow drive-through operation. Approach ramps shall be hinged so that they automatically swing down when the lift is raised to provide wheel chocks. Design of approach ramps shall offer a low approach angle to allow for low ground clearance of passenger cars. Runways and approach ramps shall have an oil resistant non-skid coating. Runways and approach ramps shall be adjustable to match vehicle tread width. A minimum of four (4) portable wheel chocks shall be supplied with lift.
  - A. **Width:** Runways and approach ramps shall have a minimum width of 24".
  - B. **Wheelbase Capacity:** Length of runways shall be sufficient to accommodate wheelbases up to at least 271".
  - C. **Approach Ramp Length:** Each approach ramp shall have a minimum length of 36".
  - D. **Runway Height:** Each runway shall have a minimum height of 8".
  - E. **Overall Length:** Overall length of runways, including approach ramps, shall not exceed 39".
  - F. **Tread Width Adjustment:** When adjusted to minimum width, the distance between the inside edges of the runways shall not exceed 41". When adjusted to maximum width, the outside to outside measurement of the runways shall be no less than 96".
5. **Power Unit:** Lift shall be powered by an electric-hydraulic power unit. Electric motor for power unit shall be rated at no less than 2 horsepower and operate on 220 volt, single phase, 60 cycle current. All operating controls shall be included.
6. **Rolling Jacks:** Lift shall be equipped with two (2) rolling jacks to serve as a stable foundation for raising wheels off the runways. Each jack shall have a minimum capacity of 8,000 pounds. The jacks shall be mounted to the inside of the runways and be capable of moving from one end of the runways to the other end for positioning under pickup points. Shall be designed to adjust to different widths as the track width of the runways is changed. The jacks shall be air over hydraulic or electric-hydraulic operated. Auxiliary adapters shall be furnished with each jack to provide versatility in load lifting.

7. Warranty: Units purchased under this specification shall be warranted against defects in material and workmanship for a minimum period of twelve (12) months (365 days) from date unit is placed in operation by AHTD.
  - A. Warranty shall include all parts, labor and transportation costs to the location of equipment.
  - B. If equipment cannot be repaired on location, warranty shall include cost of transport to the facility where the repair work will be done.
  - C. It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
  - D. If any warranty literature submitted with the bid conflicts with AHTD warranty requirements, the conflict(s) shall be specifically noted, corrected and included with the bid or the conflict(s) will be considered an exception to warranty specifications and the bid rejected.
  - E. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment. For the purposes of this paragraph "timely manner" means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph "manufacturer" means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph "replacement part" means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is capable of providing dependable performance in normal operation conditions for its normal service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.
8. Current Model: Units furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Units manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable. Manufacturers of the units supplied must have been in the business of producing operational units for at least two years and must have recently sold similar units to domestic governmental agencies. The model furnished must have been in production for a minimum of one year, or be the latest version of a previous model. Bidder/s may be required to submit documentation substantiating the aforementioned requirements. A list of user references may also be required.
9. The successful bidder shall furnish installation instructions, Operator's Manual, Parts Book and all parts, accessories and hardware required for complete installation of lift.
10. All parts and accessories necessary for the efficient operation of lift shall be furnished whether or not they are specifically mentioned in this specification.
11. Successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
12. Demonstration: The Arkansas State Highway & Transportation Department reserves the right to require a demonstration, under actual working conditions, of equipment bid under this specification before award is made. The demonstration would be performed (free of any charge) by the bidder or an authorized representative at a mutually acceptable location. If requested, the bidder should be prepared to demonstrate the equipment within thirty (30) days after notification. Failure of the bidder to perform a satisfactory demonstration within the specified time may be grounds for rejection of the bid.

**ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT**

**SPECIFICATION 12-235-34-0290**

**FOR**

**FOUR POST SURFACE MOUNTED CAR AND TRUCK LIFT**

**30,000 POUNDS CAPACITY (235" WHEELBASE)**

**WITH DRIVE-THROUGH APPROACH RAMPS**

**AND**

**TWO ROLLING JACKS**

1. **General**: Heavy duty four post surface mounted lift with drive on type runways. Shall be electric-hydraulic operated and have a minimum capacity of 30,000 pounds. Shall be designed to accommodate passenger cars, light trucks and heavy trucks, including tandem axle dump trucks. Shall comply with applicable ANSI regulations.
2. **Lifting Columns**: Four (4) steel columns equipped with adjustable cables, chains and sheaves or direct drive pistons for lift synchronization.
  - A. **Lift Height (Rise)**: 60", minimum.
  - B. **Overall Width**: 12', minimum.
  - C. **Width Inside Columns**: 10' 5", minimum.
3. **Mechanical Locks**: Each column shall be equipped with a ladder type mechanical locking system that automatically latches at intervals as the lift is raised. The locks shall be released by means of air or hydraulic cylinders with one (1) cylinder activating each lock (total of four (4) cylinders). The lock release cylinders shall be activated by a single point lock release located on the lift control panel.
4. **Runways and Approach Ramps**: Shall have two (2) runways with approach ramps located on each end to allow drive-through operation. Approach ramps shall be hinged so that they automatically swing down when the lift is raised to provide wheel chocks. Design of approach ramps shall offer a low approach angle to allow for low ground clearance of passenger cars. Runways and approach ramps shall have an oil resistant non-skid coating. Runways and approach ramps shall be adjustable to match vehicle tread width. A minimum of four (4) portable wheel chocks shall be supplied with lift.
  - A. **Width**: Runways and approach ramps shall have a minimum width of 24".
  - B. **Wheelbase Capacity**: Length of runways shall be sufficient to accommodate wheelbases up to at least 235".
  - C. **Approach Ramp Length**: Each approach ramp shall have a minimum length of 36".
  - D. **Runway Height**: Each runway shall have a minimum height of 8".
  - E. **Overall Length**: Overall length of runways, including approach ramps, shall not exceed 36'.
  - F. **Tread Width Adjustment**: When adjusted to minimum width, the distance between the inside edges of the runways shall not exceed 41". When adjusted to maximum width, the outside to outside measurement of the runways shall be no less than 96".
5. **Power Unit**: Lift shall be powered by an electric-hydraulic power unit. Electric motor for power unit shall be rated at no less than 2 horsepower and operate on 220 volt, single phase, 60 cycle current. All operating controls shall be included.
6. **Rolling Jacks**: Lift shall be equipped with two (2) rolling jacks to serve as a stable foundation for raising wheels off the runways. Each jack shall have a minimum capacity of 8,000 pounds. The jacks shall be mounted to the inside of the runways and be capable of moving from one end of the runways to the other end for positioning under pickup points. Shall be designed to adjust to different widths as the track width of the runways is changed. The jacks shall be air over hydraulic or electric-hydraulic operated. Auxiliary adapters shall be furnished with each jack to provide versatility in load lifting.

7. Warranty: Units purchased under this specification shall be warranted against defects in material and workmanship for a minimum period of twelve (12) months (365 days) from date unit is placed in operation by AHTD.
  - A. Warranty shall include all parts, labor and transportation costs to the location of equipment.
  - B. If equipment cannot be repaired on location, warranty shall include cost of transport to the facility where the repair work will be done.
  - C. It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
  - D. If any warranty literature submitted with the bid conflicts with AHTD warranty requirements, the conflict(s) shall be specifically noted, corrected and included with the bid or the conflict(s) will be considered an exception to warranty specifications and the bid rejected.
  - E. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment. For the purposes of this paragraph "timely manner" means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph "manufacturer" means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph "replacement part" means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is capable of providing dependable performance in normal operation conditions for its normal service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.
8. Current Model: Units furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Units manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable. Manufacturers of the units supplied must have been in the business of producing operational units for at least two years and must have recently sold similar units to domestic governmental agencies. The model furnished must have been in production for a minimum of one year, or be the latest version of a previous model. Bidder/s may be required to submit documentation substantiating the aforementioned requirements. A list of user references may also be required.
9. The successful bidder shall furnish installation instructions, Operator's Manual, Parts Book and all parts, accessories and hardware required for complete installation of lift.
10. All parts and accessories necessary for the efficient operation of lift shall be furnished whether or not they are specifically mentioned in this specification.
11. Successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
12. Demonstration: The Arkansas State Highway & Transportation Department reserves the right to require a demonstration, under actual working conditions, of equipment bid under this specification before award is made. The demonstration would be performed (free of any charge) by the bidder or an authorized representative at a mutually acceptable location. If requested, the bidder should be prepared to demonstrate the equipment within thirty (30) days after notification. Failure of the bidder to perform a satisfactory demonstration within the specified time may be grounds for rejection of the bid.