#### ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT EQUIPMENT AND PROCUREMENT DIVISION BID INVITATION

Contract Number:	H-16-273P		BID OPENING LOCATION: AHTD Equipment and	MAIL TO: AHTD Equipment and	DELIVER TO: AHTD Equipment and	
Bid Opening Date:	March 8, 2016	Time:	11:00 a.m.	Procurement Division 11302 West Baseline Road Little Rock, AR 72209	Procurement Division P.O. Box 2261 Little Rock, AR 72203	Procurement Division 11302 West Baseline Road Little Rock, AR 72209
delivery locations until	I the above-noted bid opening	date and	time, and then public	ect to the Conditions on page 2 of th cly opened at the above-noted bid op ned bids will not be considered.		
In compliance with this set opposite each item		all the Co	nditions thereof, the u	undersigned offers and agrees to furni	sh any and all items upon wh	ich prices are quoted, at the price
Company Name:				Name (Type or Print):		
Address:				Title:		
				Phone:	Fax:	
City:	State:		Zip:	E-Mail:		
Federal Tax ID or So	ocial Security No.:				original (not photocopied) an ted.	d in ink.

## Loader, Pneumatic Tired

Bid prices shall include delivery of all Equipment to the Arkansas State Highway and Transportation Department at the F.O.B. location(s) shown on attached Bid Sheet.

Contract may be renewed or extended upon mutual agreement of the parties, but shall not exceed limitations allowed by Arkansas State Procurement Law.

Literature Submittals – Item A2 of Bid Specifications shall supersede Item #10 of Standard Bid Conditions.

**Bid Bond** in the amount of \$1,000 required of all bidders at time of bid opening or bid will be rejected. <u>Personal and</u> <u>company checks are not acceptable as Bid Bonds</u>. See Condition 3 on page 2 of bid invitation.

**Performance Bond** in the amount of 5% of the total awarded to the respective bidders must be furnished within 10 days after receipt of notice of intent to award as a guarantee of delivery in accordance with the specifications and within the time established in the bid. **Personal and company checks are not acceptable as Performance Bonds.** See Condition 3 on page 2 of bid invitation.

Additional Bonding Requirement: If additional units are purchased from this contract, a separate Performance Bond will be required under the same conditions as stated in this Bid Invitation.

Bidder shall specify guaranteed delivery date for all vehicles/equipment bid on in the space provided under each item number for which a price is being submitted. Successful bidder shall furnish Warranty Data for each vehicle/equipment delivered. The Warranty Data shall contain all necessary information such as motor and/or serial numbers and shall be signed by the selling dealer at the time vehicle/equipment is delivered to the Highway Department. Certificate of Origin, Federal Excise Tax Exemption Certificates, Odometer Disclosure Statement and five (5) copies of the Invoice for each vehicle/equipment to be furnished to Equipment & Procurement Division, P.O. Box 2261, Little Rock, AR 72203.

The successful bidder will be required to complete delivery within 180 days after award.

Bids and Specifications are available on-line by going to the AHTD Web Site – <u>www.arkansashighways.com</u> and clicking on "Commodities & Services Bids/Contract Information". Tabulations will also be available at this site after award of bid/contract. If you have any questions, call this office at 501-569-2667.

### ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT

#### **STANDARD BID CONDITIONS**

#### H-16-273P

- 1. ACCEPTANCE AND REJECTION: The Arkansas State Highway and Transportation Department (AHTD) reserves the right to reject any or all bids, to accept bids in whole or in part (unless otherwise indicated by bidder), to waive any informalities in bids received, to accept bids on materials or equipment with variations from specifications where efficiency of operation will not be impaired, and to award bids to best serve the interest of the State.
- 2. **PRICES:** Unless otherwise stated in the Bid Invitation, the following will apply: (1) unit prices shall be bid, (2) prices should be stated in units of quantity specified (feet, each, lbs., etc.), (3) prices must be F.O.B. destination specified in bid, (4) prices must be firm and not subject to escalation, (5) bid must be firm for acceptance for 30 days from bid opening date. In case of errors in extension, unit prices shall govern. Discounts from bid price will not be considered in making awards.
- BID BONDS AND PERFORMANCE BONDS: If required, a Bid Bond in the form of a cashier's check, certified check, or surety bond issued by a surety 3. company, in an amount stated in the Bid Invitation, must accompany bid. Personal and company checks are not acceptable as Bid Bonds. Failure to submit a Bid Bond as required will cause a bid to be rejected. The Bid Bond will be forfeited as liquidated damages if the successful bidder fails to provide a required Performance Bond within the period stipulated by AHTD or fails to honor their bid. When a bidder claims and can show clear and convincing evidence that a material mistake was made in the bid and was not the bid intended, the bidder may be permitted to withdraw their bid prior to award without forfeiture of bid bond. Cashier's checks and certified checks submitted as Bid Bonds will be returned to unsuccessful bidders; surety bonds will be retained. The successful bidder will be required to furnish a Performance Bond in an amount stated in the Bid Invitation and in the form of a cashier's check, certified check, or surety bond issued by a surety company, unless otherwise stated in the Bid Invitation, as a guarantee of delivery of goods/services in accordance with the specifications and within the time established in the bid. Personal and company checks are not acceptable as Performance Bonds. In some cases, a cashier's check or certified check submitted as a Bid Bond will be held as the Performance Bond of the successful bidder. Cashier's checks or certified checks submitted as Performance Bonds will be refunded shortly after payment has been made to the successful bidder for completion of all terms of the bid; surety bonds will be retained. Surety bonds must be issued by a surety company authorized to do business in Arkansas, and must be signed by a Resident Local Agent licensed by the Arkansas State Insurance Commissioner to represent that surety company. Resident Agent's Power-of-Attorney must accompany the surety bond. Certain bids involving labor will require Performance Bonds in the form of surety bonds only (no checks of any kind allowed). These bonds shall not only serve to guarantee the completion of the work, but also to guarantee the excellence of both workmanship and material until the work is finally accepted and the provisions of the Plans, Specifications, and Special Provisions fulfilled. In such cases, the company issuing the surety bond must comply with all stipulations herein and must be named in the U.S. Treasury listing of companies holding Certificates of Authority as acceptable sureties on Federal Bonds and as acceptable reinsuring companies. Any excess between the face amount of the bond and the underwriting limitation of the bonding company shall be protected by reinsurance provided by an acceptable reinsuring company. Annual Bid and Performance Bonds on file with E & P Division must have sufficient unencumbered funds to meet current bonding requirements, or the bid will be rejected, unless the balance is submitted as set forth above, prior to bid opening.
- 4. TAXES: The AHTD is not exempt from Arkansas State Sales and Use Taxes, or local option city/county sales taxes, when applicable, and bidders are responsible to the State Revenue Department for such taxes. These taxes should not be included in bid prices, but where required by law, will be paid by the AHTD as an addition thereto, and should be added to the billing to the AHTD. The AHTD is exempt from Federal Excise Taxes on all commodities except motor fuels; and excise taxes should not be included in bid prices except for motor fuels. Where applicable, tax exemption certificates will be furnished by the AHTD.
- 5. "ALL OR NONE" BIDS: Bidders who wish to bid "All or None" on two or more items shall so stipulate on the face of bid sheet; otherwise, bid may be awarded on an individual item basis.
- 6. **SPECIFICATIONS:** Complete specifications should be attached for any substitution or alternate offered, or where amplification is necessary. Bidder's name must be placed on all attachments to the bid.
- 7. EXCEPTIONS TO SPECIFICATIONS: Any exceptions to the bid specifications must be stated in the bid. Any exceptions to manufacturer's published literature must be stated in the bid, or it will be assumed that bidder is bidding exactly as stated in the literature.
- 8. BRAND NAME REFERENCES: All brand name references in bid specifications refer to that commodity or its equivalent, unless otherwise stated in Bid Invitation. Bidder should state brand or trade name of item being bid, if such name exists.
- FREIGHT: All freight charges should be included in bid price. Any change in common carrier rates authorized by the Interstate Commerce Commission will be adjusted if such change occurs after the bid opening date. Receipted common carrier bills that reflect ICC authorized rate changes must be furnished.
- 10. SAMPLES, LITERATURE, DEMONSTRATIONS: Samples and technical literature must be provided free of any charge within 14 days of AHTD request, and free demonstrations within 30 days, unless AHTD extends time. Failure to provide as requested within this period may cause bid to be rejected. Samples, literature and demonstrations must be substantially the same as the item(s) being bid, unless otherwise agreed to by AHTD. Samples that are not destroyed will be returned upon request at bidders expense. Samples from successful bidders may be retained for comparison with items actually furnished.
- 11. **GUARANTY:** Unless otherwise indicated in Bid Invitation, it is understood and agreed that any item offered or shipped on this bid shall be newly manufactured, latest model and design, and in first class condition; and that all containers shall be new, suitable for storage or shipment and in compliance with all applicable laws relating to construction, packaging, labeling and registration.
- 12. BACKORDERS OR DELAY IN DELIVERY: Backorders or failure to deliver within the time required may constitute default. Vendor must give written notice to the AHTD, as soon as possible, of the reason for any delay and the expected delivery date. The AHTD has the right to extend delivery if reasons appear valid. If reason or delivery date is not acceptable, vendor is in default.
- 13. DEFAULT: All commodities furnished will be subject to inspection and acceptance by AHTD after delivery. Default in promised delivery or failure to meet specifications authorizes the AHTD to cancel award or any portion of same, to reasonably purchase commodities or services elsewhere and to charge full increase, if any, in cost and handling to defaulting vendor. Applicable bonds may be forfeited.
- 14. ETHICS: "It shall be a breach of ethical standards for a person to be retained, or to retain a person, to solicit or secure a State contract upon an agreement of understanding for a commission, percentage, brokerage, or contingent fee, except for retention of bona fide employees or bona fide established commercial selling agencies maintained by the contractor for the purpose of securing business." (Arkansas Code, Annotated, Section 19-11-708).

# ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT

# **NOTICE OF NONDISCRIMINATION**

The Arkansas State Highway and Transportation (Department) complies with all civil rights provisions of federal statutes and related authorities that prohibit discrimination in programs and activities receiving federal financial assistance. Therefore the Department does not discriminate on the basis of race, sex, color, age, national origin, religion or disability, in the admission, access to and treatment in the Department's programs and activities, as well as the Department's hiring or employment practices. Complaints of alleged discrimination and inquiries regarding the Department's nondiscrimination policies may be directed to Joanna P. McFadden, Section Head - EEO/DBE (ADA/504/Title VI Coordinator), P. O. Box 2261, Little Rock, AR 72203, (501) 569-2298, (Voice/TTY 711), or the following email address: Joanna.Mcfadden@ahtd.ar.gov.

Free language assistance for Limited English Proficient individuals is available upon request.

This notice is available from the ADA/504/Title VI Coordinator in large print, on audiotape and in Braille.

## ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT LITTLE ROCK, ARKANSAS EQUIPMENT AND PROCUREMENT DIVISION

## **BID SHEET**

Con	tract No.: H-16-273P	BIDDE	R:					
1.	1 – Front End Loader, Pneumatic Tired, 1.5 CY Bucket, Diesel, 4 WD, to meet AHTD Spec. 16-200-120.							
	FOB: AHTD – District 2 Headquarters, 4900 Highway 65 South, Pine Bluff, AR 71611							
	Bid Price (Do not include any	Local, State or Federal Taxes)		Each \$				
	Total for <b>1 Loader</b>			\$				
	Loader proposed as meeting	specifications:						
	Make	Model	Warranty					
	Guaranteed Delivery Date							
	Additional Units may be purch	nased at the same pricing and						
	conditions through	(Date)						
2.	<ol> <li>FOB: AHTD – District 8 Headquarters, 372 Aspen Lane, Russellville, AR 72801</li> </ol>							
	Bid Price (Do not include any	Local, State or Federal Taxes)		Each \$				
	Total for <b>1 Loader</b>			\$				
	Loader proposed as meeting specifications:							
	Make	Model	Warranty					
	Guaranteed Delivery Date							
	Additional Units may be purch	ased at the same pricing and						
	conditions through	(Date)						

BID TOTAL \$ \_\_\_\_\_

#### ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT

#### SPECIFICATION 16-200-120

## <u>FOR</u> <u>FOUR WHEEL DRIVE FRONT END LOADER</u> 1.7 CUBIC YARDS CAPACITY

#### A. <u>General Conditions</u>:

- 1. <u>Current Model</u>: Units furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Machines manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable. Manufacturers of the units supplied must have been in the business of producing operational units for at least two years and must have recently sold similar units to domestic governmental agencies. The model furnished must have been in production for a minimum of one year, or be the latest version of a previous model. Bidder/s may be required to submit documentation substantiating the aforementioned requirements. A list of user references may also be required.
- 2. <u>Literature</u>: Manufacturers literature, verifying adherence of proposed unit to each line item addressed in this specification, shall be submitted with the bid. If any literature and/or specifications of items conflict with AHTD specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.
- 3. Any deviations from specifications and requirements herein must be clearly pointed out by bidder. Otherwise it will be considered that equipment offered is in strict compliance with these specifications and requirements, and successful bidder will be held responsible therefor. Deviations must be explained in detail on an attached sheet. However, no implication is made by the Arkansas State Highway and Transportation Department that deviations will be acceptable.
- 4. <u>Manuals</u>: The successful bidder shall furnish one (1) Operator's Instruction Manual with each unit delivered and one (1) copy each of Shop Repair Manual and Parts Book to each FOB point.

The successful bidder may provide Shop Repair Manuals and Parts Manuals on computer media (CD, DVD, USB Drive, etc.) in lieu of printed manuals.

5. <u>Training</u>: The successful bidder shall furnish qualified personnel to instruct AHTD operators and service technicians on operation and maintenance of machine.

In addition, the successful bidder shall furnish information on any factory service schools which would be available for AHTD service technicians.

- 6. Shall be assembled, adjusted and made ready for continuous operation at time of delivery.
- 7. All parts, accessories and tools necessary for satisfactory operation of this unit shall be furnished whether or not they are specifically mentioned in this specification (including standard equipment as regularly furnished by manufacturer as shown on printed literature and specifications unless specifically excluded by this specification).
- 8. <u>Parts Inventory & Service Facilities</u>: The successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
- 9. <u>Demonstration</u>: The Arkansas State Highway & Transportation Department reserves the right to require a demonstration, under actual working conditions, of equipment bid under this specification before award is made. The demonstration would be performed (free of any charge) by the bidder or an authorized representative at a mutually acceptable location. If requested, the bidder should be prepared to demonstrate the equipment within thirty (30) days after notification. Failure of the bidder to perform a satisfactory demonstration within the specified time may be grounds for rejection of the bid.
- 10. <u>Cooperative Purchasing</u>: Other tax-supported entities\* in Arkansas (cities, counties, state agencies, school districts, etc.) may purchase from this Contract on an individual basis under the same specifications and conditions, and at the pricing set forth by each vendor, all at the discretion of each vendor in each case. Prices could be reduced by a vendor for minor alterations in conditions (changing order quantities, deleting options, etc.) as agreed by both parties, but could not be raised above the contract bid price except for any additional freight charges. Vendors would not be required to sell to any such entity under this contract, and those entities would not be obligated to purchase from the contract.

Each entity wishing to purchase from the contract must make contact directly with the appropriate vendor(s). The Highway Department shall remain "out of the loop" for such transactions: all contact, orders, invoices, payments, etc. regarding such transactions must take place exclusively between the tax-supported entity and the vendor. The Department shall be held harmless of any and all liability arising from such transactions.

\* Tax-supported entities are defined as those receiving more than half of total funding from appropriated tax funds.

#### B. Unit specifications:

- 1. <u>General</u>: Shall be a four wheel drive pneumatic tired Wheel Loader of unit design engineered from the ground up for front-end loading operation. Full turn tipping load rating as defined in SAE J732 shall be no less than 12,000 pounds with cab, bucket and tires as specified below. The rated operating load shall not exceed 50% of the tipping capacity per SAE J818.
- 2. Engine: Rear mounted liquid cooled diesel with a minimum piston displacement 4.4 liters developing no less than 95 net horsepower at a governed speed of not more than 2,500 RPM. Engine shall comply with current EPA standards for off-road vehicles. Shall be equipped with electric starter, battery, alternator and ammeter or charge indicator. Shall have oil pressure or fuel solenoid actuated electric hour meter (showing actual engine run time independent of engine RPM), approved dry type air cleaner, pre-cleaner, lube oil filters and fuel filters with replaceable elements, and muffler. All gauges or indicators, including temperature, oil pressure and fuel level, to be mounted in instrument panel in cab readily visible to operator from seat. Fuel tank shall have a capacity for not less than ten (10) hours of operation. Cooling system shall have anti-freeze protection to -20° F, or lower.
- 3. <u>Transmission</u>: Power shift with a minimum of three (3) forward speeds and three (3) reverse speeds, or hydrostatic with a minimum of two (2) speed ranges. Shall have a minimum road speed of 18 mph.
- 4. <u>Axles</u>: Planetary type reduction to each hub.
- 5. <u>Brakes</u>: Foot controlled, hydraulic actuated wet disc type service brakes acting on all four wheels. Parking brake as regularly furnished by manufacturer. The entire braking system shall meet current SAE J1473/ISO3450 standards.
- 6. <u>Steering</u>: Articulated frame, full hydraulic power steering.
- 7. <u>Tires</u>: 15.5 x 25 or 17.5 x 25 with L2 tread, minimum 12 Ply Rating, and water valve stem. (Radial ply equivalent may be provided in lieu of bias ply tires.)
- 8. <u>Hydraulic System</u>: Shall consist of reservoir with baffles, pump, control valve, lift and dump cylinders, necessary relief valves and necessary filters with replaceable elements. Control valves shall be convenient to operator.
- 9. <u>Bucket</u>: General purpose material bucket with a minimum SAE rated heaped capacity of 1.7 cubic yards. Bucket shall be at least as wide as the outside to outside measurement of the tires and be equipped with a bolt on cutting edge. Maximum dumping height with bucket at dump angle shall be no less than 8' 6". Raising time of bucket shall be no more than 6.4 seconds and lowering time from maximum lifting height to ground level shall be no more than 5.0 seconds. Bucket reach forward shall be no less than 32" at maximum dumping height with bucket at dump angle. Shall have below ground line digging capacity with bucket cutting edge in horizontal position.
- 10. Breakout Force: SAE J732 breakout force shall be no less than 17,000 pounds.
- 11. <u>Cab</u>: Fully enclosed pressurized ROPS cab with safety glass windshield and windows. Cab shall be equipped with air conditioning, heater-defroster unit, front and rear windshield wipers with washers, inside rear view mirror, adjustable suspension seat and seat belt.
- 12. <u>Equipment</u>: Loader shall be equipped with a backup alarm, working and traveling lights, stop and tail lights, directional signals with hazard flashers and vandalism protection equipment.
- 13. <u>Rear View Camera</u>: Loader shall be equipped with a factory installed rear view camera and in-cab mounted screen.
- 14. <u>Remote Monitoring System</u>: Unit shall be equipped with an integrated factory installed remote monitoring system which interacts with electronic system controls. System shall offer the following capabilities as a minimum.
  - A. System shall be capable of monitoring and storing electronic data produced by the machine.
  - B. Unit shall be equipped with cellular communication capability for the transmittal of collected data.
  - C. This data shall be accessible to designated employees of the department for review from any internet connection. All data shall be in real time.
  - D. Data collected by this system shall be stored by the manufacturer for a period of not less than (1) one year (twelve months). This historical data shall be accessible to designated employees of the department for review from any internet connection.
  - E. The system shall be capable of notifying the manufacturer/dealer and AHTD personnel in the event a fault code is generated by a component of the machine. If the code is a priority code (immediate attention required, such as low

engine oil pressure, low coolant, high coolant temperature, hydraulic pressure, etc.) the manufacturer/dealer will immediately contact AHTD personnel to verify receipt of message.

- F. System shall be capable of allowing remote access by technicians for the purpose of diagnostic trouble shooting and software updates.
- G. Unit shall be capable of showing the exact location of the machine as a street address and GPS coordinates.
- H. Shall be capable of showing hour meter reading in real time and have the ability to notify maintenance personnel when service is due. AHTD personnel shall have the capability to set service parameters in the system for each unit.
- I. System shall be capable of generating the following reports as a minimum.
  - (1) Unit tracking.
  - (2) Idle time.
  - (3) Machine usage.
  - (4) Engine fuel burn.
- J. System shall allow designated AHTD personnel the ability to establish geofencing and curfew parameters for each unit.
- K. The subscription for this package shall be provided to the AHTD free of charge for a minimum of (3) three years (36 months).
- 15. <u>Weight</u>: Operating weight of machine ready for continuous operation shall be no less than 17,000 pounds with cab, bucket and tires specified above.
- 16. <u>Color</u>: Manufacturer's standard color is acceptable.
- 17. <u>Warranty</u>: Units purchased under this specification shall be warranted against defects in material and workmanship for a minimum period of twelve (12) months (365 days) from date unit is placed in operation by AHTD.
  - A. Warranty shall include all parts, labor and transportation costs to the location of equipment.
  - B. If equipment cannot be repaired on location, warranty shall include cost of transport to the facility where the repair work will be done.
  - C. It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
  - D. If any warranty literature submitted with the bid conflicts with AHTD warranty requirements, the conflict(s) shall be specifically noted, corrected and included with the bid or the conflict(s) will be considered an exception to warranty specifications and the bid rejected.
  - E. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment. For the purposes of this paragraph "timely manner" means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph "manufacturer" means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph "replacement part" means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is capable of providing dependable performance in normal operation conditions for its normal service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.

#### ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT

#### SPECIFICATION 16-201-122

## FOR

### FOUR WHEEL DRIVE FRONT END LOADER 2.5 CUBIC YARDS CAPACITY

#### A. <u>General Conditions</u>:

- 1. <u>Current Model</u>: Units furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Machines manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable. Manufacturers of the units supplied must have been in the business of producing operational units for at least two years and must have recently sold similar units to domestic governmental agencies. The model furnished must have been in production for a minimum of one year, or be the latest version of a previous model. Bidder/s may be required to submit documentation substantiating the aforementioned requirements. A list of user references may also be required.
- 2. <u>Literature</u>: Manufacturers literature, verifying adherence of proposed unit to each line item addressed in this specification, shall be submitted with the bid. If any literature and/or specifications of items conflict with AHTD specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.
- 3. Any deviations from specifications and requirements herein must be clearly pointed out by bidder. Otherwise it will be considered that equipment offered is in strict compliance with these specifications and requirements, and successful bidder will be held responsible therefor. Deviations must be explained in detail on an attached sheet. However, no implication is made by the Arkansas State Highway and Transportation Department that deviations will be acceptable.
- 4. <u>Manuals</u>: The successful bidder shall furnish one (1) Operator's Instruction Manual with each unit delivered and one (1) copy each of Shop Repair Manual and Parts Book to each FOB point.

The successful bidder may provide Shop Repair Manuals and Parts Manuals on computer media (CD, DVD, USB Drive, etc.) in lieu of printed manuals.

5. <u>Training</u>: The successful bidder shall furnish qualified personnel to instruct AHTD operators and service technicians on operation and maintenance of machine.

In addition, the successful bidder shall furnish information on any factory service schools which would be available for AHTD service technicians.

- 6. Shall be assembled, adjusted and made ready for continuous operation at time of delivery.
- 7. All parts, accessories and tools necessary for satisfactory operation of this unit shall be furnished whether or not they are specifically mentioned in this specification (including standard equipment as regularly furnished by manufacturer as shown on printed literature and specifications unless specifically excluded by this specification).
- 8. <u>Parts Inventory & Service Facilities</u>: The successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
- 9. <u>Demonstration</u>: The Arkansas State Highway & Transportation Department reserves the right to require a demonstration, under actual working conditions, of equipment bid under this specification before award is made. The demonstration would be performed (free of any charge) by the bidder or an authorized representative at a mutually acceptable location. If requested, the bidder should be prepared to demonstrate the equipment within thirty (30) days after notification. Failure of the bidder to perform a satisfactory demonstration within the specified time may be grounds for rejection of the bid.
- 10. <u>Cooperative Purchasing</u>: Other tax-supported entities\* in Arkansas (cities, counties, state agencies, school districts, etc.) may purchase from this Contract on an individual basis under the same specifications and conditions, and at the pricing set forth by each vendor, all at the discretion of each vendor in each case. Prices could be reduced by a vendor for minor alterations in conditions (changing order quantities, deleting options, etc.) as agreed by both parties, but could not be raised above the contract bid price except for any additional freight charges. Vendors would not be required to sell to any such entity under this contract, and those entities would not be obligated to purchase from the contract.

Each entity wishing to purchase from the contract must make contact directly with the appropriate vendor(s). The Highway Department shall remain "out of the loop" for such transactions: all contact, orders, invoices, payments, etc. regarding such transactions must take place exclusively between the tax-supported entity and the vendor. The Department shall be held harmless of any and all liability arising from such transactions.

\* Tax-supported entities are defined as those receiving more than half of total funding from appropriated tax funds.

#### B. Unit specifications:

- <u>General</u>: Four wheel drive pneumatic tired Wheel Loader of unit design engineered from the ground up for front-end loading operation. Full turn tipping load rating as defined in SAE J732 shall be no less than 17,000 pounds with cab, bucket and tires as specified below. The rated operating load shall not exceed 50% of the tipping capacity per SAE J818.
- 2. Engine: Rear mounted liquid cooled diesel with no less than six (6) cylinders and a minimum piston displacement of 5.7 liters. Shall develop no less than 130 net horsepower at a governed speed of not more than 2,500 RPM. Engine shall comply with current EPA standards for off-road vehicles. Shall be equipped with electric starter, battery, alternator and ammeter or charge indicator. Shall have oil pressure or fuel solenoid actuated electric hour meter (showing actual engine run time independent of engine RPM), approved dry type air cleaner, pre-cleaner, lube oil filters and fuel filters with replaceable elements, and muffler. All gauges or indicators, including temperature, oil pressure and fuel level, to be mounted in instrument panel in cab readily visible to operator from seat. Fuel tank shall have a capacity for not less than ten (10) hours of operation. Cooling system shall have anti-freeze protection to -20° F, or lower.
- 3. <u>Transmission</u>: Power shift with no less than four (4) forward speeds and three (3) reverse speeds, or variable speed hydrostatic with a minimum of two (2) speed ranges. Road speed shall be no less than 20 mph.
- 4. <u>Axles</u>: Planetary type reduction to each hub.
- 5. <u>Brakes</u>: Foot controlled, hydraulic actuated wet disc type service brakes. Parking brake as regularly furnished by manufacturer. The entire braking system shall meet current SAE J1473/ISO3450 standards.
- 6. <u>Steering</u>: Articulated frame, full hydraulic power steering.
- 7. <u>Tires</u>: 17.5 x 25 or 20.5 x 25, minimum 12 Ply Rating with L2 tread and water valve stem. (Radial ply equivalent may be provided in lieu of bias ply tires.)
- 8. <u>Hydraulic System</u>: Shall consist of reservoir with baffles, pump, control valve, lift and dump cylinders, necessary relief valves and necessary filters with replaceable elements. Control valves shall be convenient to operator.
- 9. <u>Bucket</u>: Heavy material bucket with a minimum SAE rated heaped capacity of 2.5 cubic yards. Bucket shall be at least as wide as the outside to outside measurement of the tires and be equipped with a bolt on cutting edge. Maximum dumping height with bucket at dump angle shall be no less than 9' 0". Raising time of bucket shall be no more than 6.5 seconds and lowering time from maximum lifting height to ground level shall be no more than 5 seconds. Bucket reach forward shall be no less than 36" at maximum dumping height with bucket at dump angle. Shall have below ground line digging capacity with bucket cutting edge in horizontal position.
- 10. Breakout Force: SAE J732 breakout force shall be no less than 20,000 pounds.
- 11. <u>Cab</u>: Fully enclosed pressurized ROPS cab with safety glass windshield and windows. Cab shall be equipped with air conditioning, heater-defroster unit, front and rear windshield wipers with washers, inside rear view mirror, adjustable suspension seat and seat belt.
- 12. <u>Equipment</u>: Loader shall be equipped with a backup alarm, working and traveling lights, stop and tail lights, directional signals with hazard flashers and vandalism protection equipment.
- 13. <u>Rear View Camera</u>: Loader shall be equipped with a factory installed rear view camera and in-cab mounted screen.
- 14. <u>Remote Monitoring System</u>: Unit shall be equipped with an integrated factory installed remote monitoring system which interacts with electronic system controls. System shall offer the following capabilities as a minimum.
  - A. System shall be capable of monitoring and storing electronic data produced by the machine.
  - B. Unit shall be equipped with cellular communication capability for the transmittal of collected data.
  - C. This data shall be accessible to designated employees of the department for review from any internet connection. All data shall be in real time.
  - D. Data collected by this system shall be stored by the manufacturer for a period of not less than (1) one year (twelve months). This historical data shall be accessible to designated employees of the department for review from any internet connection.
  - E. The system shall be capable of notifying the manufacturer/dealer and AHTD personnel in the event a fault code is generated by a component of the machine. If the code is a priority code (immediate attention required, such as low

engine oil pressure, low coolant, high coolant temperature, hydraulic pressure, etc.) the manufacturer/dealer will immediately contact AHTD personnel to verify receipt of message.

- F. System shall be capable of allowing remote access by technicians for the purpose of diagnostic trouble shooting and software updates.
- G. Unit shall be capable of showing the exact location of the machine as a street address and GPS coordinates.
- H. Shall be capable of showing hour meter reading in real time and have the ability to notify maintenance personnel when service is due. AHTD personnel shall have the capability to set service parameters in the system for each unit.
- I. System shall be capable of generating the following reports as a minimum.
  - (1) Unit tracking.
  - (2) Idle time.
  - (3) Machine usage.
  - (4) Engine fuel burn.
- J. System shall allow designated AHTD personnel the ability to establish geofencing and curfew parameters for each unit.
- K. The subscription for this package shall be provided to the AHTD free of charge for a minimum of (3) three years (36 months).
- 15. <u>Weight</u>: Operating weight of machine ready for continuous operation shall be no less than 24,800 pounds with cab, bucket and tires specified above.
- 16. <u>Color</u>: Manufacturer's standard color is acceptable.
- 17. <u>Warranty</u>: Units purchased under this specification shall be warranted against defects in material and workmanship for a minimum period of twelve (12) months (365 days) from date unit is placed in operation by AHTD.
  - A. Warranty shall include all parts, labor and transportation costs to the location of equipment.
  - B. If equipment cannot be repaired on location, warranty shall include cost of transport to the facility where the repair work will be done.
  - C. It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
  - D. If any warranty literature submitted with the bid conflicts with AHTD warranty requirements, the conflict(s) shall be specifically noted, corrected and included with the bid or the conflict(s) will be considered an exception to warranty specifications and the bid rejected.
  - E. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment. For the purposes of this paragraph "timely manner" means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph "manufacturer" means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph "replacement part" means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is capable of providing dependable performance in normal operation conditions for its normal service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.