ARKANSAS STATE HIGHWAY COMMISSION AHTD-EQUIPMENT AND PROCUREMENT DIVISION BID INVITATION

Contract Number:	Н-17-334Н		AHTD Equipment and	MAIL TO: AHTD Equipment and	DELIVER TO: AHTD Equipment and	
Bid Opening Date:	June 6, 2017	Time:	11:00 a.m.	Procurement Division 11302 West Baseline Road Little Rock, AR 72209	Procurement Division P.O. Box 2261 Little Rock, AR 72203	Procurement Division 11302 West Baseline Road Little Rock, AR 72209
mail and delivery loo	cations until the above-noted	oid opening	date and time, and	ject to the Standard Bid Conditions of then publicly opened at the above-not bids and unsigned bids will not be of	ed bid opening location. Bic	
n compliance with the price set opposite each		all the Cor	nditions thereof, the u	undersigned offers and agrees to furnis	h any and all items upon whic	ch prices are quoted, at the
Company Name:				Name (Type or Print):_		
Address:				Title:		
				Phone:	Fax:	
City:	State	:	Zip:	E-Mail:		
Federal Tax ID or	Social Security No.:				original (not photocopied) an	d in ink.

Roller, Vibratory, Double Drum

The Arkansas Highway and Transportation Department (hereafter called the AHTD) will receive bids for a Roller, Vibratory, Double Drum.

Bid prices shall include delivery of all Equipment to the AHTD at the F.O.B. location(s) shown on attached Bid Sheet.

Contract may be renewed or extended upon mutual agreement of the parties, but shall not exceed limitations allowed by Arkansas State Procurement Law.

All bidders should complete and return the Eligible Bidder Certification (Attachment A) and Disclosure Form (see Page 2 of Standard Bid Conditions – Item 18) issued with this bid. A current copy of the DFA Illegal Immigrant Contractor Disclosure Certification (see Page 1 of Standard Bid Conditions – Item 17) should also be submitted with bid.

Literature Submittals – Item A2 of Bid Specifications shall supersede Item #11 of Standard Bid Conditions.

Bid Bond in the amount of \$1,000 required of all bidders at time of bid opening or bid will be rejected. **Personal and company checks are not acceptable as Bid Bonds.** See Condition 4 on page 1 of Standard Bid Conditions.

Performance Bond in the amount of 5% of the total awarded to the respective bidders must be furnished within 10 days after receipt of notice of intent to award as a guarantee of delivery in accordance with the specifications and within the time established in the bid. **Personal and company checks are not acceptable as Performance Bonds.** See Condition 4 on page 1 of Standard Bid Conditions.

Bidder shall specify guaranteed delivery date for all vehicles/equipment in the space provided under each item number for which a price is being submitted. Successful bidder shall furnish Warranty Data for each vehicle/equipment delivered. The Warranty Data shall contain all necessary information such as motor and/or serial numbers and shall be signed by the selling dealer at the time vehicle/equipment is delivered to the Highway Department. Certificate of Origin, Federal Excise Tax Exemption Certificates, Odometer Disclosure Statement and five (5) copies of the Invoice for each vehicle/equipment to be furnished to Equipment & Procurement Division, P.O. Box 2261, Little Rock, AR 72203.

The successful bidder will be required to complete delivery within 180 days after award.

Bids and Specifications are available on-line by going to the AHTD Web Site – www.arkansashighways.com and clicking on "Commodities and Services Bids/Contracts Information". Tabulations will also be available at this site after award of bid/contract. If you have any questions, call this office at 501-569-2667.

64-7196 thru 64-7198

ARKANSAS STATE HIGHWAY COMMISSION LITTLE ROCK, ARKANSAS AHTD-EQUIPMENT AND PROCUREMENT DIVISION

BID SHEET

Con	tract No.: H-17-334	i H BI	DDER:						
1.		ry, Double Drum, 8 – 12 Ton (Equiva FD Spec. 17-238A-148.	alent), 66" Nominal Drum	Width					
	FOB: 1 ea AHT	FOB: 1 ea AHTD – District 7 Headquarters, 2245 California Avenue, Camden, AR 71701							
	Bid Price (Do not i	nclude any Local, State or Federal Ta	axes)						
	Roller proposed as	meeting specifications:							
	Make	Model	Warranty	Each \$					
2.		ry, Double Drum, 8 – 12 Ton (Equiva ГD Spec. 17-237A-148.	alent), 59" Nominal Drum	Width					
	FOB: 1 ea AHT	D – District 9 Headquarters, 4590	Highway 65 South, Harri	son, AR 72601					
	Bid Price (Do not i	nclude any Local, State or Federal Ta	axes)						
	Roller proposed as	meeting specifications:							
	Make	Model	Warranty	Each \$					
3.		ry, Double Drum, 3 Ton ΓD Spec. 17-235A-139.							
	FOB: 1 ea AHT	D – District 7 Headquarters, 2245	California Avenue, Camo	len, AR 71701					
	Bid Price (Do not i	nclude any Local, State or Federal Ta	axes)						
	Roller proposed as	meeting specifications:							
	Make	Model	Warranty	Each \$					
	Guaranteed Deliver Additional Units m conditions through	ry Dateay be purchased at the same pricing a(Date)	and						
		(Date)	B	SID TOTAL \$					

ARKANSAS STATE HIGHWAY COMMISSION

Rev. 2/21/2017 Page 1 of 2

STANDARD BID CONDITIONS

- 1. **GENERAL:** Any special terms and conditions included in the invitation for bid override these standard terms and conditions. The standard terms and conditions and any special terms and conditions become part of any contract entered into if any or all parts of the bid are accepted by the Arkansas State Highway and Transportation Department (AHTD).
- 2. **ACCEPTANCE AND REJECTION:** AHTD reserves the right to reject any or all bids, to accept bids in whole or in part (unless otherwise indicated by bidder), to waive any informalities in bids received, to accept bids on materials or equipment with variations from specifications where efficiency of operation will not be impaired, and to award bids to best serve the interest of the State.
- 3. **PRICES:** Unless otherwise stated in the Bid Invitation, the following will apply: (1) unit prices shall be bid, (2) prices should be stated in units of quantity specified (feet, each, lbs., etc.), (3) prices must be F.O.B. destination specified in bid, (4) prices must be firm and not subject to escalation, (5) bid must be firm for acceptance for 30 days from bid opening date. In case of errors in extension, unit prices shall govern. Discounts from bid price will not be considered in making awards.
- BID BONDS AND PERFORMANCE BONDS: If required, a Bid Bond in the form of a cashier's check, certified check, or surety bond issued by a surety company, in an amount stated in the Bid Invitation, must accompany bid. **Personal and company checks** are not acceptable as Bid Bonds. Failure to submit a Bid Bond as required will cause a bid to be rejected. The Bid Bond will be forfeited as liquidated damages if the successful bidder fails to provide a required Performance Bond within the period stipulated by AHTD or fails to honor their bid. When a bidder claims and can show clear and convincing evidence that a material mistake was made in the bid and was not the bid intended, the bidder may be permitted to withdraw their bid prior to award without forfeiture of bid bond. Cashier's checks and certified checks submitted as Bid Bonds will be returned to unsuccessful bidders; surety bonds will be retained. The successful bidder will be required to furnish a Performance Bond in an amount stated in the Bid Invitation and in the form of a cashier's check, certified check, or surety bond issued by a surety company, unless otherwise stated in the Bid Invitation, as a guarantee of delivery of goods/services in accordance with the specifications and within the time established in the bid. Personal and company checks are not acceptable as Performance Bonds. In some cases, a cashier's check or certified check submitted as a Bid Bond will be held as the Performance Bond of the successful bidder. Cashier's checks or certified checks submitted as Performance Bonds will be refunded shortly after payment has been made to the successful bidder for completion of all terms of the bid; surety bonds will be retained. Surety bonds must be issued by a surety company authorized to do business in Arkansas, and must be signed by a Resident Local Agent licensed by the Arkansas State Insurance Commissioner to represent that surety company. Resident Agent's Power-of-Attorney must accompany the surety bond. Certain bids involving labor will require Performance Bonds in the form of surety bonds only (no checks of any kind allowed). These bonds shall not only serve to guarantee the completion of the work, but also to guarantee the excellence of both workmanship and material until the work is finally accepted and the provisions of the Plans, Specifications, and Special Provisions fulfilled. In such cases, the company issuing the surety bond must comply with all stipulations herein and must be named in the U.S. Treasury listing of companies holding Certificates of Authority as acceptable sureties on Federal Bonds and as acceptable reinsuring companies. Any excess between the face amount of the bond and the underwriting limitation of the bonding company shall be protected by reinsurance provided by an acceptable reinsuring company. Annual Bid and Performance Bonds on file with E & P Division must have sufficient unencumbered funds to meet current bonding requirements, or the bid will be rejected, unless the balance is submitted as set forth above, prior to bid openina.
- 5. **TAXES:** The AHTD is not exempt from Arkansas State Sales and Use Taxes, or local option city/county sales taxes, when applicable, and bidders are responsible to the State Revenue Department for such taxes. These taxes should not be included in bid prices, but where required by law, will be paid by the AHTD as an addition thereto, and should be added to the billing to the AHTD. The AHTD is exempt from Federal Excise Taxes on all commodities except motor fuels; and excise taxes should not be included in bid prices except for motor fuels. Where applicable, tax exemption certificates will be furnished by the AHTD.
- 6. **"ALL OR NONE" BIDS:** Bidders who wish to bid "All or None" on two or more items shall so stipulate on the face of bid sheet; otherwise, bid may be awarded on an individual item basis.
- 7. **SPECIFICATIONS:** Complete specifications should be attached for any substitution or alternate offered, or where amplification is necessary. Bidder's name must be placed on all attachments to the bid.
- 8. **EXCEPTIONS TO SPECIFICATIONS:** Any exceptions to the bid specifications must be stated in the bid. Any exceptions to manufacturer's published literature must be stated in the bid, or it will be assumed that bidder is bidding exactly as stated in the literature.
- 9. **BRAND NAME REFERENCES:** All brand name references in bid specifications refer to that commodity or its equivalent, unless otherwise stated in Bid Invitation. Bidder should state brand or trade name of item being bid, if such name exists.
- 10. **FREIGHT:** All freight charges should be included in bid price. Any change in common carrier rates authorized by the Interstate Commerce Commission will be adjusted if such change occurs after the bid opening date. Receipted common carrier bills that reflect ICC authorized rate changes must be furnished.

- 11. **SAMPLES, LITERATURE, DEMONSTRATIONS:** Samples and technical literature must be provided free of any charge within 14 days of AHTD request, and free demonstrations within 30 days, unless AHTD extends time. Failure to provide as requested within this period may cause bid to be rejected. Samples, literature and demonstrations must be substantially the same as the item(s) being bid, unless otherwise agreed to by AHTD. Samples that are not destroyed will be returned upon request at bidders expense. Samples from successful bidders may be retained for comparison with items actually furnished.
- 12. **GUARANTY:** Unless otherwise indicated in Bid Invitation, it is understood and agreed that any item offered or shipped on this bid shall be newly manufactured, latest model and design, and in first class condition; and that all containers shall be new, suitable for storage or shipment and in compliance with all applicable laws relating to construction, packaging, labeling and registration.
- 13. **BACKORDERS OR DELAY IN DELIVERY:** Backorders or failure to deliver within the time required may constitute default. Vendor must give written notice to the AHTD, as soon as possible, of the reason for any delay and the expected delivery date. The AHTD has the right to extend delivery if reasons appear valid. If reason or delivery date is not acceptable, vendor is in default.
- 14. **DEFAULT:** All commodities furnished will be subject to inspection and acceptance by AHTD after delivery. Default in promised delivery or failure to meet specifications authorizes the AHTD to cancel award or any portion of same, to reasonably purchase commodities or services elsewhere and to charge full increase, if any, in cost and handling to defaulting vendor. Applicable bonds may be forfeited.
- 15. **ETHICS:** "It shall be a breach of ethical standards for a person to be retained, or to retain a person, to solicit or secure a State contract upon an agreement of understanding for a commission, percentage, brokerage, or contingent fee, except for retention of bona fide employees or bona fide established commercial selling agencies maintained by the contractor for the purpose of securing business." (Arkansas Code, Annotated, Section 19-11-708).
- 16. **NOTICE OF NONDISCRIMINATION:** The Arkansas State Highway Commission through the AHTD complies with all civil rights provisions of federal statutes and related authorities that prohibit discrimination in programs and activities receiving federal financial assistance. Therefore, the AHTD does not discriminate on the basis of race, sex, color, age, national origin, religion (not applicable as a protected group under the Federal Motor Carrier Safety Administration Title VI Program), disability, Limited English Proficiency (LEP), or low-income status in the admission, access to and treatment in the AHTD's programs and activities, as well as the hiring or employment practices. Complaints of alleged discrimination and inquiries regarding the AHTD's nondiscrimination policies may be directed to Joanna P. McFadden Section Head EEO/DBE (ADA/504/Title VI Coordinator), P. O. Box 2261, Little Rock, AR 72203, (501)569-2298, (Voice/TTY 711), or the following email address: **joanna.mcfadden@ahtd.ar.gov**. Free language assistance for Limited English Proficient individuals is available upon request. This notice is available from the ADA/504/Title VI Coordinator in large print, on audiotape and in Braille.
- 17. **PROHIBITION OF EMPLOYMENT OF ILLEGAL IMMIGRANTS:** Pursuant to Arkansas Code Annotated 19-11-105, all bidders must certify prior to award of a contract that they <u>do not</u> employ or contract with any illegal immigrant(s) in its contract with the state. Bidders shall certify online at https://www.ark.org/dfa/immigrant/index.php.
- 18. **DISCLOSURE:** Failure to make any disclosure required by Governor's Executive Order 98-04, or any violation of any rule, regulation, or policy adopted pursuant to that order, **shall** be a material breach of the terms of this contract. Any contractor, whether an individual or entity, who fails to make the required disclosure or who violates any rule, regulation, or policy **shall** be subject to all legal remedies available to the agency.

ATTACHMENT A

ELIGIBLE BIDDER CERTIFICATION

The Bidder represents and warrants for itself, its employees and its subcontractors and certifies they:

- 1. Are not presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from covered transactions by any Federal department or agency;
- 2. Have not within a three-year period preceding thus Bid been convicted of or had a civil judgment rendered against them for commission of fraud or a criminal offense in connection with obtaining, attempting to obtain, or performing a public (Federal, State, or local) transaction or contract under a public transaction; violation of Federal or State antitrust statutes or commission of embezzlement, theft, forgery, bribery, falsification or destruction of records, making false statements, or receiving stolen property;
- 3. Are not presently indicted for or otherwise criminally or civilly charged by a governmental entity (Federal, State, or local) with commission of any of the offenses enumerated in paragraph two (2) of this Certification;
- 4. Have not within a one-year period preceding this application/Bid had one or more public transactions (Federal, State, or local) terminated for cause or default; and

The Bidder represents, warrants and acknowledges the understanding that restrictions placed on the employment of labor or on the scale of pay for the work on a contract will be the requirements of the Fair Labor Standards Act (Federal Wage-Hour Law) of 1938, 28 USC §201 et seq., and other applicable labor laws.

The person executing this Certification further represents, warrants and affirms the truthfulness and accuracy of the contents of the statements submitted on or with this Certification and understands that the provisions of 31 USC §3801 et seq. are applicable thereto.

BIDDER NAME					
BY:Signature					
TITLE:					

CONTRACT AND GRANT DISCLOSURE AND CERTIFICATION FORM

Failure to complete all of	f the followin	g informatio	n may result in a delay in obtainir	ng a contract	t, lease, pur	chase agreement, or grant award with any Arkansas State Agency	/ ·	
SUBCONTRACTOR: Yes No	SUBCONTR	ACTOR NAME:						
			IS THIS FOR:					
TAXPAYER ID NAME:			□ Goods?	☐ Services	s? 🗖	Both?		
YOUR LAST NAME:			FIRST NAME:			M.I.:		
ADDRESS:								
CITY:			STATE:		ZIP CODE	: COUNTY:		
AS A CONDITION	OF OBTA	INING, E	XTENDING, AMENDING	, OR REN	<u>NEWING</u>	A CONTRACT, LEASE, PURCHASE AGREEMENT	T, OR GRANT AV	<u>VARD</u>
WITH ANY ARKAI	NSAS STA	TE AGEN	ICY, THE FOLLOWING IN	FORMA	TION MU	JST BE DISCLOSED:		
				FOR	INDIV	IDUALS*		
Indicate below if: you, y Commission Member, o			ner, sister, parent, or child of yo	u or your sp	oouse is a c	urrent or former: member of the General Assembly, Constitut	ional Officer, State Bo	oard or
Position Held	Ma	ark (√)	Name of Position of Job Hel	d For H	low Long?	What is the person(s) name and how are they related to you? (i.e., Jane Q. Public, spouse, John Q. Public, Jr., child, etc.)		
Position Held	Current	t Former	(senator, representative, name of board/ commission, data entry, etc		To MM/YY	Person's Name(s)	Ro	elation
General Assembly								
Constitutional Officer								
State Board or Commission Member								
State Employee								
☐ None of the above	e applies							
			FO	R AN E	NTITY	(BUSINESS)*		
Constitutional Officer, S	State Board	or Commissi	on Member, State Employee, o	r the spouse	e, brother,	any ownership interest of 10% or greater in the entity: meml sister, parent, or child of a member of the General Assembly, asing policies or influence the management of the entity.		
Position Held	Mark (✓)		Name of Position of Job Held	For How		What is the person(s) name and what is his/her % of ownership interest and/or what is his/her position of control?		
	Current	Former	(senator, representative, name of board/ commission, data entry, etc.)	From MM/YY	To MM/YY	Person's Name(s)	Ownership Interest (%)	Position of Control
General Assembly				,	,			
Constitutional Officer								1
State Board or				t			<u> </u>	1

Commission Member
State Employee

[☐] None of the above applies

Contract and Grant Disclosure and Certification Form

Failure to make any disclosure required by Governor's Executive Order 98-04, or any violation of any rule, regulation, or policy adopted pursuant to that Order, shall be a material breach of the terms of this contract. Any contractor, whether an individual or entity, who fails to make the required disclosure or who violates any rule, regulation, or policy shall be subject to all legal remedies available to the agency.

As an additional condition of obtaining, extending, amending, or renewing a contract with a state agency I agree as follows:

- 1. Prior to entering into any agreement with any subcontractor, prior or subsequent to the contract date, I will require the subcontractor to complete a **CONTRACT AND GRANT DISCLOSURE AND CERTIFICATION FORM**. Subcontractor shall mean any person or entity with whom I enter an agreement whereby I assign or otherwise delegate to the person or entity, for consideration, all, or any part, of the performance required of me under the terms of my contract with the state agency.
- 2. I will include the following language as a part of any agreement with a subcontractor:

Failure to make any disclosure required by Governor's Executive Order 98-04, or any violation of any rule, regulation, or policy adopted pursuant to that Order, shall be a material breach of the terms of this subcontract. The party who fails to make the required disclosure or who violates any rule, regulation, or policy shall be subject to all legal remedies available to the contractor.

3. No later than ten (10) days after entering into any agreement with a subcontractor, whether prior or subsequent to the contract date, I will mail a copy of the CONTRACT AND GRANT DISCLOSURE AND CERTIFICATION FORM completed by the subcontractor and a statement containing the dollar amount of the subcontract to the state agency.

Signature		Title		Date
Vendor Contact Person		Title		Phone No.
Agency Use Only Agency	Agency	Agency	Contact	Contract or
Number	Name	Contact Person	Phone No.	Grant No.

ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT

SPECIFICATION 17-238A-148

FOR

DOUBLE DRUM VIBRATORY ROLLER 66" MINIMUM DRUM WIDTH

A. General Conditions:

- 1. <u>Current Model</u>: Units furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Machines manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable. Manufacturers of the units supplied must have been in the business of producing operational units for at least two years and must have recently sold similar units to domestic governmental agencies. The model furnished must have been in production for a minimum of one year, or be the latest version of a previous model. Bidder/s may be required to submit documentation substantiating the aforementioned requirements. A list of user references may also be required.
- 2. <u>Literature</u>: Manufacturers literature, verifying adherence of proposed unit to each line item addressed in this specification, shall be submitted with the bid. If any literature and/or specifications of items conflict with AHTD specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.
- 3. Any deviations from specifications and requirements herein must be clearly pointed out by bidder. Otherwise it will be considered that equipment offered is in strict compliance with these specifications and requirements, and successful bidder will be held responsible therefor. Deviations must be explained in detail on an attached sheet. However, no implication is made by the Arkansas State Highway and Transportation Department that deviations will be acceptable.
- 4. <u>Manuals</u>: The successful bidder shall furnish one (1) Operator's Instruction Manual with each unit delivered and one (1) copy each of Shop Repair Manual and Parts Book to each FOB point. The successful bidder may provide Shop Repair Manuals and Parts Manuals on computer media (CD ROM, Floppy Disks, etc.) in lieu of printed manuals.
- 5. <u>Training</u>: The successful bidder shall furnish qualified personnel to instruct AHTD personnel on operation and maintenance of units purchased under this specification.
 - In addition, the successful bidder shall furnish information on any factory service schools, which would be available for AHTD service technicians.
- 6. Units shall be assembled, adjusted and made ready for continuous operation at time of delivery.
- 7. All parts, accessories and tools necessary for satisfactory operation of this unit shall be furnished whether or not they are specifically mentioned in this specification (Including Standard Equipment as regularly furnished by manufacturer as shown on printed literature and specifications unless specifically excluded by this specification.
- 8. <u>Parts Inventory & Service Facilities</u>: The successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
- 9. <u>Demonstration</u>: The Arkansas State Highway & Transportation Department reserves the right to require a demonstration, under actual working conditions, of equipment bid under this specification before award is made. The demonstration would be performed (free of any charge) by the bidder or an authorized representative at a mutually acceptable location. If requested, the bidder should be prepared to demonstrate the equipment within thirty (30) days after notification. Failure of the bidder to perform a satisfactory demonstration within the specified time may be grounds for rejection of the bid.
- 10. Cooperative Purchasing: Other tax-supported entities* in Arkansas (cities, counties, state agencies, school districts, etc.) may purchase from this Contract on an individual basis under the same specifications and conditions, and at the pricing set forth by each vendor, all at the discretion of each vendor in each case. Prices could be reduced by a vendor for minor alterations in conditions (changing order quantities, deleting options, etc.) as agreed by both parties, but could not be raised above the contract bid price except for any additional freight charges. Vendors would not be required to sell to any such entity under this contract, and those entities would not be obligated to purchase from the contract.

Each entity wishing to purchase from the contract must make contact directly with the appropriate vendor(s). The Highway Department shall remain "out of the loop" for such transactions: all contact, orders, invoices, payments, etc. regarding such transactions must take place exclusively between the tax-supported entity and the vendor. The Department shall be held harmless of any and all liability arising from such transactions.

Page 2 Spec. 17-238A-148

* Tax-supported entities are defined as those receiving more than half of total funding from appropriated tax funds.

B. <u>Unit Specifications</u>:

- 1. <u>General</u>: This specification is intended to cover a self-propelled double vibratory drum roller specifically designed for the compaction of asphalt and other select granular soils. Machine shall be of articulated frame type and have a minimum operating weight with ROPS/FOPS canopy of 21,400 pounds.
- 2. <u>Engine</u>: Liquid cooled diesel developing a minimum of 120 gross horsepower at rated RPM. Engine shall be equipped with electric starter, alternator, ammeter or charge indicator, battery, governor, approved type air cleaner, lube oil and fuel filters, muffler, hour meter, and all other equipment necessary for efficient operation. Fuel tank shall have a minimum capacity of 45 gallons. Cooling system shall have anti-freeze protection to -20° F, or lower.
- 3. <u>Drums</u>: The roller shall be equipped with two (2) smooth vibratory drums in tandem. Each drum shall be no less than 66" wide but shall not exceed 69". Each drum shall have a minimum diameter of 47".
- 4. <u>Vibration</u>: The vibration system shall have a minimum of two (2) frequency settings and provide at least one frequency of no less than 3,000 vpm. The system shall be capable of at least two (2) amplitudes and of producing a maximum centrifugal force of no less than 18,000 pounds. Shall be equipped with a system for absorbing the transmission of vibration to the operator.
- 5. <u>Drive</u>: Hydrostatic full reversing type with a hydraulic drive motor mounted at each drum. The drive system shall be independent of the vibratory system. Speeds shall be variable up to no less than 7 mph.
- 6. <u>Controls</u>: All controls shall be convenient to operator from both sides of operator's platform.
- 7. <u>Steering</u>: The chassis shall articulate and oscillate. The steering system shall be hydraulically operated, actuated by means of a steering wheel or joystick, and have double acting steering cylinder/s.
- 8. <u>Brakes</u>: Service brakes shall be dynamic through the hydrostatic transmission. Parking/emergency brake shall be spring applied and hydraulically released. Parking/emergency brake shall apply automatically at loss of hydraulic pressure. Braking system shall meet the requirements of SAE J1472.
- 9. <u>Water Sprinkler System</u>: Shall have a pressure type sprinkler system with a spray bar at each drum. Shall be equipped with rust-proof polyethylene water tank/s providing a total water capacity of no less than 220 gallons.
- 10. Scrapers: Each drum shall be equipped with full width rubber scrapers, rubber mats, or coco mats.
- 11. ROPS/FOPS: Shall be equipped with a ROPS/FOPS canopy, seat and seat belts meeting the requirements of SAE J1040 and J231.
- 12. Vandalism Protection: Shall be equipped with vandalism protection including the following items as a minimum:
 - a. Lockable engine side panels or enclosure.
 - b. Lockable instrument panel.
 - c. Lockable filler caps for the fuel tank/s and radiator. Filler caps located behind locking panels or inside engine enclosure are acceptable in lieu of individual locking caps.
 - d. Lockable battery box cover/s, if battery is not located inside engine enclosure.
- 13. <u>Instruments and Gauges</u>: In addition to those already specified, the unit shall be equipped with the following as a minimum:
 - a. Fuel gauge
 - b. Engine tachometer
 - c. Engine oil pressure gauge or indicator
 - d. Engine coolant temperature gauge or indicator
 - e. Parking brake "ON" indicator
 - f. Sprinkler system "ON" indicator

Page 3

Spec. 17-238A-148

- g. Vibration "ON" indicator
- 14. <u>Asphalt Temperature Sensor</u>: Roller shall be equipped with an asphalt temperature sensor. Sensor shall be programmable allowing the operator to establish high and low temperature parameters for the mix design being compacted. Sensor shall contain a warning feature that notifies the operator if the mix temperature is outside the set parameters. The sensor display shall be mounted in a convent location for the operator.
- 15. Additional Equipment:
 - a. No less than two (2) head lights
 - b. No less than two (2) rear working lights
 - c. Turn signals
 - d. Horn
 - e. Backup alarm meeting the requirements of SAE J994 with a minimum sound level output of 97 decibels
- 16. <u>Color</u>: Manufacturer's standard color is acceptable.
- 17. <u>Warranty</u>: Units purchased under this specification shall be warranted against defects in material and workmanship for a minimum period of twelve (12) months (365 days) from date unit is placed in operation by AHTD.
 - a. Warranty shall include all parts, labor and transportation costs to the location of equipment.
 - b. If equipment cannot be repaired on location, warranty shall include cost of transport to the facility where the repair work will be done.
 - c. It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
 - d. If any warranty literature submitted with the bid conflicts with AHTD warranty requirements, the conflict(s) shall be specifically noted, corrected and included with the bid or the conflict(s) will be considered an exception to warranty specifications and the bid rejected.
 - e. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment. For the purposes of this paragraph "timely manner" means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph "manufacturer" means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph "replacement part" means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is capable of providing dependable performance in normal operation conditions for its normal service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.

ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT

SPECIFICATION 17-237A-148

FOR

DOUBLE DRUM VIBRATORY ROLLER 58" MINIMUM DRUM WIDTH

A. General Conditions:

- 1. <u>Current Model</u>: Units furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Machines manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable. Manufacturers of the units supplied must have been in the business of producing operational units for at least two years and must have recently sold similar units to domestic governmental agencies. The model furnished must have been in production for a minimum of one year, or be the latest version of a previous model. Bidder/s may be required to submit documentation substantiating the aforementioned requirements. A list of user references may also be required.
- 2. <u>Literature</u>: Manufacturers literature, verifying adherence of proposed unit to each line item addressed in this specification, shall be submitted with the bid. If any literature and/or specifications of items conflict with AHTD specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.
- 3. Any deviations from specifications and requirements herein must be clearly pointed out by bidder. Otherwise it will be considered that equipment offered is in strict compliance with these specifications and requirements, and successful bidder will be held responsible therefor. Deviations must be explained in detail on an attached sheet. However, no implication is made by the Arkansas State Highway and Transportation Department that deviations will be acceptable.
- 4. <u>Manuals</u>: The successful bidder shall furnish one (1) Operator's Instruction Manual with each unit delivered and one (1) copy each of Shop Repair Manual and Parts Book to each FOB point. The successful bidder may provide Shop Repair Manuals and Parts Manuals on computer media (CD ROM, Floppy Disks, etc.) in lieu of printed manuals.
- 5. <u>Training</u>: The successful bidder shall furnish qualified personnel to instruct AHTD personnel on operation and maintenance of units purchased under this specification.
 - In addition, the successful bidder shall furnish information on any factory service schools, which would be available for AHTD service technicians.
- 6. Units shall be assembled, adjusted and made ready for continuous operation at time of delivery.
- 7. All parts, accessories and tools necessary for satisfactory operation of this unit shall be furnished whether or not they are specifically mentioned in this specification (Including Standard Equipment as regularly furnished by manufacturer as shown on printed literature and specifications unless specifically excluded by this specification.
- 8. <u>Parts Inventory & Service Facilities</u>: The successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
- 9. <u>Demonstration</u>: The Arkansas State Highway & Transportation Department reserves the right to require a demonstration, under actual working conditions, of equipment bid under this specification before award is made. The demonstration would be performed (free of any charge) by the bidder or an authorized representative at a mutually acceptable location. If requested, the bidder should be prepared to demonstrate the equipment within thirty (30) days after notification. Failure of the bidder to perform a satisfactory demonstration within the specified time may be grounds for rejection of the bid.
- 10. Cooperative Purchasing: Other tax-supported entities* in Arkansas (cities, counties, state agencies, school districts, etc.) may purchase from this Contract on an individual basis under the same specifications and conditions, and at the pricing set forth by each vendor, all at the discretion of each vendor in each case. Prices could be reduced by a vendor for minor alterations in conditions (changing order quantities, deleting options, etc.) as agreed by both parties, but could not be raised above the contract bid price except for any additional freight charges. Vendors would not be required to sell to any such entity under this contract, and those entities would not be obligated to purchase from the contract.

Each entity wishing to purchase from the contract must make contact directly with the appropriate vendor(s). The Highway Department shall remain "out of the loop" for such transactions: all contact, orders, invoices, payments, etc. regarding such transactions must take place exclusively between the tax-supported entity and the vendor. The Department shall be held harmless of any and all liability arising from such transactions.

Page 2 Spec. 17-237A-148

* Tax-supported entities are defined as those receiving more than half of total funding from appropriated tax funds.

B. <u>Unit Specifications</u>:

- 1. <u>General</u>: This specification is intended to cover a self-propelled double vibratory drum roller specifically designed for the compaction of asphalt and other select granular soils. Machine shall be of articulated frame type and have a minimum operating weight with ROPS canopy of 15,500 pounds.
- 2. <u>Engine</u>: Liquid cooled diesel developing a minimum of 73 gross horsepower at rated RPM. Engine shall be equipped with electric starter, alternator, ammeter or charge indicator, battery, governor, approved type air cleaner, lube oil and fuel filters, muffler, hour meter, and all other equipment necessary for efficient operation. Fuel tank shall have a minimum capacity of 30 gallons. Cooling system shall have anti-freeze protection to -20° F, or lower.
- 3. <u>Drums</u>: The roller shall be equipped with two (2) smooth vibratory drums in tandem. Each drum shall be no less than 58" wide but shall not exceed 60". Each drum shall have a minimum diameter of 42".
- 4. <u>Vibration</u>: The vibration system shall have a minimum of two (2) frequency settings and provide no less than 3,000 vpm. The system shall be capable of producing a maximum centrifugal force of no less than 15,000 pounds. Shall be equipped with a system for absorbing the transmission of vibration to the operator.
- 5. <u>Drive</u>: Hydrostatic full reversing type with a hydraulic drive motor mounted at each drum. The drive system shall be independent of the vibratory system. Speeds shall be variable up to no less than 7 mph.
- 6. <u>Controls</u>: All controls shall be conveniently located for the operator.
- 7. <u>Steering</u>: The chassis shall articulate and oscillate. The steering system shall be hydraulically operated, actuated by means of a steering wheel or joystick, and have double acting steering cylinder/s.
- 8. <u>Brakes</u>: Service brakes shall be dynamic through the hydrostatic transmission. Parking/emergency brake shall be spring applied and hydraulically released. Parking/emergency brake shall apply automatically at loss of hydraulic pressure. Braking system shall meet the requirements of SAE J1472.
- 9. <u>Water Sprinkler System</u>: Shall have a pressure type sprinkler system with a spray bar at each drum. Shall be equipped with rust-proof polyethylene water tank/s providing a total water capacity of no less than 150 gallons.
- 10. Scrapers: Each drum shall be equipped with full width scrapers, rubber mats, or coco mats.
- 11. ROPS: Shall be equipped with a ROPS canopy, seat and seat belts meeting the requirements of SAE J1040.
- 12. <u>Vandalism Protection</u>: Shall be equipped with vandalism protection including the following items as a minimum:
 - a. Lockable engine side panels or enclosure.
 - b. Lockable instrument panel.
 - c. Lockable filler caps for the fuel tank/s and radiator. Filler caps located behind locking panels or inside engine enclosure are acceptable in lieu of individual locking caps.
 - d. Lockable battery box cover/s, if battery is not located inside engine enclosure.
- 13. <u>Instruments and Gauges</u>: In addition to those already specified, the unit shall be equipped with the following as a minimum:
 - a. Fuel gauge
 - b. Engine tachometer
 - Engine oil pressure gauge or indicator
 - d. Engine coolant temperature gauge or indicator
 - e. Parking brake "ON" indicator
 - f. Sprinkler system "ON" indicator
 - g. Vibration "ON" indicator

Spec. 17-237A-148

14. Additional Equipment:

- a. No less than two (2) head lights
- b. No less than two (2) rear working lights
- c. Turn signals
- d. Horn
- e. Backup alarm meeting the requirements of SAE J994 with a minimum sound level output of 97 decibels
- 15. <u>Asphalt Temperature Sensor</u>: Roller shall be equipped with an asphalt temperature sensor. Sensor shall be programmable allowing the operator to establish high and low temperature parameters for the mix design being compacted. Sensor shall contain a warning feature that notifies the operator if the mix temperature is outside the set parameters. The sensor display shall be mounted in a convent location for the operator.
- 16. Color: Manufacturer's standard color is acceptable.
- 17. <u>Warranty</u>: Units purchased under this specification shall be warranted against defects in material and workmanship for a minimum period of twelve (12) months (365 days) from date unit is placed in operation by AHTD.
 - a. Warranty shall include all parts, labor and transportation costs to the location of equipment.
 - b. If equipment cannot be repaired on location, warranty shall include cost of transport to the facility where the repair work will be done.
 - c. It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
 - d. If any warranty literature submitted with the bid conflicts with AHTD warranty requirements, the conflict(s) shall be specifically noted, corrected and included with the bid or the conflict(s) will be considered an exception to warranty specifications and the bid rejected.
 - e. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment. For the purposes of this paragraph "timely manner" means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph "manufacturer" means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph "replacement part" means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is capable of providing dependable performance in normal operation conditions for its normal service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.

ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT

SPECIFICATION 17-235A-139

FOR

DOUBLE DRUM VIBRATORY ROLLER 47" MINIMUM DRUM WIDTH

A. General Conditions:

- 1. <u>Current Model</u>: Units furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Machines manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable. Manufacturers of the units supplied must have been in the business of producing operational units for at least two years and must have recently sold similar units to domestic governmental agencies. The model furnished must have been in production for a minimum of one year, or be the latest version of a previous model. Bidder/s may be required to submit documentation substantiating the aforementioned requirements. A list of user references may also be required.
- 2. <u>Literature</u>: Manufacturers literature, verifying adherence of proposed unit to each line item addressed in this specification, shall be submitted with the bid. If any literature and/or specifications of items conflict with AHTD specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.
- 3. Any deviations from specifications and requirements herein must be clearly pointed out by bidder. Otherwise it will be considered that equipment offered is in strict compliance with these specifications and requirements, and successful bidder will be held responsible therefor. Deviations must be explained in detail on an attached sheet. However, no implication is made by the Arkansas State Highway and Transportation Department that deviations will be acceptable.
- 4. <u>Manuals</u>: The successful bidder shall furnish one (1) Operator's Instruction Manual with each unit delivered and one (1) copy each of Shop Repair Manual and Parts Book to each FOB point. The successful bidder may provide Shop Repair Manuals and Parts Manuals on computer media (CD ROM, Floppy Disks, etc.) in lieu of printed manuals.
- 5. <u>Training</u>: The successful bidder shall furnish qualified personnel to instruct AHTD personnel on operation and maintenance of units purchased under this specification.
 - In addition, the successful bidder shall furnish information on any factory service schools, which would be available for AHTD service technicians.
- 6. Units shall be assembled, adjusted and made ready for continuous operation at time of delivery.
- 7. All parts, accessories and tools necessary for satisfactory operation of this unit shall be furnished whether or not they are specifically mentioned in this specification (Including Standard Equipment as regularly furnished by manufacturer as shown on printed literature and specifications unless specifically excluded by this specification.
- 8. <u>Parts Inventory & Service Facilities</u>: The successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
- 9. <u>Demonstration</u>: The Arkansas State Highway & Transportation Department reserves the right to require a demonstration, under actual working conditions, of equipment bid under this specification before award is made. The demonstration would be performed (free of any charge) by the bidder or an authorized representative at a mutually acceptable location. If requested, the bidder should be prepared to demonstrate the equipment within thirty (30) days after notification. Failure of the bidder to perform a satisfactory demonstration within the specified time may be grounds for rejection of the bid.
- 10. Cooperative Purchasing: Other tax-supported entities* in Arkansas (cities, counties, state agencies, school districts, etc.) may purchase from this Contract on an individual basis under the same specifications and conditions, and at the pricing set forth by each vendor, all at the discretion of each vendor in each case. Prices could be reduced by a vendor for minor alterations in conditions (changing order quantities, deleting options, etc.) as agreed by both parties, but could not be raised above the contract bid price except for any additional freight charges. Vendors would not be required to sell to any such entity under this contract, and those entities would not be obligated to purchase from the contract.

Each entity wishing to purchase from the contract must make contact directly with the appropriate vendor(s). The Highway Department shall remain "out of the loop" for such transactions: all contact, orders, invoices, payments, etc. regarding such transactions must take place exclusively between the tax-supported entity and the vendor. The Department shall be held harmless of any and all liability arising from such transactions.

Page 2 Spec. 17-235A-139

* Tax-supported entities are defined as those receiving more than half of total funding from appropriated tax funds.

B. <u>Unit Specifications</u>:

- 1. <u>General</u>: This specification is intended to cover a self-propelled double drum vibratory roller specifically designed for the compaction of asphalt and other select granular soils. Machine shall be of articulated frame type and have a minimum operating weight with ROPS canopy of 5,500 pounds.
- 2. <u>Engine</u>: Liquid cooled diesel developing a minimum of 24 gross horsepower at rated RPM. Engine shall be equipped with electric starter, alternator, ammeter or charge indicator, battery, governor, approved type air cleaner, lube oil and fuel filters, muffler, hour meter, and all other equipment necessary for efficient operation. Fuel tank shall be of sufficient capacity to allow a minimum of eight (8) hours of continuous operation. Cooling system shall have antifreeze protection to -20° F, or lower.
- 3. <u>Drums</u>: The roller shall be equipped with two (2) smooth vibratory drums in tandem. Each drum shall be no less than 47" wide but shall not exceed 50". Each drum shall have a minimum diameter of 27".
- 4. <u>Vibration</u>: The vibration system shall have a minimum of one (1) frequency settings and provide no less than 3,000 vpm. The system shall be capable of producing a maximum centrifugal force of no less than 6,500 pounds. Shall be equipped with a system for absorbing the transmission of vibration to the operator.
- 5. <u>Drive</u>: Hydrostatic full reversing type with a hydraulic drive motor mounted at each drum. The drive system shall be independent of the vibratory system. Speeds shall be variable up to no less than 6 mph.
- 6. Operator's Station: All controls shall be conveniently located for the operator.
- 7. <u>Steering</u>: The chassis shall articulate and oscillate. The steering system shall be hydraulically operated, actuated by means of a steering wheel or joystick, and have double acting steering cylinder/s.
- 8. <u>Brakes</u>: Service brakes shall be dynamic through the hydrostatic transmission. Parking/emergency brake shall be spring applied and hydraulically released. Parking/emergency brake shall apply automatically at loss of hydraulic pressure. Braking system shall meet the requirements of SAE J1472.
- 9. <u>Water Sprinkler System</u>: Shall have a pressure type sprinkler system with a spray bar at each drum. Shall be equipped with rust-proof polyethylene water tank/s providing a total water capacity of no less than 50 gallons.
- 10. Scrapers: Each drum shall be equipped with full width scrapers and rubber or coco mats.
- 11. ROPS: Shall be equipped with a ROPS, seat and seat belt meeting the requirements of SAE J1040.
- 12. <u>Vandalism Protection</u>: Shall be equipped with vandalism protection including the following items as a minimum:
 - a. Lockable engine side panels or enclosure.
 - b. Lockable instrument panel.
 - c. Lockable filler caps for the fuel tank/s and radiator. Filler caps located behind locking panels or inside engine enclosure are acceptable in lieu of individual locking caps.
 - d. Lockable battery box cover/s, if battery is not located inside engine enclosure.
- 13. <u>Instruments and Gauges</u>: In addition to those already specified, the unit shall be equipped with the following as a minimum:
 - a. Fuel gauge
 - b. Engine tachometer
 - c. Engine oil pressure gauge or indicator
 - d. Engine coolant temperature gauge or indicator
 - e. Parking brake "ON" indicator
 - f. Sprinkler system "ON" indicator

Spec. 17-235A-139

g. Vibration "ON" indicator

14. Additional Equipment:

- a. No less than two (2) LED head lights
- b. No less than one (1) LED rear working lights
- c. Turn signals and hazard flashers
- d. Horn
- e. Backup alarm meeting the requirements of SAE J994 with a minimum sound level output of 97 decibels
- 15. Color: Manufacturer's standard color is acceptable.
- 16. <u>Warranty</u>: Units purchased under this specification shall be warranted against defects in material and workmanship for a minimum period of twelve (12) months (365 days) from date unit is placed in operation by AHTD.
 - a. Warranty shall include all parts, labor and transportation costs to the location of equipment.
 - b. If equipment cannot be repaired on location, warranty shall include cost of transport to the facility where the repair work will be done.
 - c. It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
 - d. If any warranty literature submitted with the bid conflicts with AHTD warranty requirements, the conflict(s) shall be specifically noted, corrected and included with the bid or the conflict(s) will be considered an exception to warranty specifications and the bid rejected.
 - e. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment. For the purposes of this paragraph "timely manner" means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph "manufacturer" means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph "replacement part" means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is capable of providing dependable performance in normal operation conditions for its normal service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.