### ARKANSAS STATE HIGHWAY COMMISSION ARDOT-EQUIPMENT AND PROCUREMENT DIVISION BID INVITATION

Contract Number:	H-18-28	89H		BID OPENING LOCATION: ARDOT Equipment and	MAIL TO: ARDOT Equipment and	DELIVER TO: ARDOT Equipment and	
Bid Opening Date:	June 5, 2018	Time:	11:00 a.m.	Procurement Division 11302 West Baseline Road Little Rock, AR 72209	Procurement Division P.O. Box 2261 Little Rock, AR 72203	Procurement Division 11302 West Baseline Road	
mail and delivery loo	cations until the above-noted b	oid opening	date and time, and t	ject to the Standard Bid Conditions o then publicly opened at the above-not bids and unsigned bids will not be o	ed bid opening location. Bid		
In compliance with t price set opposite ea		all the Cor	nditions thereof, the u	indersigned offers and agrees to furnis	h any and all items upon whic	ch prices are quoted, at the	
Company Name:				Name (Type or Print):			
Address:				Title:			
				Phone:	Fax:		
City:	State:		Zip:	E-Mail:			
Federal Tax ID or	Social Security No.:				original (not photocopied) and	d in ink.	

## Cab & Chassis

Bid prices shall include any applicable labor cost as well as delivery of all Equipment to ARDOT at the F.O.B. location(s) shown on attached Bid Sheet.

Contract may be renewed or extended upon mutual agreement of the parties, but shall not exceed limitations allowed by Arkansas State Procurement Law.

All bidders should complete and return the Eligible Bidder Certification (Attachment A) and Disclosure Form (see Page 2 of Standard Bid Conditions – Item 18) and Restriction of Boycott of Israel Certification issued with this bid. A current copy of the DFA Illegal Immigrant Contractor Disclosure Certification (see Page 1 of Standard Bid Conditions – Item 17) should also be submitted with bid. These forms are kept on file and remain current for one year from date of submission. Forms do not need to be submitted again, during that time, unless there is a status change.

## Literature Submittals – Item B2 of Bid Specifications shall supersede Item #11 of Standard Bid Conditions.

**Bid Bond** in the amount of \$1,000 required of all bidders at time of bid opening or bid will be rejected. <u>Personal and</u> <u>company checks are not acceptable as Bid Bonds</u>. See Condition 4 on page 1of Standard Bid Conditions. **Performance Bond** in the amount of 5% of the total awarded to the respective bidders must be furnished within 10 days

after receipt of notice of intent to award as a guarantee of delivery in accordance with the specifications and within the time established in the bid. <u>Personal and company checks are not acceptable as Performance Bonds.</u> See Condition 4 on page 1 of Standard Bid Conditions.

Bidder shall specify guaranteed delivery date for all vehicles/equipment in the space provided under each item number for which a price is being submitted. Successful bidder shall furnish Warranty Data for each vehicle/equipment delivered. The Warranty Data shall contain all necessary information such as motor and/or serial numbers and shall be signed by the selling dealer at the time vehicle/equipment is delivered to the Department of Transportation. Certificate of Origin, Federal Excise Tax Exemption Certificates, Odometer Disclosure Statement and five (5) copies of the Invoice for each vehicle/equipment to be furnished to Equipment & Procurement Division, P.O. Box 2261, Little Rock, AR 72203.

The successful bidder will be required to complete delivery within 180 days after award.

Bids and Specifications are available on-line by going to the ARDOT Web Site – <u>www.ardot.go</u>v and clicking on "Commodities and Services Bids/Contracts Information". Tabulations will also be available at this site after award of bid/contract. If you have any questions, call this office at 501-569-2667. 64-8212, 64-8217

00-25, 00-26, 01-07

## ARKANSAS STATE HIGHWAY COMMISSION ARDOT-EQUIPMENT AND PROCUREMENT DIVISION

## **BID SHEET**

Cont	tract No.: <mark>H-18-289H</mark>	BIDDER:		
1.		R, 175" CA, Automatic Transmissi D' Horizontal Reach to meet ARL		
		Ieadquarters, 2911 Highway 29 M Ieadquarters, 1673 Batesville Bo		
	Bid Price (Do not include any L	ocal, State or Federal Taxes)		
	2	each – Unit Price \$	Amount \$	
	Guaranteed Delivery Date Additional Units may be purcha conditions through	used at the same pricing and		
			Bid Total \$	
ADD	ITIONAL INFORMATION			
Hyd	raulic Truck Crane propose	d as meeting specifications:		
Make	:Model:			
Warr	anty:Each \$			

Attachments must be priced individually but bid will be awarded by the unit price of the complete unit.

## **ARKANSAS STATE HIGHWAY COMMISSION**

## **ARDOT - STANDARD BID CONDITIONS**

- 1. **GENERAL:** Any special terms and conditions included in the invitation for bid override these standard terms and conditions. The standard terms and conditions and any special terms and conditions become part of any contract entered into if any or all parts of the bid are accepted by the Arkansas Department of Transportation (ARDOT).
- ACCEPTANCE AND REJECTION: ARDOT reserves the right to reject any or all bids, to accept bids in whole or in part (unless otherwise indicated by bidder), to waive any informalities in bids received, to accept bids on materials or equipment with variations from specifications where efficiency of operation will not be impaired, and to award bids to best serve the interest of the State.
- 3. **PRICES:** Unless otherwise stated in the Bid Invitation, the following will apply: (1) unit prices shall be bid, (2) prices should be stated in units of quantity specified (feet, each, lbs., etc.), (3) prices must be F.O.B. destination specified in bid, (4) prices must be firm and not subject to escalation, (5) bid must be firm for acceptance for 30 days from bid opening date. In case of errors in extension, unit prices shall govern. Discounts from bid price will not be considered in making awards.
- BID BONDS AND PERFORMANCE BONDS: If required, a Bid Bond in the form of a cashier's check, certified check, or 4 surety bond issued by a surety company, in an amount stated in the Bid Invitation, must accompany bid. Personal and company checks are not acceptable as Bid Bonds. Failure to submit a Bid Bond as required will cause a bid to be rejected. The Bid Bond will be forfeited as liquidated damages if the successful bidder fails to provide a required Performance Bond within the period stipulated by ARDOT or fails to honor their bid. When a bidder claims and can show clear and convincing evidence that a material mistake was made in the bid and was not the bid intended, the bidder may be permitted to withdraw their bid prior to award without forfeiture of bid bond. Cashier's checks and certified checks submitted as Bid Bonds will be returned to unsuccessful bidders; surety bonds will be retained. The successful bidder will be required to furnish a Performance Bond in an amount stated in the Bid Invitation and in the form of a cashier's check, certified check, or surety bond issued by a surety company, unless otherwise stated in the Bid Invitation, as a guarantee of delivery of goods/services in accordance with the specifications and within the time established in the bid. Personal and company checks are not acceptable as Performance Bonds. In some cases, a cashier's check or certified check submitted as a Bid Bond will be held as the Performance Bond of the successful bidder. Cashier's checks or certified checks submitted as Performance Bonds will be refunded shortly after payment has been made to the successful bidder for completion of all terms of the bid; surety bonds will be retained. Surety bonds must be issued by a surety company that is authorized to do business in the State of Arkansas and that is listed on the current United States Department of the Treasury Listing of Approved Sureties. Surety bonds must be executed by a resident or non-resident agent who is licensed by the Arkansas State Insurance Commissioner to represent the surety company executing the bond, and the resident or non-resident agent shall file with the bond the power of attorney of the agent to act on behalf of the bonding company. Certain bids involving labor will require Performance Bonds in the form of surety bonds only (no checks of any kind allowed). These bonds shall not only serve to guarantee the completion of the work, but also to guarantee the excellence of both workmanship and material until the work is finally accepted and the provisions of the Plans, Specifications, and Special Provisions fulfilled. In such cases, the company issuing the surety bond must comply with all stipulations herein and must be named in the U.S. Treasury listing of companies holding Certificates of Authority as acceptable sureties on Federal Bonds and as acceptable reinsuring companies. Any excess between the face amount of the bond and the underwriting limitation of the bonding company shall be protected by reinsurance provided by an acceptable reinsuring company. Annual Bid and Performance Bonds on file with E & P Division must have sufficient unencumbered funds to meet current bonding requirements, or the bid will be rejected, unless the balance is submitted as set forth above, prior to bid opening.
- 5. TAXES: The ARDOT is not exempt from Arkansas State Sales and Use Taxes, or local option city/county sales taxes, when applicable, and bidders are responsible to the State Revenue Department for such taxes. These taxes should not be included in bid prices, but where required by law, will be paid by the ARDOT as an addition thereto, and should be added to the billing to the ARDOT. The ARDOT is exempt from Federal Excise Taxes on all commodities except motor fuels; and excise taxes should not be included in bid prices except for motor fuels. Where applicable, tax exemption certificates will be furnished by the ARDOT.
- 6. **"ALL OR NONE" BIDS:** Bidders who wish to bid "All or None" on two or more items shall so stipulate on the face of bid sheet; otherwise, bid may be awarded on an individual item basis.
- 7. **SPECIFICATIONS:** Complete specifications should be attached for any substitution or alternate offered, or where amplification is necessary. Bidder's name must be placed on all attachments to the bid.
- 8. **EXCEPTIONS TO SPECIFICATIONS:** Any exceptions to the bid specifications must be stated in the bid. Any exceptions to manufacturer's published literature must be stated in the bid, or it will be assumed that bidder is bidding exactly as stated in the literature.
- 9. BRAND NAME REFERENCES: All brand name references in bid specifications refer to that commodity or its equivalent, unless otherwise stated in Bid Invitation. Bidder should state brand or trade name of item being bid, if such name exists.
- 10. **FREIGHT:** All freight charges should be included in bid price. Any change in common carrier rates authorized by the Interstate Commerce Commission will be adjusted if such change occurs after the bid opening date. Receipted common carrier bills that reflect ICC authorized rate changes must be furnished.

## **ARDOT - STANDARD BID CONDITIONS**

- 11. **SAMPLES, LITERATURE, DEMONSTRATIONS:** Samples and technical literature must be provided free of any charge within 14 days of ARDOT request, and free demonstrations within 30 days, unless ARDOT extends time. Failure to provide as requested within this period may cause bid to be rejected. Samples, literature and demonstrations must be substantially the same as the item(s) being bid, unless otherwise agreed to by ARDOT. Samples that are not destroyed will be returned upon request at bidders expense. Samples from successful bidders may be retained for comparison with items actually furnished.
- 12. **GUARANTY:** Unless otherwise indicated in Bid Invitation, it is understood and agreed that any item offered or shipped on this bid shall be newly manufactured, latest model and design, and in first class condition; and that all containers shall be new, suitable for storage or shipment and in compliance with all applicable laws relating to construction, packaging, labeling and registration.
- 13. BACKORDERS OR DELAY IN DELIVERY: Backorders or failure to deliver within the time required may constitute default. Vendor must give written notice to the ARDOT, as soon as possible, of the reason for any delay and the expected delivery date. The ARDOT has the right to extend delivery if reasons appear valid. If reason or delivery date is not acceptable, vendor is in default.
- 14. **DEFAULT:** All commodities furnished will be subject to inspection and acceptance by ARDOT after delivery. Default in promised delivery or failure to meet specifications authorizes the ARDOT to cancel award or any portion of same, to reasonably purchase commodities or services elsewhere and to charge full increase, if any, in cost and handling to defaulting vendor. Applicable bonds may be forfeited.
- 15. ETHICS: "It shall be a breach of ethical standards for a person to be retained, or to retain a person, to solicit or secure a State contract upon an agreement of understanding for a commission, percentage, brokerage, or contingent fee, except for retention of bona fide employees or bona fide established commercial selling agencies maintained by the contractor for the purpose of securing business." (Arkansas Code, Annotated, Section 19-11-708).
- 16. NOTICE OF NONDISCRIMINATION: The Arkansas State Highway Commission, through ARDOT, complies with all civil rights provisions of federal statutes and related authorities that prohibit discrimination in programs and activities receiving federal financial assistance. Therefore, ARDOT does not discriminate on the basis of race, sex, color, age, national origin, religion (not applicable as a protected group under the Federal Motor Carrier Safety Administration Title VI Program), disability, Limited English Proficiency (LEP), or low-income status in the admission, access to and treatment in the ARDOT's programs and activities, as well as the ARDOT's hiring or employment practices. Complaints of alleged discrimination and inquiries regarding the ARDOT's nondiscrimination policies may be directed to Joanna P. McFadden Section Head EEO/DBE (ADA/504/Title VI Coordinator), P. O. Box 2261, Little Rock, AR 72203, (501)569-2298, (Voice/TTY 711), or the following email address: joanna.mcfadden@ahtd.ar.gov. Free language assistance for Limited English Proficient individuals is available upon request. This notice is available from the ADA/504/Title VI Coordinator in large print, on audiotape and in Braille.
- 17. PROHIBITION OF EMPLOYMENT OF ILLEGAL IMMIGRANTS: Pursuant to Arkansas Code Annotated 19-11-105, all bidders must certify prior to award of a contract that they <u>do not</u> employ or contract with any illegal immigrant(s) in its contract with the state. Bidders shall certify online at <u>https://www.ark.org/dfa/immigrant/index.php</u>.
- 18. **DISCLOSURE:** Failure to make any disclosure required by Governor's Executive Order 98-04, or any violation of any rule, regulation, or policy adopted pursuant to that order, **shall** be a material breach of the terms of this contract. Any contractor, whether an individual or entity, who fails to make the required disclosure or who violates any rule, regulation, or policy **shall** be subject to all legal remedies available to the agency.

## ATTACHMENT A

## **ELIGIBLE BIDDER CERTIFICATION**

The Bidder represents and warrants for itself, its employees and its subcontractors and certifies they:

- 1. Are not presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from covered transactions by any Federal department or agency;
- 2. Have not within a three-year period preceding thus Bid been convicted of or had a civil judgment rendered against them for commission of fraud or a criminal offense in connection with obtaining, attempting to obtain, or performing a public (Federal, State, or local) transaction or contract under a public transaction; violation of Federal or State antitrust statutes or commission of embezzlement, theft, forgery, bribery, falsification or destruction of records, making false statements, or receiving stolen property;
- 3. Are not presently indicted for or otherwise criminally or civilly charged by a governmental entity (Federal, State, or local) with commission of any of the offenses enumerated in paragraph two (2) of this Certification;
- 4. Have not within a one-year period preceding this application/Bid had one or more public transactions (Federal, State, or local) terminated for cause or default; and

The Bidder represents, warrants and acknowledges the understanding that restrictions placed on the employment of labor or on the scale of pay for the work on a contract will be the requirements of the Fair Labor Standards Act (Federal Wage-Hour Law) of 1938, 28 USC §201 et seq., and other applicable labor laws.

The person executing this Certification further represents, warrants and affirms the truthfulness and accuracy of the contents of the statements submitted on or with this Certification and understands that the provisions of 31 USC §3801 et seq. are applicable thereto.

BIDDER NAME

BY:\_\_\_\_\_\_Signature

TITLE:\_\_\_\_\_

## CONTRACT AND GRANT DISCLOSURE AND CERTIFICATION FORM

Failure to complete all of t	the following i	nformation	may result in a delay in obtaining	a contract, l	ease, purch	ase agreement, or grant award with any Arkansas State Agency.	
SUBCONTRACTOR:	SUBCONTRAC	TOR NAME:					
🗆 Yes 🔲 No							
			IS THIS FOR:				
TAXPAYER ID NAME:			□Goods? □	Services?		oth?	
YOUR LAST NAME:			FIRST NAME:			M.I.:	
ADDRESS:							
CITY:			STATE:		ZIP CODE:	COUNTY:	
AS A CONDITION O	OF OBTAIN	VING, EX	TENDING, AMENDING,	OR RENE	WING	CONTRACT, LEASE, PURCHASE AGREEMENT,	, OR GRANT AWARD
WITH ANY ARKAN	SAS STAT	E AGEN	CY, THE FOLLOWING INF	ORMATI	ON MU	<u>ST BE DISCLOSED:</u>	
				FOR II	NDIVI	DUALS*	
Indicate below if: you, yo Commission Member, or			er, sister, parent, or child of you o	or your spo	use is a cu	rent or former: member of the General Assembly, Constitution	onal Officer, State Board or
		, k(√)	Name of Position of Job Held	on of Job Held For How		What is the person(s) name and how are they (i.e., Jane Q. Public, spouse, John Q. Public, J	
Position Held	Current	Former	(senator, representative, name of board/ commission, data entry, etc.)	From MM/YY	To MM/YY	Person's Name(s)	Relation
General Assembly							
Constitutional Officer							
State Board or Commission Member							
State Employee							
□ None of the above	applies						
			FOR	AN E	ΝΤΙΤΥ	(BUSINESS)*	
Constitutional Officer, St	ate Board or	Commissio	on Member, State Employee, or t	he spouse,	brother, si	ny ownership interest of 10% or greater in the entity: membe ster, parent, or child of a member of the General Assembly, C ing policies or influence the management of the entity.	•
or commission wember,	, or state Emp	lioyee. Pos	suon of control means the power	to airect t	ne purcha	Ing policies or influence the management of the entity. What is the person(s) name and what is his/her % of own	norship interest and/or
	Mark (	$\checkmark$	Name of Position of Job Held	For How L	2002	what is the person(s) name and what is his/her % of own	lership interest and/or

Mark ( ✓ )		Name of Position of Job Held	For Hov	For How Long? What is the person(s) name and what is his/her % of ownership interest and/or what is his/her position of control?				
r osition neid	Current Former		(senator, representative, name of board/ commission, data entry, etc.)	From MM/YY	To MM/YY	Person's Name(s)	Ownership Interest (%)	Position of Control
General Assembly								
Constitutional Officer								
State Board or Commission Member								
State Employee								

□ None of the above applies

Failure to make any disclosure required by Governor's Executive Order 98-04, or any violation of any rule, regulation, or policy adopted pursuant to that Order, shall be a material breach of the terms of this contract. Any contractor, whether an individual or entity, who fails to make the required disclosure or who violates any rule, regulation, or policy shall be subject to all legal remedies available to the agency.

As an additional condition of obtaining, extending, amending, or renewing a contract with a state agency I agree as follows:

- 1. Prior to entering into any agreement with any subcontractor, prior or subsequent to the contract date, I will require the subcontractor to complete a **CONTRACT AND GRANT DISCLOSURE AND CERTIFICATION FORM**. Subcontractor shall mean any person or entity with whom I enter an agreement whereby I assign or otherwise delegate to the person or entity, for consideration, all, or any part, of the performance required of me under the terms of my contract with the state agency.
- 2. I will include the following language as a part of any agreement with a subcontractor:

Failure to make any disclosure required by Governor's Executive Order 98-04, or any violation of any rule, regulation, or policy adopted pursuant to that Order, shall be a material breach of the terms of this subcontract. The party who fails to make the required disclosure or who violates any rule, regulation, or policy shall be subject to all legal remedies available to the contractor.

3. No later than ten (10) days after entering into any agreement with a subcontractor, whether prior or subsequent to the contract date, I will mail a copy of the CONTRACT AND GRANT DISCLOSURE AND CERTIFICATION FORM completed by the subcontractor and a statement containing the dollar amount of the subcontract to the state agency.

Signature		Title		Date
Vendor Contact Pers	son	Title		Phone No
Agency Use Only Agency Number	Agency Name	Agency Contact Person	Contact Phone No.	Contract or Grant No.

# **RESTRICTION OF BOYCOTT OF ISRAEL CERTIFICATION**

Pursuant to Arkansas Code Annotated § 25-1-503, a public entity **shall not** enter into a contract valued at \$1,000 or greater with a company unless the contract includes a written certification that the person or company is not currently engaged in, and agrees for the duration of the contract not to engage in, a boycott of Israel.

By signing below, the Contractor agrees and certifies that they do not boycott Israel and will not boycott Israel during the remaining aggregate term of the contract.

If a company does boycott Israel, see Arkansas Code Annotated § 25-1-503.

Bid Number/Contract Number	
Description of product or service	
Contractor name	

Contractor Signature:
Signature must be hand written, in ink

Date: \_\_\_\_\_

### ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT

## SPECIFICATION 18-86-067

### FOR

## TRUCK MOUNTED HYDRAULIC CRANE

### A. General Specifications:

- 1. <u>Current Model</u>: Units furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Machines manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable. Manufacturers of the units supplied must have been in the business of producing operational units for at least two years and must have recently sold similar units to domestic governmental agencies. The model furnished must have been in production for a minimum of one year, or be the latest version of a previous model. Bidder/s may be required to submit documentation substantiating the aforementioned requirements. A list of user references may also be required.
- 2. <u>Literature</u>: Manufacturers literature, verifying adherence of proposed unit to each line item addressed in this specification, shall be submitted with the bid. If any literature and/or specifications of items conflict with AHTD specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.
- 3. Any deviations from specifications and requirements herein must be clearly pointed out by bidder. Otherwise it will be considered that equipment offered is in strict compliance with these specifications and requirements, and successful bidder will be held responsible therefor. Deviations must be explained in detail on an attached sheet. However, no implication is made by the Arkansas State Highway and Transportation Department that deviations will be acceptable.
- 4. <u>Delivery Requirements</u>: It will be the responsibility of the Successful Bidder to guarantee delivery of the cab & chassis as specified, including items or equipment installed by a third party contractor, within the quoted time. The Arkansas State Highway and Transportation Department will not accept delivery of decked cab & chassis.
- 5. <u>Training</u>: Successful Bidder shall instruct Arkansas Highway and Transportation Department personnel in the operation and maintenance of unit furnished under this specification.
- 6. Unit shall be assembled, adjusted and made ready for continuous operation at time of delivery.
- 7. All tools and accessories necessary for the efficient operation of the unit shall be furnished whether or not they are specifically mentioned in this specification (including standard equipment as regularly furnished by manufacturer as shown on printed literature and specifications unless specifically excluded by this specification). Truck shall be the latest current model of proven performance and under standard production by manufacturer at time of delivery.
- 8. <u>Parts Inventory & Service Facilities</u>: The successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
- 9. <u>Demonstration</u>: The Arkansas State Highway & Transportation Department reserves the right to require a demonstration, under actual working conditions, of equipment bid under this specification before award is made. The demonstration would be performed (free of any charge) by the bidder or an authorized representative at a mutually acceptable location. If requested, the bidder should be prepared to demonstrate the equipment within thirty (30) days after notification. Failure of the bidder to perform a satisfactory demonstration within the specified time may be grounds for rejection of the bid.
- 10. <u>Delivery Requirements</u>: It will be the responsibility of the Successful Bidder to guarantee delivery of the cab & chassis as specified, including items or equipment installed by a third party contractor, within the quoted time. The Arkansas State Highway and Transportation Department will not accept delivery of decked cab & chassis.
- 11. <u>Cooperative Purchasing</u>: Other tax-supported entities\* in Arkansas (cities, counties, state agencies, school districts, etc.) may purchase from this Contract on an individual basis under the same specifications and conditions, and at the pricing set forth by each vendor, all at the discretion of each vendor in each case. Prices could be reduced by a vendor for minor alterations in conditions (changing order quantities, deleting options, etc.) as agreed by both parties, but could not be raised above the contract bid price except for any additional freight charges. Vendors would not be required to sell to any such entity under this contract, and those entities would not be obligated to purchase from the contract.

Each entity wishing to purchase from the contract must make contact directly with the appropriate vendor(s). The Highway Department shall remain "out of the loop" for such transactions: all contact, orders, invoices, payments, etc. regarding such transactions must take place exclusively between the tax-supported entity and the vendor. The Department shall be held harmless of any and all liability arising from such transactions.

\* Tax-supported entities are defined as those receiving more than half of total funding from appropriated tax funds.

## B. <u>Unit Specifications</u>:

- 1. <u>General</u>: This specification is intended to cover the purchase of a hydraulic powered, telescoping boom type, truck mounted crane with a minimum load rating of 20,000 pounds at a five (5) foot load radius. Complete unit shall consist of a hydraulic crane and flatbed body, including power-take-off, pump, controls, oil reservoir, fish plating (if recommended by manufacturer), and all necessary parts, completely mounted on a cab and chassis and ready for operation. Hydraulic crane, flatbed body, accessory equipment, and Cab and Chassis shall meet the following minimum specifications.
- 2. Cab & Chassis:
  - A. <u>GVWR</u>: No less than 56,000 pounds.
  - B. Wheelbase: Minimum of 240".
  - C. <u>Cab to Axle</u>: Minimum effective CA of 175". (This is the minimum acceptable CA. If the crane manufacturer requires or recommends a longer CA, it shall be provided.)
  - D. <u>Engine</u>: Turbocharged 4 Cycle diesel with a minimum piston displacement of 6.7 liters developing no less than 325 SAE gross horsepower and no less than 750 lb. ft. SAE gross torque at rated RPM. Shall have full flow oil filter(s), fuel filters, dry type air cleaner, 12 volt electrical equipment with no less than 160 amp alternator and maintenance free batteries as regularly furnished with engine specified.
    - (1) <u>Exhaust System</u>: Horizontal or vertical exhaust acceptable depending on requirements of the hydraulic crane manufacturer. If vertical, exhaust stack shall have a rain cap or curved outlet and be equipped with a heat shield. The exhaust system may need to provide clearance for PTO installation, depending on which side of the transmission the installer chooses to mount the PTO.
    - (2) <u>Engine Shutdown</u>: Engine safety shutdown system with manual or automatic override to include the following features: low oil pressure warning bell/buzzer plus shutdown, high coolant temperature warning bell/buzzer plus shutdown and low coolant level warning bell/buzzer plus light or shutdown.
    - (3) <u>Variable Engine Speed Control</u>: Shall be equipped with engine speed control for use with PTO. Provision shall be suitable for use with a remote mounted variable engine speed control used with a truck mounted hydraulic crane or other equipment requiring remote mounted engine speed control.
    - (4) <u>Cooling System</u>: As recommended and regularly furnished by the manufacturer for use with the engine size specified above, and in prime mover for hydraulic crane, with anti-freeze protection to  $-20^{\circ}$  F, or lower.
    - (5) <u>Block Heater</u>: Engine shall be equipped with a block heater rated at no less than 1,000 watts which will operate on 120 volts AC.
  - E. <u>Front Tires and Wheels</u>: Two (2) 315/80R22.5 steel belted tubeless radials load range "L" minimum. Shall be mounted on 22.5" diameter tubeless type, hub piloted steel disc with 220 mm center hole, 285.75 mm ten (10) hole bolt circle diameter and not less than 9" rim section. All tires must have speed restriction that exceeds 65 MPH.
  - F. <u>Rear Tires and Wheels</u>: Four (4) 11R22.5 steel belted tubeless radials load range "H" minimum. Shall be mounted on 22.5" diameter tubeless type, hub piloted steel disc with 220 mm center hole, 285.75 mm ten (10) hole bolt circle diameter and not less than 8.25" rim section. All tires must have speed restriction that exceeds 65 MPH.
  - G. <u>Spare Rear Tires and Wheels</u>: One (1) 11R22.5 steel belted tubeless radials load range "H" minimum. Shall be mounted on 22.5" diameter tubeless type, hub piloted steel disc with 220 mm center hole, 285.75 mm ten (10) hole bolt circle diameter and not less than 8.25" rim section. Tires must have speed restriction that exceeds 65 MPH.
  - H. <u>Transmission</u>: Allison 3500 RDS automatic with six speed programming and PTO provision. Transmission shall have synthetic lubricant and be equipped with transmission oil cooler.
  - I. <u>Steering</u>: Hydraulic actuated power steering as regularly offered by manufacturer.
  - J. Front Axle: I Beam Type with wet seals, outboard mounted drums and a minimum capacity of 16,000 pounds.
  - K. Front Springs: As required to meet axle capacity specified above.

- L. <u>Rear Axle and Suspension</u>: Tandem with power divider, inter-axle differential lock out control and Hendrickson RT or RTE equalizing beam type suspension. Shall be full floating with wet seals, outboard mounted drums and have a minimum capacity of 40,000 pounds. Ratio provided shall achieve a maximum theoretical electronic governed speed of no less than 69 MPH and still provide acceptable startability and gradeability under loaded conditions for on/off highway applications.
- M. <u>Air System</u>: Air compressor shall have a minimum capacity of 18 cfm and draw air through the engine air cleaner. Air system shall be equipped with a heated air dryer.
- N. <u>Brakes</u>: Factory installed full air operated two shoe type with automatic slack adjusters and dust shields on front and rear. Rear brakes shall have spring set parking brakes.
- O. <u>Trailer Brake Controls</u>: Shall be equipped with trailer brake controls providing electric brake and electrical hookup. Shall include factory installed integrated electric trailer brake controller. Seven wire electric cable shall be routed to end of frame and shall be equipped with 7-wire receptacle.
- P. <u>Frame</u>: Section modulus and yield strength of frame material shall provide a minimum RBM of 2,000,000. If the hydraulic crane manufacturer requires a stronger frame or additional frame reinforcement, it shall be provided. It shall be the responsibility of the successful bidder to insure that any additional frame requirements which may be needed for proper installation of the hydraulic crane are provided (i.e. after frame length, longer wheelbase, front frame extension, frame reinforcement, clean CA or clear frame rails).
- Q. <u>Cab</u>: Conventional cab as regularly furnished by manufacturer, complete with insulation and all interior trim. Cab glass shall include windshield, roll-up windows in doors and rear cab glass as a minimum. Shall have key type locks on doors, factory installed fresh air heater-defroster unit, grab handle on each side, right and left sun shades and fitted rubber floor mats.
  - (1) <u>Cab Mounts</u>: Air suspension type rear cab mounts.
  - (2) <u>Instruments</u>: Shall include the following as a minimum:
    - (a) Speedometer/odometer
    - (b) Electric tachometer
    - (c) Electric engine hour meter
    - (d) Ammeter or volt meter
    - (e) Oil pressure gauge
    - (f) Coolant temperature gauge
    - (g) Transmission oil temperature gauge or warning light
    - (h) Air brake pressure gauge
  - (3) <u>Cruise Control</u>: Factory installed electronic cruise control.
  - (4) Air Conditioning: Factory installed air conditioning. Shall include tinted glass all around.
  - (5) <u>Tilt Steering Column</u>: Factory installed.
  - (6) <u>Windshield Wipers</u>: Dual electric intermittent windshield wipers with washers.
  - (7) <u>Auxiliary Switches</u>: Shall be equipped with a minimum of six (6) rocker switches mounted in the instrument panel for use by bodybuilder or end user to supply power to work lights, warning lights and other auxiliary electrical devices.
  - (8) <u>Seats</u>: Air suspension driver's seat and non-suspension passenger's seat. Shall include driver's and passenger's seat belts.
  - (9) <u>Radio</u>: Factory installed electronic AM/FM radio.
  - (10)<u>Heated Mirrors</u>: Dual Heated West Coast Sr. type mirrors no less than 7" x 16" with adjustable brackets and auxiliary convex mirrors.
  - (11) <u>Air Horn</u>: Single or dual-trumpet air horn.
- R. <u>Hood</u>: Tilting fiberglass or composite hood and fenders.
- S. <u>Front Bumper</u>: Swept back or similar type front bumper.
- T. <u>Lights</u>: Shall be equipped with dual beam headlights, parking lights, clearance lights, automatic backup lights, directional turn signals with column mounted switch and hazard flasher switch. Rear signals to be wired for stop and tail lights in addition to directional signals.

- U. <u>Backup Alarm</u>: Shall be equipped with an electric backup alarm meeting the requirements of SAE J994 with a minimum sound level output of 97 decibels.
- V. Fuel Tank(s): Single or dual fuel tanks with instrument panel fuel gauge. Minimum fuel capacity of 70 gallons.
- W. <u>Keys</u>: Minimum of four (4) ignition/door keys per vehicle.
- 3. <u>Hydraulic Truck Crane</u>:
  - A. <u>Type</u>: Fully hydraulic truck crane with telescoping boom installed on truck chassis between cab and truck bed. Shall be approved and recommended by manufacturer for installation on a 56,000 pound GVWR truck with a CA of 175" or greater. Unit furnished shall comply with applicable ANSI, OSHA and SAE standards.
  - B. <u>Boom</u>: Shall have three (3) sections and telescope hydraulically under full load regardless of boom angle. Shall provide a maximum sheave height from ground of no less than 45' with crane mounted on truck specified below. Total elevation range of boom shall be from no less than 10° below horizontal to no less than 75° above horizontal. Horizontal reach from centerline of rotation shall be no more than 27' when fully retracted to no less than 60' when fully extended.
  - C. <u>Boom Rotation</u>: 360°, minimum. Rotation may be continuous or non-continuous.
  - D. Load Ratings: Shall have the following minimum capacities with load over outrigger or to rear of truck:
    - (1) <u>All Boom Sections Retracted</u>:
      - (a) At 10' radius, all boom sections retracted, load rating shall be no less than 10,000 pounds.
    - (2) <u>All Boom Sections Extended</u>:
      - (a) At 20' radius, all boom sections extended, load rating shall be no less than 4,800 pounds.
      - (b) At  $0^{\circ}$  boom angle, all boom sections extended, load rating shall be no less than 2,300 pounds.
  - E. <u>Winch</u>: Hydraulically driven with minimum bare drum pull of 10,000 pounds equipped with at least 150' of no less than 1/2" rotation resistant wire rope. Downhaul weight and hook shall be furnished with crane. Sheave at end of boom shall be steel.
  - F. <u>Hydraulic System</u>: Shall have boom tilt cylinder, cylinder for telescoping boom, hydraulic motor for winch, outrigger cylinders and hydraulically actuated boom rotation. All cylinders shall be double acting. Hydraulic system shall have bypass valve to prevent overloading and shall have holding valves so that load will remain suspended in case of power or pressure failure.
  - G. <u>Hydraulic Pump</u>: It is preferred that the hydraulic pump furnished be designed for direct mounting to PTO. If space limitations require the use of a drive shaft, the shaft length shall be as short as possible.
  - H. <u>Power Take-Off</u>: "Hot shift", multi-gear type, mounted on truck transmission (Allison 3500 RDS). Shall have a pilot light to indicate when PTO is engaged.
  - I. <u>Controls</u>: Two (2) sets of fixed controls and one (1) radio remote control unit shall be provided.
    - (1) <u>Fixed Controls</u>: Located at dual control stations one complete set of controls on each side of truck chassis. Access steps and grab handles for each control station shall be provided.
    - (2) <u>Remote Control</u>: One (1) four function radio remote control unit shall be provided for controlling boom elevation, boom extension, boom rotation, and winch functions.
  - J. <u>Work Baskets</u>: One (1) gravity-leveling high capacity personnel baskets with mounting hardware shall be provided to be installed on boom when needed. Shall be designed to allow a minimum of two passengers with tools and material to be lifted to aboveground worksites. Baskets shall be constructed of steel with minimum dimensions of no less than 60" x 30" x 45". Basket shall have a minimum rated capacity of 600 pounds and be complete with locking system, safety loops and safety belts or harness.
  - K. <u>Outriggers</u>: Shall be equipped with a minimum of two (2) sets of hydraulically powered outriggers a primary set located behind the truck cab at the crane mast and a set located at the rear of the truck. All outriggers to be equipped with pads.
    - (1) <u>Primary Outriggers</u>: Shall be one of the following:
      - (a) All hydraulic, "H" type outriggers which extend outward horizontally and then downward vertically with individual control of horizontal and vertical travel of each outrigger.
      - (b) Individually controlled "A" type outriggers.

- (2) <u>Rear Outriggers</u>: All hydraulic, individually controlled "A" or "Modified A" type rear outriggers mounted behind rear wheels on truck chassis. (Alternate rear outrigger styles may be acceptable, however, if an alternate style is proposed, it must be approved by AHTD prior to bid opening.)
- (3) <u>Additional Outriggers</u>: If the manufacturer recommends the use of additional outriggers or stabilizers mounted at the front bumper, they shall also be furnished.

### 4. Flatbed Body:

- A. <u>Floor</u>: Floor to be no less than 96" wide outside and no less than 210" long, measured from rear of crane mounting base. Shall be constructed of no less than 3/16" steel tread plate.
- B. <u>Stake Pockets</u>: Shall be sized for 2" x 4" lumber or steel stakes. The stake pockets on each side of the platform shall be placed on 24" centers. There shall be a minimum of four (4) stake pockets at the rear of the platform.
- C. <u>Boom Rack</u>: Shall be equipped with a removable boom rack at rear of bed for securing boom during transport.
- D. <u>Mud Flaps</u>: Shall have mud flaps no less than 24" wide and 1/4" thick, without advertising, mounted behind rear wheels.
- E. <u>Lights & Reflectors</u>: Side marker and clearance lights shall be bolt on armored type. Reflectors shall be bolt on type. (Recessed, rubber-mounted, snap-in lights with reflector type lens and plug-in connectors may be used in lieu of armored lights and bolt on reflectors.) Lights and reflectors shall comply with Federal Motor Vehicle Safety Standard FMVSS108.
- F. <u>Rear Bumper</u>: Heavy duty design meeting DOT specifications.

## 5. <u>Color</u>:

- A. <u>Hydraulic Truck Crane</u>: Shall be painted Sherwin Williams F8W 2030 Frost White Acrylic Enamel, or approved equal.
- B. Flatbed Body: Shall be painted one of the following colors:
  - (1) Sherwin-Williams No. F1B 4009 Gloss Black Enamel, or approved equal.
  - (2) Sherwin Williams F8W2030 Frost White Acrylic Enamel, or approved equal.
- C. <u>Cab & Chassis</u>: Cab, Hood, Fenders & Wheels shall be Sherwin Williams F8W2030 Frost White Acrylic Enamel, or equal. Grill, bumper and mirrors shall be as regularly furnished by manufacturer.

## 6. Warranty:

- A. Cab and chassis shall have truck manufacturer's regular warranty. Warranty shall begin when the unit is placed in operation by AHTD. Warranty data shall be furnished with each unit. The Warranty Data shall contain all necessary information such as motor and/or serial numbers and shall be signed by the selling dealer at the time vehicle is delivered to the Highway Department.
- B. The hydraulic crane and other incidental equipment purchased under this specification shall be warranted against defective material and workmanship for a minimum period of twelve (12) months (365 Days) from date unit is placed in operation by AHTD. In addition, manufacturer's standard warranty period on certain machine components that exceeds the 12 months warranty shall remain in effect.
  - (1) Warranty shall include all parts, labor and transportation costs to the location of equipment.
  - (2) If equipment cannot be repaired on location, warranty shall include cost of transport to the facility where the repair work will be done.
  - (3) It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
- C. If any warranty literature submitted with the bid conflicts with AHTD warranty requirements, the conflict(s) shall be specifically noted, corrected and included with the bid or the conflict(s) will be considered an exception to warranty specifications and the bid rejected.
- D. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment. For the purposes of this paragraph "timely manner" means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph "manufacturer" means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph "replacement part" means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is capable of providing dependable performance in normal operation conditions for its normal

service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.

- 7. Manuals, Certificate of Origin and Invoice:
  - A. The successful bidder shall furnish one (1) copy each of Operator's Instruction Manual, Shop Repair Manual and Parts Book for aerial lift and accessories, and one (1) copy each of Shop Repair Manual and Parts Book for truck with each unit delivered including Warranty Data and Operator's Manual for truck. The Warranty Data shall contain all necessary information such as motor and/or serial numbers and shall be signed by the selling dealer at the time vehicle is delivered to the Highway Department.

The successful bidder may provide Shop Repair Manuals and Parts Manuals on computer media (CD, DVD, USB Drive, etc.) in lieu of printed manuals.

B. Certificate of Origin, Federal Excise Tax Exemption Certificate, Odometer Disclosure Statement and Five (5) copies of the Invoice to be furnished to Equipment & Procurement Division, P.O. Box 2261, Little Rock, AR 72203 (11302 W. Baseline Road, Little Rock, AR 72209, if shipping UPS, FedEx, etc.).