

Cooperative Purchasing: Other tax-supported entities* in Arkansas (cities, counties, state agencies, school districts, etc.) may purchase from this Contract on an individual basis under the same specifications and conditions, and at the pricing set forth by each vendor, all at the discretion of each vendor in each case. Prices could be reduced by a vendor for minor alterations in conditions (changing order quantities, deleting options, etc.) as agreed by both parties, but could not be raised above the contract bid price except for any additional freight charges. Vendors would not be required to sell to any such entity under this contract, and those entities would not be obligated to purchase from the contract.

Each entity wishing to purchase from the contract must make contact directly with the appropriate vendor(s). The Department of Transportation shall remain "out of the loop" for such transactions: all contact, orders, invoices, payments, etc. regarding such transactions must take place exclusively between the tax-supported entity and the vendor. The ARDOT shall be held harmless of any and all liability arising from such transactions.

* Tax-supported entities are defined as those receiving more than half of total funding from appropriated tax funds.

STANDARD BID CONDITIONS

1. **GENERAL:** Any special terms and conditions included in the invitation for bid override these standard terms and conditions. The standard terms and conditions and any special terms and conditions become part of any contract entered into if any or all parts of the bid are accepted by the Arkansas Department of Transportation (ARDOT).
2. **ACCEPTANCE AND REJECTION:** ARDOT reserves the right to reject any or all bids, to accept bids in whole or in part (unless otherwise indicated by bidder), to waive any informalities in bids received, to accept bids on materials or equipment with variations from specifications where efficiency of operation will not be impaired, and to award bids to best serve the interest of the State.
3. **PRICES:** Unless otherwise stated in the Bid Invitation, the following will apply: (1) unit prices shall be bid, (2) prices should be stated in units of quantity specified (feet, each, lbs., etc.), (3) prices must be F.O.B. destination specified in bid, (4) prices must be firm and not subject to escalation, (5) bid must be firm for acceptance for 30 days from bid opening date. In case of errors in extension, unit prices shall govern. Discounts from bid price will not be considered in making awards.
4. **BID BONDS AND PERFORMANCE BONDS:** If required, a **Bid Bond** in the form of a cashier's check, certified check, or surety bond issued by a surety company, in an amount stated in the Bid Invitation, must accompany bid. **Personal and company checks are not acceptable as Bid Bonds.** Failure to submit a Bid Bond as required will cause a bid to be rejected. The Bid Bond will be forfeited as liquidated damages if the successful bidder fails to provide a required Performance Bond within the period stipulated by ARDOT or fails to honor their bid. When a bidder claims and can show clear and convincing evidence that a material mistake was made in the bid and was not the bid intended, the bidder may be permitted to withdraw their bid prior to award without forfeiture of bid bond. Cashier's checks and certified checks submitted as Bid Bonds will be returned to unsuccessful bidders; surety bonds will be retained. The successful bidder will be required to furnish a **Performance Bond** in an amount stated in the Bid Invitation and in the form of a cashier's check, certified check, or surety bond issued by a surety company, unless otherwise stated in the Bid Invitation, as a guarantee of delivery of goods/services in accordance with the specifications and within the time established in the bid. **Personal and company checks are not acceptable as Performance Bonds.** In some cases, a cashier's check or certified check submitted as a Bid Bond will be held as the Performance Bond of the successful bidder. Cashier's checks or certified checks submitted as Performance Bonds will be refunded shortly after payment has been made to the successful bidder for completion of all terms of the bid; surety bonds will be retained. Surety bonds must be issued by a surety company authorized to do business in Arkansas, and must be signed by a Resident Local Agent licensed by the Arkansas State Insurance Commissioner to represent that surety company. Resident Agent's Power-of-Attorney must accompany the surety bond. Certain bids involving labor will require Performance Bonds in the form of surety bonds only (no checks of any kind allowed). These bonds shall not only serve to guarantee the completion of the work, but also to guarantee the excellence of both workmanship and material until the work is finally accepted and the provisions of the Plans, Specifications, and Special Provisions fulfilled. In such cases, the company issuing the surety bond must comply with all stipulations herein and must be named in the U. S. Treasury listing of companies holding Certificates of Authority as acceptable sureties on Federal Bonds and as acceptable reinsuring companies. Any excess between the face amount of the bond and the underwriting limitation of the bonding company shall be protected by reinsurance provided by an acceptable reinsuring company. Annual Bid and Performance Bonds on file with E & P Division must have sufficient unencumbered funds to meet current bonding requirements, or the bid will be rejected, unless the balance is submitted as set forth above, prior to bid opening.
5. **TAXES:** The ARDOT is not exempt from Arkansas State Sales and Use Taxes, or local option city/county sales taxes, when applicable, and bidders are responsible to the State Revenue Department for such taxes. These taxes should not be included in bid prices, but where required by law, will be paid by the ARDOT as an addition thereto, and should be added to the billing to the ARDOT. The ARDOT is exempt from Federal Excise Taxes on all commodities except motor fuels; and excise taxes should not be included in bid prices except for motor fuels. Where applicable, tax exemption certificates will be furnished by the ARDOT.
6. **"ALL OR NONE" BIDS:** Bidders who wish to bid "All or None" on two or more items shall so stipulate on the face of bid sheet; otherwise, bid may be awarded on an individual item basis.
7. **SPECIFICATIONS:** Complete specifications should be attached for any substitution or alternate offered, or where amplification is necessary. Bidder's name must be placed on all attachments to the bid.
8. **EXCEPTIONS TO SPECIFICATIONS:** Any exceptions to the bid specifications must be stated in the bid. Any exceptions to manufacturer's published literature must be stated in the bid, or it will be assumed that bidder is bidding exactly as stated in the literature.
9. **BRAND NAME REFERENCES:** All brand name references in bid specifications refer to that commodity or its equivalent, unless otherwise stated in Bid Invitation. Bidder should state brand or trade name of item being bid, if such name exists.
10. **FREIGHT:** All freight charges should be included in bid price. Any change in common carrier rates authorized by the Interstate Commerce Commission will be adjusted if such change occurs after the bid opening date. Receipted common carrier bills that reflect ICC authorized rate changes must be furnished.

11. **SAMPLES, LITERATURE, DEMONSTRATIONS:** Samples and technical literature must be provided free of any charge within 14 days of ARDOT request, and free demonstrations within 30 days, unless ARDOT extends time. Failure to provide as requested within this period may cause bid to be rejected. Samples, literature and demonstrations must be substantially the same as the item(s) being bid, unless otherwise agreed to by ARDOT. Samples that are not destroyed will be returned upon request at bidder's expense. Samples from successful bidders may be retained for comparison with items actually furnished.
12. **GUARANTY:** Unless otherwise indicated in Bid Invitation, it is understood and agreed that any item offered or shipped on this bid shall be newly manufactured, latest model and design, and in first class condition; and that all containers shall be new, suitable for storage or shipment and in compliance with all applicable laws relating to construction, packaging, labeling and registration.
13. **BACKORDERS OR DELAY IN DELIVERY:** Backorders or failure to deliver within the time required may constitute default. Vendor must give written notice to the ARDOT, as soon as possible, of the reason for any delay and the expected delivery date. The ARDOT has the right to extend delivery if reasons appear valid. If reason or delivery date is not acceptable, vendor is in default.
14. **DEFAULT:** All commodities furnished will be subject to inspection and acceptance by ARDOT after delivery. Default in promised delivery or failure to meet specifications authorizes the ARDOT to cancel award or any portion of same, to reasonably purchase commodities or services elsewhere and to charge full increase, if any, in cost and handling to defaulting vendor. Applicable bonds may be forfeited.
15. **ETHICS:** *"It shall be a breach of ethical standards for a person to be retained, or to retain a person, to solicit or secure a State contract upon an agreement of understanding for a commission, percentage, brokerage, or contingent fee, except for retention of bona fide employees or bona fide established commercial selling agencies maintained by the contractor for the purpose of securing business."* (Arkansas Code, Annotated, Section 19-11-708).
16. **NOTICE OF NONDISCRIMINATION:** The Arkansas State Highway Commission, through ARDOT, complies with all civil rights provisions of federal statutes and related authorities that prohibit discrimination in programs and activities receiving federal financial assistance. Therefore, ARDOT does not discriminate on the basis of race, sex, color, age, national origin, religion (not applicable as a protected group under the Federal Motor Carrier Safety Administration Title VI Program), disability, Limited English Proficiency (LEP), or low-income status in the admission, access to and treatment in the ARDOT's programs and activities, as well as the ARDOT's hiring or employment practices. Complaints of alleged discrimination and inquiries regarding the ARDOT's nondiscrimination policies may be directed to Joanna P. McFadden Section Head – EEO/DBE (ADA/504/Title VI Coordinator), P. O. Box 2261, Little Rock, AR 72203, (501)569-2298, (Voice/TTY 711), or the following email address: joanna.mcfadden@ardot.gov. Free language assistance for Limited English Proficient individuals is available upon request. This notice is available from the ADA/504/Title VI Coordinator in large print, on audiotape and in Braille.
17. **PROHIBITION OF EMPLOYMENT OF ILLEGAL IMMIGRANTS:** Pursuant to Arkansas Code Annotated 19-11-105, all bidders must certify prior to award of a contract that they **do not** employ or contract with any illegal immigrant(s) in its contract with the state. Bidders shall certify online at <https://www.ark.org/dfa/immigrant/index.php>.
18. **DISCLOSURE:** Failure to make any disclosure required by Governor's Executive Order 98-04, or any violation of any rule, regulation, or policy adopted pursuant to that order, **shall** be a material breach of the terms of this contract. Any contractor, whether an individual or entity, who fails to make the required disclosure or who violates any rule, regulation, or policy **shall** be subject to all legal remedies available to the agency.

ATTACHMENT A

ELIGIBLE BIDDER CERTIFICATION

The Bidder represents and warrants for itself, its employees and its subcontractors and certifies they:

1. Are not presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from covered transactions by any Federal department or agency;
2. Have not within a three-year period preceding thus Bid been convicted of or had a civil judgment rendered against them for commission of fraud or a criminal offense in connection with obtaining, attempting to obtain, or performing a public (Federal, State, or local) transaction or contract under a public transaction; violation of Federal or State antitrust statutes or commission of embezzlement, theft, forgery, bribery, falsification or destruction of records, making false statements, or receiving stolen property;
3. Are not presently indicted for or otherwise criminally or civilly charged by a governmental entity (Federal, State, or local) with commission of any of the offenses enumerated in paragraph two (2) of this Certification;
4. Have not within a one-year period preceding this application/Bid had one or more public transactions (Federal, State, or local) terminated for cause or default; and

The Bidder represents, warrants and acknowledges the understanding that restrictions placed on the employment of labor or on the scale of pay for the work on a contract will be the requirements of the Fair Labor Standards Act (Federal Wage-Hour Law) of 1938, 28 USC §201 et seq., and other applicable labor laws.

The person executing this Certification further represents, warrants and affirms the truthfulness and accuracy of the contents of the statements submitted on or with this Certification and understands that the provisions of 31 USC §3801 et seq. are applicable thereto.

BIDDER NAME

BY: _____

Signature

TITLE: _____

ILLEGAL IMMIGRANT CERTIFICATION

Pursuant to Arkansas Code Annotated § 19-11-105, Contractor(s) **shall** certify with OSP that they do not employ or contract with illegal immigrants.

By signing below, the Contractor agrees and certifies that they do not employ illegal immigrants and will not employ illegal immigrants during the remaining aggregate term of the contract.

Bid Number/Contract Number	H-19-241H
AASIS Number	N/A
Description	1 Ton Pickups
Contractor name	

Contractor Signature: _____
Signature must be hand written, in ink

Date: _____

SUBCONTRACTOR NAME:

Yes No

IS THIS FOR:

Goods? Services? Both?

TAXPAYER ID NAME:

FIRST NAME:

M.I.:

ADDRESS:

STATE:

ZIP CODE:

COUNTY:

CONTRACT AND GRANT DISCLOSURE AND CERTIFICATION FORM

Failure to complete all of the following information may result in a delay in obtaining a contract, lease, purchase agreement, or grant award with any Arkansas State Agency.

AS A CONDITION OF OBTAINING, EXTENDING, AMENDING, OR RENEWING A CONTRACT, LEASE, PURCHASE AGREEMENT, OR GRANT AWARD WITH ANY ARKANSAS STATE AGENCY, THE FOLLOWING INFORMATION MUST BE DISCLOSED:

FOR INDIVIDUALS*

Indicate below if: you, your spouse or the brother, sister, parent, or child of you or your spouse is a current or former: member of the General Assembly, Constitutional Officer, State Board or Commission Member, or State Employee:

Position Held	Mark (✓)		Name of Position of Job Held (senator, representative, name of board/ commission, data entry, etc.)	For How Long?		What is the person(s) name and how are they related to you? (i.e., Jane Q. Public, spouse, John Q. Public, Jr., child, etc.)	Relation
	Current	Former		From MM/YY	To MM/YY		
General Assembly							
Constitutional Officer							
State Board or Commission Member							
State Employee							

None of the above applies

FOR AN ENTITY (BUSINESS)*

Indicate below if any of the following persons, current or former, hold any position of control or hold any ownership interest of 10% or greater in the entity: member of the General Assembly, Constitutional Officer, State Board or Commission Member, State Employee, or the spouse, brother, sister, parent, or child of a member of the General Assembly, Constitutional Officer, State Board or Commission Member, or State Employee. Position of control means the power to direct the purchasing policies or influence the management of the entity.

Position Held	Mark (✓)		Name of Position of Job Held (senator, representative, name of board/ commission, data entry, etc.)	For How Long?		What is the person(s) name and what is his/her % of ownership interest and/or what is his/her position of control?	Ownership Interest (%)	Position of Control
	Current	Former		From MM/YY	To MM/YY			
General Assembly								
Constitutional Officer								
State Board or Commission Member								
State Employee								

None of the above applies

Contract and Grant Disclosure and Certification Form

Failure to make any disclosure required by Governor's Executive Order 98-04, or any violation of any rule, regulation, or policy adopted pursuant to that Order, shall be a material breach of the terms of this contract. Any contractor, whether an individual or entity, who fails to make the required disclosure or who violates any rule, regulation, or policy shall be subject to all legal remedies available to the agency.

As an additional condition of obtaining, extending, amending, or renewing a contract with a state agency I agree as follows:

1. Prior to entering into any agreement with any subcontractor, prior or subsequent to the contract date, I will require the subcontractor to complete a **CONTRACT AND GRANT DISCLOSURE AND CERTIFICATION FORM**. Subcontractor shall mean any person or entity with whom I enter an agreement whereby I assign or otherwise delegate to the person or entity, for consideration, all, or any part, of the performance required of me under the terms of my contract with the state agency.
2. I will include the following language as a part of any agreement with a subcontractor:

Failure to make any disclosure required by Governor's Executive Order 98-04, or any violation of any rule, regulation, or policy adopted pursuant to that Order, shall be a material breach of the terms of this subcontract. The party who fails to make the required disclosure or who violates any rule, regulation, or policy shall be subject to all legal remedies available to the contractor.
3. No later than ten (10) days after entering into any agreement with a subcontractor, whether prior or subsequent to the contract date, I will mail a copy of the **CONTRACT AND GRANT DISCLOSURE AND CERTIFICATION FORM** completed by the subcontractor and a statement containing the dollar amount of the subcontract to the state agency.

Signature _____	Title _____ Date _____
Vendor Contact Person _____	Title _____ Phone No. _____

<small>Agency Use Only</small>			
Agency Number _____	Agency Name _____	Agency Contact Person _____	Agency Contact Phone No. _____
			Contract or Grant No. _____

RESTRICTION OF BOYCOTT OF ISRAEL CERTIFICATION

Pursuant to Arkansas Code Annotated § 25-1-503, a public entity **shall not** enter into a contract valued at \$1,000 or greater with a company unless the contract includes a written certification that the person or company is not currently engaged in, and agrees for the duration of the contract not to engage in, a boycott of Israel.

By signing below, the Contractor agrees and certifies that they do not currently boycott Israel and will not boycott Israel during any time in which they are entering into, or while in contract, with any public entity as defined in § 25-1-503* If at any time after signing this certification the contractor decides to engage in a boycott of Israel, the contractor must notify the contracting public entity in writing.

If a company does boycott Israel, see Arkansas Code Annotated § 25-1-503.

Name of public entity	
Description of product or service	
Contractor name	

Contractor Signature: _____
Signature must be hand written, in ink

Date: _____

“Public Entity” means the State of Arkansas, or a political subdivision of the state, including all boards, commissions, agencies, institutions, authorities, and bodies politic and corporate of the state, created by or in accordance with state law or regulations, and does include colleges, universities, a statewide public employee retirement system, and institutions in Arkansas as well as units of local and municipal government.

08102018

ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARKANSAS
ARDOT-EQUIPMENT & PROCUREMENT DIVISION
PICKUP TRUCKS
BID SHEET

Bid No. H-19-241H
Page 1 of 4

BIDDER: _____

1. 15 - Pickups, 1 ton, Crew Cab & Chassis, Dual Rear Wheels, Automatic Transmission, w/Standard Flat Bed Body to meet ARDOT Spec. 19-54-024

FOB - ARDOT District 6 Headquarters, 8900 Mabelvale Pike, Little Rock, AR 72209----- 5 ea.
FOB - ARDOT District 7 Headquarters, 2245 California Avenue, Camden, AR 71701----- 2 ea.
FOB - ARDOT District 8 Headquarters, 372 Aspen Lane, Russellville, AR 72801----- 3 ea.
FOB - ARDOT District 9 Headquarters, 4590 Highway 65 South, Harrison, AR 72601----- 5 ea.

Make and Model _____

Bid Price (Do not include any Local, State or Federal Taxes) Each \$ _____

Total for 15 Vehicles \$ _____

Guaranteed Delivery Date _____

Additional units may be purchased at this price through _____

2. 3 - Pickups, 1 ton, Crew Cab & Chassis, Dual Rear Wheels, Automatic Transmission, 4WD, w/Standard Flat Bed Body to meet ARDOT Spec. 19-54A-024

FOB - ARDOT District 2 Headquarters, 4900 Highway 65 South, Pine Bluff, AR 71611 ----- 3 ea.

Make and Model _____

Bid Price (Do not include any Local, State or Federal Taxes) Each \$ _____

Total for 1 Vehicles \$ _____

Guaranteed Delivery Date _____

Additional units may be purchased at this price through _____

3. 1 - Pickup, 1 ton, Crew Cab & Chassis, Short Bed, Diesel, Automatic Transmission, 4WD to meet ARDOT Spec. 19-57-024

FOB - ARDOT District 8 Headquarters, 372 Aspen Lane, Russellville, AR 72801-----2 ea.

Make and Model _____

Bid Price (Do not include any Local, State or Federal Taxes) Each \$ _____

Total for 1 Vehicles \$ _____

Guaranteed Delivery Date _____

Additional units may be purchased at this price through _____

ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARKANSAS
ARDOT-EQUIPMENT & PROCUREMENT DIVISION
PICKUP TRUCKS
BID SHEET

Bid No. H-19-241H
Page 2 of 4

-
-
4. 2 - Pickups, 1 ton, Crew Cab & Chassis, Automatic Transmission, Dual Rear Wheels, w/Standard Height Service Body to meet ARDOT Spec. 19-55-020

FOB - ARDOT District 2 Headquarters, 4900 Highway 65 South, Pine Bluff, AR 71611----- 1 ea.
FOB - ARDOT District 3 Headquarters, 2911 Highway 29 North, Hope, AR 71801----- 1 ea.

Make and Model _____

Bid Price (Do not include any Local, State or Federal Taxes) Each \$ _____

Total for 2 Vehicles \$ _____

Guaranteed Delivery Date _____

Additional units may be purchased at this price through _____

5. 5 - Pickups, 1 ton, Crew Cab & Chassis, Automatic Transmission, 4WD, Diesel w/Standard Flat Bed Body to meet ARDOT Spec. 19-58-024

FOB - ARDOT District 5 Headquarters, 1673 Batesville Boulevard, Batesville, AR 73501----- 4 ea.
FOB - ARDOT District 10 Headquarters, 2510 West Kingshighway, Paragould, AR 72450----- 1 ea.

Make and Model _____

Bid Price (Do not include any Local, State or Federal Taxes) Each \$ _____

Total for 5 Vehicles \$ _____

Guaranteed Delivery Date _____

Additional units may be purchased at this price through _____

ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARKANSAS
ARDOT-EQUIPMENT & PROCUREMENT DIVISION
PICKUP TRUCKS
BID SHEET

Bid No. H-19-241H
Page 3 of 4

6. 1 - Pickup, 1 ton, Long Bed to meet ARDOT Spec. 19-22-016

FOB - ARDOT District 10 Headquarters, 2510 West Kingshighway, Paragould, AR 72450----- 1 ea.

Make and Model _____

Bid Price (Do not include any Local, State or Federal Taxes) Each \$ _____

Total for 1 Vehicles \$ _____

Guaranteed Delivery Date _____

Additional units may be purchased at this price through _____

7. 1 - Cab & Chassis, 16,000# GVWR, Automatic Transmission, Diesel Engine to meet ARDOT Spec. 19-36-020

FOB - ARDOT District 1 Headquarters, 2701 Highway 64 West, Wynne, AR 72396----- 1 ea.

Make and Model _____

Bid Price (Do not include any Local, State or Federal Taxes) Each \$ _____

Total for 1 Vehicles \$ _____

Guaranteed Delivery Date _____

Additional units may be purchased at this price through _____

ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARKANSAS
ARDOT-EQUIPMENT & PROCUREMENT DIVISION
PICKUP TRUCKS
BID SHEET

Bid No. **H-19-241H**
Page 4 of 4

8. **1** - Cab & Chassis, 19,000# GVWR, 60" CA, Automatic Transmission, Diesel Engine, w/Standard Height Service Body and Electric Crane to meet ARDOT Spec. **19-45-020**

FOB - ARDOT District 4 Headquarters, 808 Frontier Road, Barling, AR 72923----- 1 ea.

Make and Model _____

Bid Price (Do not include any Local, State or Federal Taxes) Each \$ _____

Total for **1** Vehicles \$ _____

Guaranteed Delivery Date _____

Additional units may be purchased at this price through _____

BID TOTAL _____

ADDITIONAL INFORMATION

Service Body proposed as meeting specifications:

Make: _____ **Model:** _____

Warranty: _____ **Each \$** _____

Electric Crane proposed as meeting specifications:

Make: _____ **Model:** _____

Warranty: _____ **Each \$** _____

Attachments must be priced individually but bid will be awarded by the unit price of the complete unit.

SUBCONTRACTOR NAME:

Yes No

IS THIS FOR:

Goods? Services? Both?

TAXPAYER ID NAME:

FIRST NAME:

M.I.:

ADDRESS:

CITY:

STATE:

ZIP CODE:

COUNTY:

CONTRACT AND GRANT DISCLOSURE AND CERTIFICATION FORM

Failure to complete all of the following information may result in a delay in obtaining a contract, lease, purchase agreement, or grant award with any Arkansas State Agency.

AS A CONDITION OF OBTAINING, EXTENDING, AMENDING, OR RENEWING A CONTRACT, LEASE, PURCHASE AGREEMENT, OR GRANT AWARD WITH ANY ARKANSAS STATE AGENCY, THE FOLLOWING INFORMATION MUST BE DISCLOSED:

FOR INDIVIDUALS*

Indicate below if: you, your spouse or the brother, sister, parent, or child of you or your spouse is a current or former: member of the General Assembly, Constitutional Officer, State Board or Commission Member, or State Employee:

Position Held	Mark (✓)		Name of Position of Job Held (senator, representative, name of board/ commission, data entry, etc.)	For How Long?		What is the person(s) name and how are they related to you? (i.e., Jane Q. Public, spouse, John Q. Public, Jr., child, etc.)	Relation
	Current	Former		From MM/YY	To MM/YY		
General Assembly							
Constitutional Officer							
State Board or Commission Member							
State Employee							

None of the above applies

FOR AN ENTITY (BUSINESS)*

Indicate below if any of the following persons, current or former, hold any position of control or hold any ownership interest of 10% or greater in the entity: member of the General Assembly, Constitutional Officer, State Board or Commission Member, State Employee, or the spouse, brother, sister, parent, or child of a member of the General Assembly, Constitutional Officer, State Board or Commission Member, or State Employee. Position of control means the power to direct the purchasing policies or influence the management of the entity.

Position Held	Mark (✓)		Name of Position of Job Held (senator, representative, name of board/ commission, data entry, etc.)	For How Long?		What is the person(s) name and what is his/her % of ownership interest and/or what is his/her position of control?		
	Current	Former		From MM/YY	To MM/YY	Person's Name(s)	Ownership Interest (%)	Position of Control
General Assembly								
Constitutional Officer								
State Board or Commission Member								
State Employee								

None of the above applies

Contract and Grant Disclosure and Certification Form

Failure to make any disclosure required by Governor's Executive Order 98-04, or any violation of any rule, regulation, or policy adopted pursuant to that Order, shall be a material breach of the terms of this contract. Any contractor, whether an individual or entity, who fails to make the required disclosure or who violates any rule, regulation, or policy shall be subject to all legal remedies available to the agency.

As an additional condition of obtaining, extending, amending, or renewing a contract with a state agency I agree as follows:

1. Prior to entering into any agreement with any subcontractor, prior or subsequent to the contract date, I will require the subcontractor to complete a **CONTRACT AND GRANT DISCLOSURE AND CERTIFICATION FORM**. Subcontractor shall mean any person or entity with whom I enter an agreement whereby I assign or otherwise delegate to the person or entity, for consideration, all, or any part, of the performance required of me under the terms of my contract with the state agency.
2. I will include the following language as a part of any agreement with a subcontractor:

Failure to make any disclosure required by Governor's Executive Order 98-04, or any violation of any rule, regulation, or policy adopted pursuant to that Order, shall be a material breach of the terms of this subcontract. The party who fails to make the required disclosure or who violates any rule, regulation, or policy shall be subject to all legal remedies available to the contractor.
3. No later than ten (10) days after entering into any agreement with a subcontractor, whether prior or subsequent to the contract date, I will mail a copy of the **CONTRACT AND GRANT DISCLOSURE AND CERTIFICATION FORM** completed by the subcontractor and a statement containing the dollar amount of the subcontract to the state agency.

Signature _____	Title _____	Date _____
Vendor Contact Person _____	Title _____	Phone No. _____

Agency Use Only			
Agency Number _____	Agency Name _____	Agency Contact Person _____	Contact Phone No. _____
			Contract or Grant No. _____

ARKANSAS DEPARTMENT OF TRANSPORTATION
SPECIFICATION 19-54-024
FOR
CREW CAB AND CHASSIS
13,000 POUNDS GVWR
WITH FLATBED BODY

A. General Conditions:

1. **Current Model:** All vehicles shall meet the requirements of Arkansas Department of Transportation Specifications attached to and made a part of this bid. Vehicles furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Vehicles manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable.
2. **Literature:** Manufacturers literature, verifying adherence of proposed unit to each line item addressed in this specification, shall be submitted with the bid. If any literature and/or specifications of items conflict with ARDOT specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.
3. Any deviations from specifications and requirements herein must be clearly pointed out by bidder. Otherwise it will be considered that equipment offered is in strict compliance with these specifications and requirements, and successful bidder will be held responsible therefor. Deviations must be explained in detail on an attached sheet. However, no implication is made by the Arkansas Department of Transportation that deviations will be acceptable.
4. **Manuals:** The successful bidder shall furnish one (1) Operator's Instruction Manual with each unit delivered.
5. **Service & Inspection:** Each Vehicle shall be completely serviced, cleaned and thoroughly inspected (in accordance with manufacturer's required or recommended pre-delivery service) just prior to delivery to the Arkansas Department of Transportation.
6. **Advertisement:** No Dealer advertisement shall be affixed to the vehicle.
7. Any equipment furnished on vehicles purchased under this specification for which "Federal Register Standard" has been established at time of delivery shall comply with the requirements of applicable standard and all equipment required by said standard shall be furnished whether or not it is specifically mentioned in the specification.
8. **Parts Inventory & Service Facilities:** The successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
9. **Test Drive:** The Arkansas Department of Transportation reserves the right to test drive make and model of vehicle bid on prior to contract being awarded. Samples may be demonstrator models with equipment similar, but not necessarily identical, to that listed in the specification.
10. **Cooperative Purchasing:** Other tax-supported entities* in Arkansas (cities, counties, state agencies, school districts, etc.) may purchase from this Contract on an individual basis under the same specifications and conditions, and at the pricing set forth by each vendor, all at the discretion of each vendor in each case. Prices could be reduced by a vendor for minor alterations in conditions (changing order quantities, deleting options, etc.) as agreed by both parties, but could not be raised above the contract bid price except for any additional freight charges. Vendors would not be required to sell to any such entity under this contract, and those entities would not be obligated to purchase from the contract.

Each entity wishing to purchase from the contract must make contact directly with the appropriate vendor(s). The Highway Department shall remain "out of the loop" for such transactions: all contact, orders, invoices, payments, etc. regarding such transactions must take place exclusively between the tax-supported entity and the vendor. The Department shall be held harmless of any and all liability arising from such transactions.

* Tax-supported entities are defined as those receiving more than half of total funding from appropriated tax funds.

B. Unit Specifications:

1. GVWR: No less than 13,000 pounds.
2. Wheelbase: Minimum of 171”.
3. Cab to Axle: 60”, nominal.
4. Engine: Minimum piston displacement of 5.7 liters equipped with dry type air cleaner, maintenance free battery with a minimum rating of 600 cold cranking amps at 0° F, full flow oil filter and not less than 200 amp alternator.
5. Fuel: The vehicle shall be OEM designed as an alternative fuel vehicle meeting EPA requirements. Vehicle furnished shall be capable of using ethanol/fuel blends up to E85.
6. Cooling: Heavy duty cooling system with anti-freeze protection to -20° F, or lower.
7. Transmission: Automatic, with a minimum of six (6) forward speeds. Shall include an auxiliary transmission oil cooler.
8. Steering: Hydraulic actuated power steering as regularly offered by manufacturer.
9. Front Axle: Independent front wheel suspension or I beam type. Capacity of front axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above.
10. Rear Axle: Hypoid type, full floating axle with locking or limited slip differential and a ratio of 3.73, 4.10 or 4.30 to 1. (Alternate ratio may be provided if approved by ARDOT prior to delivery.) Capacity of rear axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above. Rear springs shall consist of both main and auxiliary or overloads.
11. Brakes: Power front and rear disc with four wheel anti-lock. Mechanical parking brake as regularly furnished by manufacturer.
12. Cab: Four (4) Door Crew Cab, complete with insulation and all standard interior trim, dual electric intermittent windshield wipers with washers, right and left sun visors, floor covering consisting of manufacturer’s standard materials and colors for model and trim level provided, factory installed fresh air heater defroster unit, factory installed electronic AM/FM radio, key lock on front doors, inside rear view mirror and right and left side trailer tow type exterior mirrors with extended or extendible arms. Mirror heads to measure no less than 6” x 9”.
13. Seating: Two (2) three (3) person seating capacity bench seats. Front seat to be split bench style. Upholstery to consist of manufacturer’s standard materials and colors for model and trim level provided. Seat belts shall be provided for all seating positions.
14. Air Conditioning: Shall be equipped with factory installed air conditioning and include tinted glass.
15. Tilt Steering Column: Factory installed.
16. Speed Control: Factory installed automatic cruise control.
17. Wheels: Seven (7) 17” diameter steel disc with no less than 6.0” rim section. Rear wheels to be dual.
18. Tires: Seven (7), no less than LT235/80R17 or LT245/75R17, E load range, all season tubeless radials (duals on rear).
19. Fuel Tank(s): Minimum fuel capacity of 22 gallons. Fuel fill hose assembly furnished with fuel tank(s) shall be a minimum of 36” in length to allow attachment to an aftermarket body.
20. Front Tow Hooks: Two (2), minimum.
21. Lights: Dual beam headlights, parking lights, self-canceling directional turn signals with hazard flasher switch, back up lights, front side marker lights and front cab clearance and identification lamps. Rear lights to consist of stop and tail lights in addition to directional signals.
22. Equipment: Front bumper, front and rear shock absorbers, jack and lug wrench.

23. **Trailer Tow Equipment:** Heavy duty trailering equipment including frame mounted hitch receiver (Class V, minimum), trailer wiring with seven (7) wire harness, heavy duty flasher and factory installed integrated trailer brake controller. Frame mounted hitch receiver may be an aftermarket installation meeting Class V requirements at a minimum.
24. **Keys:** Minimum of four (4) ignition/door keys per vehicle.
25. **Color:** Sherwin Williams F8W2030 Frost White Acrylic Enamel, or equal. Front bumper, grill, mirrors and wheels as regularly furnished by manufacturer.

C. Body:

1. **General:** Platform type body with an outside width of no less than 94" but not to exceed 96". Length shall be no less than 101" but shall not exceed 114". Floor shall consist of no more than three (3) pieces and be constructed of no less than 1/8" steel tread plate. Shall have removable sides and fold down tailgate no less than 12" high. Sides and tailgate to be constructed of no less than 12 USS gauge steel material.
2. **Long Sills:** No less than 4" structural steel or high strength formed steel channel.
3. **Cross Members:** No less than 4" high strength steel material on not more than 20" centers.
4. **Side Rails:** No less than 4" high strength steel material.
5. **Lights and Reflectors:** Sides and corners to have all necessary lights and reflectors to meet FCC regulations. Side marker and clearance lights shall be bolt on armored type. Reflectors shall be bolt on type. (Recessed, rubber mounted, snap-in lights with reflector type lens and plug-in connectors may be used in lieu of armored lights and bolt on reflectors.
6. **Mud Flaps:** Shall have mud flaps, without advertising, mounted behind rear wheels.
7. **Rear Bumper:** Heavy duty rear bumper meeting DOT specifications.
8. **Tapered Front Bulkhead:** Shall have a bulkhead at front of bed designed to protect rear of cab. Bulkhead shall be approximately 36" high (cab height) and be constructed of no less than 12 USS gauge steel. Shall be approximately cab width to slightly wider than the cab at the top and taper outward on each side to the approximate width of the bed at the bottom. Bulkhead shall have an opening covered with expanded metal to offer rear visibility. Nominal height and width of the bulkhead opening shall correspond with the size and location of the rear cab window of the cab & chassis.
9. **Color:** Shall be primed and painted Sherwin-Williams F1B-4009 Gloss Black Enamel, or equivalent.

D. Warranty:

- A. Cab & chassis purchased under this specification shall include manufacturer's standard warranty.
- B. Body purchased under this specification shall be warranted against defects in material and workmanship for a minimum period of twelve (12) months (365 days) from date unit is placed in operation by ARDOT.
- C. Warranty shall include all parts and labor cost associated with needed repairs based on defects in material and workmanship.
- D. It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
- E. If any warranty literature submitted with the bid conflicts with ARDOT warranty requirements, the conflict(s) shall be specifically noted, corrected and included with the bid or the conflict(s) will be considered an exception to warranty specifications and the bid rejected.
- F. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment. For the purposes of this paragraph "timely manner" means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph "manufacturer" means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph "replacement part" means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is

capable of providing dependable performance in normal operation conditions for its normal service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.

ARKANSAS DEPARTMENT OF TRANSPORTATION
SPECIFICATION 19-54A-024
FOR
CREW CAB AND CHASSIS
13,000 POUNDS GVWR
FOUR WHEEL DRIVE
WITH FLATBED BODY

A. General Conditions:

1. **Current Model:** All vehicles shall meet the requirements of Arkansas Department of Transportation Specifications attached to and made a part of this bid. Vehicles furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Vehicles manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable.
2. **Literature:** Manufacturers literature, verifying adherence of proposed unit to each line item addressed in this specification, shall be submitted with the bid. If any literature and/or specifications of items conflict with ARDOT specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.
3. Any deviations from specifications and requirements herein must be clearly pointed out by bidder. Otherwise it will be considered that equipment offered is in strict compliance with these specifications and requirements, and successful bidder will be held responsible therefor. Deviations must be explained in detail on an attached sheet. However, no implication is made by the Arkansas Department of Transportation that deviations will be acceptable.
4. **Manuals:** The successful bidder shall furnish one (1) Operator's Instruction Manual with each unit delivered.
5. **Service & Inspection:** Each Vehicle shall be completely serviced, cleaned and thoroughly inspected (in accordance with manufacturer's required or recommended pre-delivery service) just prior to delivery to the Arkansas Department of Transportation.
6. **Advertisement:** No Dealer advertisement shall be affixed to the vehicle.
7. Any equipment furnished on vehicles purchased under this specification for which "Federal Register Standard" has been established at time of delivery shall comply with the requirements of applicable standard and all equipment required by said standard shall be furnished whether or not it is specifically mentioned in the specification.
8. **Parts Inventory & Service Facilities:** The successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
9. **Test Drive:** The Arkansas Department of Transportation reserves the right to test drive make and model of vehicle bid on prior to contract being awarded. Samples may be demonstrator models with equipment similar, but not necessarily identical, to that listed in the specification.
10. **Cooperative Purchasing:** Other tax-supported entities* in Arkansas (cities, counties, state agencies, school districts, etc.) may purchase from this Contract on an individual basis under the same specifications and conditions, and at the pricing set forth by each vendor, all at the discretion of each vendor in each case. Prices could be reduced by a vendor for minor alterations in conditions (changing order quantities, deleting options, etc.) as agreed by both parties, but could not be raised above the contract bid price except for any additional freight charges. Vendors would not be required to sell to any such entity under this contract, and those entities would not be obligated to purchase from the contract.

Each entity wishing to purchase from the contract must make contact directly with the appropriate vendor(s). The Highway Department shall remain "out of the loop" for such transactions: all contact, orders, invoices, payments, etc. regarding such transactions must take place exclusively between the tax-supported entity and the vendor. The Department shall be held harmless of any and all liability arising from such transactions.

* Tax-supported entities are defined as those receiving more than half of total funding from appropriated tax funds.

B. Unit Specifications:

1. GVWR: No less than 13,000 pounds.
2. Wheelbase: Minimum of 171”.
3. Cab to Axle: 60”, nominal.
4. Engine: Minimum piston displacement of 5.7 liters equipped with dry type air cleaner, maintenance free battery with a minimum rating of 600 cold cranking amps at 0° F, full flow oil filter and not less than 200 amp alternator.
5. Fuel: The vehicle shall be OEM designed as an alternative fuel vehicle meeting EPA requirements. Vehicle furnished shall be capable of using ethanol/fuel blends up to E85.
6. Cooling: Heavy duty cooling system with anti-freeze protection to -20° F, or lower.
7. Transmission: Automatic, with a minimum of six (6) forward speeds. Shall include an auxiliary transmission oil cooler.
8. Transfer Case: Minimum of two (2) speed ranges.
9. Steering: Hydraulic actuated power steering as regularly offered by manufacturer.
10. Front Axle: Hypoid type with a ratio of 3.73, 4.10 or 4.30 to 1 (Alternate ratio may be provided if approved by ARDOT prior to delivery.) Shall be equipped with automatic or manual locking hubs, or axle disconnect system. Capacity of front axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above.
11. Rear Axle: Hypoid type, full floating axle with locking or limited slip differential and a ratio of 3.73, 4.10 or 4.30 to 1. (Alternate ratio may be provided if approved by ARDOT prior to delivery.) Capacity of rear axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above. Rear springs shall consist of both main and auxiliary or overloads.
12. Brakes: Power front and rear disc with four wheel anti-lock. Mechanical parking brake as regularly furnished by manufacturer.
13. Cab: Four (4) Door Crew Cab, complete with insulation and all standard interior trim, dual electric intermittent windshield wipers with washers, right and left sun visors, floor covering consisting of manufacturer’s standard materials and colors for model and trim level provided, factory installed fresh air heater defroster unit, factory installed electronic AM/FM radio, key lock on front doors, inside rear view mirror and right and left side trailer tow type exterior mirrors with extended or extendible arms. Mirror heads to measure no less than 6” x 9”.
14. Seating: Two (2) three (3) person seating capacity bench seats. Front seat to be split bench style. Upholstery to consist of manufacturer’s standard materials and colors for model and trim level provided. Seat belts shall be provided for all seating positions.
15. Air Conditioning: Shall be equipped with factory installed air conditioning and include tinted glass.
16. Tilt Steering Column: Factory installed.
17. Speed Control: Factory installed automatic cruise control.
18. Wheels: Seven (7) 17” diameter steel disc with no less than 6.0” rim section. Rear wheels to be dual.
19. Tires: Seven (7) On/Off-Road or All Terrain tubeless radials no less than LT245/75R17 or LT235/80R17, E load range (duals on rear).
20. Fuel Tank(s): Minimum fuel capacity of 22 gallons. Fuel fill hose assembly furnished with fuel tank(s) shall be a minimum of 36” in length to allow attachment to an aftermarket body.
21. Front Tow Hooks: Two (2), minimum.
22. Lights: Dual beam headlights, parking lights, self-canceling directional turn signals with hazard flasher switch, back up lights, front side marker lights and front cab clearance and identification lamps. Rear lights to consist of stop and tail lights in addition to directional signals.

23. **Equipment:** Front bumper, front and rear shock absorbers, jack and lug wrench.
24. **Trailer Tow Equipment:** Heavy duty trailering equipment including frame mounted hitch receiver (Class V, minimum), trailer wiring with seven (7) wire harness, heavy duty flasher and factory installed integrated trailer brake controller. Frame mounted hitch receiver may be an aftermarket installation meeting Class V requirements at a minimum.
25. **Keys:** Minimum of four (4) ignition/door keys per vehicle.
26. **Color:** Sherwin Williams F8W2030 Frost White Acrylic Enamel, or equal. Front bumper, grill, mirrors and wheels as regularly furnished by manufacturer.

C. Body:

1. **General:** Platform type body with an outside width of no less than 94” but not to exceed 96”. Length shall be no less than 101” but shall not exceed 114”. Floor shall consist of no more than three (3) pieces and be constructed of no less than 1/8” steel tread plate. Shall have removable sides and fold down tailgate no less than 12” high. Sides and tailgate to be constructed of no less than 12 USS gauge steel material.
2. **Long Sills:** No less than 4” structural steel or high strength formed steel channel.
3. **Cross Members:** No less than 4” high strength steel material on not more than 20” centers.
4. **Side Rails:** No less than 4” high strength steel material.
5. **Lights and Reflectors:** Sides and corners to have all necessary lights and reflectors to meet FCC regulations. Side marker and clearance lights shall be bolt on armored type. Reflectors shall be bolt on type. (Recessed, rubber mounted, snap-in lights with reflector type lens and plug-in connectors may be used in lieu of armored lights and bolt on reflectors.
6. **Mud Flaps:** Shall have mud flaps, without advertising, mounted behind rear wheels.
7. **Rear Bumper:** Heavy duty rear bumper meeting DOT specifications.
8. **Tapered Front Bulkhead:** Shall have a bulkhead at front of bed designed to protect rear of cab. Bulkhead shall be approximately 36” high (cab height) and be constructed of no less than 12 USS gauge steel. Shall be approximately cab width to slightly wider than the cab at the top and taper outward on each side to the approximate width of the bed at the bottom. Bulkhead shall have an opening covered with expanded metal to offer rear visibility. Nominal height and width of the bulkhead opening shall correspond with the size and location of the rear cab window of the cab & chassis.
9. **Color:** Shall be primed and painted Sherwin-Williams F1B-4009 Gloss Black Enamel, or equivalent.

D. Warranty:

1. Cab & chassis purchased under this specification shall include manufacturer’s standard warranty.
2. Body purchased under this specification shall be warranted against defects in material and workmanship for a minimum period of twelve (12) months (365 days) from date unit is placed in operation by ARDOT.
3. Warranty shall include all parts and labor cost associated with needed repairs based on defects in material and workmanship.
4. It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
5. If any warranty literature submitted with the bid conflicts with ARDOT warranty requirements, the conflict(s) shall be specifically noted, corrected and included with the bid or the conflict(s) will be considered an exception to warranty specifications and the bid rejected.
6. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment. For the purposes of this paragraph “timely manner” means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph “manufacturer” means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph “replacement part”

means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is capable of providing dependable performance in normal operation conditions for its normal service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.

ARKANSAS DEPARTMENT OF TRANSPORTATION

SPECIFICATION 19-57-024

FOR

CREW CAB AND CHASSIS

13,000 POUNDS GVWR

FOUR WHEEL DRIVE, DIESEL

1. **GVWR**: No less than 13,000 pounds.
2. **Wheelbase**: Minimum of 171".
3. **Cab to Axle**: 60", nominal.
4. **Engine**: Liquid cooled turbocharged diesel with a minimum piston displacement of 6.6 liters developing no less than 325 SAE gross horsepower at rated RPM and no less than 700 lb. ft. SAE gross torque. Shall be equipped with exhaust brake, air cleaner, no less than two (2) maintenance free batteries with a minimum rating each of 730 cold cranking amps at 0° F, full flow oil filter, fuel filter and not less than 200 amp alternator. Engine shall be equipped with a block heater which will operate on 120 volts AC.
5. **Cooling**: Heavy duty cooling system with anti-freeze protection to -20° F, or lower.
6. **Transmission**: Automatic, with a minimum of six (6) forward speeds. Transmission shall be equipped with PTO provision and include an auxiliary transmission oil cooler.
7. **Transfer Case**: Minimum of two (2) speed ranges.
8. **Steering**: Hydraulic actuated power steering as regularly offered by manufacturer.
9. **Front Axle**: Hypoid type with a ratio of 3.73 or 4.10 to 1 (Alternate ratio may be provided if approved by ARDOT prior to delivery.) Shall be equipped with automatic or manual locking hubs, or axle disconnect system. Capacity of front axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above.
10. **Rear Axle**: Hypoid type, full floating, with locking or limited slip differential and a ratio of 3.73 or 4.10 to 1. (Alternate ratio may be provided if approved by ARDOT prior to delivery.) Capacity of rear axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above. Rear springs shall consist of both main and auxiliary or overloads.
11. **Brakes**: Power front and rear disc with four wheel anti-lock. Mechanical parking brake as regularly furnished by manufacturer.
12. **Cab**: Four (4) Door Crew Cab, complete with insulation and all standard interior trim, dual electric intermittent windshield wipers with washers, right and left sun visors, floor covering consisting of manufacturer's standard materials and colors for model and trim level provided, factory installed fresh air heater defroster unit, factory installed electronic AM/FM radio, key lock on front doors, inside rear view mirror and right and left side exterior mirrors with extended or extendible arms. Mirror heads to measure no less than 6" x 9".
13. **Seating**: Two (2) three (3) person seating capacity bench seats. Front seat to be cloth split bench style with fold-down arm rest. Rear seat upholstery to consist of manufacturer's standard materials and colors for model and trim level provided. Seat belts shall be provided for all seating positions.
14. **Air Conditioning**: Shall be equipped with factory installed air conditioning and include tinted glass.
15. **Tilt Steering Column**: Factory installed.
16. **Speed Control**: Factory installed automatic cruise control.
17. **Wheels**: Seven (7) 17" diameter steel disc with no less than 6.0" rim section. Rear wheels to be dual.
18. **Tires**: Seven (7) On/Off-Road or All Terrain tubeless radials no less than LT245/75R17 or LT235/80R17, E load range (duals on rear).
19. **Fuel Tank(s)**: Minimum fuel capacity of 22 gallons. Fuel fill hose assembly furnished with fuel tank(s) shall be a minimum of 36" in length to allow attachment to an aftermarket body.
20. **Front Tow Hooks**: Two (2), minimum.
21. **Lights**: Dual beam headlights, parking lights, self-canceling directional turn signals with hazard flasher switch, back up lights, front side marker lights and front cab clearance and identification lamps. Rear lights to consist of stop and tail lights in addition to directional signals.

22. Equipment: Front bumper, front and rear shock absorbers, jack and lug wrench.
23. Trailer Tow Equipment: Heavy duty trailering equipment including factory installed integrated trailer brake controller, trailer wiring with seven (7) wire harness and heavy duty flasher.
24. Keys: Minimum of four (4) ignition/door keys per vehicle.
25. Color: Sherwin Williams F8W2030 Frost White Acrylic Enamel, or equal. Front bumper, grill, mirrors and wheels as regularly furnished by manufacturer.

ARKANSAS DEPARTMENT OF TRANSPORTATION

SPECIFICATION 19-55-020

FOR

CREW CAB AND CHASSIS

13,000 POUNDS GVWR

WITH SERVICE BODY

A. General Conditions:

1. **Current Model:** All vehicles shall meet the requirements of Arkansas Department of Transportation Specifications attached to and made a part of this bid. Vehicles furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Vehicles manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable.
2. **Literature:** Manufacturers literature, verifying adherence of proposed unit to each line item addressed in this specification, shall be submitted with the bid. If any literature and/or specifications of items conflict with ARDOT specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.
3. Any deviations from specifications and requirements herein must be clearly pointed out by bidder. Otherwise it will be considered that equipment offered is in strict compliance with these specifications and requirements, and successful bidder will be held responsible therefor. Deviations must be explained in detail on an attached sheet. However, no implication is made by the Arkansas Department of Transportation that deviations will be acceptable.
4. **Manuals:** The successful bidder shall furnish one (1) Operator's Instruction Manual with each unit delivered.
5. **Service & Inspection:** Each Vehicle shall be completely serviced, cleaned and thoroughly inspected (in accordance with manufacturer's required or recommended pre-delivery service) just prior to delivery to the Arkansas Department of Transportation.
6. **Advertisement:** No Dealer advertisement shall be affixed to the vehicle.
7. Any equipment furnished on vehicles purchased under this specification for which "Federal Register Standard" has been established at time of delivery shall comply with the requirements of applicable standard and all equipment required by said standard shall be furnished whether or not it is specifically mentioned in the specification.
8. **Parts Inventory & Service Facilities:** The successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
9. **Test Drive:** The Arkansas Department of Transportation reserves the right to test drive make and model of vehicle bid on prior to contract being awarded. Samples may be demonstrator models with equipment similar, but not necessarily identical, to that listed in the specification.
10. **Cooperative Purchasing:** Other tax-supported entities* in Arkansas (cities, counties, state agencies, school districts, etc.) may purchase from this Contract on an individual basis under the same specifications and conditions, and at the pricing set forth by each vendor, all at the discretion of each vendor in each case. Prices could be reduced by a vendor for minor alterations in conditions (changing order quantities, deleting options, etc.) as agreed by both parties, but could not be raised above the contract bid price except for any additional freight charges. Vendors would not be required to sell to any such entity under this contract, and those entities would not be obligated to purchase from the contract.

Each entity wishing to purchase from the contract must make contact directly with the appropriate vendor(s). The Highway Department shall remain "out of the loop" for such transactions: all contact, orders, invoices, payments, etc. regarding such transactions must take place exclusively between the tax-supported entity and the vendor. The Department shall be held harmless of any and all liability arising from such transactions.

* Tax-supported entities are defined as those receiving more than half of total funding from appropriated tax funds.

B. Unit Specifications:

1. GVWR: No less than 13,000 pounds.
2. Wheelbase: Minimum of 171”.
3. Cab to Axle: 60”, nominal.
4. Engine: Minimum piston displacement of 5.7 liters equipped with dry type air cleaner, maintenance free battery with a minimum rating of 600 cold cranking amps at 0° F, full flow oil filter and not less than 200 amp alternator.
5. Fuel: The vehicle shall be OEM designed as an alternative fuel vehicle meeting EPA requirements. Vehicle furnished shall be capable of using ethanol/fuel blends up to E85.
6. Cooling: Heavy duty cooling system with anti-freeze protection to -20° F, or lower.
7. Transmission: Automatic, with a minimum of six (6) forward speeds. Shall include an auxiliary transmission oil cooler.
8. Steering: Hydraulic actuated power steering as regularly offered by manufacturer.
9. Front Axle: Independent front wheel suspension or I beam type. Capacity of front axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above.
10. Rear Axle: Hypoid type, full floating axle with locking or limited slip differential and a ratio of 3.73, 4.10 or 4.30 to 1. (Alternate ratio may be provided if approved by ARDOT prior to delivery.) Capacity of rear axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above. Rear springs shall consist of both main and auxiliary or overloads.
11. Brakes: Power front and rear disc with four wheel anti-lock. Mechanical parking brake as regularly furnished by manufacturer.
12. Cab: Four (4) Door Crew Cab, complete with insulation and all standard interior trim, dual electric intermittent windshield wipers with washers, right and left sun visors, floor covering consisting of manufacturer’s standard materials and colors for model and trim level provided, factory installed fresh air heater defroster unit, factory installed electronic AM/FM radio, key lock on front doors, inside rear view mirror and right and left side trailer tow type exterior mirrors with extended or extendible arms. Mirror heads to measure no less than 6” x 9”.
13. Seating: Two (2) three (3) person seating capacity bench seats. Front seat to be split bench style. Upholstery to consist of manufacturer’s standard materials and colors for model and trim level provided. Seat belts shall be provided for all seating positions.
14. Air Conditioning: Shall be equipped with factory installed air conditioning and include tinted glass.
15. Tilt Steering Column: Factory installed.
16. Speed Control: Factory installed automatic cruise control.
17. Wheels: Seven (7) 17” diameter steel disc with no less than 6.0” rim section. Rear wheels to be dual.
18. Tires: Seven (7), no less than LT235/80R17 or LT245/75R17, E load range, all season tubeless radials (duals on rear).
19. Fuel Tank(s): Minimum fuel capacity of 22 gallons. Fuel fill hose assembly furnished with fuel tank(s) shall be a minimum of 36” in length to allow attachment to an aftermarket body.
20. Front Tow Hooks: Two (2), minimum.
21. Lights: Dual beam headlights, parking lights, self-canceling directional turn signals with hazard flasher switch, back up lights, front side marker lights and front cab clearance and identification lamps. Rear lights to consist of stop and tail lights in addition to directional signals.
22. Equipment: Front bumper, front and rear shock absorbers, jack and lug wrench.
23. Keys: Minimum of four (4) ignition/door keys per vehicle.

24. Color: Sherwin Williams F8W2030 Frost White Acrylic Enamel, or equal. Front bumper, grill, mirrors and wheels as regularly furnished by manufacturer.

C. Service Body:

1. Body: Shall be standard height service body normally designed to mount on a cab and chassis with dual rear tires and 60" CA measurement.
2. Construction: Electrically welded all steel construction with edges rolled or folded. Body shall have longitudinal members and cross members welded for floor support. Body floor shall be constructed of no less than 12 gauge safety tread plate.
3. Dimensions:
 - (1) Body Length: 107" – 110".
 - (2) Body Width: 93" – 96".
 - (3) Body Height: 40", minimum.
 - (4) Body Floor To Compartment Top: 23" minimum.
 - (5) Compartment Depth: 18", minimum.
 - (6) Floor Width: 49" – 55".
4. Compartments: Each side of the body shall have a minimum of one (1) vertical compartment in front of the rear wheels, one (1) horizontal compartment over the rear wheels and a minimum of one (1) vertical compartment behind the rear wheels. Vertical compartments shall be full height and have adjustable shelves. Each horizontal compartment shall have adjustable dividers. All doors shall be protected from weather and have double panels with flush type handles and locks keyed alike. Doors shall have rubber seals to keep out water and dust.
5. Crane Reinforcement: Right (curbside) rear corner of body shall be reinforced to allow for future installation of a corner mounted service crane with a lifting capacity of 3,200 pounds and a mounting base approximately 12" – 16" long x 12" – 16" wide. The reinforcement plate for crane mounting base shall not to be pre-drilled.
6. Tailgate: Body shall have a hinged tailgate no less than 9" high that opens to floor level with chain or arm support.
7. Bumper: Shall have a rear step plate type bumper with recess and ball hitch plate. Bumper brackets shall mount to truck frame.
8. Lights: Combination tail and directional lights and backup lights to meet ICC regulations.
9. Color: Body shall be painted Sherwin Williams F8W2030 Frost White Acrylic Enamel, or equal.

D. Warranty:

1. Cab & chassis purchased under this specification shall include manufacturer's standard warranty.
2. Body purchased under this specification shall be warranted against defects in material and workmanship for a minimum period of twelve (12) months (365 days) from date unit is placed in operation by ARDOT.
3. Warranty shall include all parts and labor cost associated with needed repairs based on defects in material and workmanship.
4. It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
5. If any warranty literature submitted with the bid conflicts with ARDOT warranty requirements, the conflict(s) shall be specifically noted, corrected and included with the bid or the conflict(s) will be considered an exception to warranty specifications and the bid rejected.
6. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment.

For the purposes of this paragraph “timely manner” means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph “manufacturer” means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph “replacement part” means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is capable of providing dependable performance in normal operation conditions for its normal service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.

ARKANSAS DEPARTMENT OF TRANSPORTATION

SPECIFICATION 19-58-024

FOR

CREW CAB AND CHASSIS

13,000 POUNDS GVWR

FOUR WHEEL DRIVE, DIESEL

WITH FLAT BED BODY

A. General Conditions:

1. **Current Model:** All vehicles shall meet the requirements of Arkansas Department of Transportation Specifications attached to and made a part of this bid. Vehicles furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Vehicles manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable.
2. **Literature:** Manufacturers literature, verifying adherence of proposed unit to each line item addressed in this specification, shall be submitted with the bid. If any literature and/or specifications of items conflict with ARDOT specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.
3. Any deviations from specifications and requirements herein must be clearly pointed out by bidder. Otherwise it will be considered that equipment offered is in strict compliance with these specifications and requirements, and successful bidder will be held responsible therefor. Deviations must be explained in detail on an attached sheet. However, no implication is made by the Arkansas Department of Transportation that deviations will be acceptable.
4. **Manuals:** The successful bidder shall furnish one (1) Operator's Instruction Manual with each unit delivered.
5. **Service & Inspection:** Each Vehicle shall be completely serviced, cleaned and thoroughly inspected (in accordance with manufacturer's required or recommended pre-delivery service) just prior to delivery to the Arkansas Department of Transportation.
6. **Advertisement:** No Dealer advertisement shall be affixed to the vehicle.
7. Any equipment furnished on vehicles purchased under this specification for which "Federal Register Standard" has been established at time of delivery shall comply with the requirements of applicable standard and all equipment required by said standard shall be furnished whether or not it is specifically mentioned in the specification.
8. **Parts Inventory & Service Facilities:** The successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
9. **Test Drive:** The Arkansas Department of Transportation reserves the right to test drive make and model of vehicle bid on prior to contract being awarded. Samples may be demonstrator models with equipment similar, but not necessarily identical, to that listed in the specification.
10. **Cooperative Purchasing:** Other tax-supported entities* in Arkansas (cities, counties, state agencies, school districts, etc.) may purchase from this Contract on an individual basis under the same specifications and conditions, and at the pricing set forth by each vendor, all at the discretion of each vendor in each case. Prices could be reduced by a vendor for minor alterations in conditions (changing order quantities, deleting options, etc.) as agreed by both parties, but could not be raised above the contract bid price except for any additional freight charges. Vendors would not be required to sell to any such entity under this contract, and those entities would not be obligated to purchase from the contract.

Each entity wishing to purchase from the contract must make contact directly with the appropriate vendor(s). The Highway Department shall remain "out of the loop" for such transactions: all contact, orders, invoices, payments, etc. regarding such transactions must take place exclusively between the tax-supported entity and the vendor. The Department shall be held harmless of any and all liability arising from such transactions.

* Tax-supported entities are defined as those receiving more than half of total funding from appropriated tax funds.

B. Unit Specifications:

1. GVWR: No less than 13,000 pounds.
2. Wheelbase: Minimum of 171”.
3. Cab to Axle: 60”, nominal.
4. Engine: Liquid cooled turbocharged diesel with a minimum piston displacement of 6.6 liters developing no less than 325 SAE gross horsepower at rated RPM and no less than 700 lb. ft. SAE gross torque. Shall be equipped with exhaust brake, air cleaner, no less than two (2) maintenance free batteries with a minimum rating each of 730 cold cranking amps at 0° F, full flow oil filter, fuel filter and not less than 200 amp alternator. Engine shall be equipped with a block heater which will operate on 120 volts AC.
5. Cooling: Heavy duty cooling system with anti-freeze protection to -20° F, or lower.
6. Transmission: Automatic, with a minimum of six (6) forward speeds. Transmission shall be equipped with PTO provision and include an auxiliary transmission oil cooler.
7. Transfer Case: Minimum of two (2) speed ranges.
8. Steering: Hydraulic actuated power steering as regularly offered by manufacturer.
9. Front Axle: Hypoid type with a ratio of 3.73 or 4.10 to 1 (Alternate ratio may be provided if approved by ARDOT prior to delivery.) Shall be equipped with automatic or manual locking hubs, or axle disconnect system. Capacity of front axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above.
10. Rear Axle: Hypoid type, full floating, with locking or limited slip differential and a ratio of 3.73 or 4.10 to 1. (Alternate ratio may be provided if approved by ARDOT prior to delivery.) Capacity of rear axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above. Rear springs shall consist of both main and auxiliary or overloads.
11. Brakes: Power front and rear disc with four wheel anti-lock. Mechanical parking brake as regularly furnished by manufacturer.
12. Cab: Four (4) Door Crew Cab, complete with insulation and all standard interior trim, dual electric intermittent windshield wipers with washers, right and left sun visors, floor covering consisting of manufacturer’s standard materials and colors for model and trim level provided, factory installed fresh air heater defroster unit, factory installed electronic AM/FM radio, key lock on front doors, inside rear view mirror and right and left side exterior mirrors with extended or extendible arms. Mirror heads to measure no less than 6” x 9”.
13. Seating: Two (2) three (3) person seating capacity bench seats. Front seat to be cloth split bench style with fold-down arm rest. Rear seat upholstery to consist of manufacturer’s standard materials and colors for model and trim level provided. Seat belts shall be provided for all seating positions.
14. Air Conditioning: Shall be equipped with factory installed air conditioning and include tinted glass.
15. Tilt Steering Column: Factory installed.
16. Speed Control: Factory installed automatic cruise control.
17. Wheels: Seven (7) 17” diameter steel disc with no less than 6.0” rim section. Rear wheels to be dual.
18. Tires: Seven (7) On/Off-Road or All Terrain tubeless radials no less than LT245/75R17 or LT235/80R17, E load range (duals on rear).
19. Fuel Tank(s): Minimum fuel capacity of 22 gallons. Fuel fill hose assembly furnished with fuel tank(s) shall be a minimum of 36” in length to allow attachment to an aftermarket body.
20. Front Tow Hooks: Two (2), minimum.
21. Lights: Dual beam headlights, parking lights, self-canceling directional turn signals with hazard flasher switch, back up lights, front side marker lights and front cab clearance and identification lamps. Rear lights to consist of stop and tail lights in addition to directional signals.
22. Equipment: Front bumper, front and rear shock absorbers, jack and lug wrench.
23. Trailer Tow Equipment: Heavy duty trailering equipment including frame mounted hitch receiver (Class V, minimum), trailer wiring with seven (7) wire harness, heavy duty flasher and factory installed integrated trailer brake controller. Frame mounted hitch receiver may be an aftermarket installation meeting Class V requirements at a minimum.
24. Keys: Minimum of four (4) ignition/door keys per vehicle.

25. Color: Sherwin Williams F8W2030 Frost White Acrylic Enamel, or equal. Front bumper, grill, mirrors and wheels as regularly furnished by manufacturer.

C. Flat Bed Body:

1. General: Platform type body with an outside width of no less than 94" but not to exceed 96". Length shall be no less than 101" but shall not exceed 114". Floor shall consist of no more than three (3) pieces and be constructed of no less than 1/8" steel tread plate. Shall have removable sides and fold down tailgate no less than 12" high. Sides and tailgate to be constructed of no less than 12 USS gauge steel material.
2. Long Sills: No less than 4" structural steel or high strength formed steel channel.
3. Cross Members: No less than 4" high strength steel material on not more than 20" centers.
4. Side Rails: No less than 4" high strength steel material.
5. Lights and Reflectors: Sides and corners to have all necessary lights and reflectors to meet FCC regulations. Side marker and clearance lights shall be bolt on armored type. Reflectors shall be bolt on type. (Recessed, rubber mounted, snap-in lights with reflector type lens and plug-in connectors may be used in lieu of armored lights and bolt on reflectors.
6. Mud Flaps: Shall have mud flaps, without advertising, mounted behind rear wheels.
7. Rear Bumper: Heavy duty rear bumper meeting DOT specifications.
8. Tapered Front Bulkhead: Shall have a bulkhead at front of bed designed to protect rear of cab. Bulkhead shall be approximately 36" high (cab height) and be constructed of no less than 12 USS gauge steel. Shall be approximately cab width to slightly wider than the cab at the top and taper outward on each side to the approximate width of the bed at the bottom. Bulkhead shall have an opening covered with expanded metal to offer rear visibility. Nominal height and width of the bulkhead opening shall correspond with the size and location of the rear cab window of the cab & chassis.
9. Color: Shall be primed and painted Sherwin-Williams F1B-4009 Gloss Black Enamel, or equivalent.

D. Warranty:

1. Cab & chassis purchased under this specification shall include manufacturer's standard warranty.
2. Body purchased under this specification shall be warranted against defects in material and workmanship for a minimum period of twelve (12) months (365 days) from date unit is placed in operation by ARDOT.
3. Warranty shall include all parts and labor cost associated with needed repairs based on defects in material and workmanship.
4. It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
5. If any warranty literature submitted with the bid conflicts with ARDOT warranty requirements, the conflict(s) shall be specifically noted, corrected and included with the bid or the conflict(s) will be considered an exception to warranty specifications and the bid rejected.
6. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment. For the purposes of this paragraph "timely manner" means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph "manufacturer" means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph "replacement part" means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is capable of providing dependable performance in normal operation conditions for its normal service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.

ARKANSAS DEPARTMENT OF TRANSPORTATION

SPECIFICATION 19-22-016

FOR

PICKUP TRUCK

13,000 POUNDS GVWR

LONG BED

1. **GVWR**: No less than 13,000 pounds.
2. **Wheelbase**: Minimum of 132", maximum of 144".
3. **Engine**: Minimum piston displacement of 5.7 liters equipped with dry type air cleaner, maintenance free battery with a minimum rating of 650 cold cranking amps at 0° F, full flow oil filter and not less than 150 amp alternator.
4. **Fuel**: The vehicle shall be OEM designed as an alternative fuel vehicle meeting EPAAct requirements. Vehicle furnished shall be capable of using ethanol/fuel blends up to E85.
5. **Cooling**: Heavy duty cooling system with anti-freeze protection to -20° F, or lower.
6. **Transmission**: Automatic, with a minimum of six (6) forward speeds. Shall include an auxiliary transmission oil cooler.
7. **Steering**: Hydraulic actuated power steering as regularly offered by manufacturer.
8. **Front Axle**: Independent front wheel suspension, I beam, or solid type axle. Capacity of front axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above.
9. **Rear Axle**: Hypoid type, full floating, with locking or limited slip differential and a ratio of 3.73 or 4.10 to 1. (Alternate ratio may be provided if approved by ARDOT prior to delivery.) Capacity of rear axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above. Rear springs shall consist of both main and auxiliary or overloads.
10. **Brakes**: Power front and rear disc with four wheel anti-lock. Mechanical parking brake as regularly furnished by manufacturer.
11. **Cab**: Regular Cab complete with insulation and all standard interior trim, dual electric intermittent windshield wipers, right and left sun visors, factory installed electronic AM/FM radio, floor covering consisting of manufacturer's standard materials and colors for model and trim level provided, factory installed fresh air heater defroster unit, key lock on doors, inside rear view mirror, and right and left side trailer tow type exterior mirrors with extended or extendible arms. Mirror heads to measure no less than 6" x 9".
12. **Seating**: Split bench seat with fold-down center arm rest and three (3) person seating. Upholstery to consist of manufacturer's standard materials and colors for model and trim level provided. Seat belts shall be provided for all seating positions.
13. **Air Conditioning**: Shall be equipped with factory installed air conditioning and include tinted glass.
14. **Tilt Steering Column**: Factory installed.
15. **Speed Control**: Factory installed automatic cruise control.
16. **Body**: Wide type pickup body no less than 96" in length inside, complete with tailgate.
17. **Wheels**: Seven (7) 17" or 18" diameter steel disc with no less than 6.0" rim section. Rear wheels to be dual.
18. **Tires**: Seven (7), no less than LT235/80R17, LT245/75R17 or LT265/70R18, E load range, all season tubeless radials (duals on rear).
19. **Fuel Tank(s)**: Minimum fuel capacity of 26 gallons.
20. **Lights**: Dual beam headlights, parking lights, self canceling directional turn signals with hazard flasher switch, back up lights, front side marker lights and front cab clearance and identification lamps. Rear lights to consist of stop and tail lights in addition to directional signals.

21. Equipment: Equipment: Front bumper, heavy duty step type rear bumper with hitch plate and license plate light, rear license plate bracket, front and rear shock absorbers, spare tire carrier as regularly furnished by manufacturer, hub caps, jack and lug wrench.
22. Keys: Minimum of four (4) ignition/door keys per vehicle.
23. Color: Sherwin Williams F8W2030 Frost White Acrylic Enamel, or equal. Front bumper, grill, mirrors and wheels as regularly furnished by manufacturer.
24. Literature: Manufacturers literature, verifying adherence of proposed unit to each line item addressed in this specification, shall be submitted with the bid. If any literature and/or specifications of items conflict with ARDOT specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.

ARKANSAS DEPARTMENT OF TRANSPORTATION

SPECIFICATION 19-36-020

FOR

CAB AND CHASSIS

16,000 POUNDS GVWR

DIESEL

- A. **GVWR**: No less than 16,000 pounds.
- B. **Wheelbase**: Minimum of 140", maximum of 146".
- C. **Cab to Axle**: 60", nominal.
- D. **Engine**: Liquid cooled turbocharged diesel with a minimum piston displacement of 6.6 liters developing no less than 325 SAE gross horsepower at rated RPM and no less than 700 lb. ft. SAE gross torque. Shall be equipped with exhaust brake, air cleaner, no less than two (2) maintenance free batteries with a minimum rating each of 730 cold cranking amps at 0° F, full flow oil filter, fuel filter and not less than 150 amp alternator. Engine shall be equipped with a block heater which will operate on 120 volts AC.
- E. **Cooling**: Heavy duty cooling system with anti-freeze protection to -20° F, or lower.
- F. **Transmission**: Automatic, with a minimum of six (6) forward speeds. Transmission shall be equipped with PTO provision and include an auxiliary transmission oil cooler.
- G. **Steering**: Hydraulic actuated power steering as regularly offered by manufacturer.
- H. **Front Axle**: I-beam or solid type axle. Capacity of front axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above.
- I. **Rear Axle**: Hypoid type, full floating, with a ratio of 4.10, 4.30 or 4.44 to 1. (Alternate ratio may be provided if approved by ARDOT prior to delivery.) Capacity of rear axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above. Rear springs shall consist of both main and auxiliary or overloads.
- J. **Brakes**: Power front and rear disc with four-wheel anti-lock. Parking brake as regularly furnished by manufacturer.
- K. **Cab**: Conventional Cab complete with insulation and all standard interior trim, dual electric intermittent windshield wipers, right and left sun visors, factory installed electronic AM/FM radio, floor covering consisting of manufacturer's standard materials and colors for model and trim level provided, factory installed fresh air heater defroster unit, key lock on doors, inside rear view mirror, and right and left side trailer tow type exterior mirrors with extended or extendible arms. Mirror heads to measure no less than 6" x 9".
- L. **Seating**: Split bench seat with fold-down center arm rest and three (3) person seating. Upholstery to consist of manufacturer's standard materials and colors for model and trim level provided. Seat belts shall be provided for all seating positions.
- M. **Air Conditioning**: Shall be equipped with factory installed air conditioning and include tinted glass.
- N. **Tilt Steering Column**: Factory installed.
- O. **Speed Control**: Automatic speed control (may be dealer installed, but of same manufacturer as vehicle).
- P. **Wheels**: Seven (7) 19.5" steel disc with no less than 6.0" rim section. Rear wheels to be dual.
- Q. **Tires**: Seven (7), no less than 225/70R19.5 - G load range, all season tubeless radials (duals on rear).
- R. **Fuel Tank(s)**: Minimum fuel capacity of 40 gallons. Fuel fill hose assembly(s) furnished with fuel tank(s) shall be a minimum of 36" in length to allow attachment to an aftermarket body.
- S. **Front Tow Hooks**: Two (2), minimum.
- T. **Lights**: Dual beam headlights, parking lights, self-canceling directional turn signals with hazard flasher switch, back up lights, front side marker lights and front cab clearance and identification lamps. Rear lights to consist of stop and tail lights in addition to directional signals.
- U. **Equipment**: Front bumper, front and rear shock absorbers, jack and lug wrench.
- V. **Keys**: Minimum of three (3) ignition/door keys per vehicle.
- W. **Color**: Sherwin Williams F8W2030 Frost White Acrylic Enamel, or equal. Front bumper, grill, mirrors and wheels as regularly furnished by manufacturer.

ARKANSAS DEPARTMENT OF TRANSPORTATION

SPECIFICATION 19-45-020

FOR

CAB AND CHASSIS

19,000 POUNDS GVWR

DIESEL

WITH SERVICE BODY

AND ELECTRIC POWERED CRANE

A. General Conditions:

1. **Current Model:** All vehicles shall meet the requirements of Arkansas Department of Transportation Specifications attached to and made a part of this bid. Vehicles furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Vehicles manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable.
2. **Literature:** Manufacturers literature, verifying adherence of proposed unit to each line item addressed in this specification, shall be submitted with the bid. If any literature and/or specifications of items conflict with ARDOT specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.
3. Any deviations from specifications and requirements herein must be clearly pointed out by bidder. Otherwise it will be considered that equipment offered is in strict compliance with these specifications and requirements, and successful bidder will be held responsible therefor. Deviations must be explained in detail on an attached sheet. However, no implication is made by the Arkansas Department of Transportation that deviations will be acceptable.
4. **Manuals:** The successful bidder shall furnish one (1) Operator's Instruction Manual with each unit delivered.
5. **Service & Inspection:** Each Vehicle shall be completely serviced, cleaned and thoroughly inspected (in accordance with manufacturer's required or recommended pre-delivery service) just prior to delivery to the Arkansas Department of Transportation.
6. **Advertisement:** No Dealer advertisement shall be affixed to the vehicle.
7. Any equipment furnished on vehicles purchased under this specification for which "Federal Register Standard" has been established at time of delivery shall comply with the requirements of applicable standard and all equipment required by said standard shall be furnished whether or not it is specifically mentioned in the specification.
8. **Parts Inventory & Service Facilities:** The successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
9. **Test Drive:** The Arkansas Department of Transportation reserves the right to test drive make and model of vehicle bid on prior to contract being awarded. Samples may be demonstrator models with equipment similar, but not necessarily identical, to that listed in the specification.
10. **Cooperative Purchasing:** Other tax-supported entities* in Arkansas (cities, counties, state agencies, school districts, etc.) may purchase from this Contract on an individual basis under the same specifications and conditions, and at the pricing set forth by each vendor, all at the discretion of each vendor in each case. Prices could be reduced by a vendor for minor alterations in conditions (changing order quantities, deleting options, etc.) as agreed by both parties, but could not be raised above the contract bid price except for any additional freight charges. Vendors would not be required to sell to any such entity under this contract, and those entities would not be obligated to purchase from the contract.

Each entity wishing to purchase from the contract must make contact directly with the appropriate vendor(s). The Highway Department shall remain "out of the loop" for such transactions: all contact, orders, invoices, payments, etc. regarding such transactions must take place exclusively between the tax-supported entity and the vendor. The Department shall be held harmless of any and all liability arising from such transactions.

* Tax-supported entities are defined as those receiving more than half of total funding from appropriated tax funds.

B. Unit Specifications:

1. Chassis:

- A. GVWR: No less than 19,000 pounds.
- B. Wheelbase: Minimum of 140", maximum of 146".
- C. Cab to Axle: 60", nominal.
- D. Engine: Liquid cooled turbocharged diesel with a minimum piston displacement of 6.6 liters developing no less than 325 SAE gross horsepower at rated RPM and no less than 700 lb. ft. SAE gross torque. Shall be equipped with exhaust brake, air cleaner, no less than two (2) maintenance free batteries with a minimum rating each of 730 cold cranking amps at 0° F, full flow oil filter, fuel filter and not less than 150 amp alternator. Engine shall be equipped with a block heater which will operate on 120 volts AC.
- E. Cooling: Heavy duty cooling system with anti-freeze protection to -20° F, or lower.
- F. Transmission: Automatic, with a minimum of six (6) forward speeds. Transmission shall be equipped with PTO provision and include an auxiliary transmission oil cooler.
- G. Steering: Hydraulic actuated power steering as regularly offered by manufacturer.
- H. Front Axle: I-beam or solid type axle. Capacity of front axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above.
- I. Rear Axle: Hypoid type, full floating, with a ratio of 4.10, 4.30 or 4.44 to 1. (Alternate ratio may be provided if approved by ARDOT prior to delivery.) Capacity of rear axle and springs shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above. Rear springs shall consist of both main and auxiliary or overloads.
- J. Brakes: Power front and rear disc with four wheel anti-lock. Parking brake as regularly furnished by manufacturer.
- K. Cab: Conventional Cab complete with insulation and all standard interior trim, dual electric intermittent windshield wipers, right and left sun visors, factory installed electronic AM/FM radio, floor covering consisting of manufacturer's standard materials and colors for model and trim level provided, factory installed fresh air heater defroster unit, key lock on doors, inside rear view mirror, and right and left side trailer tow type exterior mirrors with extended or extendible arms. Mirror heads to measure no less than 6" x 9".
- L. Seating: May consist of a split bench seat with three (3) person seating or a driver's high back bucket seat and two (2) person passenger seat. Upholstery to consist of manufacturer's standard materials and colors for model and trim level provided. Seat belts shall be provided for all seating positions.
- M. Air Conditioning: Shall be equipped with factory installed air conditioning and include tinted glass.
- N. Tilt Steering Column: Factory installed.
- O. Speed Control: Factory installed automatic cruise control.
- P. Wheels: Seven (7) 19.5" steel disc with no less than 6.0" rim section. Rear wheels to be dual.
- Q. Tires: Seven (7), no less than 225/70R19.5 - G load range, all season tubeless radials (duals on rear).
- R. Fuel Tank(s): Minimum fuel capacity of 40 gallons. Fuel fill hose assembly(s) furnished with fuel tank(s) shall be a minimum of 36" in length to allow attachment to an aftermarket body.
- S. Front Tow Hooks: Two (2), minimum.
- T. Lights: Dual beam headlights, parking lights, self canceling directional turn signals with hazard flasher switch, back up lights, front side marker lights and front cab clearance and identification lamps. Rear lights to consist of stop and tail lights in addition to directional signals.
- U. Equipment: Front bumper, front and rear shock absorbers, jack and lug wrench.
- V. Keys: Minimum of four (4) ignition/door keys per vehicle.
- W. Color: Sherwin Williams F8W2030 Frost White Acrylic Enamel, or equal. Front bumper, grill, mirrors and wheels as regularly furnished by manufacturer.

2. **Service Body:** Standard height service body designed to mount on the Cab & Chassis specified above.
 - A. **Construction:** Electrically welded all steel construction with edges rolled or folded. Body shall have longitudinal members and cross members welded for floor support. Body floor shall be constructed of no less than 12 gauge safety tread plate.
 - B. **Dimensions:**
 - (1) **Body Length:** 107" – 110".
 - (2) **Body Width:** 93" – 96".
 - (3) **Body Height:** 40", minimum.
 - (4) **Body Floor To Compartment Top:** 23" minimum.
 - (5) **Compartment Depth:** 18", minimum.
 - (6) **Floor Width:** 49" – 55".
 - C. **Compartments:** Each side of the body shall have a minimum of one (1) vertical compartment in front of the rear wheels, one (1) horizontal compartment over the rear wheels and a minimum of one (1) vertical compartment behind the rear wheels. Vertical compartments shall be full height and have adjustable shelves. Each horizontal compartment shall have adjustable dividers. All doors shall be protected from weather and have double panels with flush type handles and locks keyed alike. Doors shall have rubber seals to keep out water and dust.
 - D. **Crane Reinforcement:** Right (curbside) rear corner of body shall be reinforced to allow for installation of a corner mounted service crane with a lifting capacity of 3,200 pounds and a mounting base approximately 12" – 16" long x 12" – 16" wide.
 - E. **Tailgate:** Body shall have a hinged tailgate no less than 9" high that opens to floor level with chain or arm support.
 - F. **Bumper:** Shall have a rear step plate type bumper with recess and ball hitch plate. Bumper brackets shall mount to truck frame.
 - G. **Lights:** Combination tail and directional lights and backup lights to meet ICC regulations.
 - H. **Color:** Service Body shall be painted Sherwin Williams F8W2030 Frost White Acrylic Enamel or equal to match Cab & Chassis specified above. Service crane specified below may be manufacturer's standard color.
3. **Service Crane:** Electric powered crane designed for mounting on the service body specified above. Unit shall have a minimum crane rating of 10,000 ft. lbs. and a lifting capacity of no less than 3,200 pounds at 3' from centerline of rotation. Crane provided shall provide power elevation, power extension and power rotation of the boom.
 - A. **Hoisting Unit:** Electric powered reversible winch driven by a 12 volt DC motor rated at no less than 1.8 horsepower. Winch shall be equipped with at least 60' of no less than 7/32" aircraft type steel cable with a minimum breaking strength of 5,600 pounds and be complete with swivel block with hook.
 - B. **Boom:** Shall be designed from seamless steel tubing and mounted on a pedestal type base. Shall provide a minimum horizontal reach from centerline of rotation of 7', when retracted, to a maximum horizontal reach of no less than 15' when fully extended.
 - (1) **Rotation:** 360° continuous power rotation.
 - (2) **Boom Elevation:** Power boom elevation ranging from horizontal to no less than 70° above horizontal.
 - (3) **Boom Extension:** Shall be equipped with hydraulically powered boom extension from 7' minimum to no less than 11'. Boom extension may be manual or hydraulic from 11' minimum to no less than 15'.
 - C. **Hydraulic System:** Shall be a self contained 12 volt DC system powered by the vehicle electrical system.
 - D. **Mounting:** Boom pedestal shall be designed to mount on the reinforced curbside rear corner of service body specified above. Mounting base shall be square or rectangular, approximately 12" - 18" long x 12" - 16" wide.
 - E. **Lifting Capacity:** No less than 3,200 pounds at 3' radius, no less than 900 pounds at 11' radius and no less than 650 pounds at 15' radius.

- F. Detachable Jack Leg: A quick-detachable outrigger jack leg, for stabilizing vehicle when crane is in operation, shall be furnished. Jack leg furnished shall be suitable for installation on a truck which has a height from top of rear bumper to ground of 25". Jack leg shall be designed and recommended for use with electric powered crane provided under this specification.
 - G. Boom Support: A boom support shall be furnished with the service crane to hold and retain the boom during transport. Boom support shall be suitable for installation on a standard height service body with 18" – 20" compartment depth.
 - H. Additional Equipment: Unit shall be complete with removable remote control unit with no less than 18' of cable.
4. Warranty: Units purchased under this specification shall be warranted against defects in material and workmanship for a minimum period of twelve (12) months (365 days) from date unit is placed in operation by ARDOT.
- A. Warranty shall include all parts, labor and transportation costs to the location of equipment.
 - B. If equipment cannot be repaired on location, warranty shall include cost of transport to the facility where the repair work will be done.
 - C. It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
 - D. If any warranty literature submitted with the bid conflicts with ARDOT warranty requirements, the conflict(s) shall be specifically noted, corrected and included with the bid or the conflict(s) will be considered an exception to warranty specifications and the bid rejected.
 - E. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment. For the purposes of this paragraph "timely manner" means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph "manufacturer" means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph "replacement part" means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is capable of providing dependable performance in normal operation conditions for its normal service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.