

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				7	ARK.			
				JOB NO.	070418	1	52	
				② HALFWAY CREEK STR. & APPRS. (S)				

ARKANSAS DEPARTMENT OF TRANSPORTATION
CONSTRUCTION PLANS FOR STATE HIGHWAY


HALFWAY CREEK STR. & APPRS. (S)

BRADLEY COUNTY
ROUTE 160 SECTION 9


JOB 070418

FED. AID PROJ. NHPP-0006(38)

NOT TO SCALE



ARK. HWY. DIST. NO. 7




PROJECT LOCATION

VICINITY MAP

BRIDGE DATA

- ① STA. 208+68.75 BR. END
- 165' -6" BRIDGE LENGTH
- 164' -6" INTEGRAL PRESTRESSED CONCRETE GIRDER UNIT (TYPE II) (54'-9", 55', 54'-9")
- BR. NO. 07475
- 30' - 0" CLEAR ROADWAY
- STA. 210+34.25 BR. END

STA. 199+73.93
BEGIN JOB 070418
LOG MILE 9.50



STA. 216+55.98
END JOB 070418

DESIGN TRAFFIC DATA

DESIGN YEAR	-----	2040
2020 ADT	-----	470
2040 ADT	-----	540
2040 DHV	-----	59
DIRECTIONAL DISTRIBUTION	-----	60%
TRUCKS	-----	9%
DESIGN SPEED	-----	50 MPH



APPROVED



11-15-19
DEPUTY DIRECTOR
AND CHIEF ENGINEER

	BEGIN PROJECT	MID-POINT OF PROJECT	END PROJECT
LATITUDE	N 33°20' 6.45"	N 33°20' 7.59"	N 33°20' 8.20"
LONGITUDE	W 92°7' 56.18"	W 92°7' 44.78"	W 92°7' 36.41"

GROSS LENGTH OF PROJECT	1682.05	FEET OR	0.319	MILES
NET " " ROADWAY	1516.55	" "	0.288	"
NET " " BRIDGES	165.50	" "	0.031	"
NET " " PROJECT	1682.05	" "	0.319	"

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. RD. PROJ. NO.	SHEET NO.	TOTAL SHEETS
12-20-19				6	ARK.			
						JOB NO. 070418	2	52

INDEX OF SHEETS

② INDEX OF SHEETS AND STANDARD DRAWINGS

SHEET NO.	TITLE	BRIDGE NO.	DRWG. NO.
1	TITLE SHEET		
2	INDEX OF SHEETS AND STANDARD DRAWINGS		
3	GOVERNING SPECIFICATIONS AND GENERAL NOTES		
4	TYPICAL SECTIONS OF IMPROVEMENT		
5	SPECIAL DETAILS		
6 - 11	TEMPORARY EROSION CONTROL DETAILS		
12 - 15	MAINTENANCE OF TRAFFIC DETAILS		
16 - 17	PERMANENT PAVEMENT MARKING DETAILS		
18 - 21	QUANTITIES		
22	SCHEDULE OF BRIDGE QUANTITIES	07475	61366
23	SUMMARY OF QUANTITIES AND REVISIONS		
24 - 26	SURVEY CONTROL DETAILS		
27 - 28	PLAN AND PROFILE SHEETS		
29	LAYOUT OF BRIDGE HIGHWAY 160 OVER HALFWAY CREEK (SHEET 1 OF 2)	07475	61367
30	LAYOUT OF BRIDGE HIGHWAY 160 OVER HALFWAY CREEK (SHEET 2 OF 2)	07475	61368
31	DETAILS OF END BENTS	07475	61369
32	DETAILS OF INTERMEDIATE BENTS	07475	61370
33	DETAILS OF ELASTOMERIC BEARINGS	07475	61371
34	DETAILS OF 164'-6" INTEGRAL PRESTRESSED CONCRETE GIRDER UNIT (SHEET 1 of 8)	07475	61372
35	DETAILS OF 164'-6" INTEGRAL PRESTRESSED CONCRETE GIRDER UNIT (SHEET 2 of 8)	07475	61373
36	DETAILS OF 164'-6" INTEGRAL PRESTRESSED CONCRETE GIRDER UNIT (SHEET 3 of 8)	07475	61374
37	DETAILS OF 164'-6" INTEGRAL PRESTRESSED CONCRETE GIRDER UNIT (SHEET 4 of 8)	07475	61375
38	DETAILS OF 164'-6" INTEGRAL PRESTRESSED CONCRETE GIRDER UNIT (SHEET 5 of 8)	07475	61376
39	DETAILS OF 164'-6" INTEGRAL PRESTRESSED CONCRETE GIRDER UNIT (SHEET 6 of 8)	07475	61377
40	DETAILS OF 164'-6" INTEGRAL PRESTRESSED CONCRETE GIRDER UNIT (SHEET 7 of 8)	07475	61378
41	DETAILS OF 164'-6" INTEGRAL PRESTRESSED CONCRETE GIRDER UNIT (SHEET 8 of 8)	07475	61379
42	DETAILS OF TYPE SPECIAL APPROACH SLAB	07475	61380
43 - 52	CROSS SECTIONS		



BRIDGE STANDARD DRAWINGS

DRWG. NO.	TITLE	DATE
55000	STANDARD DETAILS FOR EMBANKMENT CONSTRUCTION AND BACKFILL AT BRIDGE ENDS	02-27-14
55001	STANDARD DETAILS FOR DUMPED RIPRAP AND FILTER BLANKET AND COMPUTING EXCAVATION FOR STRUCTURES	02-27-14
55005	STANDARD DETAILS FOR PERMANENT STEEL BRIDGE DECK FORMS FOR STEEL & CONCRETE GIRDER SPANS	03-24-16
55010	STANDARD DETAILS FOR TYPE D BRIDGE NAME PLATE	01-15-19
55020	STANDARD DETAILS FOR STEEL H-PILES AND PILE ENCASEMENTS	03-24-16
55022	STANDARD DETAILS FOR CONCRETE PILES	03-24-16
55030A	STANDARD DETAILS FOR TYPE A APPROACH GUTTERS	09-02-15

ROADWAY STANDARD DRAWINGS

DRWG. NO.	TITLE	DATE
FES-1	FLARED END SECTION	10-18-96
FES-2	FLARED END SECTION	10-18-96
GR-6	GUARDRAIL DETAILS	11-07-09
GR-7	GUARDRAIL DETAILS	11-07-09
GR-8	GUARDRAIL DETAILS	11-07-09
GR-9	GUARDRAIL DETAILS	11-07-09
GR-10	GUARDRAIL DETAILS	11-07-09
GR-11	GUARDRAIL DETAILS	11-07-09
GR-12	GUARDRAIL DETAILS	11-07-09
MB-1	MAILBOX DETAILS	11-18-04
PCC-1	CONCRETE PIPE CULVERT FILL HEIGHTS & BEDDING	02-27-14
PCM-1	METAL PIPE CULVERT FILL HEIGHTS & BEDDING	02-27-14
PCP-1	PLASTIC PIPE CULVERT (HIGH DENSITY POLYETHYLENE)	02-27-14
PCP-2	PLASTIC PIPE CULVERT (PVC F949)	02-27-14
PCP-3	PLASTIC PIPE CULVERT (POLYPROPYLENE)	11-07-19
PM-1	PAVEMENT MARKING DETAILS	06-01-17
PU-1	DETAILS OF PIPE UNDERDRAIN	12-08-16
SE-2	TABLES AND METHOD OF SUPERELEVATION FOR TWO-WAY TRAFFIC	11-07-19
TC-1	STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION	11-07-19
TC-2	STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION	11-07-19
TC-3	STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION	11-07-19
TC-4	STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION-TEMPORARY PRECAST BARRIER	11-07-19
TC-5	STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION-TEMPORARY PRECAST BARRIER	11-07-19
TEC-1	TEMPORARY EROSION CONTROL DEVICES	11-16-17
TEC-2	TEMPORARY EROSION CONTROL DEVICES	06-02-94
TEC-3	TEMPORARY EROSION CONTROL DEVICES	11-03-94

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
12-03-19				6	ARK.			
12-20-19						070418	3	52

GOVERNING SPECIFICATIONS

ARKANSAS STATE HIGHWAY COMMISSION STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION, EDITION OF 2014, AND THE FOLLOWING SPECIAL PROVISIONS AND SUPPLEMENTAL SPECIFICATIONS:

2 GOVERNING SPECS, AND GENERAL NOTES



NUMBER

TITLE

GENERAL NOTES

- ERRATA_____ ERRATA FOR THE BOOK OF STANDARD SPECIFICATIONS
- FHWA-1273__ REQUIRED CONTRACT PROVISIONS FEDERAL-AID CONSTRUCTION CONTRACTS
- FHWA-1273__ SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - NOTICE TO CONTRACTORS
- FHWA-1273__ SUPPLEMENT - SPECIFIC EQUAL EMPLOYMENT OPPORTUNITY RESPONSIBILITIES (23 U.S.C. 140)
- FHWA-1273__ SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - GOALS AND TIMETABLES
- FHWA-1273__ SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - FEDERAL STANDARDS
- FHWA-1273__ SUPPLEMENT - POSTERS AND NOTICES REQUIRED FOR FEDERAL-AID PROJECTS
- FHWA-1273__ SUPPLEMENT - WAGE RATE DETERMINATION
- 100-3_____ CONTRACTOR'S LICENSE
- 100-4_____ DEPARTMENT NAME CHANGE
- 102-2_____ ISSUANCE OF PROPOSALS
- 108-1_____ LIQUIDATED DAMAGES
- 108-2_____ WORK ALLOWED PRIOR TO ISSUANCE OF WORK ORDER
- 110-1_____ PROTECTION OF WATER QUALITY AND WETLANDS
- 303-1_____ AGGREGATE BASE COURSE
- 306-1_____ QUALITY CONTROL AND ACCEPTANCE
- 400-1_____ TACK COATS
- 400-4_____ DESIGN AND QUALITY CONTROL OF ASPHALT MIXTURES
- 400-5_____ PERCENT AIR VOIDS FOR ACHM MIX DESIGNS
- 400-6_____ LIQUID ANTI-STRIP ADDITIVE
- 410-1_____ CONSTRUCTION REQUIREMENTS AND ACCEPTANCE OF ASPHALT CONCRETE PLANT MIX COURSES
- 410-2_____ DEVICES FOR MEASURING DENSITY FOR ROLLING PATTERNS
- 600-2_____ INCIDENTAL CONSTRUCTION
- 603-1_____ LANE CLOSURE NOTIFICATION
- 604-1_____ RETROREFLECTIVE SHEETING FOR TRAFFIC CONTROL DEVICES IN CONSTRUCTION ZONES
- 606-1_____ PIPE CULVERTS FOR SIDE DRAINS
- 617-1_____ GUARDRAIL TERMINAL (TYPE 2)
- 620-1_____ MULCH COVER
- 800-1_____ STRUCTURES
- 802-3_____ CONCRETE FOR STRUCTURES
- 804-2_____ REINFORCING STEEL FOR STRUCTURES
- 808-1_____ INSTALLATION OF ELASTOMERIC BEARINGS
- 808-2_____ ELASTOMERIC BEARINGS
- JOB_070418__ BIDDING REQUIREMENTS AND CONDITIONS
- JOB_070418__ BROADBAND INTERNET SERVICE FOR ASPHALT CONCRETE PLANT
- JOB_070418__ BROADBAND INTERNET SERVICE FOR FIELD OFFICE
- JOB_070418__ CARGO PREFERENCE ACT REQUIREMENTS
- JOB_070418__ CLASS C FLY ASH IN PORTLAND CEMENT CONCRETE PAVEMENT AND CLASS S(AE) CONCRETE
- JOB_070418__ CONSTRUCTION IN SPECIAL FLOOD HAZARD AREAS
- JOB_070418__ DIRECT TENSION INDICATORS FOR HIGH STRENGTH BOLT ASSEMBLIES
- JOB_070418__ DISADVANTAGED BUSINESS ENTERPRISE BIDDER'S RESPONSIBILITIES
- JOB_070418__ EXTENSION FOR PIPE CULVERTS
- JOB_070418__ FLEXIBLE BEGINNING OF WORK
- JOB_070418__ GOALS FOR DISADVANTAGED BUSINESS ENTERPRISE PARTICIPATION
- JOB_070418__ MANDATORY ELECTRONIC CONTRACT
- JOB_070418__ MANDATORY ELECTRONIC DOCUMENT SUBMITTAL
- JOB_070418__ NESTING SITES OF MIGRATORY BIRDS
- JOB_070418__ PLASTIC PIPE
- JOB_070418__ PRICE ADJUSTMENT FOR ASPHALT BINDER
- JOB_070418__ SECTION 404 NATIONWIDE 14 PERMIT REQUIREMENTS
- JOB_070418__ SHORING FOR CULVERTS
- JOB_070418__ SOIL STABILIZATION
- JOB_070418__ STORM WATER POLLUTION PREVENTION PLAN
- JOB_070418__ SUBMISSION OF ASPHALT CONCRETE HOT MIX ACCEPTANCE TEST RESULTS
- JOB_070418__ TRAFFIC CONTROL DEVICES IN CONSTRUCTION ZONES (MASH)
- JOB_070418__ UTILITY ADJUSTMENTS
- JOB_070418__ WARM MIX ASPHALT


1. GRADE LINE DENOTES FINISHED GRADE WHERE SHOWN ON PLANS.
2. ALL PIPE LINES, POWER, TELEPHONE, AND TELEGRAPH LINES TO BE MOVED OR LOWERED BY THE RESPECTIVE OWNERS AS PER AGREEMENT WITH SUCH OWNERS.
3. ANY EQUIPMENT OR APPURTENANCE THAT INTERFERES WITH THE PROPOSED CONSTRUCTION AND WHICH MAY BE THE PROPERTY OF UTILITY SERVICE ORGANIZATIONS SHALL BE MOVED BY THE OWNERS UNLESS OTHERWISE PROVIDED.
4. THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING U. S. MAILBOXES WITHIN THE PROJECT LIMITS IN SUCH A MANNER THAT THE PUBLIC MAY RECEIVE CONTINUED MAIL SERVICE. PAYMENT WILL BE CONSIDERED INCLUDED IN THE PRICE BID FOR THE VARIOUS BID ITEMS.
5. ALL LAND MONUMENTS LOCATED WITHIN THE CONSTRUCTION AREA SHALL BE PROTECTED IN ACCORDANCE WITH SECTION 107.12 OF THE STANDARD SPECIFICATIONS.
6. ALL TREES THAT DO NOT DIRECTLY INTERFERE WITH THE PROPOSED CONSTRUCTION SHALL BE SPARED AS DIRECTED BY THE ENGINEER. CARE AND DISCRETION SHALL BE USED TO ENSURE THAT ALL TREES NOT TO BE REMOVED SHALL BE HARMED AS LITTLE AS POSSIBLE DURING THE CONSTRUCTION OPERATIONS.
7. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING A FENCE TO CONTROL LIVESTOCK IN AREAS WHERE PASTURES ARE SEVERED. WIRE FENCE MAY BE CONSTRUCTED INITIALLY, OR IN LIEU THEREOF, THE CONTRACTOR AT HIS OWN EXPENSE, MAY ELECT TO PROVIDE TEMPORARY FENCING SUITABLE TO CONTAIN LIVESTOCK.
8. THE SEQUENCE AS SHOWN ON THE MAINTENANCE OF TRAFFIC PLANS IS A GENERAL OUTLINE FOR THE CONSTRUCTION OF THIS PROJECT, AND IN NO WAY IS IT INTENDED TO COVER EVERY ITEM IN THE PROJECT. ITEMS NOT CRITICAL TO THE CONSTRUCTION SEQUENCE MAY BE CONSTRUCTED IN ANY STAGE AS APPROVED BY THE RESIDENT ENGINEER.
9. ALL FLEXIBLE BASE AND ASPHALTIC PAVEMENTS REMOVED SHALL BE PAID FOR UNDER THE ITEM NO. 210 - UNCLASSIFIED EXCAVATION.
10. THE EXISTING ASPHALT PAVEMENT TO BE REMOVED FROM THE REMAINING PAVEMENT SHALL BE SEPARATED BY SAWING ALONG A NEAT LINE. AFTER SAWING, THE PAVEMENT TO BE REMOVED SHALL BE CAREFULLY REMOVED IN A MANNER THAT WILL NOT DAMAGE THE PAVEMENT THAT IS TO REMAIN. ANY DAMAGE OF THE ASPHALT PAVEMENT THAT IS TO REMAIN IN PLACE SHALL BE REPAIRED AT THE CONTRACTOR'S EXPENSE.

9/23/2019

R070418.DGN


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. AID PROJ. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				7	ARK.			
				JOB NO.	070418		4	52

2 TYPICAL SECTIONS OF IMPROVEMENT



HWY. 160 - FULL DEPTH
 STA. 203+00.00 - STA. 208+68.70
 STA. 210+34.25 - STA. 215+00.00

ON ALL SUPERELEVATED CURVES AND THRU SUPERELEVATION TRANSITIONS THE ALGEBRAIC DIFFERENCE BETWEEN PAVEMENT SLOPE AND SHOULDER SLOPE SHALL NOT EXCEED 0.08 '/'.



HWY. 160 SUPERELEVATION
 PAVEMENT SECTION IS THE SAME AS SHOWN ABOVE
 STA. 199+73.93 - STA. 200+33.00
 STA. 210+45.00 - STA. 215+17.77
 STA. 215+63.01 - STA. 217+55.98


NOTES:
 REFER TO CROSS SECTIONS FOR DEVIATION FROM THE NORMAL SLOPES. NO CHANGES SHALL BE MADE FROM THE PLANNED SLOPES WITHOUT THE APPROVAL OF THE ENGINEER.

THE THICKNESS OF AGGREGATE BASE COURSE SHALL BE WITHIN PLUS OR MINUS ONE INCH OF THE PLAN THICKNESS SHOWN. THE CONTRACTOR WILL CORRECT ANY DEFICIENT THICKNESS THAT DOES NOT MEET TOLERANCE INDICATED. PAYMENT WILL NOT BE MADE FOR MATERIAL PLACED IN EXCESS OF THE TOLERANCE INDICATED.

ASPHALT FOR LEVELING OF EXISTING PAVEMENT SHALL BE PLACED ONLY IF AND WHERE DIRECTED BY THE ENGINEER. CALCULATIONS FOR THE AMOUNT OF LEVELING AND/OR LEVELING OPERATIONS SHALL BE PERFORMED BEFORE CONSTRUCTION NOTCH AND WIDENING. CALCULATIONS WILL NOT BE PAID FOR DIRECTLY, BUT PAYMENT WILL BE CONSIDERED INCLUDED IN THE VARIOUS PAY ITEMS.

THE FINAL 2" OF SURFACE COURSE IS TO BE PLACED AFTER ALL OTHER COURSES HAVE BEEN LAID. LONGITUDINAL JOINTS SHALL BE AT LANE LINES.

WITH APPROVAL OF THE ENGINEER, THE CONTRACTOR WILL BE ALLOWED TO SUBSTITUTE, AT NO ADDITIONAL COST TO THE DEPARTMENT, THE FIRST LIFT OF ACHM SURFACE COURSE (1/2") IN LIEU OF AGGREGATE BASE COURSE ON THE SHOULDERS.




HWY. 160 - NOTCH AND WIDEN
 STA. 199+73.93 - STA. 203+00.00
 STA. 215+00.00 - STA. 216+55.98

9/23/2019


R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
JOB NO. 070418							5	52


2 SPECIAL DETAILS



SECTION OF APPROACH SLAB




DETAIL FOR TRANSITIONS



NOTE: TURNOUTS AND PRIVATE DRIVES SHALL BE MODIFIED WHERE NECESSARY TO MEET LOCAL CONDITIONS AS DIRECTED BY THE ENGINEER.


- ASPHALT CONCRETE HOT MIX SURFACE COURSE (220 LBS. PER SQ. YD.)
AGGREGATE BASE COURSE (CLASS 7)
7" COMP. DEPTH IF ASPHALT DRIVE EXIST OR
6" CONCRETE IF CONCRETE DRIVE EXIST.
- AGGREGATE BASE COURSE (CLASS 7)
9" COMP. DEPTH OR CONFORM
TO EXISTING DRIVEWAY

DETAIL FOR DRIVEWAY TURNOUTS (COLLECTORS)




TOP VIEW

NOTE: PIPE COLLAR TO BE UTILIZED AS APPROVED BY THE ENGINEER.



WIDENING FOR GUARDRAIL

NOTE: REFER TO STD. DWG. GR-9A AND CROSS SECTIONS FOR SLOPE REQUIREMENTS BEHIND GUARDRAIL.



FRONT VIEW



SIDE VIEW

PIPE EXTENSION REINFORCED CONCRETE COLLAR DETAIL

9/12/2019 R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
JOB NO. 070418							7	52

② TEMPORARY EROSION CONTROL DETAILS



LEGEND

- (E-5) = SAND BAG DITCH CHECKS
- (E-14) = SEDIMENT BASIN
- (E-11) = SILT FENCE
- (E-6) = ROCK DITCH CHECKS


DATE OF REVISION	REVISION

CLEARING AND GRUBBING
TEMPORARY EROSION CONTROL DETAILS


9/23/2019 R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		8	52
JOB NO. 070418								

2 TEMPORARY EROSION CONTROL DETAILS



STA. 199+73.93
BEGIN JOB 070418
LOG MILE 9.50



LEGEND



(E-5)	SAND BAG DITCH CHECKS
(E-14)	SEDIMENT BASIN
(E-11)	SILT FENCE
(E-6)	ROCK DITCH CHECKS

DATE OF REVISION	REVISION

9/23/2019 R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418		9	52

2 TEMPORARY EROSION CONTROL DETAILS



LEGEND


- (E-5) = SAND BAG DITCH CHECKS
- (E-14) = SEDIMENT BASIN
- (E-11) = SILT FENCE
- (E-6) = ROCK DITCH CHECKS

DATE OF REVISION	REVISION

9/23/2019 R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
JOB NO. 070418							11	52

② TEMPORARY EROSION CONTROL DETAILS




LEGEND

(E-5)	= SAND BAG DITCH CHECKS
(E-14)	= SEDIMENT BASIN
(E-11)	= SILT FENCE
(E-6)	= ROCK DITCH CHECKS

DATE OF REVISION	REVISION

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS	
				6	ARK.				
JOB NO.							070418	12	52

② MAINTENANCE OF TRAFFIC DETAILS



SEQUENCE OF CONSTRUCTION

STAGE 1
 MAINTAIN TRAFFIC ON EXISTING LANES.
 CONSTRUCT BRIDGE.
 CONSTRUCT APPROACHES ON LT. SIDE.



STAGE 2
 SHIFT TRAFFIC TO NEW LOCATION.
 REMOVE EXISTING BRIDGE.
 REMOVE EXISTING LANES.
 FINISH NEW LOCATION ON RT. SIDE.

END OF JOB
 INSTALL FINAL LIFT OF SURFACE.
 INSTALL GUARDRAIL AND FINAL STRIPING.


8" PINE, 33.201057655 92.075490664
 PINE, 33.201057655 92.075490664

(1) RII-2
 (48" X 30")
 16" BARR.
 TYP. M.L.T.
ROAD CLOSED


STA. 199+73.93
 BEGIN JOB 070418
 LOG MILE 9.50



22 TRAFFIC DRUMS
 20' O.C. DRIVEWAY
 15 VERTICAL PANELS
 50' O.C. ROADWAY



DETAIL FOR
 STAGE 1 TRAFFIC



DO NOT PASS SIGNS AND SHOULDER CLOSED TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER.

STAGE 1
 MAINTENANCE OF TRAFFIC DETAILS

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418		13	52


② MAINTENANCE OF TRAFFIC DETAILS



SEQUENCE OF CONSTRUCTION

- STAGE 1
 MAINTAIN TRAFFIC ON EXISTING LANES.
 CONSTRUCT BRIDGE.
 CONSTRUCT APPROACHES ON LT. SIDE.
- STAGE 2
 SHIFT TRAFFIC TO NEW LOCATION.
 REMOVE EXISTING BRIDGE.
 REMOVE EXISTING LANES.
 FINISH NEW LOCATION ON RT. SIDE.
- END OF JOB
 INSTALL FINAL LIFT OF SURFACE.
 INSTALL GUARDRAIL AND FINAL STRIPING.

STA. 216+55.98
 END JOB 070418




CONSTRUCTION PAVEMENT MARKINGS (MAIN LANE)
 STA. 213+30 TO 217+60= 430 LIN. FT.

STAGE 1
 MAINTENANCE OF TRAFFIC DETAILS

R070418.DGN 9/23/2019


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
							JOB NO. 070418	14 52

② MAINTENANCE OF TRAFFIC DETAILS



SEQUENCE OF CONSTRUCTION
 STAGE 1
 MAINTAIN TRAFFIC ON EXISTING LANES.
 CONSTRUCT BRIDGE.
 CONSTRUCT APPROACHES ON LT. SIDE.
 STAGE 2
 SHIFT TRAFFIC TO NEW LOCATION.
 REMOVE EXISTING BRIDGE.
 REMOVE EXISTING LANES.
 FINISH NEW LOCATION ON RT. SIDE.
 END OF JOB
 INSTALL FINAL LIFT OF SURFACE.
 INSTALL GUARDRAIL AND FINAL STRIPING.

8" PINE, 33.201057655 92.075490664
 PINE, 33.201057655 92.075490664



REMOVAL OF PERMANENT PAVEMENT MARKINGS
 LT. EDGE LINE + DBL. CENTERLINE MARKINGS
 STA. 199+73 - STA. 204+16 = 1772 LIN. FT
 STA. 213+19 - STA. 216+55 = 1344 LIN. FT
 CONSTRUCTION PAVEMENT MARKINGS
 STA. 197+73 - STA. 217+60 = 7948 LIN. FT

NOTE:
 TURNOUTS AND PRIVATE DRIVES
 SHALL BE MODIFIED WHERE
 NECESSARY TO MEET LOCAL
 CONDITIONS AS DIRECTED BY
 THE ENGINEER.

STAGE 2
 MAINTENANCE OF TRAFFIC DETAILS

9/23/2019
 R070418.DCN

SEQUENCE OF CONSTRUCTION

STAGE 1

MAINTAIN TRAFFIC ON EXISTING LANES.
CONSTRUCT BRIDGE.
CONSTRUCT APPROACHES ON LT. SIDE.

STAGE 2

SHIFT TRAFFIC TO NEW LOCATION.
REMOVE EXISTING BRIDGE.
REMOVE EXISTING LANES.
FINISH NEW LOCATION ON RT. SIDE.

END OF JOB



INSTALL FINAL LIFT OF SURFACE.
INSTALL GUARDRAIL AND FINAL STRIPING.

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418		15	52

② MAINTENANCE OF TRAFFIC DETAILS



STA. 216+55.98
END JOB 070418



(1) RII-2
(48" X 30")
(1) WI-6
(48" X 24")
16' BARR.
TYP. III T.

13 TRAFFIC DRUMS
20' O.C. DRIVEWAY
50' ROADWAY



(1) Q20-2
(48" X 24")

9/23/2019

R070418.DCN

STAGE 2
MAINTENANCE OF TRAFFIC DETAILS

STAGE 1

MAINTAIN TRAFFIC ON EXISTING LANES.
CONSTRUCT BRIDGE.
CONSTRUCT APPROACHES ON LT. SIDE.

STAGE 2


SHIFT TRAFFIC TO NEW LOCATION.
REMOVE EXISTING BRIDGE.
REMOVE EXISTING LANES.
FINISH NEW LOCATION ON RT. SIDE.

END OF JOB

INSTALL FINAL LIFT OF SURFACE.
INSTALL GUARDRAIL AND FINAL STRIPING.

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
							JOB NO. 070418	16 52

2 PERMANENT PAVEMENT MARKING DETAILS



STA. 199+73.93
BEGIN JOB 070418
LOG MILE 9.50

REFLECTORIZED PAINT PAVEMENT MARKINGS
STA. 197+73.93 TO STA. 217+55.98
6" DBL. YELLOW CENTERLINE = 3964 LIN. FT.
6" WHITE EDGE LINE = 3964 LIN. FT.

RAISED PAVEMENT MARKERS
STA. 197+73.93 TO STA. 217+55.98
TYPE II (YEL/YEL) 80' O.C. = 25 EACH

PERMANENT PAVEMENT MARKING DETAILS

9/23/2019
R070418.DGN

STAGE 1

MAINTAIN TRAFFIC ON EXISTING LANES.
CONSTRUCT BRIDGE.
CONSTRUCT APPROACHES ON LT. SIDE.

STAGE 2


SHIFT TRAFFIC TO NEW LOCATION.
REMOVE EXISTING BRIDGE.
REMOVE EXISTING LANES.
FINISH NEW LOCATION ON RT. SIDE.

END OF JOB

INSTALL FINAL LIFT OF SURFACE.
INSTALL GUARDRAIL AND FINAL STRIPING.

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418		17	52

② PERMANENT PAVEMENT MARKING DETAILS



STA. 216+55.98
END JOB 070418

6" WHITE EDGE LINE

6" DOUBLE YELLOW CENTERLINE

PROP. R/W

EXISTING R/W

6" WHITE EDGE LINE

EXISTING R/W

9/23/2019

R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418		18	52

② QUANTITIES



ADVANCE WARNING SIGNS AND DEVICES

SIGN NUMBER	DESCRIPTION	SIGN SIZE	STAGE 1	STAGE 2	END OF JOB	MAXIMUM NUMBER REQUIRED	TOTAL SIGNS REQUIRED		VERTICAL PANELS	TRAFFIC DRUMS	BARRICADES (TYPE III)		FURNISHING & INSTALLING PRECAST CONC. BARRIER	
							NO.	SQ. FT.			EACH	RIGHT		LEFT
												LIN. FT.		
W20-1	ROAD WORK 1500 FT.	48"x48"	2	2	2	2	2	32.0						
W20-1	ROAD WORK 1000 FT.	48"x48"	2	2	2	2	2	32.0						
W20-1	ROAD WORK 500 FT.	48"x48"	2	2	2	2	2	32.0						
G20-2	END ROAD WORK	48"x24"	2	2	2	2	2	16.0						
R11-2	ROAD CLOSED	48"x30"	2	2		2	2	20.0						
OM-3L	OBJECT MARKER	12"x36"	3			3	3	9.0						
OM-3R	OBJECT MARKER	12"x36"	4			4	4	12.0						
W1-6	LARGE ARROW	48"x24"		2		2	2	16.0						
R4-1	DO NOT PASS	24"x30"	2	2	2	2	2	10.0						
W21-5a	RIGHT SHOULDER CLOSED	36"x36"	2	2	2	2	2	18.0						
W8-1	BUMP	30"x30"		2		2	2	12.5						
	VERTICAL PANELS		26			26			26					
	TRAFFIC DRUMS		25	43		43				43				
	TYPE III BARRICADE-RT. (16')		1	1		1					16			
	TYPE III BARRICADE-LT. (16')		1	1		1						16		
	FURNISHING AND INSTALLING PRECAST CONCRETE BARRIER			174		174							174	
TOTALS:								209.5		26	43	16	16	174

NOTE: THIS IS A LOW TRAFFIC VOLUME ROAD AS DEFINED IN SECTION 604.03, STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION.

CONSTRUCTION PAVEMENT MARKINGS AND PERMANENT PAVEMENT MARKINGS

DESCRIPTION	STAGE 1	STAGE 2	END OF JOB	REMOVAL OF PERMANENT PAVEMENT MARKINGS	CONSTRUCTION PAVEMENT MARKINGS	RAISED PAVEMENT MARKERS	REFLECTORIZED PAINT PAVEMENT MARKING	
						TYPE II (YEL/YEL)	6"	
						(YEL/YEL)	WHITE	YELLOW
	LIN. FT. - EACH			LIN. FT.		EACH	LIN. FT.	
REMOVAL OF PERMANENT PAVEMENT MARKINGS	3116			3116				
CONSTRUCTION PAVEMENT MARKINGS	627	7948			8575			
RAISED PAVEMENT MARKERS TYPE II (YEL/YEL)			25			25		
REFLECTORIZED PAINT PAVEMENT MARKING WHITE (6")			3964				3964	
REFLECTORIZED PAINT PAVEMENT MARKING YELLOW (6")			3964					3964
TOTALS:				3116	8575	25	3964	3964

NOTE: THIS IS A LOW TRAFFIC VOLUME ROAD AS DEFINED IN SECTION 604.03, STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION.

NOTE: THE 6" YELLOW STRIPING QUANTITY HAS BEEN ESTIMATED BASED ON A DOUBLE YELLOW CENTERLINE STRIPE FOR THE ENTIRE PROJECT. THE PROJECT MUST BE MARKED FOR PASSING/NO PASSING ZONES PRIOR TO THE PLACEMENT OF ANY FINAL STRIPING. CONTACT THE MAINTENANCE DIVISION AFTER THE FINAL LIFT OF SURFACE COURSE HAS BEEN PLACED TO SCHEDULE THE ZONING OF THE PROJECT.

9/23/2019

R070418.DCN

QUANTITIES

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. PROJ. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
							JOB NO.	070418
							19	52

CLEARING AND GRUBBING

STATION	STATION	LOCATION	CLEARING	GRUBBING
			STATION	STATION
199+73	216+60	HWY. 160	17	17
TOTALS:			17	17

② QUANTITIES



SOIL LOG

STATION	LATITUDE			LONGITUDE			LOCATION	DEPTH FEET	LIQUID LIMIT	PLASTICITY INDEX	AASHTO CLASSIFICATION	COLOR
	DEG	MIN	SEC	DEG	MIN	SEC						
198+99.74	33	20	6.70	92	7	48.10	21 RT	0-5	ND	NP	A-4(0)	BROWN
198+99.74	33	20	6.70	92	7	48.20	05 RT	0-5	20	7	A-4(0)	BR/GR
198+99.74	33	20	6.70	92	7	48.10	12 RT	0-5	19	7	A-4(0)	BROWN
198+99.74	33	20	6.70	92	7	48.10	21 RT	0-5	ND	NP	A-2-4(0)	BROWN
204+97.58	33	20	7.60	92	7	41.30	05 LT	0-5	27	14	A-6(2)	BROWN
204+97.58	33	20	7.70	92	7	41.20	12 LT	0-5	25	12	A-6(2)	BROWN
204+97.58	33	20	7.80	92	7	41.20	21 LT	0-5	19	5	A-4(0)	BR/GR

SOIL CHARACTERISTICS TABULATED ABOVE ARE REPRESENTATIVE AT THE LOCATION OF THE SAMPLE, AND FROM SURFACE INDICATIONS ARE TYPICAL FOR THE LIMITS SHOWN. THESE DATA ARE SHOWN FOR INFORMATION ONLY. THE STATE WILL NOT BE RESPONSIBLE FOR VARIATIONS IN THE SOIL CHARACTERISTICS AND/OR EXTENT OF SAME DIFFERING FROM THE ABOVE TABULATIONS.
 Z- AUGER REFUSAL
 NP - NON-PLASTIC
 ND - NOT DETERMINABLE

EARTHWORK

STATION	STATION	LOCATION / DESCRIPTION	UNCLASSIFIED EXCAVATION	COMPACTED EMBANKMENT	* SOIL STABILIZATION
			CU. YD.	CU. YD.	TON
199+73.93	216+55.98	STAGE 1-MAIN LANES	529	12572	
199+73.93	216+55.98	STAGE 2-MAIN LANES	1527	745	
199+73.93	216+55.98	APPROACHES		150	
199+73.93	216+55.98	TEMPORARY APPROACHES		100	
208+68.75	210+34.25	BRIDGE EXCAVATION	280		
ENTIRE PROJECT	TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER				200
TOTALS:			2336	13567	200

* QUANTITY ESTIMATED.
 SEE SECTION 104.03 OF THE STD. SPECS.

NOTE: EARTHWORK QUANTITIES SHOWN ABOVE SHALL BE PAID AS PLAN QUANTITY.

BENCH MARKS

STATION	LOCATION	BENCH MARKS
		EACH
208+68.50	HWY. 160 BRIDGE END	1
TOTAL:		1

NOTE: SHOWN FOR INFORMATION ONLY. BENCH MARKS SHALL BE FURNISHED AND PLACED BY STATE FORCES.

4" PIPE UNDERDRAIN

STATION	STATION	LOCATIONS	4" PIPE UNDERDRAINS	UNDERDRAIN OUTLET PROTECTORS
			LIN. FT.	EACH
* ENTIRE PROJECT TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER			300	3
TOTALS:			300	3

* NOTE: QUANTITY ESTIMATED.
 SEE SECTION 104.03 OF THE STD. SPECS.

EROSION CONTROL

STATION	STATION	LOCATION	PERMANENT EROSION CONTROL					TEMPORARY EROSION CONTROL								
			SEEDING	LIME	MULCH COVER	WATER	SECOND SEEDING APPLICATION	TEMPORARY SEEDING	MULCH COVER	WATER	SAND BAG DITCH CHECKS	ROCK DITCH CHECKS	SILT FENCE	SEDIMENT BASIN	OBLITERATION OF SEDIMENT BASIN	*SEDIMENT REMOVAL & DISPOSAL
			ACRE	TON	ACRE	M.GAL.	ACRE	ACRE	ACRE	M.GAL.	(E-5) BAG	(E-6) CU.YD.	(E-11) LIN. FT.	(E-14) CU.YD.	CU.YD.	CU. YD.
ENTIRE PROJECT	CLEARING AND GRUBBING														139	
ENTIRE PROJECT	STAGE 1		1.82	3.64	1.82	185.6	1.82	0.18	0.18	3.7		12			4	
ENTIRE PROJECT	STAGE 2		1.74	3.48	1.74	177.5	1.74									
*ENTIRE PROJECT TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER.			2.00	4.00	2.00	204.0	2.00	1.50	1.50	30.6	44	12	1500	300	300	362
TOTALS:			5.56	11.12	5.56	567.1	5.56	4.38	4.38	89.4	132	24	5141	300	300	505

BASIS OF ESTIMATE:

- LIME2 TONS / ACRE OF SEEDING
- WATER.....102.0 M.G. / ACRE OF SEEDING
- WATER.....20.4 M.G. / ACRE OF TEMPORARY SEEDING
- SAND BAG DITCH CHECKS.....22 BAGS / LOCATION
- ROCK DITCH CHECKS.....3 CU.YD./LOCATION

NOTE: THE TEMPORARY EROSION CONTROL DEVICES SHOWN ABOVE AND ON THE PLANS SHALL BE INSTALLED IN SUCH A SEQUENCE AS TO DETER EROSION AND SEDIMENTATION ON U.S. WATERWAYS AS EXPLAINED BY THE NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM PERMIT.

*QUANTITIES ESTIMATED.
 SEE SECTION 104.03 OF THE STD. SPECS.

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
							JOB NO.	070418
							SHEET NO.	20
							TOTAL SHEETS	52

② QUANTITIES



MAILBOXES

LOCATION	MAILBOXES	MAILBOX SUPPORTS
		(SINGLE) EACH
ENTIRE PROJECT	1	1
TOTALS:	1	1

APPROACH GUTTERS AND SLABS

STATION	STATION	LOCATION	APPROACH GUTTER (TYPE A)	APPROACH SLABS	REINFORCING STEEL-RDWY. (GR. 60)	AGGREGATE BASE CRS. (CLASS 7)
			CU. YD.	CU. YD.	POUND	TON
207+05.24	208+68.50	APPROACH GUTTER ON LT.	4.25		360	
206+30.24	208+68.50	APPROACH GUTTER ON RT.	4.25		360	
210+34.50	212+53.13	APPROACH GUTTER ON LT.	4.25		360	
210+34.50	211+78.13	APPROACH GUTTER ON RT.	4.25		360	
208+58.50	208+68.50	APPROACH SLAB		27.70	1940	30.37
210+34.50	210+35.50	APPROACH SLAB		27.70	1940	30.37
TOTALS:			17.00	55.40	5320	60.74

NOTE: USE T=13" FOR 4' SHOULDER.

SELECTED PIPE BEDDING

LOCATION	SELECTED PIPE BEDDING
	CU. YD.
ENTIRE PROJECT TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER	20
TOTAL:	20

NOTE: QUANTITY ESTIMATED. SEE SECTION 104.03 OF THE STD. SPECS.

DRIVEWAYS & TURNOUTS

STATION	SIDE	LOCATION	WIDTH FEET	ACHM SURFACE COURSE (1/2") 220 LBS. PER SQ. YD. (PG 64-22)		AGGREGATE BASE COURSE (CLASS 7) TON	SIDE DRAINS 18" LIN. FT.	STANDARD DRAWINGS
				SQ. YD.	TON			
199+61	RT.	HWY. 160	16	39.99	4.40	16.33		
201+36	RT.	HWY. 160	16	55.14	6.07	22.52	28	PCC-1, PCM-1, PCP-1, PCP-2
205+21	LT.	HWY. 160	16	142.32	15.66	58.11	28	PCC-1, PCM-1, PCP-1, PCP-2
205+78	LT.	HWY. 160	16	78.52	8.64	32.06	34	PCC-1, PCM-1, PCP-1, PCP-2
TOTALS:						130.00	90	

BASIS OF ESTIMATE:
ACHM SURFACE COURSE (1/2").....94.7% MIN. AGGR.....5.3% ASPHALT BINDER
MAXIMUM NUMBER OF GYRATIONS = 115 FOR PG 64-22

* QUANTITY ESTIMATED
SEE SECTION 104.03 OF THE STD. SPECS.
TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER.

NOTE: FOR R.C. PIPE CULVERT INSTALLATIONS USE TYPE 3 BEDDING UNLESS OTHERWISE SPECIFIED.
NOTE: FOR C.M. PIPE CULVERT INSTALLATIONS USE TYPE 2 BEDDING UNLESS OTHERWISE SPECIFIED.

COLD MILLING ASPHALT PAVEMENT

STATION	STATION	LOCATION	AVG. WIDTH	COLD MILLING ASPHALT PAVEMENT
			FEET	SQ. YD.
197+73.93	199+73.93	MAIN LANES	20.00	444.44
216+55.98	217+55.98	MAIN LANES	20.00	222.22
TOTAL:				666.66

NOTE: AVERAGE MILLING DEPTH 1".

ASPHALT CONCRETE PATCHING FOR MAINTENANCE OF TRAFFIC

LOCATION	TON	TACK COAT
		GALLON
ENTIRE PROJECT - TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER	8	16
TOTALS:	8	16

BASIS OF ESTIMATE:
ASPHALT CONCRETE PATCHING FOR MAINTENANCE OF TRAFFIC...25 TON/MILE
TACK COAT FOR MAINTENANCE OF TRAFFIC.....50 GAL./MILE

NOTE: QUANTITY ESTIMATED. SEE SECTION 104.03 OF THE STD. SPECS.

ACHM PATCHING OF EXISTING ROADWAY

DESCRIPTION	TON
ENTIRE PROJECT - TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER	100
TOTAL:	100

NOTE: QUANTITY ESTIMATED. SEE SECTION 104.03 OF THE STD. SPECS.

DUMPED RIPRAP AND FILTER BLANKET

STATION	LOCATION	DUMPED RIPRAP	FILTER BLANKET
		CU. YD.	SQ. YD.
215+00	OUTLET OF PIPE CULVERT	22	44
TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER		11	22
TOTALS:		33	66

*NOTE: QUANTITY ESTIMATED. SEE SECTION 104.03 OF THE STANDARD SPECIFICATIONS

NOTE: FILTER BLANKET SHALL BE GEOTEXTILE FABRIC (TYPE 5).

GUARDRAIL

STATION	STATION	LOCATION	GUARDRAIL (TYPE A)	THRIE BEAM GUARDRAIL TERMINAL	GUARDRAIL TERMINAL (TYPE 2)
			LIN. FT.	EACH	
207+65.35	208+59.10	LT. SIDE	75	1	1
206+40.35	208+59.10	RT. SIDE	150	1	1
210+43.90	212+62.65	LT. SIDE	150	1	1
210+43.90	211+37.65	RT. SIDE	75	1	1
TOTALS:			450	4	4

9/12/2019

R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
12-20-19				6	ARK.		21	52
							JOB NO.	070418

2 QUANTITIES



BASE AND SURFACING

STATION	STATION	LOCATION	LENGTH FEET	AGGREGATE BASE COURSE (CLASS 7)		TACK COAT					ACHM BINDER COURSE (1")				ACHM SURFACE COURSE (1/2")												
				TON / STATION	TON	(0.05 GAL. PER SQ. YD.)			(0.17 GAL. PER SQ. YD.)		TOTAL GALLONS	AVG. WID. FEET	SQ.YD.	POUND / SQ.YD.	PG 64-22 TON	AVG. WID. FEET	SQ.YD.	POUND / SQ.YD.	PG 64-22 TON	AVG. WID. FEET	SQ.YD.	POUND / SQ.YD.	PG 64-22 TON	TOTAL PG 64-22 TON			
						TOTAL WID. FEET	SQ.YD.	GALLON	TOTAL WID. FEET	SQ.YD.															GALLON		
MAIN LANES																											
197+73.93	199+73.93	HWY. 160 200' TRANSITION	200.00	34.75	69.50	30.35	674.44	33.72	20.00	444.44	75.55	109.27	5.23	116.22	330.00	19.18	5.13	114.00	220.00	12.54	25.00	555.56	220.00	61.11	73.65		
199+73.93	203+00.00	HWY. 160 NOTCH AND WIDENING	326.07	127.75	416.55	42.71	1547.38	77.37				77.37	6.46	234.05	330.00	38.62	6.25	226.44	220.00	24.91	30.00	1086.90	220.00	119.56	144.47		
203+00.00	205+97.24	HWY. 160 MAIN LANE	297.24	173.00	514.23	44.71	1476.62	73.83				73.83	22.46	741.78	330.00	122.39	22.25	734.84	220.00	80.83	30.00	990.80	220.00	108.99	189.82		
205+97.24	208+68.75	HWY. 160 MAIN LANE	271.51	173.00	469.71	44.71	1348.80	67.44				67.44	22.46	677.57	330.00	111.80	22.25	671.23	220.00	73.84	30.00	905.03	220.00	99.55	173.39		
210+34.25	212+86.13	HWY. 160 MAIN LANE	251.88	173.00	435.75	44.71	1251.28	62.56				62.56	22.46	628.58	330.00	103.72	22.25	622.70	220.00	68.50	30.00	839.60	220.00	92.36	160.86		
212+86.13	215+00.00	HWY. 160 MAIN LANE	213.87	173.00	370.00	44.71	1062.46	53.12				53.12	22.46	533.72	330.00	88.06	22.25	528.73	220.00	58.16	30.00	712.90	220.00	78.42	136.58		
215+00.00	216+55.98	HWY. 160 NOTCH AND WIDENING	155.98	127.75	199.26	42.71	740.21	37.01				37.01	6.46	111.96	330.00	18.47	6.25	108.32	220.00	11.92	30.00	519.93	220.00	57.19	69.11		
216+55.98	217+55.98	HWY. 160 100' TRANSITION	100.00	34.75	34.75	30.35	337.22	16.86	20.00	222.22	37.78	54.64	5.23	58.11	330.00	9.59	5.13	57.00	220.00	6.27	25.00	277.78	220.00	30.56	36.83		
WIDENING FOR GUARDRAIL																											
205+97.24	206+30.24	GR. TAPER ON RT.	33.00	VAR.	5.03																						
206+30.24	208+68.50	GR. WIDENING ON RT.	238.26	30.50	72.67																						
206+72.24	207+05.24	GR. TAPER ON LT.	33.00	VAR.	5.03																						
207+05.24	208+68.50	GR. WIDENING ON LT.	163.26	30.50	49.79																						
210+34.50	211+78.13	GR. WIDENING ON RT.	143.63	30.50	43.81																						
211+78.13	212+11.13	GR. TAPER ON RT.	33.00	VAR.	5.03																						
210+34.50	212+53.13	GR. WIDENING ON LT.	218.63	30.50	66.68																						
212+53.13	212+86.13	GR. TAPER ON LT.	33.00	VAR.	5.03																						
ADDITIONAL FOR LEVELING																											
199+73.93	203+00.00	HWY. 160 MAIN LANE	326.07						VAR.	363.33	61.77	61.77															
215+00.00	216+55.98	HWY. 160 MAIN LANE	155.98						VAR.	177.78	30.22	30.22															
ADDITIONAL FOR SUPERELEVATION																											
197+73.93	201+00.00	HWY. 160 MAIN LANE	326.07	VAR.	85.02																						
210+45.00	215+17.97	HWY. 160 MAIN LANE	472.97	VAR.	120.61																						
215+72.50	217+55.98	HWY. 160 MAIN LANE	183.48	VAR.	68.44																						
TOTALS:					3036.89		8438.41	421.91				1207.77	205.32	627.23		3101.99		511.83		3063.26		336.97		6395.57		834.62	1171.59

BASIS OF ESTIMATE:
 ACHM SURFACE COURSE (1/2").....94.7% MIN. AGGR.....5.3% ASPHALT BINDER
 ACHM BINDER COURSE (1").....95.6% MIN. AGGR.....4.4% ASPHALT BINDER
 MAXIMUM NUMBER OF GYRATIONS = 115 FOR PG 64-22
 TACK COAT QUANTITIES WERE CALCULATED USING THE EMULSIFIED ASPHALT RATES. REFER TO SS-400-1 FOR THE RESIDUAL ASPHALT APPLICATION RATES.

STRUCTURES

STATION	DESCRIPTION	R.C. PIPE CULVERT ALTERNATES		FLARED END SECTION ALTERNATES FOR PIPE CULVERT ALTERNATES	SOLID SODDING	WATER	STD. DWG. NOS.
		ALT. 1 (CLASS III)	ALT. 2, 3, 4, 5, 6, AND 7				
		48"	48"	48"	EACH	SQ.YD.	
215+00	HWY. 160. ON LT.	78	78	6	33	0.42	PCC-1, PCM-1, PCM-2, PCP-1, PCP-2, PCP-3, FES-1, FES-2
TOTALS:		78	78	6	33	0.42	

BASIS OF ESTIMATE:
 WATER.....12.6 GAL. / SQ. YD. OF SOLID SODDING
 NOTE: FOR R.C. PIPE CULVERT INSTALLATIONS USE TYPE 3 BEDDING UNLESS OTHERWISE SPECIFIED.
 NOTE: FOR C.M. PIPE CULVERT INSTALLATIONS USE TYPE 2 BEDDING UNLESS OTHERWISE SPECIFIED.

9/12/2019

R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.		070418	22	52
				① 07475 - QUANTITIES - 61366				

SCHEDULE OF BRIDGE QUANTITIES - JOB NO. 070418

BRIDGE NO.	NAME PLATE TITLE	UNIT OF STRUCTURE	ITEM NO.	205	SS & 802	SP, SS, & 802	SS & 802	803	SS & 804	SS & 804	SS & 805	SS & 805	SS & 805	SS & 805	SS & 805	SP, SS & 807	SS & 808	812	816	816	
			ITEM	REMOVAL OF EXISTING BRIDGE STRUCTURE (SITE NO.)	CLASS S CONCRETE-BRIDGE	CLASS S(AE) CONCRETE-BRIDGE	PRESTRESSED CONCRETE GIRDERS (TYPE II)	CLASS 1 PROTECTIVE SURFACE TREATMENT	REINFORCING STEEL - BRIDGE (GRADE 60)	EPOXY COATED REINFORCING STEEL (GRADE 60)	① STEEL PILING (HP 10 X 42)	CONCRETE PILING (24" SQUARE)	TEST PILE (HP 10 X 42)	TEST PILE (24" SQUARE)	PREBORING	STRUCTURAL STEEL IN BEAM SPANS (A709, GR. 50W)	ELASTOMERIC BEARINGS	BRIDGE NAME PLATE (TYPE D)	FILTER BLANKET	DUMPED RIPRAP	
			UNIT	LUMP SUM	CU. YD.	CU. YD.	LIN. FT.	GAL.	LB.	LB.	LIN. FT.	LIN. FT.	LIN. FT.	LIN. FT.	LIN. FT.	LB.	CU. IN.	EACH	SQ. YD.	CU. YD.	
07475	HIGHWAY 160 OVER HALFWAY CREEK	BENT NOS. 1 & 4		24.30					2,311	550	480		140		100				407	235	
		BENT NOS. 2 & 3		29.60					2,869				280		80	250	3,654.0				
		164'-6" INTEGRAL PRESTRESSED CONCRETE GIRDER UNIT				226.40	654.0	14.0			47,300						450		1		
		SITE NO. 1 (EXISTING BR. NO. M2116)	1																		
		TOTAL FOR JOB NO. 070418			53.90	226.40	654.0	14.0	5,180	47,850	480	280	140	80	350	450	3,654.0	1	407	235	

THOMAS GERARD
DESIGN SECTION SUPERVISOR

① Steel piling is required to be Grade 50.




SCHEDULE OF BRIDGE QUANTITIES
HALFWAY CREEK STR. & APPRS. (S)
BRADLEY COUNTY

ROUTE 160 SEC. 9
ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARK.

DRAWN BY: KJT DATE: 10/17/2019 FILENAME: b070418_q1.dgn
 CHECKED BY: DHP DATE: 11/1/19 SCALE: No Scale
 DESIGNED BY: DATE: BRIDGE ENGINEER
 BRIDGE NO. 07475 DRAWING NO. 61366

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						070418	24	52

② SURVEY CONTROL DETAILS



SURVEY CONTROL COORDINATES

Project Name: s070418
 Date: 9/14/2017
 Coordinate System: ARKANSAS STATE PLANE - SOUTH ZONE BASED ON GPS CONTROL,
 PROJECTED TO GROUND.
 Units: U.S. SURVEY FOOT

Point Name	Northing	Easting	Elev	Feature	Description
1	1555564.8857	1271654.5073	126.238	CTL	AHTD STD. MON. STAMPED PN:1
2	1555612.4097	1272155.7384	124.458	CTL	AHTD STD. MON. STAMPED PN:2
3	1555661.0931	1272507.6277	115.566	CTL	AHTD STD. MON. STAMPED PN:3
4	1555721.1064	1273017.9960	114.362	CTL	AHTD STD. MON. STAMPED PN:4
5	1555657.1032	1274367.7485	114.781	CTL	AHTD STD. MON. STAMPED PN:5
100	1555814.1028	1273710.0752	114.998	GPS	AHTD GPS *060020
101	1555459.8168	1274933.7694	119.098	GPS	AHTD GPS *060020A
900	1555537.0557	1271545.0093	125.613	TBM	CHISELED SQUARE
901	1555749.0004	1273468.7265	111.312	TBM	CHISELED SQUARE
902	1555826.8980	1273721.5705	112.450	TBM	CHISELED SQUARE

POINT NO.	TYPE	STATION	NORTHING	EASTING
8000	POB	191+42.88	1555490.4038	1271124.5044
8014	PC	195+70.76	1555565.8718	1271545.6748
8016	PT	199+73.93	1555619.4480	1271945.1356
8017	PC	200+33.07	1555624.7257	1272004.0477
8019	PT	204+93.34	1555674.9888	1272461.5300
8007	PC	211+21.67	1555756.1389	1273084.6024
8009	PT	213+30.27	1555775.5281	1273292.2495
8010	PC	216+55.98	1555793.9856	1273617.4359
8012	PT	220+06.35	1555755.1960	1273963.9903
8013	POE	224+42.65	1555634.7771	1274383.3441

*Note - Rebar and Cap - Standard - 5/8" Rebar with 2" Aluminum Cap stamped
 *(standard markings common to all caps), or as indicated
 (other markings indicated in the point description of the individual point).
 USE CAF = 1.0 FOR STAKEOUT FOR THIS PROJECT
 A PROJECT CAF OF 0.999990795143 HAS BEEN USED TO COMPUTE THE ABOVE GROUND COORDINATES.
 THIS CAF IS INTENDED FOR USE WITHIN THE PROJECT LIMITS.
 GRID DISTANCE = GROUND DISTANCE X CAF.
 GRID COORDINATES ARE STORED UNDER FILE NAME s070418gi.ctl
 HORIZONTAL DATUM: NAD 83 (2011)
 VERTICAL DATUM: NAVD 88 POSITIONAL ACCURACY THIRD ORDER, UNLESS SPECIFIED OTHERWISE
 AT A SPECIFIC POINT.

REFERENCE POINTS (1500 SERIES) ARE TO BE USED TO ESTABLISH CONTROL
 IF THE PRIMARY CONTROL POINTS LISTED ABOVE HAVE BEEN DESTROYED.
 REFERENCE POINTS ARE NOT TO BE USED FOR VERTICAL CONTROL

BASIS OF BEARING:
 ARKANSAS STATE PLANE GRID BEARINGS - 0302-SOUTH ZONE
 DETERMINED FROM GPS CONTROL POINTS: *060020-*060020A
 CONVERGENCE ANGLE: 00-04-19.43 LEFT AT LT: 33-20-07.47 LG: 092-07-43.52
 GRID AZIMUTH = ASTRONOMICAL AZIMUTH - CONVERGENCE ANGLE.

9/23/2019

R070418.DGN


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS	
				6	ARK.				
JOB NO.							070418	25	52

② SURVEY CONTROL DETAILS



PI = 197+72.47
 Δ = 5° 02' 22.55" RT.
D = 1'15'00.00"
T = 201.71'
L = 403.04'
PC = 195+70.76
PT = 199+73.93
e = MATCH EXISTING


STA. 199+73.93
BEGIN JOB 070418
LOG MILE 9.50



PI = 206+63.24
 Δ = 2° 18' 04.79" LT.
D = 0°30'00.00"
T = 230.16'
L = 460.27'
PC = 200+33.07
PT = 204+93.34
e = NO SUPER

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
JOB NO. 070418							26	52


② SURVEY CONTROL DETAILS



STA. 216+55.98
END JOB 070418

PI = 212+26.02
Δ = 4° 10' 18.94" RT.
D = 2° 00' 00.00"
T = 104.34'
L = 208.59'
PC = 211+21.67
PT = 213+30.27
e = 0.04' /'
Ls = 250'

PI = 218+32.84
Δ = 19° 16' 12.77" RT.
D = 5° 30' 00.00"
T = 176.85'
L = 350.36'
PC = 216+55.98
PT = 220+06.35
e = MATCH EXISTING




9/23/2019

R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				7	ARK.		27	52

2 PLAN AND PROFILE SHEETS



PI = 197+72.47
 Δ = 5° 02' 22.55" RT.
D = 1'15"00.00"
T = 201.71'
L = 403.04'
PC = 195+70.76
PT = 199+73.93
e = MATCH EXISTING


STA 205+21 IN PLACE
18" X 36" R.C. PIPE CULVERT
LT. SIDE DRAIN
REMOVE AND INSTALL
18" X 28" PIPE CULVERT
LT. SIDE DRAIN
CONSTRUCT APPROACH = 10 CU. YD.

STA.	STA.	GUARDRAIL (TYPE A)	THREE BEAM GUARDRAIL TERMINAL	GUARDRAIL TERMINAL (TYPE 2)
207+65.35	208+59.10	75		
206+40.35	208+59.10	150		
210+43.90	212+62.65	150		
210+43.90	211+37.65	75		

STA. 208+93.00 - STA. 209+87.80
94' X 24" BRIDGE CONSISTING OF
PRECAST CONCRETE SLAB SPANS
WITH CONCRETE PIERS
BRIDGE NO. M2116
REMOVAL OF EXISTING BRIDGE
STRUCTURE (SITE NO. 1) = 1.00 LUMP SUM.

STA. 205+78 IN PLACE
18" X 20" R.C. PIPE CULVERT
LT. SIDE DRAIN
REMOVE AND INSTALL
18" X 34" PIPE CULVERT
LT. SIDE DRAIN
CONSTRUCT APPROACH = 35 CU. YD.

PI = 212+26.02
 Δ = 4° 10' 18.94" RT.
D = 2° 00' 00.00"
T = 104.34'
L = 208.59'
PT = 211+21.67
PC = 213+30.27
e = 0.04'/'
Ls = 250'




STA. 199+73.93
BEGIN JOB 070418
LOG MILE 9.50

STA. 201+36 IN PLACE
18" X 24" R.C. PIPE CULVERT
RT. SIDE DRAIN
REMOVE AND INSTALL
18" X 28" PIPE CULVERT
RT. SIDE DRAIN
CONSTRUCT APPROACH = 5 CU. YD.

PI = 206+63.24
 Δ = 2° 18' 04.79" LT.
D = 0° 30' 00.00"
T = 230.16'
L = 460.27'
PC = 200+33.07
PT = 204+93.34
e = NO SUPER

STA. 208+68.75 BR. END
165' - 6" BRIDGE LENGTH
164' - 6" INTEGRAL
PRESTRESSED CONCRETE
GIRDER UNIT (TYPE II)
(54'-9", 55', 54'-9")
BR. NO. 07431
30' - 0" CLEAR ROADWAY
STA. 210+34.25 BR. END

REFER TO SURVEY CONTROL DETAIL SHEETS FOR HORIZONTAL AND VERTICAL CONTROL DATA.



STA. 197+73.93 MATCH EXISTING (0.029'/'')
STA. 198+33.00 MAX SUPERELEVATION (0.026'/'')
STA. 200+33.00 END SUPERELEVATION

HALFWAY CREEK AT STA. 209+05 - STA. 210+20
IS CLASSIFIED AS A PERENNIAL. THE TOP OF
CHANNEL ELEVATION IS 110 FT. MSL. REFER TO
SECTION 110.05(C) TEMPORARY FILL OF THE
2014 STANDARD SPECIFICATIONS.

STA. 210+45.00 BEGIN SUPERELEVATION
STA. 212+25.97 MAX. SUPERELEVATION (0.029'/'')
STA. 213+36.80 MAX. SUPERELEVATION (0.029'/'')
STA. 215+17.77 END SUPERELEVATION

9/23/2019 R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				7	ARK.			
JOB NO. 070418							28	52

2 PLAN AND PROFILE SHEETS




STA. 215+00 IN PLACE
 TRI. 48" X 52" R.C. PIPE CULVERT
 WITH HEADWALLS LT. & RT.
 REMOVE HEADWALLS LT. & RT.
 18" LT. & 4" RT. (CLASS III) (TYPE 3 BEDDING)
 WITH FES LT. & RT.
 025= 140.51 CFS D.A. = RELIEF STRUCTURE
 48" R.C. PIPE = 78 LIN. FT.
 48" FES = 6 EA.

PI = 212+26.02
 Δ = 4° 10' 18.94" RT.
 D = 2° 00' 00.00"
 T = 104.34'
 L = 208.59'
 PC = 211+21.67
 PT = 213+30.27
 e = 0.041'
 Ls = 250'


STA. 217+55.98 IN PLACE
 48" X 50" R.C. PIPE CULVERT
 WITH HEADWALLS LT. & RT.
 RETAIN

PI = 218+32.84
 Δ = 19° 16' 12.77" RT.
 D = 5° 30' 00.00"
 T = 176.85'
 L = 350.36'
 PC = 216+55.98
 PT = 220+06.35
 e = MATCH EXISTING



REFER TO SURVEY CONTROL DETAIL SHEETS FOR HORIZONTAL AND VERTICAL CONTROL DATA.

MAIN LANES



9/23/2019 R070418.DGN


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418	29	52	
07475 - LAYOUT - 61367								

For R/W Data, See Roadway Plans.

Note: Type A Approach Gutters ("W" = 4'-0") and Type Special Approach Slab (Width = 22'-0) shall be placed at both ends of the bridge. See Dwg. Nos. 55030A and 61380, respectively.

Note: Place 1'-6" Dumped Riprap on top of Filter Blanket. See Std. Dwg. No. 55001. Top of Riprap Elev. = 114.5 (typ. both ends of bridge).

Install 4" Pipe Underdrain with Outlet Protectors at both bridge ends in accordance with Section 611 and Std. Dwg. PU-1. For additional details, see Dwg. No. 61373. Pipe Underdrains will not be paid for directly but shall be considered subsidiary to various bid items.



PLAN

The Contractor shall excavate the existing embankment as shown at both ends of bridge to elevation 112.0. Approx. 280 cu. yds. of excavation. See Roadway Plans for additional existing embankment excavation details.

NOTE: Stations shown are along C.L. Construction. Elevations shown are theoretical working point elevations at C.L. Bridge. Any vertical dimension referenced to C.L. Deck is based on theoretical working point elevation at C.L. Bridge. See "Rounding Detail" on Dwg. No. 61372 for additional information.


HYDRAULIC DATA

FLOOD DESCRIPTION	FREQUENCY	TOTAL DISCHARGE ⁽²⁾	DISCHARGE THIS SITE	NATURAL WATER SURFACE ELEVATION ⁽¹⁾	WATER SURFACE ELEVATION WITH BACKWATER
	YEARS	CFS	CFS	FEET	FEET
Design	25	3000	2858.8	113.1	113.7
Base	100	4480	4305.9	114.0	114.9
Extreme	500	6400	6182.9	114.9	116.3
Overtopping	>500	-	-	-	-

⁽¹⁾ Unconstricted water surface elevation without structure or roadway approaches.
⁽²⁾ The total discharge includes flow at this site and culvert at Sta. 215+00.00


Q100 backwater elevation for existing structure = 115.1 feet
 Proposed Low Bridge Chord Elev. = 116.53 feet

Drainage Area = 24.8 square miles
 Historical H.W. Elev. = 115.4 ft.




VERTICAL ALIGNMENT DATA

Along C.L. Construction
No Scale



ELEVATION



SHEET 1 OF 2
 LAYOUT OF BRIDGE
 HIGHWAY 160 OVER HALFWAY CREEK
 HALFWAY CREEK STR. & APPRS. (S)
 BRADLEY COUNTY


ROUTE 160 SEC. 9
 ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.

DRAWN BY: DPT DATE: 07/24/18 FILENAME: b070418_11.dgn
 CHECKED BY: DHT DATE: 11/17/19 SCALE: 1"=20'
 DESIGNED BY: TMG DATE: 5/2019
 BRIDGE NO. 07475 DRAWING NO. 61367

PRINT DATE: 11/8/2019

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.		070418	30	52

07475 - LAYOUT - 61368



- BORING LEGEND**
- A1-Moist, Soft, Brown Sandy Clay
 - B1-Wet, Medium Dense, Brown Sand with Silt and Trace Gravel
 - C1-Moist, Stiff, Dark Gray Clay (Claiborne Group, Cockfield Formation)
 - D1-Wet, Very Dense, Gray Silty Sand
 - E1-Wet, Very Dense, Gray Sandy Silt with Trace Gravel
 - F1-Wet, Dense, Gray Silt with Trace Gravel and Trace Lignite
 - G1-Moist, Medium Dense, Gray Silt with Sand
 - H1-Moist, Very Stiff, Dark Gray Clay with Some Lignite
 - J1-Moist, Very Stiff to Hard, Dark Gray Clay with Some Sand and Some Lignite
 - K1-Moist, Very Dense, Dark Brown and Dark Gray Sand with Layers of Clay
 - L1-Moist, Very Dense, Dark Brown and Dark Gray Sand with Some Clay Layers
 - M1-Moist, Very Dense, Gray Sand
 - N1-Asphalt
 - P1-Moist, Soft, Brown Sandy Clay with Some Gravel
 - Q1-Moist, Loose, Light Brown Silty Sand
 - R1-Moist, Stiff, Dark Gray Fat Clay with Trace Lignite (Claiborne Group, Cockfield Formation)
 - S1-Moist, Stiff, Dark Gray Lean Clay
 - T1-Wet, Dense, Dark Brown Silt
 - U1-Wet, Medium Dense, Dark Brown Silt
 - V1-Moist, Medium Dense, Dark Gray Silt with Sand and Trace Lignite
 - W1-Moist, Very Stiff, Dark Gray Lean Clay
 - X1-Moist, Very Stiff, Dark Brown Fat Clay with Lignite Layers
 - Y1-Moist, Very Stiff, Dark Gray Fat Clay with Some Lignite
 - Z1-Moist, Hard, Dark Brown Lean Clay
 - A2-Moist, Very Stiff, Dark Brown Fat Clay
 - B2-Moist, Hard, Dark Brown Fat Clay

"N" VALUES

- Sta. 208+43 - 32' Right of Construction Centerline
- 4.5- 5.5,N=2
 - 9.5- 10.5,N=11
 - 15.5- 16.5,N=10
 - 20.5- 20.9,N=60(5")
 - 25.5- 26.3,N=75(10")
 - 30.5- 31.5,N=40
 - 35.5- 36.5,N=22
 - 40.5- 41.5,N=28
 - 45.5- 46.5,N=25
 - 50.5- 51.5,N=25
 - 55.5- 56.5,N=31
 - 60.5- 61.5,N=26
 - 65.5- 66.5,N=56
 - 70.5- 71.3,N=87(10")
 - 75.5- 75.7,N=75(2")
 - 80.5- 81.3,N=75(10")
 - 85.5- 85.7,N=50(2")
 - 90- 90.4,N=60(5")
 - 95- 95.4,N=60(5")
 - 100.5-100.9,N=60(5")
- Sta. 210+35 - 30' Right of Construction Centerline
- 5.0- 6.0,N=4
 - 10.0- 11.0,N=9
 - 15.5- 16.5,N=9
 - 20.5- 21.5,N=13
 - 25.5- 26.5,N=13
 - 30.5- 31.5,N=15
 - 35.5- 36.5,N=46
 - 40.5- 41.5,N=36
 - 45.5- 46.5,N=30
 - 50.5- 51.5,N=27
 - 55.5- 56.5,N=27
 - 60.5- 61.5,N=30
 - 65.5- 66.5,N=25
 - 70.5- 71.5,N=27
 - 75.5- 76.5,N=26
 - 80.5- 81.5,N=31
 - 85.5- 86.5,N=30
 - 90.5- 91.5,N=32
 - 95.5- 96.5,N=33
 - 100.5-101.5,N=30

Note:
Lignite was encountered in the borings and may be encountered in greater extents in the project area

GENERAL NOTES:

BENCHMARK: Vertical Control Data are shown on the Survey Control Data Sheets.

CONSTRUCTION SPECIFICATIONS: Arkansas State Highway and Transportation Department Standard Specifications for Highway Construction (2014 edition) with applicable Supplemental Specifications and Special Provisions. Section and Subsection refer to the Standard Construction Specifications unless otherwise noted in the Plans.

DESIGN SPECIFICATIONS: AASHTO LRFD Bridge Design Specifications, Seventh Edition (2014) with 2015 interim revisions.

LIVE LOADING: HL-93

SEISMIC ZONE: 1 $S_{D1} = 0.146$ **SITE CLASS:** D

MATERIALS AND STRENGTHS:

Class S(AE) Concrete (superstructure)	$f'_c = 4,000$ psi
Class S Concrete (prestressed concrete girders)	$f'_c = 8,000$ psi
Prestressing Strands (AASHTO M 203, Gr. 270)	$f_{pu} = 270,000$ psi
Class S Concrete (substructure)	$f'_c = 3,500$ psi
Reinforcing Steel (Grade 60, AASHTO M 31 or M 322, Type A)	$f_y = 60,000$ psi
Structural Steel (ASTM A709, Gr. 50)	$FY = 50,000$ psi
Structural Steel (ASTM A709, Gr. 50W)	$FY = 50,000$ psi
Structural Steel (ASTM A709, Gr. 36)	$FY = 36,000$ psi

DRIVING SYSTEM: The driving system approval and the ultimate bearing capacity determination for piling shall be based on the requirements of Subsection 805.09(b), "Method B - Wave Equation Analysis (WEAP)." It is estimated that the minimum rated hammer energy required to obtain the ultimate bearing capacity at Bents 1 and 4 will be 20,000 foot pounds per blow and Bents 2 and 3 will be 80,000 foot pounds per blow.

BRIDGE DECK: The concrete bridge deck shall be given a tined finish as specified for final finishing in Subsection 802.19 for Class 5 Tined Bridge Roadway Surface Finish.

PROTECTIVE SURFACE TREATMENT: Class 1 Protective Surface Treatment shall be applied to the roadway surface and to the roadway face and top of the concrete parapet rails.

DETAIL DRAWINGS	DRAWING NOS.
End Bents	61369
Intermediate Bents	61370
Elastomeric Bearings	61371
164'-6" Integral Prestressed Concrete Girder Unit (Type II)	61372 - 61379
Type Special Approach Slab	61380
Steel H-Piling	55020
Concrete Piling	55022

EXISTING BRIDGE: Existing Bridge No. M2116 (Log Mile 9.68) is 24.5' wide and 95.0' long and consists of precast concrete channel beam units on reinforced concrete pier caps supported by timber piles. The existing bridge is located approximately 45 feet centerline to centerline downstream of new bridge.

REMOVAL AND SALVAGE: After new bridge is open to traffic, the Contractor shall remove Existing Bridge No. M2116 in accordance with Section 205. Remnant timber piling and concrete riprap from a previous structure shall also be removed to a depth of 2' below natural ground. This work shall be considered subsidiary to the item "Removal of Existing Bridge Structure." All material from the existing bridge shall become the property of the Contractor except the following, at the Direction of the Engineer. 10 interior and 4 exterior existing bridge precast concrete channel units and 12 guardrail and guardrail posts that are in good condition shall become property of Bradley County, which shall be protected and delivered to the address 1424 Bradley Road 25 North, Warren, AR. The remaining materials that are in good condition shall be become property of the State, which shall be protected and loaded onto State trucks. This work shall be considered subsidiary to the item "Removal of Existing Bridge Structure (Site No.)."


MAINTENANCE OF TRAFFIC: See Roadway Plans.

BORING LOGS: Boring logs may be obtained from the Construction Contract Procurement Section of the Program Management Division.

CONCRETE PILING: Piling in Bents 2 and 3 shall be 24" square prestressed concrete and shall be driven with an approved air, steam, or diesel hammer to a minimum ultimate bearing capacity of 300 tons per pile. Drive all piles to a minimum penetration of 25' below natural ground. Lengths of piling shown are assumed for estimating quantities only. Actual lengths are to be determined in the field. Drive one 40' test pile in Bent 2 and one 40' test pile in Bent 3.

STEEL PILING: All piling in Bents 1 and 4 shall be HP 10x42 (Grade 50) and shall be driven with an approved air, steam, or diesel hammer to a minimum ultimate bearing capacity of 150 tons per pile. Piling shall be driven after embankment to bottom of cap is in-place. Lengths shown are for estimating quantities only. Actual lengths are to be determined in the field. Drive one 70' test pile in Bent 1 and one 70' test pile in Bent 4.

PREBORING: Preboring is required for all piles. In Bents 1 and 4, prebored holes shall have a diameter of 6" greater than the diagonal of the pile for a depth of 10' below the bottom of the cap. After driving is completed, the prebored holes shall be backfilled with sand or pea gravel. Bents 2 and 3 shall be prebored to achieve minimum penetration. The actual size of preboring shall be determined in the field by the Engineer. After the piles have been driven, the holes shall be backfilled in accordance with Subsection 805.08(a). At all bents the Contractor shall be responsible for keeping prebored holes free of debris prior to driving piles and backfilling which may require the use of temporary casings or other approved methods. Any related cost for backfilling and temporary casing will not be paid for directly, but shall be considered subsidiary to the item "Preboring".



SHEET 2 OF 2
LAYOUT OF BRIDGE
HIGHWAY 160 OVER HALFWAY CREEK
HALFWAY CREEK STR. & APPRS. (S)
BRADLEY COUNTY


ROUTE 160 SEC. 9
ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.

BRIDGE NO. 07475 DRAWING NO. 61368


DESIGNED BY: TMG DATE: 5/2019 SCALE: 1"=20'
 CHECKED BY: DHP DATE: 11/7/19
 DRAWN BY: DPT DATE: 9/23/2019 FILENAME: b070418_11.dgn

PRINT DATE: 11/8/2019

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.		070418	31	52
				07475 - END BENTS - 61369				



PLAN
1/2" = 1'-0"




ELEVATION
1/2" = 1'-0"
Looking Back - Bent 1
Looking Ahead - Bent 4

BAR LIST - PER BENT

Mark	No. Req'd.	Length	Pin Dia.	Bending Diagrams
B401	2	32'-10"	Str.	<p>Dimensions are out to out of bars.</p>
B402	54	11'-0"	2"	
B403	10	7'-10"	2"	
B404E	72	4'-2"	Str.	
B405	8	10'-8"	2"	
B406E	6	9'-3"	Str.	
B407E	6	8'-2"	2"	
B408E	6	5'-3"	Str.	
B601	6	34'-2"	4 1/2"	
B602	6	32'-10"	Str.	

See Dwg. Nos. 61378 for additional details.



SECTION A-A
No Scale

GENERAL NOTES

All concrete in end bent cap shall be Class "S" with a minimum 28 day compressive strength $f'_c = 3,500$ psi and shall be poured in the dry. All exposed corners shall be chamfered 3/4" unless noted otherwise.

All reinforcing steel shall be Grade 60 (yield strength = 60,000 psi) conforming to AASHTO M 31 or M 322, Type A, with mill test reports.

Granular Backfill and Pipe Underdrain required behind cap. See Dwg. No. 61373 for details.

For additional information, see Layout.

B406E, B407E, and B408E shall have a 2'-10" embedment into the cap.




DETAILS OF END BENTS

ROUTE 9235
 SEC. 11-8-19
ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.

DRAWN BY: KJT DATE: 10/1/2019 FILENAME: b070418_b1.dgn
 CHECKED BY: DHP DATE: 11/7/19 SCALE: As Noted
 DESIGNED BY: DHP DATE: 09/2019
 BRIDGE NO. 07475 DRAWING NO. 61369

PRINT DATE: 11/7/2019


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418	32	52	
				07475 - INT. BENTS - 61370				



PLAN
1/2" = 1'-0"

Mark	No. Req'd.	Length	Pin Dia.	Bending Diagrams	
B401	8	30'-8"	Str.	Dimensions are out to out of bars	
B402	24	13'-0"	2"	3'-2" B402 3'-2" B403 1'-7" B404	
B403	15	9'-4"	2"	3'-2" B403 3'-2" B404 2'-8"	
B404	20	5'-8"	2"	3'-2" B403 3'-2" B404 2'-8"	
B405	20	5'-10"	2"	3'-2" B405 3'-2" B406 30'-8"	
B406	20	10'-10"	2"	3'-2" B405 3'-2" B406 30'-8"	
B407	4	4'-6"	Str.	3'-2" B405 3'-2" B406 30'-8"	
B601	6	32'-0"	4 1/2"	3'-2" B405 3'-2" B406 30'-8"	
B602	8	30'-8"	Str.	3'-2" B405 3'-2" B406 30'-8"	


Bars designated with an "E" suffix are to be epoxy coated.




ELEVATION
1/2" = 1'-0"
Looking Ahead

GENERAL NOTES

All concrete in bent cap shall be Class "S" with a minimum 28 day compressive strength $f'_c = 3,500$ psi and shall be poured in the dry. All exposed corners shall be chamfered 3/4" unless noted otherwise.
All reinforcing steel shall be Grade 60 (yield strength = 60,000 psi) conforming to AASHTO M 31 or M 322, Type A, with mill test reports.
For additional information, see Layout.




TYPICAL PEDESTAL DETAILS
No Scale




PEDESTAL PLAN
No Scale

① Adjust spacing as needed to avoid anchor bolts.




SECTION C-C
No Scale




SECTION A-A
No Scale

② Typical between piling




SECTION B-B
No Scale



TYPICAL ANCHOR BOLT LAYOUT
No Scale

For Details of Elastomeric Bearings, see Dwg. No. 61371.




DETAILS OF INTERMEDIATE BENTS
ROUTE SEC.
ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARK.

DRAWN BY: KJT DATE: 10/1/2019 FILENAME: b070418_b1.dgn
CHECKED BY: DHP DATE: 11/1/19 SCALE: As Noted
DESIGNED BY: DHP DATE: 09/2019
BRIDGE NO. 07475 DRAWING NO. 61370

PRINT DATE: 11/7/2019

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418	33	52	
				07475- ELASTO. BRNGS. - 61371				




FRONT VIEW


① C.L. Elastomeric Pad shall be aligned with C.L. Girder.

The grade and the direction of bevel of the external load plate may not be accurately depicted with respect to T_a and T_b values shown in the "Table of Fabricator Variables".

Prior to erection of the girders, the Contractor shall verify the orientation of the bearings with respect to T_a and T_b .



SIDE VIEW




ANCHOR BOLT DETAIL


Anchor Bolts may be cast in place or drilled and grouted into place. If Anchor Bolts are to be cast in place, the Galvanized Sheet Metal Sleeves will not be required.

If Anchor Bolts are to be drilled and grouted in place, the Galvanized Sheet Metal Sleeves shall be cast in place as shown. Sleeves shall be dry packed with styrofoam, urethane foam or approved equal prior to pouring of concrete. After pouring of the cap and prior to erection of girders, the dry pack shall be removed and holes for the anchor bolts shall be accurately drilled into the concrete. Bolts placed in drilled holes shall be accurately set and fixed using a QPL approved epoxy or non-shrink grout that completely fills the holes. Galvanized Sheet Metal Sleeves will not be paid for directly, but will be considered subsidiary to the item "Structural Steel in Beam Spans (A709, Gr. 50W)".

- ② Care shall be taken to ensure that the external load plate is in full and complete contact with the bearing insert plate before welding begins.
- ③ Bearing Insert Plate (A709, Gr. 50W) & Studs shall be considered subsidiary to the item "Prestressed Concrete Girders (Type II)". Studs shall conform to Subsection 807.08.



PLAN VIEW



ELASTOMERIC BEARING

t_e = Thickness of elastomer cover on top and bottom of pad.
 t_i = Thickness of elastomer between steel laminae.
 N = Number of elastomer layers of thickness t_i .

GENERAL NOTES

- Elastomeric Bearings shall conform to Section 808 and shall be paid for at the unit price bid for "Elastomeric Bearings".
- External load plates shall conform to ASTM A709, Gr. 50W. Pipe sleeves shall be ASTM A500, Grade B, and shall be galvanized to conform to AASHTO M 232, Class C or ASTM B695, Class 50.
- External load plates shall be completely fabricated (including bevel and bolt holes) and shall be cleaned before vulcanizing to the elastomeric bearing. The surface in contact with the elastomeric bearing shall be cleaned in accordance with Subsection 808.03. Other surfaces shall be blast cleaned in accordance with Subsection 807.84(b) for painted steel and 807.84(e) for unpainted Grade 50W steel.
- Anchor Bolts, Washers and Nuts shall conform to Subsection 807.07. The anchor bolt grade of steel shall be as specified in the "Table of Fabricator Variables". Indentations shall be circular with rounded bottoms and staggered as shown in the details.
- Pipe Sleeves, Anchor Bolts, Washers and Nuts shall be paid for at the unit price bid for "Structural Steel in Beam Spans (A709, Gr. 50W)". External load plates will not be measured and paid for separately, but will be considered incidental to the unit price bid for "Elastomeric Bearings".
- Bearings shall be seated in accordance with Subsection 808.08. This work and materials are considered subsidiary to the item "Elastomeric Bearings" and will not be paid for directly.

TABLE OF FABRICATOR VARIABLES

④ Maximum Design Load = Service I Limit State

BRIDGE NO.	LOCATION		BEARING TYPE	NO. of BEARINGS EACH BENT	④ MAXIMUM DESIGN LOAD (KIPS)	G	H	ELASTOMERIC PAD				NO. & THICKNESS OF STEEL LAMINAE	T	EXTERNAL LOAD PLATE						ANCHOR BOLT							
	BENT NO(S)	GIRDER NO.						A	B	N	t_i			t_e	C	D	E	F	K	M	T_a	T_b	ANCHOR BOLT (\emptyset X L)	PIPE SLEEVE SIZE (\emptyset X L)	SHEET METAL SLEEVE SIZE (\emptyset X L)	STEEL WASHER SIZE (O.D.)	
07475	2 & 3	All	Fix.	8	123	6 1/2"	3 3/4"	18"	7"	2	1/2"	1/4"	3 @ 12 Ga.	1 1/16"	8"	28 1/2"	2 1/4"	2 1/4"	1/2"	11 1/2"	2.00	2.00	1 1/2" x 23"	55	1 1/2" x 4"	3" x 13"	3"



DETAILS OF ELASTOMERIC BEARINGS

ROUTE SEC.
 ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.

DRAWN BY: KJT DATE: 10/9/19 FILENAME: b070418_e1.dgn
 CHECKED BY: DHP DATE: 11/7/19 SCALE: No Scale
 DESIGNED BY: DHP DATE: 09/2019
 BRIDGE NO. 07475 DRAWING NO. 61371

PRINT DATE: 11/7/2019

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
JOB NO. 070418							34	52
① 07475 - SPAN DETAILS - 61372								

Slab Reinforcing:

Longitudinal: S506E Top & S401E Bottom placed as shown
 S504E & S505E Top Placed as shown, see "HALF REINFORCING PLAN AND SLAB POURING SEQUENCE", Dwg. No. 61374.


Transverse: S501E @ 12" o.c. in top, S402E @ 12" o.c. in bottom
 S502E @ 12" o.c. bent up over girders
 S503E @ 6" in top of overhangs (bundled with No. 5 bars) Alternate

At the Contractor's option, two straight epoxy coated No. 5 bars, one placed in top and one placed in bottom, may be substituted for bar S502E. Payment will be based on the weight of bar S502E.


Bar positions or clearances from the forms shall be maintained by means of stays, ties, hangers or other approved devices per Subsection 804.06. Placement of slab bolsters or high-chairs with full-length lower runners directly on removable deck forms will not be allowed.

Class 1 Protective Surface Treatment shall be applied to the Roadway Surface and the Roadway Face and Top of Concrete Parapet Rail.




- ① Working point to gutterline.
- ② Tolerance: Minus = $\frac{1}{4}$ ";
Plus equal to the amount of slab thickening used to meet slab thickness tolerance. See "ADJUSTMENT FOR SLAB THICKNESS TOLERANCE".
- ③ See "ADJUSTMENT FOR SLAB THICKNESS TOLERANCE".
- ④ Partial Depth Diaphragm




TYPICAL ROADWAY SECTION AT BENTS
 $\frac{1}{2}'' = 1'-0''$



TYPICAL ROADWAY SECTION
 $\frac{1}{2}'' = 1'-0''$



Working Point Matches Theoretical Roadway Grade.
ROUNDING DETAIL
 No Scale




ts = slab thickness as shown on superstructure details - See "TYPICAL ROADWAY SECTION" and "TYPICAL ROADWAY SECTION AT BENTS".

- ⑤ Tolerance when removable deck forming is used is $+\frac{1}{2}$ " - $\frac{1}{4}$ ". Haunch forming is required and shall be adjusted to maintain slab thickness tolerance. See Std. Dwg. No. S5005 for tolerances when permanent steel deck forms are used.

"Girder Elevation" sketches show the range of acceptability of the top of the Girder relative to bottom of slab after the placement of the slab. When the top of the Girder projects more than $\frac{3}{8}$ " into the slab, a raise in grade will be necessary. Girders shall be set in a sufficient number of spans over suitable increments so the revised grade line will produce a smooth riding surface. Variation of haunch height will be at the Contractor's expense.

ADJUSTMENT FOR SLAB THICKNESS TOLERANCE

- ⑥ Two S504E or S505E bars in between S506E bar spaces.




SHEET 1 OF 8
 DETAILS OF 164'-6" INTEGRAL
 PRESTRESSED CONCRETE GIRDER UNIT

ROUTE SEC.
 ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.


DRAWN BY: KJT DATE: 10/1/2019 FILENAME: b070418_b1.dgn
 CHECKED BY: DHP DATE: 11/7/19 SCALE: As Noted
 DESIGNED BY: DHP DATE: 09/2019
 BRIDGE NO. 07475 DRAWING NO. 61372

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		35	52
				JOB NO.	070418		35	52
				07475 - SPAN DETAILS - 61373				




TYPICAL SECTION AT END BENT DIAPHRAGMS

Looking Back - Bent 1
Looking Ahead - Bent 4
1/2" = 1'-0"




TYPICAL SECTION AT PARTIAL DEPTH DIAPHRAGMS

1/2" = 1'-0"




SECTION D-D

1" = 1'-0"



SECTION E-E


1" = 1'-0"



SECTION C-C

Shown at Midspan,
Diaphragms at Intermediate Bents Similar
1" = 1'-0"

- Galvanized Threaded Inserts shall be Dayton-Richmond F-42 Loop Ferule Inserts or approved equal. 3/4"Ø x 3'-6" Galvanized Threaded Rods shall be ASTM A709, Grade 36 or AASHTO M 31 or M 322 Type A, Grade 60. Galvanizing shall be in accordance with AASHTO M 232, Class C or ASTM B695, Class 50. These items will not be paid for directly, but shall be considered subsidiary to the item "Prestressed Concrete Girders (Type II)".
- See End Bent details on Dwg. No. 61369 for reinforcing and additional details.
- Unreinforced bearing pads shall meet the requirements of Section 808 with the exception that hardness shall be 50 durometer. Unreinforced bearing pads shall not be paid for directly but shall be considered subsidiary to the item "Class S(AE) Concrete-Bridge".
- S601E centered about the girders placed through 1 1/4" Ø holes in web.
- Prestressed Stands, see Dwg. No. 61376.
- For additional details of pipe underdrain see Std. Dwg. PU-1 and Section 611. Pipe underdrains will not be measured or paid for separately, but will be considered subsidiary to various bid items.
- Polystyrene Foam Board, Filter Fabric and Granular Material shall not be paid for directly, but shall be considered subsidiary to the various bid items.
- Limits of the concrete End Bent Diaphragm shall match plan dimension of End Bent Cap.




SHEET 2 OF 8
DETAILS OF 164'-6" INTEGRAL
PRESTRESSED CONCRETE GIRDER UNIT

ROUTE SEC.
ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARK.

DRAWN BY: KJT DATE: 10/1/2019 FILENAME: b070418_s1.dgn
CHECKED BY: JHP DATE: 11/7/19 SCALE: As Noted
DESIGNED BY: DHP DATE: 09/2019
BRIDGE NO. 07475 DRAWING NO. 61373


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.		070418	37	52

07475 - SPAN DETAILS - 61375



HALF FRAMING PLAN

$\frac{3}{8}'' = 1'-0''$



ALTERNATE POURING SEQUENCE

No Scale

5 Stay-in-place forms, if used, shall be installed in a manner that facilitates the direction of the Pour.

Alternate Slab Pouring Sequence Notes:

Pours with the same number may be placed simultaneously or separately. All Pours (1) must be placed before Pours (2) can be placed. 72 hours shall elapse between adjacent pours.


No deviations from the pouring sequence or alternate pouring sequence shown will be allowed.

Concrete in bridge superstructure shall be placed, consolidated and screeded off for the entire pour before any concrete has taken its initial set. This may require the use of a retarding agent.

The partial depth concrete diaphragms shall not be poured prior to 90 days after release of strands for the girders.

Concrete diaphragms at Bents 1 & 4 shall be poured monolithically with the deck. All other concrete diaphragms shall be placed no less than 48 hours prior to deck slab pour.

A minimum of 72 hours shall elapse between completion of the slab and the pouring of the bridge railing. Any railing pours made before the entire slab unit has been placed must be approved by the Engineer.




DETAILS OF STEEL DIAPHRAGM

$1'' = 1'-0''$

Steel Diaphragms shall be used at locations noted as "Temporary Steel Diaphragm". The Temporary Steel Diaphragm and components will not be paid for directly, but shall be considered subsidiary to the Item "Prestressed Concrete Girders (Type II)".

Permanent Steel Diaphragms may be used in lieu of concrete diaphragms at locations noted as "Partial Depth Diaphragm". Payment will be based on concrete diaphragms.

All components of Steel Diaphragms (Permanent and Temporary) shall be galvanized in accordance with AASHTO M111.



VIEW AT INTERMEDIATE BENT

$\frac{3}{4}'' = 1'-0''$



SHEET 4 OF 8
 DETAILS OF 164'-6" INTEGRAL
 PRESTRESSED CONCRETE GIRDER UNIT


ROUTE SEC.
 ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.

DRAWN BY: KJT DATE: 10/1/2019 FILENAME: b070418_s1.dgn
 CHECKED BY: DHP DATE: 11/1/19 SCALE: As Noted
 DESIGNED BY: DHP DATE: 09/2019

BRIDGE NO. 07475 DRAWING NO. 61375

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		38	52
				JOB NO.		070418		

07475 - SPAN DETAILS - 61376



BAR LIST - PER GIRDER



MARK	NO. REQ'D.	LN	P.D.
G301	18	2'-6"	Str.
G401	44	2'-7"	2"
G402	22	1'-11"	3"
G403	140	4'-6"	2"
G404	10	12'-1"	2"
G405	2	55'-6"	3"
G501	24	4'-6"	2 1/2"

BENDING DIAGRAMS

Dimensions are out to out of bars.


All bars in BAR LIST shall be subsidiary to the item "Prestressed Concrete Girders (Type II)". See span drawings for bar list of span reinforcing.

At the Contractor's option, the two G401 bars may be furnished as one bar.



Span Pt.	Inches	
	W _A	X _A
0.00	0.000	0.000
0.10	0.627	0.197
0.20	1.101	0.417
0.30	1.428	0.591
0.40	1.621	0.702
0.50	1.684	0.743

Symmetrical about mid-point of span



CAMBER & DEFLECTIONS (INCHES)

Note: 'W_A' & 'X_A' are based on the required minimum concrete strength and may vary from the dimension shown. 'W_A' & 'X_A' shall be measured along bottom of girders unless otherwise approved by the Engineer. See "ADJUSTMENT FOR SLAB THICKNESS TOLERANCE" on Dwg. No. 61372 for limitations of the girder final position under dead load. The Contractor is responsible for any adjustment necessary to meet slab thickness tolerance and to achieve an acceptable finished grade. No payment shall be made for any additional concrete in the haunches when camber is less than shown.


TABLE OF GIRDER VARIABLES

6 At intermediate bents only, saw cut or grind all strands flush with end of the girder. The ends of the girders and the cut-off strands shall be coated with a 1/8" min. thick coating of a QPL approved epoxy resin.

1/2" x 1'-4 1/2" x 1'-5 1/2" Bearing Insert PL, see Dwg. No. 61371.

END OF GIRDER VIEW AT INTERMEDIATE BENT

- At End Bents 1 & 4, shop bend 6 bottom prestressing strands from end of the girder into diaphragms as shown. Cut any remaining strands flush with the end of girder. See "Strand Arrangements" detail for patterns.
- At the Contractor's option, the location for bent up strands may be varied. The total number of bent - up strands shall not be changed.
- Holes and inserts shown are for diaphragms. See Dwg. No. 61373 for additional details.
- This dimension shall be increased for effects of vertical profile on girder length to maintain 6" between ends of girders.
- For Bearing Pad Details at Bents 1 & 4, see Dwg. No. 61373.
- For Elastomeric Bearing Details at Bents 2 & 3, see Dwg. No. 61371.



END OF GIRDER DETAIL




SHEET 5 OF 8
 DETAILS OF 164'-6" INTEGRAL PRESTRESSED CONCRETE GIRDER UNIT

ROUTE SEC.
 ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.


DRAWN BY: KJT DATE: 10/1/2019 FILENAME: b070418_s1.dgn
 CHECKED BY: DHP DATE: 11/7/19 SCALE: No Scale
 DESIGNED BY: DHP DATE: 09/2019
 BRIDGE NO. 07475 DRAWING NO. 61376

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418		39	52
				07475 - SPAN DETAILS - 61377				




DETAILS OF PARAPET RAIL

Note: For location of Open and Closed Parapet panels, see "HALF REINFORCING PLAN AND SLAB POURING SEQUENCE", Dwg. No. 61374.



- (F) C.L. Full-Depth Parapet Joint (1/4" to 1" max.) as shown in the Plan Details. Stop 4" from top of slab.
- (P) C.L. Partial-Depth Parapet Joint (1/4" to 1" max.) as shown in the Plan Details. Stop 1'-2" from top of slab.




All panels shall be braced as required to prevent racking. All open joints shall be sawed as soon as practical to a minimum width of 1/4". To control cracking before sawing, all joints must be grooved before the concrete is set. Sawing of the joints must be controlled so it will follow the grooved joint.

The extruded parapet shall conform to the horizontal and vertical lines shown on the plans or as directed by the Engineer and shall present a smooth, uniform appearance and texture. Exposed surfaces may be given a light brush finish or a Class 3 Textured Coating Finish in place of the Class 2 Rubbed Finish.

DETAILS OF OPTIONAL SLIPFORMING OF CONCRETE PARAPET RAIL


TABLE OF PARAPET RAIL DATA

"A" Closed Parapet	"B"	P4xxE Bar
8'-0"	15	P404E
8'-3"	16	P406E




NOTE: The surfaces of the 3/8" plates which will not be in contact with concrete shall be painted with aluminum epoxy paint in accordance with Section 638, or as approved by the Engineer. Only one coat is required and shall be applied in the fabricator's shop. Painting shall not be paid for directly, but shall be considered subsidiary to various pay items specified in the plans.

Parapet studs shall be 5" long, granular flux filled, solid fluxed or equal, and automatically end welded to the plate. Studs and plates shall meet the requirements of Section 807 and shall not be paid for directly, but shall be considered subsidiary to Class S (AE) Concrete - Bridge.




SHEET 6 OF 8
 DETAILS OF 164'-6" INTEGRAL PRESTRESSED CONCRETE GIRDER UNIT
 ROUTE SEC.
 ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.
 DRAWN BY: KJT DATE: 10/1/2019 FILENAME: b070418_s1.dgn
 CHECKED BY: DHP DATE: 11/7/19 SCALE: No Scale
 DESIGNED BY: DHP DATE: 09/2019
 BRIDGE NO. 07475 DRAWING NO. 61377


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418	40	52	
				07475 - SPAN DETAILS - 61378				




VIEW R-R
1/2" = 1'-0"




SECTION S-S
1/2" = 1'-0"




SECTION Y-Y
No Scale




PLAN VIEW OF RAIL
1/2" = 1'-0"




SECTION X-X
No Scale



SECTION W-W
No Scale



THREE DIMENSIONAL VIEW OF WING AND RAIL AT INTEGRAL END BENT
No Scale





SHEET 7 OF 8
 DETAILS OF 164'-6" INTEGRAL PRESTRESSED CONCRETE GIRDER UNIT
 ROUTE SEC.
 ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.
 DRAWN BY: KJT DATE: 10/1/2019 FILENAME: b070418_s1.dgn
 CHECKED BY: DHP DATE: 11/7/19 SCALE: As Noted
 DESIGNED BY: DHP DATE: 09/2019
 BRIDGE NO. 07475 DRAWING NO. 61378

BAR LIST

MARK	NO. REQ'D.	LENGTH	P.D.
P401E	520	5'-6"	3"
P402E	144	4'-10"	3"
P403E	96	4'-6"	Str.
P404E	56	7'-8"	Str.
P405E	126	12'-8"	Str.
P406E	28	7'-11"	Str.
P501E	520	4'-8"	3 3/4"
R401E	16	3'-11"	2"
R402E	16	4'-0"	2"
R403E	24	9'-8"	Str.
R404E	24	4'-6"	Str.
R601E	32	6'-3"	Str.
R602E	12	5'-0"	Str.
S401E	220	43'-3"	Str.
S402E	169	32'-10"	Str.
S403E	64	8'-0"	2"
S404E	192	7'-2"	Str.
S405E	16	6'-4"	2"
S406E	168	6'-9"	2"
S501E	171	32'-10"	Str.
S502E	160	33'-6"	3"
S503E	642	4'-7"	Str.
S504E	152	8'-11"	3 3/4"
S505E	152	15'-0"	Str.
S506E	156	43'-9"	Str.
S507E	60	4'-0"	Str.
S601E	36	5'-6"	Str.
S602E	16	7'-6"	4 1/2"
W401E	20	5'-1"	2"
W402E	20	6'-3"	Str.
W701E	12	14'-10"	5 1/4"
W702E	40	13'-3"	Str.

BENDING DIAGRAMS

Dimensions are out to out of bars.
Bars with an "E" suffix are to be epoxy coated.



② 1/2" overtolerance, No undertolerance

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
							JOB NO.	070418
							①	07475 - SPAN DETAILS - 61379

GENERAL NOTES

CONCRETE: All concrete, except for prestressed girders, shall be Class S(AE) with a minimum 28 day compressive strength $f'_c = 4,000$ psi. Concrete shall be poured in the dry and all exposed corners shall be chamfered $3/4"$ unless otherwise noted.

The superstructure details shown are for use when removable deck forming is used and are the basis for measurement of Class S(AE) Concrete. See Standard Drawing No. 55005 for allowable modifications and for tolerances when Permanent Steel Bridge Deck Forms are used.

The concrete deck (roadway surface) shall be given a fine finish in accordance with Subsection 802.19 for Class 5 Tined Bridge Roadway Surface Finish. Movement of the finishing machine across new concrete shall be on planks placed on the surface and shall be prohibited for 72 hours after finishing the pour. Sufficient concrete must be placed ahead of the strike-off to fully load the girder. When permitted, the use of a longitudinal strike-off will require that a vertical camber adjustment be made in the strike-off to account for the future dead load deflection due to any railings.

REINFORCING STEEL: All reinforcing steel shall be Grade 60 conforming to AASHTO M 31 or M 322, Type A, with mill test reports and shall be epoxy coated. The reinforcing steel is to be accurately located in the forms and firmly held in place by steel wire supports, sufficient in number and size to prevent displacement during the course of construction. The wire supports will not be paid for directly, but will be considered subsidiary to the item "Epoxy Coated Reinforcing Steel (Grade 60)".

STRUCTURAL STEEL: Structural steel shall be ASTM A709 as specified in the plans. Unless otherwise noted, Grade 50W steel shall not be painted and all exposed surfaces shall be cleaned in accordance with Subsection 807.84(e). Grade 36 and Grade 50 steel shall be painted unless otherwise noted and all exposed surfaces shall be cleaned in accordance with Subsection 807.84. Structural steel completely embedded in concrete may be ASTM A709, Gr. 36, Gr. 50, or Gr. 50W unless otherwise noted.

Drawings show general features of design only. Shop drawings shall be made in accordance with the specifications, submitted, and approval secured before fabrication is begun.

Requests for substitution of structural steel shapes shown with shapes of greater size must be submitted by the Contractor to the Engineer for approval. Steels of equal or greater strengths will be accepted only when shown on the approved shop drawings. Payment, where applicable, will be based on the basis of shapes and materials shown in the plans, and no additional compensation will be made for any adjustments due to substitutions.

All welding that is to be done during fabrication of structural steel, including temporary welds, shall be detailed on the shop drawings and submitted for approval. All welding shall conform to Subsection 807.26.

PRESTRESSED GIRDER: Prestressing steel shall be 0.6"Ø Low Relaxation strands with a minimum ultimate strength of 270 ksi, and shall conform to AASHTO M 203.

Prestressed strands will not be paid for directly, but will be considered subsidiary to the item "Prestressed Concrete Girders (Type II)".

All girders shall be Type II as noted on the details and shall be the standard prestressed sections adopted by the Joint Committee of AASHTO and the Prestressed Concrete Institute. All girders shall be cast in concrete floored pallets and in metal forms. All work and materials shall be as specified in Subsection 802.22.

Concrete shall be Class S and shall have a minimum 28 day compressive strength, $f'_c = 8,000$ psi. The initial tensile force applied to each 0.6"Ø strand shall be 43,950 lbs. except as noted. Transfer of this tensioning load to the girder shall not be done until the compressive strength of the concrete is 6,000 psi.

Dimensions shown are to the center of the strands.

Holes and Inserts shall be cast into the girder. Field drilling of holes shall not be permitted.

The tops of the girder shall be roughened to an amplitude of $1/4"$ and shall be scrubbed transversely with a coarse wire brush to remove all laitance to produce an adequate surface for bonding to the slab.

After detensioning, saw cut, grind, or bend up strands as designated by the plans. Heat-cutting or bending methods shall not be used within 6" of the girder.

The points of support and directions of the reactions with respect to member shall be approximately the same during transportation and storage as when the member is in its final position.

Reinforcing steel shall be Grade 60 ($f_y = 60,000$ psi.) conforming to AASHTO M 31 or M 322, Type A with mill test reports.


The Contractor may submit alternate strand patterns with design calculations for review and approval.

Drawings show general feature of design only. Shop drawings shall be made in accordance with the specifications, submitted, and approval secured before fabrication is begun.

Extreme care shall be exercised in handling and moving precast prestressed concrete girders. Girders must be maintained in an upright position at all times and must be picked up from points near the girder ends. Disregard of this requirement may lead to collapse of the girder. The Contractor's proposed lifting details shall be submitted on shop drawings to the Engineer for approval. The use of holes for lifting purposes will not be permitted.

The Contractor shall submit the method and sequence for release of strands to the Engineer for approval prior to casting of the girders.

Distances from the forms and spacing of the Prestressing Steel shall be maintained by stays, ties, hangers, spacers, or other approved supports which shall be shown on the Shop Drawings.



SHEET 8 OF 8
DETAILS OF 164'-6" INTEGRAL
PRESTRESSED CONCRETE GIRDER UNIT

ROUTE SEC.
ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARK.


BRIDGE ENGINEER

DRAWN BY: KJT DATE: 10/1/2019 FILENAME: b070418_s1.dgn
CHECKED BY: DHP DATE: 11/7/19 SCALE: As Noted
DESIGNED BY: DHP DATE: 09/2019

BRIDGE NO. 07475 DRAWING NO. 61379


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. PROJ. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418		42	52
				07475 - APPROACH SLAB - 61380				

Notes:
The surface finish for Approach Slabs shall match that used on the bridge deck.



PLAN - APPROACH SLAB

1/4" = 1'-0"



DETAILS OF LONGITUDINAL CONSTRUCTION JOINT

1/4" = 1'-0"


BAR LIST

Mark	No. Req'd	Length	P.D.
S401	29	21'-8"	Str.
S402	44	2'-8"	Str.
S403	40	3'-0"	Str.
S501	44	29'-8"	Str.

QUANTITIES FOR ONE TYPE SPECIAL APPROACH SLAB


(FOR INFORMATION ONLY)

Reinforcing Steel (lbs.)	Concrete (Cu. yds.)
1,940	27.70




SECTION X-X

1/4" = 1'-0"




SECTION A-A

Not to Scale



SECTION B-B

Not to Scale



SECTION Y-Y


Not to Scale

GENERAL NOTES

All concrete shall be Class S (AE) with a minimum 28 day compressive strength $f_c = 4,000$ psi and shall be poured in the dry.

All reinforcing steel shall be Grade 60 (yield strength = 60,000 psi) conforming to AASHTO M 31 or M 322, Type A, with mill test reports.

Approach Slabs will be measured and paid for in accordance with Section 504.



DETAILS OF TYPE SPECIAL APPROACH SLAB

ROUTE SEC. ARKANSAS STATE HIGHWAY COMMISSION

LITTLE ROCK, ARK.

DRAWN BY: DPT DATE: 11/5/2019 FILENAME: b070418_as.dgn

CHECKED BY: DPT DATE: 11/7/19 SCALE: As Shown




DESIGNED BY: STJ DATE:

BRIDGE NO. 07475 DRAWING NO. 61380

PRINT DATE: 11/7/2019

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. AID DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
JOB NO. 070418							43	52

2 CROSS SECTIONS






CROSS SECTION STA. 197+74 TO STA. 199+74

10/9/2019 R070418.DCN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418		44	52




2 CROSS SECTIONS



CROSS SECTION STA. 200+00 TO STA. 201+36

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 070418	45	52

② CROSS SECTIONS






CROSS SECTION STA. 202+00 TO STA. 204+00

10/9/2019 R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418		46	52

2 CROSS SECTIONS






CROSS SECTION STA. 204+80 TO STA. 205+21

R070418.DGN 10/9/2019

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	070418		47	52

② CROSS SECTIONS






CROSS SECTION STA. 205+78 TO STA. 207+00

10/9/2019 R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		48	52
JOB NO. 070418								




② CROSS SECTIONS



CROSS SECTION STA. 208+00 TO STA. 208+83

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		49	52
				JOB NO.	070418			

② CROSS SECTIONS






CROSS SECTION STA. 210+16 TO STA. 211+00

10/9/2019 R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 070418	50	52

2 CROSS SECTIONS






CROSS SECTION STA. 212+00 TO STA. 214+00

10/9/2019

R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		51	52
				JOB NO.		070418		

② CROSS SECTIONS





CROSS SECTION STA. 215+00 TO STA. 216+60

10/9/2019

R070418.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
JOB NO. 070418							52	52


② CROSS SECTIONS




CROSS SECTION STA. 217+00 TO STA. 217+60

R070418.DGN 10/9/2019


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
JOB NO.							1	
EMBAKMENT & BACKFILL							55000	





EMBAKMENT CONSTRUCTION AND FOOTING BACKFILL AT VERTICAL WALL ABUTMENTS




EMBAKMENT CONSTRUCTION AT SPILL-THROUGH PILE END BENTS




EMBAKMENT CONSTRUCTION AND FOOTING BACKFILL AT SPILL-THROUGH END BENTS



SPILL-THROUGH END BENTS WITH TURNBACK WING



SPILL-THROUGH END BENTS WITH STUB WING



SPILL-THROUGH END BENTS WITH TRANSITION WING

METHOD OF DETERMINING FILL SLOPE LOCATION AT BRIDGE ENDS


GENERAL NOTES

The Bridge End Embankment shall be defined as a section of embankment, not less than 20 feet long adjacent to the bridge end, together with the side slopes and slopes under the bridge end including around the end of wingwalls. Embankment adjacent to structures shall be constructed in 6 inch horizontal layers (loose measure) and compacted by the use of mechanical equipment to the satisfaction of the Engineer. Refer to Subsections 210.09, 210.10 and 801.08 for construction requirements.


STANDARD DETAILS FOR EMBAKMENT CONSTRUCTION AND BACKFILL AT BRIDGE ENDS

ARKANSAS STATE HIGHWAY COMMISSION
 LITTLE ROCK, ARK.
 DRAWN BY: KDH DATE: 2-27-2014 FILENAME: b55000.dgn
 CHECKED BY: BEF DATE: 2-27-2014 SCALE: NO SCALE
 DESIGNED BY: STD. DATE: -
 DRAWING NO. 55000


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.		RIPRAP & EXCAV. 55001		




EXCAVATION FOR STRUCTURES - ABUTMENT IN NEW EMBANKMENT INTERIOR BENT IN NEW EMBANKMENT AND NATURAL GROUND




EXCAVATION FOR STRUCTURES - BRIDGE LOCATION WITH DESIGNATED CHANNEL CHANGE




PLAN OF DUMPED RIPRAP




ELEVATION OF RIPRAP BERME WITH RIPRAP




EXCAVATION FOR STRUCTURES - ABUTMENT IN NATURAL GROUND




EXCAVATION FOR STRUCTURES - ABUTMENT IN NEW EMBANKMENT INTERIOR BENT IN NATURAL GROUND




SECTION A-A (Toe Excavation in Soil)




ELEVATION OF RIPRAP BERME WITHOUT RIPRAP




SECTION B-B




SECTION A-A (Toe Excavation in Rock)




OPEN ABUTMENT WITH TURNBACK WINGS



EXCAVATION FOR STRUCTURES - BENT IN ROADWAY FILL SECTION AND NATURAL GROUND



EXCAVATION FOR STRUCTURES - ABUTMENT IN NATURAL GROUND AND NEW EMBANKMENT



DETAIL C

Note: Use this type of toe when rock is encountered which is in a stable condition.

Note: In lieu of an aggregate filter blanket, a synthetic fiber geotextile fabric complying with the requirements of Subsection 816.02(e) may be used.


Note: Details for computing excavation for structures are included for information as to how plan quantities were calculated and for use when adjusting quantities when changing footing elevation.

STANDARD DETAILS FOR DUMPED RIPRAP AND FILTER BLANKET AND COMPUTING EXCAVATION FOR STRUCTURES
ARKANSAS STATE HIGHWAY COMMISSION

LITTLE ROCK, ARK.
 DRAWN BY: KDH DATE: 2-27-2014 FILENAME: b55001.dgn
 CHECKED BY: BEF DATE: 2-27-2014 SCALE: NO SCALE
 DESIGNED BY: STD. DATE: _____




DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
3/24/16				6	ARK.			
JOB NO.								

BRIDGE DECK FORMS 55005



PART PLAN - SQUARE SPAN
3/8" = 1'-0"


PART PLAN - SKEWED SPAN
3/8" = 1'-0"




SECTION C-C
1" = 1'-0"

SECTION C-C - ALTERNATE
1" = 1'-0"
(Applicable when corrugations do not match spacing of main reinforcement)


t_s = slab thickness as shown on superstructure detail drawings.
GENERAL NOTES




SECTION B-B
1" = 1'-0"




SECTION B-B
1" = 1'-0"




SECTION B-B
1" = 1'-0"




SECTION B-B
1" = 1'-0"




SECTION B-B
1" = 1'-0"



SECTION B-B (FOR CONCRETE GIRDERS)
1" = 1'-0"



SECTION B-B (FOR CONCRETE GIRDERS)
1" = 1'-0"



SECTION D-D
1" = 1'-0"

① Distance from top of slab to bottom of top flange as measured at centerline girder and as shown on superstructure detail drawings. This dimension may vary within the following limits to maintain the grade and slab thickness tolerances: Minimum - occurs when either the top flange or the support angle leg contacts the bottom reinforcing steel; Maximum = $t_s + 1/4"$ + flange thickness. See Section C-C for slab thickness tolerance between adjacent girder flanges.

② Distance from top of slab to top of girder as measured at centerline girder and as shown on superstructure detail drawings. This dimension may vary within the following limits to maintain the grade and slab thickness tolerances: Minimum - occurs when either the top of girder or the support angle leg contacts the bottom reinforcing steel; Maximum - value shown on the superstructure detail drawings when removable forms are used. See Section C-C for slab thickness tolerance between adjacent girder flanges.

Permanent steel deck forms may be used at the Contractor's option and shall be at no additional cost to the Department. Such use may result in changes to the dead load deflection of the girder. Any cost for adjustments due to a change in the dead load deflection will be borne by the Contractor. Payment for deck concrete and structural steel will not be increased due to use of permanent steel deck forms.

Permanent steel deck forms shall conform to Subsection 802.4(b). Detailed plans, including detailed calculations and manufacturer's technical brochure, shall be submitted to and approved by the Engineer before work of forming the bridge deck is started.

Welding of form supports to the tension flange of steel girders will be permitted only in areas where shear connectors are used. When welding is not allowed, the method of fastening Z or L supports to the flange must be approved by the Engineer.

Form sheets shall be fastened to supporting members and to each other with galvanized metal screws sufficient in size and number to provide a secure attachment. Alternate methods of attachment must be approved by the Engineer.

When the pitch of form corrugations match the reinforcing spacing, transversely align form sheets across the bridge to maintain the correct orientation of continuous reinforcing bars in the corrugations.

Bar support rods, when used, shall be sized and spaced to adequately support the bottom reinforcing mat at the required position.

High chairs shall be sized to support the top mat of reinforcing at the proper position. High chairs shall be placed at locations shown on the detail drawings.

Specifications: Arkansas State Highway and Transportation Department Standard Specifications for Highway Construction (204 Edition), with applicable Supplemental Specifications and Special Provisions.

STANDARD DETAILS FOR PERMANENT STEEL BRIDGE DECK FORMS FOR STEEL & CONCRETE GIRDER SPANS

ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARK.

DRAWN BY: KDH DATE: 2-27-2014 FILENAME: b55005.dgn
CHECKED BY: BEF DATE: 2-27-2014 SCALE: NONE
DESIGNED BY: STD. DATE: —



△ Revised weld dimension by KWH, Ck'd by BEF, 3/24/16.

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
12-1-14		1-15-19		6	ARK.			
1-14-15								
1-17-17								

① TYPE D NAME PLATE 55010

The name of the bridge as shown on the plans shall be placed on Lines 1 - 3 using 1/8" raised letters and numerals 3/8" high.

Line	Example 1	Example 2	Example 3	Example 4
Line 1	Red River	Southern	Saline	Highway 5
Line 2	Relief	Railroad	River	
Line 3		Overpass	Relief	



GENERAL NOTES

Specifications: Arkansas State Highway and Transportation Department Standard Specifications for Highway Construction, (2014 Edition) with applicable Supplemental Specifications and Special Provisions.

Name plates shall be cast bronze and shall meet the material requirements as specified in Section 812.

Body of plate shall be 1/4" thick and shall include four tapering cone lugs 3/8" to 5/8" x 2" long. The border and all lettering shall be raised 1/8" above the face of plate and shall be polished.

All lettering shall be plain gothic, square cut and not tapered.

The number of plates required and the location and name on the plate for each bridge shall be as designated on the plans.

- ▲ Revised Chair and Vice Chair Added New Commissioner
1-15-19 CGP Checked By: CRE
- ▲ Added New Commissioner
1-17-17 KDH Checked By: CRE
- ▲ Revised Chair and Vice Chair Added New Commissioner
1-14-15 KDH Checked By: CRE
- ▲ Revised Deputy Director/Chief Engineer Added Deputy Director/Chief Operating Officer
12-1-14 KDH Checked By: CRE

Place the design live loading here using 1/8" raised letters and numerals 1/4" high. Examples: HS 20 HL-93

Place the Year in which Contract was awarded here using 1/8" raised numerals 3/8" high. Example: 2001

Place the name of the company awarded the construction contract here using 1/8" raised letters and numerals 3/8" high. Example: ABCD CONSTRUCTION, INC.

Place the Bridge number here using 1/8" raised letters and numerals 1/4" high. Examples: A1234 05432

TYPICAL BRIDGE NAME PLATE

STANDARD DETAILS FOR TYPE D BRIDGE NAME PLATE

ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARK.

DRAWN BY: KDH DATE: 2-27-2014 FILENAME: b55010.dgn
CHECKED BY: BEF DATE: 2-27-2014 SCALE: NO SCALE
DESIGNED BY: STD. DATE: _____



GENERAL NOTES FOR STEEL H-PILES:

Steel H-Piles shall conform to AASHTO M 270, Grade 36 or greater.

See Bridge Layout and Bent Details for pile size, estimated length, spacing, pile anchorage (if required) and for driving information.

Steel H-Piles that extend above the ground and are not protected by pile encasement shall be painted in accordance with Subsection 805.02.

Brackets, lugs, cap plates, pile tips, driving points, pile painting, splicing and welding shall not be paid for directly, but shall be considered subsidiary to the item "Steel Piling".



Notes:

All bracing shall be cut and welded in the field. Each brace shall be furnished in one piece. Payment shall be made under Item 807.

Unless noted otherwise, omit X-Bracing when "H" is less than 8 feet.


Omit X-Bracing and Bottom Bracing when "H" is 5 feet or less.

When required on the Bridge Layout sheet, pile encasements shall be constructed. See Notes and Details for H-Pile Encasements.

Omit all bracing (and V-groove in cap) when pile encasement is extended to bottom of bent cap.

TYPICAL DETAILS OF H-PILE TREESTLE INTERMEDIATE BENT


(Shown with Partial Height Encasement)



The Contractor may for his own convenience and at his own expense provide as many as three splices per pile. Minimum spacing between splices shall be 5 feet.

TYPICAL SPICE DETAILS

H-pile splicers manufactured by Associated Pile and Fitting Corporation, LB Foster Piling, Skyline Steel or equivalent may be used in lieu of the "Typical Splice Details" shown. H-pile splicers shall match the same grade of steel specified for the piling and shall be welded to the pile with a 5/8 inch fillet weld around the entire perimeter of the splice. Flanges shall be welded with a complete penetration groove weld complying with AASHTO/AWS Joint Designation B-U4a or B-U4b. All welding shall conform to Subsection 807.26 of the AHTD Standard Specifications for Highway Construction (2014 Edition).



REINFORCING DETAIL FOR STEEL H-PILE TIP

Notes: Steel pile tip reinforcing not required when approved H-Pile driving points are used.

Steel pile tip reinforcing shall not be paid for directly, but shall be considered subsidiary to the item "Steel Piling".

- HP14x73 - PL 1/2" x 6" x 11"
- HP12x53 - PL 1/2" x 6" x 9"
- HP10x42 - PL 1/2" x 6" x 7"

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
3/24/16				6	ARK.			
JOB NO.							STEEL H-PILES	55020

GENERAL NOTES FOR H-PILE ENCASEMENTS:


See Bridge Layout for additional notes, any pile encasement restrictions and required location of pile encasements.

All concrete shall be Class S with a minimum 28-day compressive strength, f'c = 3,500 psi. If concrete cannot be placed in the dry, Seal Concrete may be used from top to bottom of encasement.

Reinforcing steel shall be Grade 60 conforming to AASHTO M 31 or M 322, Type A.


Welded Wire Fabric shall conform to AASHTO M 55 or M 221. Galvanized Corrugated Steel Pipe shall conform to AASHTO M 36 and M 218.

Concrete, welded wire fabric or reinforcing steel and galvanized pipe shall not be paid for directly, but shall be considered subsidiary to the item "Pile Encasement".



PILE ENCASEMENT DETAIL FOR STEEL H-PILES

(Shown with Encasement to Bottom of Cap)




SECTION F-F

* Measured out-to-out of bar.

TABLE OF VARIABLES FOR PILE ENCASEMENT

Pile Size	"D"		"L"*
	Square Encsmt.	Round Encsmt.	
HP10x42	1'-7"	2'-0"	1'-4"
HP12x53	1'-8"	2'-2"	1'-5"
HP14x73	1'-11"	2'-6"	1'-8"



ALTERNATE PILE ENCASEMENT DETAIL FOR STEEL H-PILES

(Shown with Partial Height Encasement)

- Unless otherwise noted on Bridge Layout.
- 3'-0" minimum or as shown on Bridge Layout.
- Encasement dimensions shall be sized to maintain a minimum concrete cover of 4" from the H-Pile. Reinforcement shall be sized to provide a minimum concrete cover of 1 1/2" and a minimum clearance of 1 1/4" from the pile.
- Alternate pile encasement, when not extended to bottom of cap, shall have 2" concrete taper for water runoff as shown in the Partial Height Encasement detail.

Added alternate method of splicing H-piles and revised pile encasement note. 3/24/2016 AMS



This document was originally issued and sealed by Charles R. Ellis, PE No. 9235, on March 24, 2016. This copy is not a signed and sealed document.

STANDARD DETAILS FOR STEEL H-PILES AND PILE ENCASEMENTS

ARKANSAS STATE HIGHWAY COMMISSION

LITTLE ROCK, ARK.

DRAWN BY: A.M.S. DATE: 2/27/2014 FILENAME: b55020.dgn
 CHECKED BY: B.E.F. DATE: 2/27/2014 SCALE: NO SCALE
 DESIGNED BY: STD. DATE: —





DRAWING NO. 55020

BRIDGE ENGINEER

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
3/24/16				6	ARK.			
JOB NO.								

MAXIMUM PICKUP LENGTHS "L"

Type of Pick-Up	Prestressed		Non-Prestressed	Prestressed					Non-Prestressed		
	16" Oct.	18" Oct.	16" or 18" Oct.	14" Sq.	16" Sq.	18" Sq.	20" Sq.	24" Sq.	14" Sq.	16" Sq.	18" Sq.
One Point	52'	55'	46'	55'	59'	63'	66'	71'	52'	51'	55'
Two Point	75'	80'	67'	79'	84'	90'	95'	102'	75'	74'	79'
Three Point	105'	112'	93'	110'	117'	126'	132'	143'	104'	103'	111'



GENERAL NOTES:

CONSTRUCTION SPECIFICATIONS: Arkansas State Highway and Transportation Department Standard Specifications for Highway Construction (2014 Edition) with applicable Supplemental Specifications and Special Provisions.

DESIGN SPECIFICATIONS: AASHTO LRFD Bridge Design Specifications, current Edition with Interim Specifications.

SEISMIC PERFORMANCE ZONES: 1 & 2

Unless otherwise noted in the plans, the Contractor may use prestressed or non-prestressed piles for 14", 16" and 18" piles. The Contractor shall use prestressed piles for 20" and 24" piles. Prestressed and non-prestressed piling shall be measured and paid for at the contract unit price bid for "Concrete Piling".

SPIRAL REINFORCING: Spiral reinforcing shall be steel wire meeting the requirements of AASHTO M 32 or M 225 or shall be plain round steel bars meeting the requirements of Grade 60, AASHTO M 31 or M 322, Type A.

MANUFACTURE, TRANSPORTATION AND STORAGE: Shipment of piles from the plant site or pile driving will not be permitted until the required minimum compressive strength is reached, and in no case less than 10 days after pouring the concrete. Prestressed piles may be removed from the casting bed to nearby storage any time after transfer of stress. See Section 802 "Concrete for Structures" for additional information.

Unless otherwise approved by the Engineer, all protruding or exposed pile lifting or transporting devices above the finished ground shall be removed after pile driving is complete. Removal shall be a minimum of 1' below the surface of the pile and the cavity shall be filled with a non-shrink grout listed on the Department's OPL.

FORMS: For forming exterior of piles, the use of steel forms on concrete-founded casting beds is required unless otherwise approved by the Engineer. Side forms may have a maximum drift on each side not exceeding 1/4" per foot.

TOLERANCES: Pile ends shall be plane surfaces perpendicular to the longitudinal axis of pile with a maximum tolerance of 1/8" per foot transversely.

The maximum sweep (deviation from straightness measured from end to end of the pile, while not subject to bending forces) shall not exceed 1/8" in 10 feet.

BUILD-UPS: To provide for build-ups of piles where authorized by the Engineer, the concrete in the pile shall be cut back to provide a 60 bar diameter lap splice. For piles equal to or less than 18", the reinforcing for build-up shall be the reinforcing shown for non-prestressed piles. Otherwise, the reinforcing for build-up shall be as shown in the table "Pile Build-Up for 20" & 24" Prestressed Piles" and the 60 bar diameter splice length shall be based on the bar sizes shown.

INSTALLATION, MEASUREMENT AND PAYMENT: See Section 805 "Piling".

ADDITIONAL NOTES FOR PRESTRESSED PILES ONLY:

CONCRETE: Concrete in prestressed piles shall be Class (S/AE) and shall have a minimum compressive strength (f'c) of 5,000 psi at 28 days. Compressive strength at transfer of the prestressing force shall be not less than 4,000 psi. Concrete in build-ups shall have a minimum compressive strength of 4,000 psi and shall be cured for a minimum of 10 days.


PRESTRESSING REINFORCING: Seven-wire stress-relieved or low relaxation strands shall conform to the general requirements of AASHTO M 203. Broken wires within individual strands will be permitted up to 2% of the total number of wires in each pile, providing that there is not more than one broken wire per strand. Two or more broken wires per strand will be cause for replacement of the strand, even though the two broken wires are within the 2% limitation.

ADDITIONAL NOTES FOR NON-PRESTRESSED PILES ONLY:

All concrete shall be Class (S/AE) and shall have a minimum compressive strength (f'c) of 4,000 psi at 28 days. All longitudinal reinforcing bars shall be deformed bars and shall conform to the requirements of Grade 60, AASHTO M 31 or M 322, Type A.

For anchorage of pile to bent, see Bent Details.

NOTE: Strand location shall be symmetrical about the axis of the pile with no more than one strand difference between any two adjacent sides. Circular spiral ties are required for odd number of strands.



PRESTRESSED CONCRETE PILES


① Number based on Initial prestress force of "B" x Ultimate Tensile Stress, Prestress Losses and min. 700 psi Unit Prestress on concrete after Losses.

"B" [0.75 Low Relaxation
0.70 Stress-Relieved]

⑤ See table "Prestressed Concrete Pile Properties" for actual number of strands per pile size.

PRESTRESSED CONCRETE PILE PROPERTIES

Grade	Strand Diameter	① Number of Strands per Size "D"							Minimum Ultimate Tensile Strength Per Strand (Lbs.)	Initial Prestressing Force Per Strand (Lbs.)
		16" Oct.	18" Oct.	14" Sq.	16" Sq.	18" Sq.	20" Sq.	24" Sq.		
Stress-Relieved	250	11	13	10	13	16	20	28	27,000	18,900
	270	8	10	8	10	12	15	21	36,000	25,200
Low Relaxation	250	9	11	8	12	14	17	24	31,000	21,700
	270	7	9	6	8	10	13	18	41,300	28,900
Stress-Relieved	250	9	11	8	11	14	17	24	27,000	20,200
	270	7	9	6	8	10	13	18	36,000	27,000
Low Relaxation	250	8	10	7	9	12	15	21	31,000	23,300
	270	6	8	6	7	9	11	16	41,300	31,000



NON-PRESTRESSED CONCRETE PILES

NON-PRESTRESSED PILE REINFORCING


Pile Size	No. Req'd.	Bar Size
16" Oct.	8	#7
18" Oct.	8	#7
14" Sq.	8	#7
16" Sq.	8	#7
18" Sq.	8	#8

④ 14" sq. piles to be used in Seismic Performance Zone 1 only.

PILE BUILD-UP FOR 20" & 24" PRESTRESSED PILES

Pile Size	No. Req'd.	Bar Size
20" Sq.	8	#9
24" Sq.	12	#9

NOTE: Reinforcing bars shall meet the requirements for Grade 60, AASHTO M 31 or M 322, Type A.



Revised to accommodate 20" and 24" square prestressed piles by KNY, Ck'd. by BEF, 3/24/16.

③ The five additional turns of spiral reinforcing may be omitted for build-up without additional driving.

This document was originally issued and sealed by Charles R. Ellis, PE No. 9235, on March 24, 2016. This copy is not a signed and sealed document.




STANDARD DETAILS FOR CONCRETE PILES
ARKANSAS STATE HIGHWAY COMMISSION
LITTLE ROCK, ARK.

DRAWN BY: KDH DATE: 2-27-2014 FILENAME: b55022.dgn
CHECKED BY: BEF DATE: 2-27-2014 SCALE: NO SCALE
DESIGNED BY: STD DATE: —


BRIDGE ENGINEER

DRAWING NO. 55022


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
9/2/15				6	ARK.			
JOB NO.							TYPE A GUTTERS	55030A



HALF PLAN OF APPROACH GUTTERS FOR SQUARE BRIDGE




PLAN OF APPROACH GUTTERS FOR SKEWED BRIDGE




SECTION A-A

⑧ Eliminate Type I Preformed Joint at end bent backwall and at face of wingwalls when gutters used with Type A Approach Slabs. Poured joint sealer is required, however backer rod shall be eliminated.

① Construct gutter curb with height-transition as shown if drop inlet is not placed at end of gutter.
 Construct gutter curb full height (no height-transition) if drop inlet is placed at end of gutter. Curb height transition placed on drop inlet. See drop inlet details.



SECTION B-B
N.T.S.



SECTION C-C
N.T.S.

Note:
 All longitudinal lines within the limits of horizontal curves shall be on curves concentric to C.L. Bridge. Adjustment to longitudinal bar lengths may be required. Transverse reinforcing shall be placed on radial lines to C.L. Bridge.

△ Revised to add "W" = 2'-0"; By LJB
 Checked By: K.W.Y. 9/2/15

BAR LIST FOR ONE TYPE A GUTTER

Mark	No. Req'd. for Width "W"					Length
	2'-0"	3'-0"	4'-0"	6'-0"	8'-0"	
G401	④	④	④	④	④	"W" - 4"
G402 - G406	1 each	1 each	1 each	1 each	1 each	"W" - 3" to "W" + 2"
G407	1	1	1	1	1	"W" + 3"
G408	15	15	15	15	15	"W" + 10"
G501	4	6	8	12	16	29'-8"
G502	1	1	1	1	1	(35'-5") - "L"
G503	1	1	1	1	1	30'-8" - "L"
G409	⑥	⑥	⑥	⑥	⑥	⑤
G410	1	1	1	1	1	"W" + 3"
G411	16	16	16	16	16	"W" + 10"
G504	1	1	1	1	1	⑤
G505	1	1	1	1	1	⑤
G506 - G5XX ⑦	1 each	1 each	1 each	1 each	1 each	⑤

④ 0 for "L" = 10'
 1 for "L" = 11'
 2 for "L" = 12'
 2 for "L" = 13'
 ⑦ G509 for "W" = 2' △
 G511 for "W" = 3'
 G513 for "W" = 4'
 G517 for "W" = 6'
 G521 for "W" = 8'

⑤ Bar Lengths vary with Skew and Wingwall Length.
 ⑥ No. Req'd. varies with Skew and Wingwall length.

QUANTITIES FOR ONE SQUARE APPROACH GUTTER (FOR INFORMATION ONLY)

"W" Width (ft.)	Reinforcing Steel (Lbs.)	Concrete (Cu. Yds.)
2	210	2.55
3	285	3.40
4	360	4.25
6	515	5.90
8	665	7.55

Quantities are based on "L" = 10'-0".

GENERAL NOTES

All concrete shall be Class S or Class S(AE) or mixture used for Portland Cement Concrete Pavement and shall be poured in the dry.
 All reinforcing steel shall be Grade 60 (yield strength = 60,000 psi) conforming to AASHTO M 31 or M 322, Type A, with mill test reports.
 Approach Gutters will be measured and paid for in accordance with Section 504.





STANDARD DETAILS FOR TYPE A APPROACH GUTTERS

ARKANSAS STATE HIGHWAY COMMISSION

LITTLE ROCK, ARK.

DRAWN BY: A.M.S. DATE: 2/27/2014 FILENAME: b55030a.dgn
 CHECKED BY: K.W.Y. DATE: 2/27/2014 SCALE: 3/8" = 1'-0"
 DESIGNED BY: STD. DATE: or As Shown


DRAWING NO. 55030A



R.C. CURTAIN WALL DIMENSIONS & QUANTITIES

PIPE DIA.	H ₁	L ₁	L	L (DBL.) 2	SINGLE R.C.P.C.		DOUBLE R.C.P.C.	
					CONC.	REINF. STEEL	CONC.	REINF. STEEL
					CU. YDS.	LBS.	CU. YDS.	LBS.
18"	1 1/2"	3'-5"	8'-0"	6'-3"	0.31	27.7	0.45	39.5
24"	1'-0 1/2"	4'-6"	9'-6"	7'-6"	0.37	33.4	0.53	48.0
30"	1'-3 1/2"	5'-7"	11'-0"	9'-0"	0.45	39.0	0.67	59.0
36"	1'-7"	6'-8"	13'-0"	10'-6"	0.58	52.6	0.83	73.9
42"	2'-1 1/2"	7'-3"	15'-6"	12'-0"	0.82	77.1	1.10	100.7
48"	2'-5"	7'-10"	17'-0"	13'-0"	0.98	94.9	1.27	120.4
54"	2'-9 1/2"	8'-5"	18'-6"	14'-0"	1.16	115.8	1.47	143.7
60"	3'-4"	9'-0"	20'-6"	15'-6"	1.47	149.7	1.84	180.3
72"	4'-5"	10'-2"	25'-6"	18'-6"	2.31	232.6	2.73	271.0

NOTE: QUANTITIES SHOWN ARE FOR ONE (1) CURTAIN WALL.



REINFORCING STEEL SCHEDULE

PIPE DIA.	SINGLE R.C. PIPE CULVERT								DOUBLE R.C. PIPE CULVERT									
	H401		H402		V401		V402		H401		H402		V401		V402			
	L	NO.	L	NO.	L	NO.	L	NO.	L	NO.	L	NO.	L	NO.	L	NO.		
18"	7'-8"	2	1'-11 1/2"	4	1'-7 1/2"	8	8"	8	12'-2"	2	1'-11 1/2"	4	8"	2	1'-7 1/2"	10	8"	14
24"	9'-2"	2	2'-2"	4	1'-8 1/2"	10	8"	9	14'-8"	2	2'-2"	4	8"	2	1'-8 1/2"	12	8"	18
30"	10'-8"	2	2'-4 1/2"	4	1'-11 1/2"	10	8"	12	17'-8"	2	2'-4 1/2"	4	8"	2	1'-11 1/2"	14	8"	22
36"	12'-8"	2	2'-10"	6	2'-3"	12	8"	14	20'-8"	2	2'-10"	6	8"	3	2'-3"	14	8"	28
42"	15'-2"	2	3'-9 1/2"	8	2'-9 1/2"	16	8"	15	23'-8"	2	3'-9 1/2"	8	8"	4	2'-9 1/2"	18	8"	30
48"	16'-8"	2	4'-3"	10	3'-1"	18	8"	16	25'-8"	2	4'-3"	10	8"	5	3'-1"	20	8"	32
54"	18'-2"	2	4'-8 1/2"	12	3'-5 1/2"	20	8"	17	27'-8"	2	4'-8 1/2"	12	8"	6	3'-5 1/2"	22	8"	34
60"	20'-2"	2	5'-5"	14	4'-0"	24	8"	18	30'-8"	2	5'-5"	14	8"	7	4'-0"	26	8"	36
72"	25'-2"	2	7'-4"	18	5'-1"	30	8"	20	36'-8"	2	7'-4"	18	8"	9	5'-1"	33	8"	40


ALL REINFORCING STEEL #4 BARS @ 6" O.C.

SOLID SODDING


PIPE DIA.	SINGLE R.C.P.C.						DOUBLE R.C.P.C.					
	3:1		4:1		6:1		3:1		4:1		6:1	
	SO. YDS.						SO. YDS.					
18"	5	8	12	16	20	6	8	11	13	16	20	
24"	8	12	16	20	24	8	11	14	17	21	26	
30"	13	18	23	28	33	14	18	23	28	33	39	
36"	17	23	29	35	41	18	23	29	35	41	48	
42"	21	28	35	42	49	22	28	35	42	49	57	
48"	25	33	41	49	57	26	33	41	49	57	66	
54"	29	38	47	56	65	31	38	47	56	65	75	
60"	33	43	53	63	73	36	43	53	63	73	84	
72"	45	57	70	84	99	48	57	69	83	97	111	

NOTE: QUANTITIES SHOWN ABOVE ARE FOR ONE (1) END OF F.E.S.

- GENERAL NOTES**
- A CAST-IN-PLACE OR PRECAST CURTAIN WALL MAY BE USED. PAYMENT FOR THE CURTAIN WALL SHALL BE CONSIDERED TO BE INCLUDED IN THE UNIT PRICE BID EACH FOR FLARED END SECTIONS OF THE SEVERAL SIZES, WHICH PRICE SHALL BE FULL COMPENSATION FOR FURNISHING ALL MATERIALS INCLUDING REINFORCING STEEL AND CONCRETE; FOR FORMS, MIXING AND PLACING; FOR EXCAVATION AND BACKFILL; AND FOR ALL LABOR, TOOLS, EQUIPMENT AND INCIDENTALS NECESSARY TO COMPLETE THE WORK.
 - ALL EXPOSED EDGES SHALL BE CHAMFERED 3/4".
 - CONCRETE FOR CURTAIN WALL SHALL MEET THE REQUIREMENTS FOR CLASS A OR S CONCRETE AS PROVIDED IN SECTION 802 OF THE STANDARD SPECIFICATIONS OR FOR PAVING CONCRETE AS PROVIDED IN SECTION 501 OF THE STANDARD SPECIFICATIONS.
 - WELDED WIRE MESH 3 x 3 W/10 x W/10 MAY BE USED IN LIEU OF REINFORCING BARS.




10-18-96 ADDED NOTE TO SOLID SODDING		ARKANSAS STATE HIGHWAY COMMISSION
10-12-95 CORRECTED SPELLING		
8-3-94 ADDED GENERAL NOTE NO. 4		
8-15-91 REV. CURTAIN WALL QUANT. STEEL SCH. & SOLID SOD QUANT.		FLARED END SECTION
3-2-81 ALLOW PRECAST IN 2 OR MORE PIECES CHAMFER EDGES		
5-15-80 ADDED PRECAST WALL & GENERAL NOTES		
10-2-72 REVISED AND REDRAWN		STANDARD DRAWING FES-1
DATE	REVISION	FILMED



END SECTION FOR REINFORCED CONCRETE PIPE CULVERTS

TABLE OF DIMENSIONS

DIA.	WALL	A	B	C	D	E	S	DIA. + 1"	P	R-1	R-2	G-T	WT.	h
18"	2 1/2"	9"	2'-3"	3'-10"	6'-1"	3'-0"	3#1	19"	29"	15 1/2"	12"	2"	1000	1'-0 1/2"
24"	3"	9 1/2"	3'-7 1/2"	2'-6"	6'-1 1/2"	4'-0"	3#1	25"	33 3/4"	16 3/4"	14"	2 1/2"	1600	1'-1 1/2"
30"	3 1/2"	1'-0"	4'-6"	1'-7 3/4"	6'-1 3/4"	5'-0"	3#1	31"	37"	18 1/2"	15"	3 1/4"	1940	1'-4 3/4"
36"	4"	1'-3"	5'-3"	2'-10 3/4"	8'-1 1/4"	6'-0"	3#1	37"	47 1/4"	24 3/4"	20"	3 1/2"	4100	1'-8"
42"	4 1/2"	1'-9"	5'-3"	2'-11"	8'-2"	6'-6"	3#1	43"	53 3/4"	27 1/2"	22"	3 1/2"	5380	2'-2 1/2"
48"	5"	2'-0"	6'-0"	2'-2"	8'-2"	7'-0"	3#1	49"	56 1/2"	28 1/2"	22"	3 1/2"	6550	2'-6"
54"	5 1/2"	2'-4"	6'-6"	1'-10"	8'-4"	7'-6"	3#1	55"	65 1/2"	33 1/4"	24"	4"	8750	2'-10 1/2"
60"	6"	3'-10"	6'-6"	1'-10"	8'-4"	8'-0"	3#1	61"	72 1/2"	36 1/4"	24"	4"	9270	3'-5"
72"	7"	3'-10"	6'-6"	1'-10"	8'-4"	9'-0"	3#1	73"	77 3/4"	38 3/4"	24"	5"	13250	4'-6"




NOTE: TONGUE END ON UPSTREAM SECTION
GROOVE END ON DOWNSTREAM SECTION


ARCH PIPE

EQUIV. DIA.	SPAN		RISE		W	A	B	C	D	E	P	R2	G-T	S
	AASHTO M 206	AHD NOMINAL	AASHTO M 206	AHD NOMINAL										
15	18	18	11	11	2"	4"	2'-0"	4'-0"	6'-0"	3'-0"	29"	12"	1 1/2"	2 1/2#1
18	22	22	13 1/2	14	2 1/2"	5"	2'-0"	4'-1"	6'-1"	3'-6"	32 1/4"	13"	2 1/2"	2 1/2#1
21	26	26	15 1/2	16	2 3/4"	7"	2'-3"	3'-10"	6'-1"	4'-0"	34 1/4"	14"	2 1/2"	2 1/2#1
24	28 1/2	29	18	18	3"	9"	2'-3"	3'-10"	6'-1"	5'-0"	36 3/4"	15"	2 1/2"	2 1/2#1
30	36 1/4	36	22 1/2	23	3 1/2"	10"	3'-1"	3'-0 1/2"	6'-1 1/2"	6'-0"	47 3/4"	20"	3"	2 1/2#1
36	43 3/4	44	26 3/4	27	4"	10 1/2"	4'-0"	2'-1 1/2"	6'-1 1/2"	6'-6"	54 3/4"	22"	3 1/2"	2 1/2#1
42	51 1/8	51	31 3/4	31	4 1/2"	11 1/2"	4'-7"	1'-10 1/4"	6'-5 1/4"	7'-2"	59 1/2"	23"	3 3/4"	2 1/2#1
48	58 1/2	59	36	36	5"	1'-3"	5'-3"	2'-10 1/4"	8'-1 1/4"	7'-10"	70 3/4"	24"	4 1/4"	2 1/2#1
54	65	65	40	40	5 1/2"	1'-7"	5'-3"	2'-11"	8'-2"	8'-6"	72 1/4"	24"	4 3/4"	2 1/2#1
60	73	73	45	45	6"	1'-10"	5'-6"	2'-8"	8'-2"	9'-0"	77 3/4"	24"	5"	2 1/2#1


* THE MEASURED SPAN AND RISE SHALL NOT VARY MORE THAN ± 2 PER CENT FROM THE VALUES SPECIFIED BY AASHTO M 206.



END VIEW CONCRETE ARCH PIPE




PLAN



CIRCULAR PIPE

CIRCULAR PIPE


D. DIA.	GAUGE	A 1" ±	B. MAX. 1" ±	H 1" ±	L 1/2" ±	W 2" ±	S
12	16	6	6	6	21	24	2 1/2#1
15	16	7	8	6	26	30	2 1/2#1
18	16	8	10	6	31	36	2 1/2#1
21	16	9	12	6	36	42	2 1/2#1
24	16	10	13	6	41	48	2 1/2#1
30	14	12	16	8	51	60	2 1/2#1
36	14	14	19	9	60	72	2 1/2#1
42	12	16	22	11	69	84	2 1/2#1
48	12	18	27	12	78	90	2 1/2#1
54	12	18	30	12	84	102	2#1
60	12	18	33	12	87	114	1 3/4#1
66	12	18	36	12	87	120	1 1/2#1
72	12	18	39	12	87	126	1 1/3#1



C.M. ARCH PIPE

C.M. ARCH PIPE


EQUIV. DIA.	SPAN	RISE	A 1" ±	B. MAX. 1" ±	H 1" ±	L 1/2" ±	W 2" ±	S	GAUGE
15"	17	13	7	9	6	19	30	2 1/2#1	16
18"	21	15	7	10	6	23	36	2 1/2#1	16
21"	24	18	8	12	6	28	42	2 1/2#1	16
24"	28	20	9	14	6	32	48	2 1/2#1	16
30"	35	24	10	16	6	39	60	2 1/2#1	14
36"	42	29	12	18	8	46	75	2 1/2#1	14
42"	49	33	13	21	9	53	85	2 1/2#1	12
48"	57	38	18	26	12	63	90	2 1/2#1	12
54"	64	43	18	30	12	70	102	2 1/2#1	12
60"	71	47	18	33	12	77	114	2 1/4#1	12




SECTION A-A

NOTE: ALTERNATE CONNECTIONS TO THE PIPE CULVERTS, IN ACCORDANCE WITH MANUFACTURER'S STANDARD PRACTICES, MAY BE MADE SUBJECT TO THE APPROVAL OF THE ENGINEER.

END SECTIONS FOR CORRUGATED METAL PIPE CULVERTS




MULTIPLE R.C. PIPE CULVERTS




MULTIPLE C.M. PIPE CULVERTS

10-18-96	REVISED ASTM REF. TO AASHTO		ARKANSAS STATE HIGHWAY COMMISSION
5-15-80	REVISED DISTANCE BETWEEN MULTIPLE R.C.P. F.E.S.	664-5-15-80	
7-14-78	C.M. ARCH SIZES TO CONFORM WITH AASHTO SIZES	752-7-14-78	
8-22-75	ADDED MULTIPLE PIPE CULVERTS	517-8-22-75	
12-5-74	REMOVED NOTE RE REINF. FOR R.C. F.E.S.	500-12-5-74	
5-24-73	CMP END SECTION, SHOW PIPE PAY LENGTH	627-5-24-73	
10-2-72	REVISED AND REDRAWN	760-10-2-72	
DIA 11	REVISION	FILED	

FLARED END SECTION
STANDARD DRAWING FES-2




WASHER PLATE




BASE PLATE

Note: Bolts, nuts, washers and plates shall be galvanized in accordance with Section 807 of the Standard Specifications.



FOR DESIGN SPEEDS OF 50 MPH OR LESS

ALIGN FACE OF GUARDRAIL WITH FACE OF CURB.





FOR DESIGN SPEEDS OF 55 MPH OR MORE

PLACE GUARDRAIL POSTS AGAINST BACK OF CURB.


DETAIL OF GUARDRAIL PLACEMENT BEHIND CURB (W-BEAM)

FOR DESIGN SPEEDS OF 50 MPH OR LESS ALL CURB FACES, AS SHOWN ON STD. DRWG. CG-1, MAY BE USED. FOR DESIGN SPEEDS OF 55 MPH OR MORE TYPE "E" CURB FACE SHALL BE USED.




Plan View Steel Posts

Either hole configuration acceptable



Plan View Wood Posts

Either hole configuration acceptable



Notes: For overlying soil depths (A) ranging from 0 to 18", the depth of required drilling (B) is equal to 24".


Zone A: Backfill according to Section 617.03(a).

Zone B: Backfill hole in 6" lifts with material meeting the requirements of Section 802.02(c) - Alternate gradation. Compact to 95% maximum dry density per ASTM D-698.


Notes: For overlying soil depths (A) ranging from 18" to 44", the depth of required drilling (B) is equal to either 12" or 44" minus the depth of soil whichever is less.

Zone A & B: Backfill according to Section 617.03(a).


DETAIL OF POST PLACEMENT IN SOLID ROCK (W-BEAM)



SECTION A-A



DETAIL OF CONNECTION



PLAN LAYOUT OF TYPE A GUARDRAIL AT LOW-FILL CULVERTS

NOTE: THIS DETAIL IS TO BE USED ONLY WHEN THE COVER OVER THE CULVERT DOES NOT PERMIT FULL EMBEDMENT OF GUARDRAIL POSTS AS SHOWN ON STD. DRWG. GR-6.




NOTE: WHEN POSSIBLE, POSTS SHALL BE SPACED TO AVOID INTERIOR AND EXTERIOR WALLS OF CULVERT. WHEN THIS IS NOT POSSIBLE AND POSTS MUST BE INSTALLED OVER AN INTERIOR OR EXTERIOR WALL, ANCHOR BOLTS SHALL BE INSTALLED BY DRILLING AND EPOXYING USING METHODS AND MATERIALS APPROVED BY THE ENGINEER.


DATE	REVISION	FILMED
11-07-19	RENUMBERED, RENAMED, REVISED REFERENCE	
11-16-17	REVISED GUARDRAIL HEIGHT	
07-14-10	RAISED HEIGHT OF GUARDRAIL 1"	
04-12-07	REVISED DETAIL OF GUARDRAIL PLACEMENT BEHIND CURB	
11-10-05	ADDED GUARDRAIL PLACEMENT BEHIND CURB; REVISED DETAIL OF CONNECTION	
11-18-04	REVISED POST PLACEMENT IN ROCK & CULVERT CONNECTION DETAILS. ADDED DETAIL FOR GUARDRAIL PLACEMENT AT LOW-FILL CULVERTS	
03-30-00	REMOVED CONCRETE INSERT ANCHOR	
08-12-98	CHANGED STEEL SPACER BLOCK TO WOOD BLOCKOUT, ADDED DET. OF GUARDRAIL CONNECTION TO R.C. BOX CULV'T., DELETED DET. OF STEEL LINE POST CONN. & ADDED DET. OF GUARDRAIL PLACE. BEHIND CURB & DET. OF POSTPLACE. IN SOLID ROCK	
04-03-96	PLACED ARROWS AT CUT STEEL WASHERS	4-3-96
10-18-96	REV. ASTM REF. TO AASHTO	
11-22-95	ADDED OPTIONAL HOLES	
06-02-94	REVISED ALTERNATE POST SIZE	
08-05-93	REVISED STEEL POST SIZE	
10-01-92	REDRAWN & REVISED	10-1-92
08-02-90	DEL. WASHER ON ANCHOR ASSEMBLY	8-2-90
07-15-88	CONFORMED TO 1988 SPECS	
03-04-88	REVISED ANCHOR NOTE	
10-30-87	REVISED ANCHOR ASSEMBLY	712-10-30-87
10-30-87	REVISED PLACEMENT BEHIND CURB	547-10-30-87
10-09-87	REDRAWN & REVISED	803-10-9-87

ARKANSAS STATE HIGHWAY COMMISSION


GUARDRAIL DETAILS

STANDARD DRAWING GR-7






NOTE: NORMAL SECTION TO BE WIDENED APPROX. 5'-6" EACH SIDE TO SUPPORT GUARDRAIL.




SECTION A-A




SECTION B-B

DETAILS OF WIDENING FOR GUARDRAIL




SECTION ON TANGENT




SECTION ON CURVE

DETAILS SHOWING POSITION OF GUARDRAIL ON HIGHWAY




METHOD OF INSTALLATION OF GUARDRAIL AT FIXED OBSTACLE


			ARKANSAS STATE HIGHWAY COMMISSION
			GUARDRAIL DETAILS
			STANDARD DRAWING GR-9
11-07-19	RENUMBERED AND RENAMED		
4-17-08	MINOR REVISION		
11-10-05	DRAWN		
DATE	REVISION	DATE	FILM




THRIE BEAM RAIL WITH STEEL TUBING BLOCKOUT AND STEEL POST
POSTS 1-7




W-BEAM TO THRIE BEAM TRANSITION RAIL WITH WOOD OR PLASTIC BLOCKOUT AND STEEL POST
POST 8



THRIE BEAM RAIL WITH WOOD OR PLASTIC BLOCKOUTS & WOOD POSTS
POSTS 1-6



THRIE BEAM RAIL WITH WOOD OR PLASTIC BLOCKOUT & WOOD POST
POST 7




W-BEAM TO THRIE BEAM TRANSITION RAIL WITH WOOD OR PLASTIC BLOCKOUT & WOOD POST
POST 8

GENERAL NOTES:


RAIL POSTS SHALL BE SET PERPENDICULAR TO THE ROADWAY PROFILE GRADE AND VERTICALLY IN CROSS SECTION.

WOOD POSTS & WOOD BLOCKS SHALL BE EITHER DENSE NO. 1 STRUCTURAL OR BETTER 9.7f (1400 f) OR NO. 11350 f SOUTHERN PINE.


			ARKANSAS STATE HIGHWAY COMMISSION
			GUARDRAIL DETAILS
			STANDARD DRAWING GR-II
11-16-17	REVISED GUARDRAIL HEIGHT, CHANGED STD. DWG. NUMBER FROM GR-10A TO GR-II		
07-14-10	REVISED POST 8 DIMENSIONS		
11-29-07	ADDED PLASTIC BLOCKOUTS		
08-22-02	REVISED LIP CURB NOTE		
03-30-00	DRAWN & ISSUED		
DATE	REVISION	FILMED	



ELEVATION



PLAN



PLAN

- (1) VERIFY BOLT SPACING FROM RAIL TRANSITION PRODUCER.
- (2) REFER TO APPROACH GUTTER DETAILS.
- (3) LENGTH OF BLOCKOUT ON POST 8 TO BE MODIFIED TO FIT RAIL WIDTH.

THRIE BEAM GUARDRAIL CONNECTION AT BRIDGE ENDS

GENERAL NOTES:

THE THRIE BEAM RAIL, SPECIAL END SHOE, AND THE TRANSITION SECTION SHALL BE MADE OF STEEL AND SHALL BE 12 GAGE. ZINC COATING SHALL BE TYPE I.

RAIL POSTS SHALL BE SET PERPENDICULAR TO THE ROADWAY PROFILE GRADE AND VERTICALLY IN CROSS SECTION.

ALL BOLTS SHALL BE SUFFICIENT LENGTH TO EXTEND THROUGH THE FULL THICKNESS OF THE NUT AND NO MORE THAN 3/4" BEYOND IT.

ALL LAP SPLICES, INCLUDING SPECIAL END SHOES, SHALL BE MADE IN THE DIRECTION SHOWN ON STANDARD DRAWINGS GR-8 & GR-13.

REFER TO STD. DRWG. GR-11 FOR POST DETAILS.


USE THRIE BEAM GUARDRAIL COMPONENTS OF SAME MATERIAL FOR ENTIRE JOB.

THRIE BEAM POSTS SHALL BE SAME MATERIAL AS W-BEAM POSTS FOR ENTIRE JOB.


POSTS SHALL BE PLACED AT THE MID-SPAN OF THE W-BEAM.

WOOD POSTS & WOOD BLOCKS SHALL BE EITHER DENSE NO. 1 STRUCTURAL OR BETTER 9.7f (400 f) OR NO. 1 1350 f SOUTHERN PINE.


			ARKANSAS STATE HIGHWAY COMMISSION
			GUARDRAIL DETAILS
			STANDARD DRAWING GR-12
11-07-19	RENAMED & REVISED REFERENCES		
11-16-17	RE-DRAWN FROM STD. DRWG. GR-10 & ISSUED		
DATE	REVISION	FILMED	




SHELF



PLATFORM




SINGLE INSTALLATION




BRACKET

GENERAL NOTES


1. MAILBOX POSTS MAY BE WOOD OR METAL. WOOD POSTS SHALL BE PRESSURE TREATED FOR GROUND CONTACT IN ACCORDANCE WITH SECTION 637.02 OF THE STANDARD SPECIFICATIONS.
2. ANTI-TWIST PLATES SHALL BE USED ONLY ON METAL POSTS.
3. MAILBOX SHELF, BRACKET & PLATFORM SHALL BE GALVANIZED OR PAINTED STEEL, HOWEVER TREATED WOOD MAY BE USED WITH WOODEN POSTS. THE WOODEN SHELF, BRACKET & PLATFORM SHALL BE A MINIMUM OF 3/4" THICK AND SHALL BE ASSEMBLED WITH BOLTS OF THE APPROPRIATE LENGTH WITH SIX 8 X 3/4" FLATHEAD WOOD SCREWS USED TO ATTACH THE MAILBOX TO THE PLATFORM.
4. THE MAILBOX SHELF AND PLATFORM THAT IS SHOWN IS FOR STANDARD SIZE MAILBOXES. THE SHELF AND PLATFORM SIZE SHALL BE MODIFIED TO FIT MAILBOXES OF A DIFFERENT SIZE.
5. METAL PIPE FOR MAILBOX SUPPORT SHALL BE 2" OUTSIDE DIAMETER STEEL WITH A WALL THICKNESS OF 0.45" AND A WEIGHT OF 2.72 LBS PER FT. OUTSIDE DIAMETER AND WEIGHT SHALL HAVE A TOLERANCE OF +/- 5% ACCORDING TO AASHTO M 181.
6. MAILBOX SUPPORT SYSTEM DIFFERING FROM THOSE SHOWN MAY BE USED, PROVIDED THEY ARE ON THE AHTD QUALIFIED PRODUCTS LIST FOR MAILBOX SUPPORTS.



DOUBLE INSTALLATION




ANTI-TWIST PLATE



CLAMP

SPACER



SPACING FOR MULTIPLE POST INSTALLATION

11-18-04		REVISED NOTES
10-9-03		REVISED NOTE 6
8-22-02		REVISED NOTE 6
10-18-96		CORRECTED AASHTO
10-1-92		CORRECTED SPELLING
9-26-91		NEW PHONE NUMBER
8-15-91		ADDED NOTE
11-30-89		ADJUSTED HEIGHT & ADDED NOTE
2-16-89		DELETED SLOTS FROM SHELF & PLTF
11-17-88	10-1-92	ADJUSTED DIMENSIONS OF STEEL POSTS
7-15-88	20-7-15-88	ISSUED
DATE	FILMED	REVISION

ARKANSAS STATE HIGHWAY COMMISSION

MAILBOX DETAILS

STANDARD DRAWING MB-1

REINFORCED CONCRETE ARCH PIPE DIMENSIONS

EQUIV. DIA.	SPAN		RISE	
	AASHTO M 206	AHTD NOMINAL	AASHTO M 206	AHTD NOMINAL
INCHES	INCHES			
15	18	18	11	11
18	22	22	13½	14
21	26	26	15½	16
24	28½	29	18	18
30	36¼	36	22¼	23
36	43¾	44	26¾	27
42	51½	51	31¾	31
48	58½	59	36	36
54	65	65	40	40
60	73	73	45	45
72	88	88	54	54
84	102	102	62	62
90	115	115	72	72
96	122	122	77½	77
108	138	138	87½	87
120	154	154	96¾	97
132	168¾	169	106½	107

THE MEASURED SPAN AND RISE SHALL NOT VARY MORE THAN ± 2 PERCENT FROM THE VALUES SPECIFIED BY AASHTO M206.

REINFORCED CONCRETE HORIZONTAL ELLIPTICAL PIPE DIMENSIONS

EQUIV. DIA.	AASHTO M 207	
	SPAN	RISE
INCHES	INCHES	
18	23	14
24	30	19
27	34	22
30	38	24
33	42	27
36	45	29
39	49	32
42	53	34
48	60	38
54	68	43
60	76	48
66	83	53
72	91	58
78	98	63
84	106	68

THE MEASURED SPAN AND RISE SHALL NOT VARY MORE THAN ± 2 PERCENT FROM THE VALUES SPECIFIED BY AASHTO M207.

CONSTRUCTION SEQUENCE


1. PLACE STRUCTURAL BEDDING MATERIAL TO GRADE. DO NOT COMPACT.
 2. INSTALL PIPE TO GRADE.
 3. COMPACT STRUCTURAL BEDDING OUTSIDE THE MIDDLE THIRD OF THE PIPE.
 4. PLACE AND COMPACT THE HAUNCH AREA UP TO THE MIDDLE OF THE PIPE.
 5. COMPLETE BACKFILL ACCORDING TO SUBSECTION 606.03.(f)(1).
- NOTE: HAUNCH AND STRUCTURAL BEDDING MATERIAL WILL NOT BE PAID FOR SEPARATELY, BUT COMPENSATION WILL BE CONSIDERED TO BE INCLUDED IN THE PRICE BID PER LINEAR FOOT OF CONCRETE PIPE.

- LEGEND -

- D₁ = NORMAL INSIDE DIAMETER OF PIPE
- D_o = OUTSIDE DIAMETER OF PIPE
- H = FILL COVER HEIGHT OVER PIPE (FEET)
- MIN. = MINIMUM
- UNDISTURBED SOIL

INSTALLATION TYPE	MATERIAL REQUIREMENTS FOR HAUNCH AND STRUCTURAL BEDDING
TYPE 1	AGGREGATE BASE COURSE (CLASS 5 OR CLASS 7)
TYPE 2	SELECTED MATERIALS (CLASS SM-1, SM-2, OR SM-4) OR TYPE 1 INSTALLATION MATERIAL*
TYPE 3**	AASHTO CLASSIFICATION A-1 THRU A-6 SOIL OR TYPE 1 OR 2 INSTALLATION MATERIAL

* SM-3 WILL NOT BE ALLOWED.
** MATERIALS SHALL NOT INCLUDE ORGANIC MATERIALS OR STONES LARGER THAN 3 INCHES.



EMBANKMENT AND TRENCH INSTALLATIONS

1. MATERIAL IN THE HAUNCH AND OUTER STRUCTURAL BEDDING SHALL BE COMPACTED TO 95% OF THE MAXIMUM DENSITY ACCORDING TO THE TYPE OR CLASS OF MATERIAL USED.
2. FOR TRENCHES WITH WALLS OF NATURAL SOIL, THE DENSITY OF THE SOIL IN THE LOWER SIDE ZONE SHALL BE AS FIRM AS THE 95% DENSITY REQUIRED FOR THE HAUNCH. IF THE EXISTING SOIL DOES NOT MEET THIS CRITERIA, IT SHALL BE REMOVED AND RECOMPACTED TO 95% OF THE MAXIMUM DENSITY ACCORDING TO THE TYPE OF MATERIAL USED.
3. FOR EMBANKMENTS, THE MATERIAL IN THE LOWER SIDE ZONE SHALL BE COMPACTED TO 95% OF THE MAXIMUM DENSITY ACCORDING TO THE TYPE OR CLASS OF MATERIAL USED.

GENERAL NOTES

1. CONCRETE PIPE CULVERT CONSTRUCTION SHALL CONFORM TO ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION (CURRENT EDITION), WITH APPLICABLE SUPPLEMENTAL SPECIFICATIONS AND SPECIAL PROVISIONS, UNLESS OTHERWISE NOTED IN THE PLANS, SECTION AND SUBSECTION REFER TO THE STANDARD CONSTRUCTION SPECIFICATIONS.
2. CONCRETE PIPE CULVERT DESIGN SHALL CONFORM TO AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, FIFTH EDITION (2010) WITH 2010 INTERIMS.
3. ALL PIPE SHALL CONFORM TO SECTION 606. CIRCULAR R.C. PIPE CULVERTS SHALL CONFORM TO AASHTO M10, R.C. ARCH PIPE CULVERTS SHALL CONFORM TO AASHTO M206 AND HORIZONTAL ELLIPTICAL PIPE CULVERTS SHALL CONFORM TO AASHTO M207.
4. ALL PIPE SHALL BE PROTECTED DURING CONSTRUCTION BY A COVER SUFFICIENT TO PREVENT DAMAGE FROM PASSAGE OF EQUIPMENT.
5. THE MINIMUM TRENCH WIDTH SHALL BE THE OUTSIDE DIAMETER OF THE PIPE PLUS 24 INCHES. THE MAXIMUM ALLOWABLE TRENCH WIDTH SHALL BE THE MINIMUM WIDTH PRACTICABLE FOR WORKING CONDITIONS.
6. MULTIPLE PIPE CULVERTS SHALL BE INSTALLED WITH A MINIMUM CLEARANCE OF 24 INCHES BETWEEN STRINGS OF PIPE. REFER TO STD. DWG. FES-2 FOR MINIMUM CLEARANCE WHERE FLARED END SECTIONS ARE USED.
7. IMPERVIOUS MATERIAL SHOULD BE PLACED AS DIRECTED BY THE ENGINEER AT THE ENDS OF THE CULVERT TO PREVENT LOSS OF STRUCTURAL BEDDING WHEN PERVIOUS MATERIAL IS USED FOR STRUCTURAL BEDDING AND/OR BACKFILL.
8. NOT MORE THAN ONE LIFTING HOLE MAY BE PROVIDED IN CONCRETE PIPE TO FACILITATE HANDLING. HOLE MAY BE CAST IN PLACE, CUT INTO THE FRESH CONCRETE AFTER FORMS ARE REMOVED, OR DRILLED. THE HOLE SHALL NOT BE MORE THAN TWO INCHES IN DIAMETER OR TWO INCHES SQUARE. CUTTING OR DISPLACEMENT OF REINFORCEMENT WILL NOT BE PERMITTED. SPALLED AREAS AROUND THE HOLE SHALL BE REPAIRED IN A WORKMANLIKE MANNER. LIFTING HOLE SHALL BE FILLED WITH MORTAR, CONCRETE, OR OTHER METHOD AS APPROVED BY THE ENGINEER.
9. WHEN DIRECTED BY THE ENGINEER, UNSUITABLE MATERIAL THAT IS ENCOUNTERED AT THE BOTTOM OF THE EXCAVATED TRENCH (BELOW THE AREA IDENTIFIED AS "STRUCTURAL BEDDING" ABOVE) WILL BE EXCAVATED AND REPLACED WITH SELECTED PIPE BEDDING. THE QUANTITY OF MATERIAL REQUIRED TO BACKFILL THE UNDERCUT AREA UP TO THE SELECTED PIPE BEDDING PAY LIMIT DESIGNATED ABOVE WILL BE MEASURED AND PAID FOR AS "SELECTED PIPE BEDDING."
10. WHEN THE EXISTING MATERIAL EXCAVATED FOR THE PIPE TRENCH IS DETERMINED BY THE ENGINEER TO BE UNSUITABLE FOR BACKFILLING THE PIPE (ABOVE THE AREA IDENTIFIED ABOVE AS THE HAUNCH), BORROW MATERIAL OR MATERIAL FROM THE ROADWAY EXCAVATION WILL BE USED TO BACKFILL THE PIPE. IF SUITABLE MATERIAL IS NOT AVAILABLE, THE ENGINEER MAY AUTHORIZE THE USE OF "SELECTED PIPE BACKFILL."

MINIMUM HEIGHT OF FILL "H" OVER CIRCULAR R.C. PIPE CULVERTS

INSTALLATION TYPE	CLASS OF PIPE			
	CLASS III		CLASS IV	CLASS V
PIPE ID (IN.)	FEET			
12-15	2	2.5	2	1
18-24	2.5	3	2	1
27-33	3	4	2	1
36-42	3.5	5	2	1
48	4.5	5.5	2	1
54-60	5	7	2	1
66-78	6	8	2	1
84-108	7.5	8	2	1

NOTE: FOR MINIMUM COVER VALUES, "H" SHALL INCLUDE A MINIMUM OF 12" OF PAVEMENT AND/OR BASE.

MAXIMUM HEIGHT OF FILL "H" OVER CIRCULAR R.C. PIPE CULVERTS

INSTALLATION TYPE	CLASS OF PIPE		
	CLASS III	CLASS IV	CLASS V
TYPE 1	21	32	50
TYPE 2	16	25	39
TYPE 3	12	20	30

NOTE: IF FILL HEIGHT EXCEEDS 50 FEET, A SPECIAL DESIGN CONCRETE PIPE WILL BE REQUIRED USING TYPE 1 INSTALLATION.

MINIMUM HEIGHT OF FILL "H" OVER R.C. ARCH & HORIZONTAL ELLIPTICAL PIPE CULVERTS

INSTALLATION TYPE	CLASS OF PIPE	
	CLASS III	CLASS IV
TYPE 2 OR TYPE 3	2.5	1.5

NOTE: TYPE 1 INSTALLATION WILL NOT BE ALLOWED FOR ARCH & HORIZONTAL ELLIPTICAL PIPE CULVERTS.

NOTE: FOR MINIMUM COVER VALUES, "H" SHALL INCLUDE A MINIMUM OF 12" OF PAVEMENT AND/OR BASE.

MAXIMUM HEIGHT OF FILL "H" OVER R.C. ARCH & HORIZONTAL ELLIPTICAL PIPE CULVERTS

INSTALLATION TYPE	CLASS OF PIPE	
	CLASS III	CLASS IV
TYPE 2	13	21
TYPE 3	10	16

NOTE: TYPE 1 INSTALLATION WILL NOT BE ALLOWED FOR ARCH & HORIZONTAL ELLIPTICAL PIPE CULVERTS.

DATE	REVISION	DATE FILMED
2-27-14	REVISED GENERAL NOTE 1.	
12-15-11	REVISED FOR LRFD DESIGN SPECIFICATIONS	
5-18-00	REVISED TYPE 3 BEDDING & ADDED NOTE	
3-30-00	REVISED INSTALLATIONS	
11-06-97	ISSUED	

ARKANSAS STATE HIGHWAY COMMISSION

CONCRETE PIPE CULVERT FILL HEIGHTS & BEDDING

STANDARD DRAWING PCC-1



INSTALLATION TYPE	•• MATERIAL REQUIREMENTS FOR STRUCTURAL BACKFILL AND STRUCTURAL BEDDING
TYPE 2	•SELECTED MATERIALS (CLASS SM-1, SM-2 OR SM-4)

- AGGREGATE BASE COURSE (CLASS 4, 5, 6, OR 7) MAY BE USED IN LIEU OF SELECTED MATERIAL.
SM3 WILL NOT BE ALLOWED.
 - STRUCTURAL BEDDING MATERIAL SHALL HAVE A MAXIMUM PARTICLE SIZE OF 1/2 INCH. STRUCTURAL BACKFILL MATERIAL SHALL BE FREE OF ORGANIC MATERIAL, STONES LARGER THAN 1.50 INCH IN GREATEST DIMENSION, OR FROZEN LUMPS.
- STRUCTURAL BACKFILL AND STRUCTURAL BEDDING MATERIAL WILL NOT BE PAID FOR SEPARATELY, BUT COMPENSATION WILL BE CONSIDERED TO BE INCLUDED IN THE PRICE BID PER LINEAR FOOT OF HDPE PIPE.

MINIMUM TRENCH WIDTH BASED ON FILL HEIGHT "H"

PIPE DIAMETER	TRENCH WIDTH (FEET)	
	"H" < 10'-0"	"H" > OR = 10'-0"
18"	4'-6"	4'-6"
24"	5'-0"	6'-0"
30"	5'-6"	7'-6"
36"	6'-0"	9'-0"
42"	7'-0"	10'-6"
48"	8'-0"	12'-0"

NOTE:
18" MIN. (18" - 30" DIAMETERS)
24" MIN. (36" - 48" DIAMETERS)
MINIMUM COVER VALUES, "H" SHALL INCLUDE A MINIMUM 12" OF PAVEMENT AND/OR BASE.


MULTIPLE INSTALLATION OF HIGH DENSITY POLYETHYLENE PIPES

PIPE DIAMETER	CLEAR DISTANCE BETWEEN PIPES
18"	1'-6"
24"	2'-0"
30"	2'-6"
36"	3'-0"
42"	3'-6"
48"	4'-0"

MINIMUM COVER FOR CONSTRUCTION LOADS

PIPE DIAMETER	MIN. COVER (FEET) FOR INDICATED CONSTRUCTION LOADS			
	18.0-50.0 (KIPS)	50.0-75.0 (KIPS)	75.0-110.0 (KIPS)	110.0-175.0 (KIPS)
36" OR LESS	2'-0"	2'-6"	3'-0"	3'-0"
42" OR GREATER	3'-0"	3'-0"	3'-6"	4'-0"

MINIMUM COVER SHALL BE MEASURED FROM TOP OF PIPE TO TOP OF THE MAINTAINED CONSTRUCTION ROADWAY SURFACE. THE SURFACE SHALL BE MAINTAINED.



TYPE 2 EMBANKMENT AND TRENCH INSTALLATIONS

- STRUCTURAL BACKFILL, EMBANKMENT, AND OUTER STRUCTURAL BEDDING MATERIAL SHALL BE COMPACTED TO 95% OF THE MAXIMUM DENSITY ACCORDING TO THE TYPE OR CLASS OF MATERIAL USED.

CONSTRUCTION SEQUENCE

- PLACE STRUCTURAL BEDDING MATERIAL TO GRADE. DO NOT COMPACT.
- INSTALL PIPE TO GRADE.
- COMPACT STRUCTURAL BEDDING OUTSIDE THE MIDDLE THIRD OF THE PIPE.
- THE STRUCTURAL BACKFILL SHALL BE PLACED AND COMPACTED IN LAYERS NOT EXCEEDING 8". THE LAYERS SHALL BE BROUGHT UP EVENLY AND SIMULTANEOUSLY TO THE ELEVATION OF THE MINIMUM COVER.
- PIPE INSTALLATION MAY REQUIRE THE USE OF RESTRAINTS, WEIGHTING OR OTHER APPROVED METHODS IN ORDER TO HELP MAINTAIN GRADE AND ALIGNMENT.

- LEGEND -

H = FILL HEIGHT (FT.)
D_o = OUTSIDE DIAMETER OF PIPE
MAX. = MAXIMUM
MIN. = MINIMUM

==== = STRUCTURAL BACKFILL MATERIAL
===== = UNDISTURBED SOIL

GENERAL NOTES

- PIPE SHALL CONFORM TO AASHTO M294, TYPE S. INSTALLATION SHALL CONFORM TO JOB SPECIAL PROVISION "PLASTIC PIPE" AND SECTION 606 OF THE STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION (CURRENT EDITION).
- PLASTIC PIPE CULVERT DESIGN SHALL CONFORM TO AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, FIFTH EDITION (2010) WITH 2010 INTERIMS.
- THE MAXIMUM ALLOWABLE TRENCH WIDTH SHALL BE THE MINIMUM WIDTH PLUS A SUFFICIENT WIDTH TO ENSURE WORKING ROOM TO PROPERLY AND SAFELY PLACE AND COMPACT HAUNCHING AND OTHER BACKFILL MATERIAL.
- IMPERVIOUS MATERIAL SHOULD BE PLACED AS DIRECTED BY THE ENGINEER AT THE ENDS OF THE CULVERT TO PREVENT LOSS OF STRUCTURAL BEDDING WHEN PERVIOUS MATERIAL IS USED FOR STRUCTURAL BEDDING AND/OR BACKFILL.
- WHEN DIRECTED BY THE ENGINEER, UNSUITABLE MATERIAL THAT IS ENCOUNTERED AT THE BOTTOM OF THE EXCAVATED TRENCH (BELOW THE AREA IDENTIFIED AS "STRUCTURAL BEDDING" ABOVE) WILL BE EXCAVATED AND REPLACED WITH SELECTED PIPE BEDDING. THE QUANTITY OF MATERIAL REQUIRED TO BACKFILL THE UNDERCUT AREA UP TO THE SELECTED PIPE BEDDING PAY LIMIT DESIGNATED ABOVE WILL BE MEASURED AND PAID FOR AS "SELECTED PIPE BEDDING."
- WHEN THE EXISTING MATERIAL EXCAVATED FOR THE PIPE TRENCH IS DETERMINED BY THE ENGINEER TO BE UNSUITABLE FOR BACKFILLING THE PIPE (ABOVE THE AREA IDENTIFIED ABOVE AS STRUCTURAL BACKFILL), BORROW MATERIAL OR MATERIAL FROM THE ROADWAY EXCAVATION WILL BE USED TO BACKFILL THE PIPE. IF SUITABLE MATERIAL IS NOT AVAILABLE, THE ENGINEER MAY AUTHORIZE THE USE OF "SELECTED PIPE BACKFILL."
- FOR PIPE TYPES THAT ARE NOT SMOOTH ON THE OUTSIDE (CORRUGATED OR PROFILE WALLS), BACKFILL GRADATIONS SHOULD BE SELECTED THAT WILL PERMIT THE FILLING OF THE CORRUGATION OR PROFILE VALLEY.
- HIGH DENSITY POLYETHYLENE PIPES OF DIAMETERS OTHER THAN SHOWN WILL NOT BE ALLOWED.
- JOINTS FOR HDPE PIPE SHALL MEET THE REQUIREMENTS FOR SOIL TIGHTNESS AS SPECIFIED IN AASHTO SECTION 26.4.2.4 AND 30.4.2 "AASHTO LRFD BRIDGE CONSTRUCTION SPECIFICATIONS." JOINTS SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS.

DATE	REVISION	DATE FILMED
2-27-14	REVISED GENERAL NOTE L	
12-15-11	REVISED GENERAL NOTES & MINIMUM COVER NOTE	
11-17-10	ISSUED	

ARKANSAS STATE HIGHWAY COMMISSION	
PLASTIC PIPE CULVERT (HIGH DENSITY POLYETHYLENE)	
STANDARD DRAWING	PCP-1

INSTALLATION TYPE	** MATERIAL REQUIREMENTS FOR STRUCTURAL BACKFILL AND STRUCTURAL BEDDING
TYPE 2	*SELECTED MATERIALS (CLASS SM-1, SM-2, OR SM-4)

- AGGREGATE BASE COURSE (CLASS 4, 5, 6, OR 7) MAY BE USED IN LIEU OF SELECTED MATERIAL. SM3 WILL NOT BE ALLOWED.
 - STRUCTURAL BEDDING MATERIAL SHALL HAVE A MAXIMUM PARTICLE SIZE OF 1/2 INCH. STRUCTURAL BACKFILL MATERIAL SHALL BE FREE OF ORGANIC MATERIAL, STONES LARGER THAN 1.50 INCH IN GREATEST DIMENSION, OR FROZEN LUMPS.
- STRUCTURAL BACKFILL AND STRUCTURAL BEDDING MATERIAL WILL NOT BE PAID FOR SEPARATELY, BUT COMPENSATION WILL BE CONSIDERED TO BE INCLUDED IN THE PRICE BID PER LINEAR FOOT OF PVC PIPE.

MINIMUM TRENCH WIDTH BASED ON FILL HEIGHT "H"

PIPE DIAMETER	TRENCH WIDTH (FEET)	
	"H" < 10'-0"	"H" >OR= 10'-0"
18"	4'-6"	4'-6"
24"	5'-0"	6'-0"
30"	5'-6"	7'-6"
36"	6'-0"	9'-0"

MULTIPLE INSTALLATION OF PVC PIPES

PIPE DIAMETER	CLEAR DISTANCE BETWEEN PIPES
18"	1'-6"
24"	2'-0"
30"	2'-6"
36"	3'-0"


GENERAL NOTES

- PIPE SHALL CONFORM TO ASTM F949, CELL CLASS I2454, INSTALLATION SHALL CONFORM TO JOB SPECIAL PROVISION "PLASTIC PIPE" AND SECTION 606 OF THE STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION (CURRENT EDITION).
- PLASTIC PIPE CULVERT DESIGN SHALL CONFORM TO AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, FIFTH EDITION (2010) WITH 2010 INTERIMS.
- THE MAXIMUM ALLOWABLE TRENCH WIDTH SHALL BE THE MINIMUM WIDTH PLUS A SUFFICIENT WIDTH TO ENSURE WORKING ROOM TO PROPERLY AND SAFELY PLACE AND COMPACT HAUNCHING AND OTHER BACKFILL MATERIAL.
- IMPERVIOUS MATERIAL SHOULD BE PLACED AS DIRECTED BY THE ENGINEER AT THE ENDS OF THE CULVERT TO PREVENT LOSS OF STRUCTURAL BEDDING WHEN PERVIOUS MATERIAL IS USED FOR STRUCTURAL BEDDING AND/OR BACKFILL.
- WHEN DIRECTED BY THE ENGINEER, UNSUITABLE MATERIAL THAT IS ENCOUNTERED AT THE BOTTOM OF THE EXCAVATED TRENCH (BELOW THE AREA IDENTIFIED AS "STRUCTURAL BEDDING" ABOVE) WILL BE EXCAVATED AND REPLACED WITH SELECTED PIPE BEDDING. THE QUANTITY OF MATERIAL REQUIRED TO BACKFILL THE UNDERCUT AREA UP TO THE SELECTED PIPE BEDDING PAY LIMIT DESIGNATED ABOVE WILL BE MEASURED AND PAID FOR AS "SELECTED PIPE BEDDING."
- WHEN THE EXISTING MATERIAL EXCAVATED FOR THE PIPE TRENCH IS DETERMINED BY THE ENGINEER TO BE UNSUITABLE FOR BACKFILLING THE PIPE (ABOVE THE AREA IDENTIFIED ABOVE AS STRUCTURAL BACKFILL), BORROW MATERIAL OR MATERIAL FROM THE ROADWAY EXCAVATION WILL BE USED TO BACKFILL THE PIPE. IF SUITABLE MATERIAL IS NOT AVAILABLE, THE ENGINEER MAY AUTHORIZE THE USE OF "SELECTED PIPE BACKFILL."
- FOR PIPE TYPES THAT ARE NOT SMOOTH ON THE OUTSIDE (CORRUGATED OR PROFILE WALLS), BACKFILL GRADATIONS SHOULD BE SELECTED THAT WILL PERMIT THE FILLING OF THE CORRUGATION OR PROFILE VALLEY.
- PVC PIPES OF DIAMETERS OTHER THAN SHOWN WILL NOT BE ALLOWED.
- JOINTS FOR PVC PIPE SHALL MEET THE REQUIREMENTS FOR SOIL TIGHTNESS AS SPECIFIED IN AASHTO SECTION 26.4.2.4 AND 30.4.2 "AASHTO LRFD BRIDGE CONSTRUCTION SPECIFICATIONS." JOINTS SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS.

MAXIMUM FILL HEIGHT BASED ON STRUCTURAL BACKFILL

PIPE DIAMETER	"H"
18"	45'-0"
24"	45'-0"
30"	40'-0"
36"	40'-0"

- NOTE: 12" MIN. (18" - 36" DIAMETERS) MINIMUM COVER VALUE, "H" SHALL INCLUDE A MINIMUM 12" OF PAVEMENT AND/OR BASE.



TYPE 2 EMBANKMENT AND TRENCH INSTALLATIONS

1. STRUCTURAL BACKFILL, EMBANKMENT, AND OUTER STRUCTURAL BEDDING MATERIAL SHALL BE COMPACTED TO 95% OF THE MAXIMUM DENSITY ACCORDING TO THE TYPE OR CLASS OF MATERIAL USED.

CONSTRUCTION SEQUENCE

- PLACE STRUCTURAL BEDDING MATERIAL TO GRADE. DO NOT COMPACT.
- INSTALL PIPE TO GRADE.
- COMPACT STRUCTURAL BEDDING OUTSIDE THE MIDDLE THIRD OF THE PIPE.
- THE STRUCTURAL BACKFILL SHALL BE PLACED AND COMPACTED IN LAYERS NOT EXCEEDING 8". THE LAYERS SHALL BE BROUGHT UP EVENLY AND SIMULTANEOUSLY TO THE ELEVATION OF THE MINIMUM COVER.
- PIPE INSTALLATION MAY REQUIRE THE USE OF RESTRAINTS, WEIGHTING OR OTHER APPROVED METHODS IN ORDER TO HELP MAINTAIN GRADE AND ALIGNMENT.

- LEGEND -


- H = FILL HEIGHT (FT.)
- D_o = OUTSIDE DIAMETER OF PIPE
- MAX. = MAXIMUM
- MIN. = MINIMUM
- [Symbol] = STRUCTURAL BACKFILL MATERIAL
- [Symbol] = UNDISTURBED SOIL

DATE	REVISION	DATE FILMED
2-27-14	REVISED GENERAL NOTE 1.	
12-15-11	REV GENERAL NOTES & MINIMUM COVER NOTE; DELETED SM3 MATERIAL	
11-17-10	ISSUED	


ARKANSAS STATE HIGHWAY COMMISSION

PLASTIC PIPE CULVERT (PVC F949)

STANDARD DRAWING PCP-2




CONCRETE PAVEMENT




ASPHALT PAVEMENT


BROKEN LINE STRIPING




SOLID LINE STRIPING ON CONCRETE PAVEMENT



SOLID LINE STRIPING ON ASPHALT PAVEMENT




ASPHALT PAVEMENT




CONCRETE PAVEMENT

STRIPING AT ADJACENT NO PASSING LANES



YIELD LINE DETAIL




CROSSWALK AND STOPBAR DETAILS

NOTES:

1. REFER TO THE STRIPING DETAILS FOR PAVEMENT MARKING LINE WIDTHS.
2. THIS DRAWING SHALL BE USED IN CONJUNCTION WITH THE LATEST REVISED ADDITION OF THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES."
3. RAISED PAVEMENT MARKERS SHALL BE PLACED ON AN 80 FEET SPACING UNLESS OTHERWISE SHOWN IN THE PLANS.


2" FOR ASPHALT OR CONCRETE PAVEMENT
6" FOR BITUMINOUS SURFACE TREATMENT



PAVEMENT EDGE LINE MARKING


NOTE:
THE RED LENS OF THE TYPE II R.P.M. SHALL FACE THE INCORRECT TRAFFIC MOVEMENT.

TYPE II
RED/CLEAR OR
YELLOW/YELLOW



PRISMATIC REFLECTOR

NOTE:
DIMENSIONS SHOWN FOR RAISED PAVEMENT MARKERS ARE TYPICAL. THE CONTRACTOR MAY SUBSTITUTE SIMILAR MARKERS WITH THE APPROVAL OF THE ENGINEER. REQUESTING APPROVAL FOR SIMILAR MARKERS MAY BE MADE BY REFERRING TO THE AHTD QUALIFIED PRODUCTS LIST.



DETAIL OF STANDARD RAISED PAVEMENT MARKERS







6-1-17	ADDED YIELD LINE DETAIL	
5-12-16	REVISED LINE WIDTHS, SPACING, & NOTES	
9-12-13	REVISED DETAIL OF STANDARD RAISED PAVEMENT MARKERS	
11-17-10	REVISED GENERAL NOTES & REMOVED PLOWABLE PVMT MRKRS	
11-18-04	REVISED NOTE 2 & GENERAL NOTES	
8-22-02	ADDED CROSSWALK & STOPBAR DTLS.	
7-02-98	ADDED DETAILS OF STD. RAISED PAV'T. MARKERS	
4-26-96	REV. NOTES 3&4; ADDED R.P.M.	
9-30-80	DRAWN	1-9-30-80
DATE	REVISION	FILMED

ARKANSAS STATE HIGHWAY COMMISSION

PAVEMENT MARKING DETAILS

STANDARD DRAWING PM-1

NOTE:
 1. UNLESS OTHERWISE SPECIFIED ON THE PLANS, THE UNDERDRAIN COVER SHALL BE THOROUGHLY COMPACTED EARTH AND SHALL BE SUBSIDIARY TO PIPE UNDERDRAIN.
 2. GRANULAR MATERIAL SHALL BE WRAPPED WITH GEOTEXTILE FABRIC, LAP FABRIC 12" OR THE WIDTH OF THE TRENCH AT THE TOP.




DETAILS OF PIPE UNDERDRAIN

NOTES FOR PIPE UNDERDRAINS

1. GEOTEXTILE FABRIC SHALL MEET THE REQUIREMENTS OF SECTION 625 FOR TYPE I. PAYMENT FOR GEOTEXTILE FABRIC AND GRANULAR FILTER MATERIAL SHALL BE INCLUDED IN THE PRICE BID PER LIN. FT. FOR "4" PIPE UNDERDRAINS" IN ACCORDANCE WITH SECTION 610 OF THE STANDARD SPECIFICATIONS.
2. 4" NON-PERFORATED SCHEDULE 40 PVC PIPE LATERALS WITH OUTLET PROTECTORS SHALL BE INSTALLED AS SHOWN HEREON. LATERALS WILL BE MEASURED AND PAID FOR AS "4" PIPE UNDERDRAINS." UNDERDRAIN OUTLET PROTECTORS WILL BE MEASURED AND PAID FOR BY THE UNIT IN ACCORDANCE WITH SECTION 610 OF THE STANDARD SPECIFICATIONS.
3. EXISTING 4" PIPE UNDERDRAINS MAY BE CONNECTED TO PROPOSED DROP INLETS OR EXTENDED WHERE DIRECTED BY THE ENGINEER. PAYMENT FOR CONNECTING TO DROP INLETS SHALL BE CONSIDERED INCLUDED IN THE PRICE BID FOR "4" PIPE UNDERDRAINS."
4. THE LOCATION OF ALL LATERALS SHALL BE MARKED WITH 4" X 12" PERMANENT PAVEMENT MARKING TAPE (TYPE II/WHITE) AT THE OUTSIDE EDGE OF THE SHOULDER, PLACED TRANSVERSE TO TRAFFIC. PAYMENT FOR THIS WORK SHALL BE INCLUDED IN THE PRICE BID FOR THE VARIOUS CONTRACT ITEMS.
5. PAYMENT FOR THE RODENT SCREEN SHALL BE INCLUDED IN THE PRICE BID PER EACH FOR "UNDERDRAIN OUTLET PROTECTORS."
6. ANY EXISTING UNDERDRAINS THAT INTERFERE WITH INSTALLATION OF THE NEW UNDERDRAIN SYSTEM SHALL BE REMOVED AND DISPOSED OF AS DIRECTED BY THE ENGINEER. PAYMENT WILL BE CONSIDERED INCLUDED IN THE PRICE BID FOR THE VARIOUS CONTRACT ITEMS. EXISTING UNDERDRAIN OUTLET PROTECTORS SHALL BE REMOVED UNDER THE ITEM "REMOVAL AND DISPOSAL OF UNDERDRAIN OUTLET PROTECTORS."
7. AT LOCATIONS WHERE A SINGLE LATERAL IS USED THE CONTRACTOR SHALL HAVE THE FOLLOWING OPTIONS: 1. INSTALL OUTLET PROTECTOR AS SHOWN ON STANDARD DRAWING PU-1 AND GROUT THE UNUSED HOLE OR 2. INSTALL AN OUTLET PROTECTOR WITH A SINGLE HOLE.

FERNCO 1056-44 (4" CI/PLASTIC) OR FERNCO 1051-44 (4" AC/DIOR 4" CI/PLASTIC) COUPLING OR EQUAL WITH 2 CLAMPS (TYPICAL) UNDERDRAIN OUTLET PROTECTORS FERNCO 1056-44 (4" CI/PLASTIC) OR FERNCO 1051-44 (4" AC/DIOR 4" CI/PLASTIC) COUPLING OR EQUAL WITH 2 CLAMPS (TYPICAL)



NOTE: LATERALS SHALL BE INSTALLED AT ALL SAGS AND AT 250' INTERVALS ON GRADES. THE 250' DISTANCE MAY BE EXCEEDED ONLY WHERE NECESSARY FOR AN ACCEPTABLE OUTLET.
 NOTE: PVC PIPE FOR LATERALS SHALL MEET THE REQUIREMENTS OF ASTM D 1785 (LATEST REVISION) FOR SCHEDULE 40 PIPE.

DATE	REVISION	DATE FILMED
12-8-16	ADDED NOTES FOR PIPE UNDERDRAINS, REVISED RODENT SCREEN DETAIL AND NOTES, REMOVED NOTE 1 FOR GRANULAR MATERIAL, ADDED NOTE FOR GEOTEXTILE FABRIC	
4-10-03	REVISED NOTE 3	
1-12-00	REVISED DETAIL OF UNDERDRAIN LATERALS	
11-18-98	REVISED NOTE	
10-18-96	REVISED MIN. DEPTH & GEOTEXTILE FABRIC	
4-26-96	ADDED LATERAL NOTE: 5 1/2" TO 5"	
11-22-95	REVISED LATERALS	
7-20-95	REVISED LATERALS & ADDED NOTE	
11-3-94	REVISED FOR DUAL LATERALS	11-3-94
10-1-92	SUBSTITUTED GEOTEXTILE	10-1-92
8-15-91	ADDED POLYETHYLENE PIPE	8-15-91
11-8-90	DELETED ALTERNATE NOTE	11-8-90
1-25-90	ADDED 4" SNAP ADAPTER	1-25-90
11-30-89	DEL. (SUBGRADE); ADDED (WHERE REQUIRED)	11-30-89
7-15-88	ISSUED P.L.M.	647-7-15-88

ARKANSAS STATE HIGHWAY COMMISSION

DETAILS OF PIPE UNDERDRAIN

STANDARD DRAWING PU-1

SUPERELEVATION TABLE FOR TWO - WAY TRAFFIC

DEGREE OF CURVE	30 MPH		35 MPH		40 MPH		45 MPH		50 MPH		55 MPH		60 MPH		65 MPH		70 MPH		75 MPH		
	e	Ls (FT)		e	Ls (FT)		e	Ls (FT)		e	Ls (FT)		e	Ls (FT)		e	Ls (FT)		e	Ls (FT)	
		MINIMUM	DESIRABLE		MINIMUM	DESIRABLE		MINIMUM	DESIRABLE		MINIMUM	DESIRABLE		MINIMUM	DESIRABLE		MINIMUM	DESIRABLE		MINIMUM	DESIRABLE
0° 15'	NC			NC			NC			NC			NC			NC			NC		
0° 30'	NC			NC			NC			NC			NC			NC			NC		
0° 45'	NC			NC			NC			RC	96		RC	96		RC	96		RC	96	
1° 00'	NC			NC			NC			0.022	101		0.028	110		0.030	120		0.030	120	
1° 15'	NC			NC			RC	84		0.022	95		0.032	125		0.038	139		0.038	139	
1° 30'	NC			RC	78		0.022	88		0.028	108		0.032	125		0.038	139		0.044	154	
1° 45'	RC	72		RC	78		0.026	97		0.030	113		0.036	134		0.044	154		0.050	168	
2° 00'	RC	72		0.024	86		0.028	101		0.034	122		0.042	149		0.048	163		0.056	182	
2° 15'	RC	72		0.026	90		0.032	109		0.038	131		0.046	158		0.054	178		0.062	197	
2° 30'	0.022	75		0.028	94		0.034	113		0.042	140		0.050	168		0.058	187		0.068	211	
2° 45'	0.024	79		0.030	98		0.038	122		0.048	149	200	0.054	178	250	0.064	202		0.072	221	
3° 00'	0.026	83		0.034	105		0.040	126		0.050	158		0.058	187		0.068	211		0.078	235	
3° 15'	0.028	86		0.036	109		0.044	134		0.052	162		0.062	197		0.072	221		0.082	245	
3° 30'	0.030	90		0.038	113		0.048	139	200	0.058	171		0.068	206		0.078	230		0.088	254	
3° 45'	0.032	93		0.040	117		0.050	147		0.058	176		0.070	216		0.080	240		0.090	264	
4° 00'	0.034	97		0.042	121		0.052	151		0.062	185		0.072	221		0.084	250		0.094	274	
4° 15'	0.036	100		0.044	125	200	0.054	155		0.064	189		0.076	230		0.088	254		0.096	278	
4° 30'	0.038	100	200	0.048	129		0.058	160		0.068	198		0.078	235		0.090	264		0.098	283	
4° 45'	0.038	104		0.048	133		0.060	168		0.070	203		0.082	245		0.092	269		0.100	288	
5° 00'	0.040	108		0.050	137		0.062	172		0.072	207		0.084	250	350	0.094	274		0.098	283	
5° 30'	0.044	115		0.054	144		0.066	181		0.078	221		0.088	259		0.098	283		0.100	288	
6° 00'	0.046	119		0.058	152		0.070	189		0.082	230	250	0.092	269		0.098	283		0.100	288	
6° 30'	0.050	126		0.062	160		0.074	198		0.086	239		0.096	278	300	0.098	283		0.100	288	
7° 00'	0.052	130		0.064	164		0.078	206		0.090	248		0.098	283		0.100	288		0.100	288	
7° 30'	0.054	133		0.068	172		0.080	210		0.092	252		0.100	288		0.100	288		0.100	288	
8° 00'	0.058	140		0.070	176		0.084	219		0.094	257		0.098	283		0.100	288		0.100	288	
8° 30'	0.060	144		0.072	179		0.086	223	250	0.096	261		0.098	283		0.100	288		0.100	288	
9° 00'	0.062	148		0.078	187		0.088	227		0.098	266		0.098	283		0.100	288		0.100	288	
9° 30'	0.064	151		0.078	191		0.092	235		0.092	270		0.092	270		0.100	288		0.100	288	
10° 00'	0.066	155		0.080	195		0.094	240		0.094	240		0.094	240		0.100	288		0.100	288	
11° 00'	0.070	162		0.084	203		0.096	244		0.096	244		0.096	244		0.100	288		0.100	288	
12° 00'	0.074	169		0.088	211	250	0.098	248		0.098	248		0.098	248		0.100	288		0.100	288	
13° 00'	0.076	173		0.090	215		0.090	215		0.100	252	300	0.100	252		0.100	252		0.100	252	
14° 00'	0.080	180		0.094	222		0.094	222		0.094	222		0.094	222		0.100	252		0.100	252	
15° 00'	0.082	184		0.096	226		0.096	226		0.096	226		0.096	226		0.100	252		0.100	252	
16° 00'	0.086	191		0.098	230		0.098	230		0.098	230		0.098	230		0.100	252		0.100	252	
17° 00'	0.088	194		0.098	234		0.098	234		0.098	234		0.098	234		0.100	252		0.100	252	
18° 00'	0.090	198	250	0.098	238		0.098	238		0.098	238		0.098	238		0.100	252		0.100	252	
19° 00'	0.092	202		0.098	242		0.098	242		0.098	242		0.098	242		0.100	252		0.100	252	
20° 00'	0.094	205		0.098	246		0.098	246		0.098	246		0.098	246		0.100	252		0.100	252	
21° 00'	0.096	209		0.098	250		0.098	250		0.098	250		0.098	250		0.100	252		0.100	252	
22° 00'	0.096	209		0.098	250		0.098	250		0.098	250		0.098	250		0.100	252		0.100	252	
23° 00'	0.098	212		0.098	250		0.098	250		0.098	250		0.098	250		0.100	252		0.100	252	
24° 00'	0.098	212		0.098	250		0.098	250		0.098	250		0.098	250		0.100	252		0.100	252	
25° 00'	0.100	216		0.100	254		0.100	254		0.100	254		0.100	254		0.100	252		0.100	252	


ABBREVIATIONS

- NC - NORMAL CROWN
- RC - REVERSE CROWN, SUPERELEVATION AT NORMAL CROWN SLOPE
- e - RATE OF SUPERELEVATION (FT. PER FT.)
- Ls - LENGTH OF SUPERELEVATION TRANSITION (FT.)
- L - DISTANCE FROM BEGINNING OF SUPERELEVATION TRANSITION TO ANY POINT (FT.)
- d - WIDTH OF PAVEMENT (FT.) OR WIDTH OF SUBGRADE (FT.)
- C - NORMAL CROWN (FT.)


- GENERAL NOTES**
- ON PAVEMENT WITH TWO-WAY TRAFFIC, THE SUPERELEVATION SHALL BE REVOLVED ON THE INSIDE PAVEMENT EDGE UNLESS OTHERWISE NOTED ON THE PLANS
 - SUPERELEVATION VALUES SHOWN ON THE CROSS SECTIONS ARE VALUES (+) OR (-) TO BE ADDED TO OR SUBTRACTED FROM THE POINT OF CONTROL.
 - LENGTHS FOR L MAY BE ROUNDED IN MULTIPLES OF 25 FT. OR 50 FT. TO PERMIT SIMPLER CALCULATIONS.
 - PAVEMENTS WIDER THAN 2 LANES SHALL HAVE ADDITIONAL TRANSITION LENGTHS AS FOLLOWS:
 - 3 LANE UNDIVIDED - - - - - +20%
 - 4 LANE UNDIVIDED - - - - - +50%
 - 5 LANE UNDIVIDED - - - - - +80%
 - 6 LANE UNDIVIDED - - - - - +100%

NOTE: MAINTAIN NORMAL CROWN ON INSIDE UNTIL SUPERELEVATION EXCEEDS 2C.
 RATE OF SUPERELEVATION SHALL BE COMPUTED ON STRAIGHT LINE METHOD USING APPLICABLE Ls.

SUPERELEVATION FORMULA = $\frac{Ls \cdot e}{L}$



STANDARD METHOD WHEN SUPERELEVATION REVOLVES AROUND CENTER LINE



STANDARD METHOD WHEN SUPERELEVATION REVOLVES AROUND INNER SUBGRADE POINT OR INNER PAVEMENT EDGE






NOTE: MAINTAIN NORMAL CROWN ON INSIDE UNTIL SUPERELEVATION EXCEEDS 2C.

DATE	REVISION	DATE FILLED
11-07-19	REVISED SUPERELEVATION TABLE	
10-18-96	ADDED FORMULA	
01-09-87	ISSUED	534-1-9-87

ARKANSAS STATE HIGHWAY COMMISSION

TABLES AND METHOD OF SUPERELEVATION FOR TWO-WAY TRAFFIC

STANDARD DRAWING SE-2

<p>RI-1</p>  <p>STANDARD 30"x30" EXPRESSWAY 36"x36" SPECIAL 48"x48"</p>	<p>RI-2</p>  <p>STD. 36"x36" EXPWY. 48"x48" FWY. 60"x60"x60"</p>	<p>R2-1</p>  <p>STD. 24"x30" EXPWY. 36"x48" FWY. 48"x60"</p>	<p>W3-5</p>  <p>STD. 36"x36" EXPWY. 48"x48" FWY. 48"x48"</p>	<p>W3-5a</p>  <p>STD. 36"x36" EXPWY. 48"x48" FWY. 48"x48"</p>	<p>R4-1</p>  <p>STD. 24"x30" EXPWY. 36"x48" FWY. 48"x60"</p>	<p>R4-2</p>  <p>STD. 24"x30" EXPWY. 36"x48" FWY. 48"x60"</p>
<p>R5-1</p>  <p>STD. 30"x30" EXPWY. 36"x36" SPECIAL 48"x48"</p>	<p>R11-2</p>  <p>48"x30"</p>	<p>R11-3A</p>  <p>60"x30"</p>	<p>R11-4</p>  <p>60"x30"</p>	<p>W21-5a</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>W1-1</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>W1-2</p>  <p>STD. 36"x36" FWY. 48"x48"</p>
<p>W1-3</p>  <p>STD. 48"x48"</p>	<p>W1-4</p>  <p>STD. 48"x48"</p>	<p>W1-6</p>  <p>STD. 48"x24" SPECIAL 60"x30"</p>	<p>W1-8</p>  <p>STD. 18"x24" SPECIAL 24"x30" EXPWY. 30"x36" FWY. 36"x48"</p>	<p>W3-1</p>  <p>STD. 36"x36" SPECIAL 48"x48"</p>	<p>W3-2</p>  <p>STD. 36"x36" SPECIAL 48"x48"</p>	<p>W4-2</p>  <p>STD. 36"x36" FWY. 48"x48"</p>
<p>W5-1</p>  <p>STD. 36"x36" SPECIAL 48"x48"</p>	<p>W6-3</p>  <p>EXPWY. 36"x36" SPECIAL 48"x48"</p>	<p>W8-7</p>  <p>EXPWY. 36"x36" FWY. 48"x48"</p>	<p>W9-2</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>W13-1</p>  <p>STD. 24"x24"</p>	<p>W20-1</p>  <p>STD. 48"x48"</p>	<p>W20-2</p>  <p>STD. 48"x48"</p>
<p>W20-4</p>  <p>STD. 48"x48"</p>	<p>W20-5</p>  <p>STD. 48"x48"</p>	<p>W20-7a</p>  <p>500 FEET W6-2 24" STD. 36"x36" FWY. 48"x48"</p>	<p>W21-2</p>  <p>STD. 30"x30" SPECIAL 36"x36"</p>	<p>W21-5</p>  <p>STD. 30"x30" SPECIAL 36"x36"</p>	<p>W24-1</p>  <p>STD. 36"x36"</p>	<p>W1-4b</p>  <p>STD. 48"x48"</p>
<p>W8-11</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>W8-9</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>G20-1</p>  <p>60"x24"</p>	<p>G20-2</p>  <p>48"x24"</p>	<p>OM-3L OM-3R</p>  <p>12"x36"</p>	<p>M4-9</p>  <p>STD. 30"x24" SPECIAL 48"x36" SPECIAL 60"x48"</p>	<p>M4-10</p>  <p>48"x18"</p>
						<p>R55-1</p>  <p>36"x60" • USE 6" C LETTERS •• USE 4" D LETTERS</p>

ADVANCE DISTANCES (XXXX)

500 FT	1/2 MILE
1000 FT	3/4 MILE
1500 FT	1 MILE

AHEAD


GENERAL NOTES:

- ALL TRAFFIC CONTROL DEVICES USED ON ROAD CONSTRUCTION SHALL CONFORM TO THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, LATEST EDITION, AND TO THE STANDARD HIGHWAY SIGNS, LATEST EDITION, OR AS APPROVED BY THE FEDERAL HIGHWAY ADMINISTRATION.
- TRAFFIC CONTROL DEVICES SHALL BE SET UP JUST BEFORE THE START OF CONSTRUCTION OPERATIONS AND SHALL BE PROPERLY MAINTAINED DURING THE TIME SUCH CONDITIONS EXIST. THEY SHALL REMAIN IN PLACE ONLY AS LONG AS NEEDED AND REMOVED THEREAFTER.
- EXISTING SIGNS AND CONSTRUCTION SIGNS SHALL BE KEPT IN PROPER POSITION, AND BE CLEAN AND LEGIBLE AT ALL TIMES. SIGNS THAT DO NOT APPLY TO EXISTING CONDITIONS SHALL BE REMOVED. SIGNS THAT ARE DAMAGED, DEFACED, OR THAT ACCUMULATE DIRT DURING CONSTRUCTION SHALL BE CLEANED, REPAIRED, OR REPLACED.
- SIGNS ARE USUALLY MOUNTED ON A SINGLE POST, ALTHOUGH THOSE WIDER THAN 36" OR LARGER THAN 10 SQ. FT. SHALL BE MOUNTED ON TWO POSTS OR ABOVE A TYPE III BARRICADE.
- SIGN POSTS DIRECT BURIED IN SOIL SHALL BE 2 LB. MINIMUM CHANNEL POST OR 4"x4" WOOD POSTS. CHANNEL POSTS SHALL BE PAINTED GREEN. WOOD POSTS SHALL BE PAINTED WHITE. ALL POSTS SHALL BE NEATLY CONSTRUCTED, AND SHALL BE REPLUMBED, CLEANED, OR REPAIRED AS NEEDED FOR THE DURATION OF THE JOB. THERE SHALL NOT BE MORE THAN 2 POSTS IN A 7' PATH FOR WOOD OR CHANNEL POSTS. ANY CHANNEL POST SPLICE SHALL BE IN ACCORDANCE WITH STANDARD DRAWING TC-3.
- POST MOUNTED SIGNS IN RURAL AREAS SHALL BE CONSTRUCTED WITH THE NEAR EDGE OF THE SIGN FROM 6 TO 12 FEET FROM THE PAVEMENT EDGE. SIGNS IN URBAN AREAS AND BARRICADE MOUNTED SIGNS SHALL BE MOUNTED A MINIMUM OF 2 FEET FROM THE PAVEMENT EDGE.
- ALL POST AND BARRICADE MOUNTED SIGNS MOUNTED IN URBAN AREAS SHALL BE MOUNTED A MINIMUM DISTANCE OF 7' FROM THE BOTTOM OF THE SIGN TO THE ROADWAY SURFACE. ALL POST AND BARRICADE MOUNTED SIGNS MOUNTED IN RURAL AREAS SHALL BE MOUNTED A MINIMUM DISTANCE OF 7' FROM THE BOTTOM OF THE SIGN TO THE ROADWAY SURFACE, EXCEPT A MINIMUM OF 6' SHALL BE USED WHEN MOUNTING AN ADVISORY SIGN BELOW A WARNING SIGN. TEMPORARY SIGNS MAY BE MOUNTED ON PORTABLE SUPPORTS FOR INTERMEDIATE TERM STATIONARY WORK CONDITIONS. THE SIGNS MINIMUM MOUNTING HEIGHT SHALL BE 5'. RETROREFLECTIVE DEVICES SHALL BE USED. TEMPORARY SIGNS MAY BE MOUNTED ON PORTABLE SUPPORTS FOR SHORT-TERM, SHORT DURATION, AND MOBILE CONDITIONS. THEY SHALL BE NO LESS THAN ONE (1) FOOT ABOVE THE TRAVELED WAY. LONG-TERM STATIONARY SIGNS SHALL BE DIRECT BURIED IN SOIL, UNLESS CONDITIONS NECESSITATE THE USE OF PORTABLE SIGNS, OR AS APPROVED BY THE ENGINEER. CONCRETE PADS, CONCRETE OR ROCK BALLAST, OR OTHER SOLID MATERIALS SHALL NOT BE UTILIZED WITH PORTABLE SIGN SUPPORTS.
- FLAGGERS SHALL USE REFLECTORIZED STOP-SLOW PADDLES. FLAGS MAY BE USED ONLY FOR EMERGENCY SITUATIONS.
- MOST OF THE SIGNS SHOWN ARE ORIENTED TO THE RIGHT. HOWEVER, THIS DOES NOT PRECLUDE THE USE OF MIRROR IMAGES OF THESE SIGNS WHERE THE REVERSE ORIENTATION MIGHT BETTER CONVEY TO MOTORISTS THE PROPER DIRECTION OF MOVEMENT.
- R55-1 SIGNS SHALL BE PLACED AT LEAST 1500' BUT NOT MORE THAN 1 MILE IN ADVANCE OF THE WORK ZONE. IF A SPEED LIMIT REDUCTION IS IN EFFECT, THE SIGN SHALL BE PLACED A MINIMUM OF 500' IN ADVANCE OF THE "REDUCED SPEED AHEAD" SIGN.


*** NOTE:** SUPPORTS FOR SIGNS, BARRICADES, AND VERTICAL PANELS THAT ARE DIFFERENT FROM THE REQUIREMENTS SHOWN IN NOTES 4 & 5, BUT MEET THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH), WILL BE ACCEPTED. COMPLIANCE WITH THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH) IS REQUIRED FOR ALL PROJECTS.

11-07-19	REVISED FOR MASH	
4-13-17	DELETED RSP-1 & ADDED W21-5a	
9-2-15	REVISED REDUCED SPEED LIMIT AHEAD SIGNS	
	REVISED ROAD WORK NEXT XX MILES	
12-15-11	REVISED W24-1	
11-17-10	DELETED W8-9a & ADDED W8-9	
10-15-09	ADDED REFERENCE TO MASH & ADDED SIGN W24-1	
4-17-08	REVISED SIGN DESIGNATIONS	
11-18-04	REVISED NOTES	
10-9-03	REVISED NOTE 1	
11-16-01	REVISED NOTE 7	
9-28-00	REVISED NOTE	
1-18-98	ADDED NOTE	
6-26-97	REVISED NOTE 5	
4-03-97	REVISED NOTE 5	
10-18-96	ADDED CONTROLLED ACCESS HWY. SIGN & TO NOTE 7	
10-12-95	ADDED R55-1	
6-8-95	REVISED TO CORRECT SIGN ILLUSTRATIONS	6-8-95
2-2-95	REVISED PER PART VI, MUTCD SEPT. 3, 1993	
8-15-91	DRAWN AND PLACED IN USE	
DATE	REVISION	FILMED

ARKANSAS STATE HIGHWAY COMMISSION
STANDARD TRAFFIC CONTROLS
FOR HIGHWAY CONSTRUCTION
STANDARD DRAWING TC-1





(A) TYPICAL APPLICATION - DAYTIME MAINTENANCE OPERATIONS OF SHORT DURATION ON A 4-LANE DIVIDED ROADWAY WHERE HALF OF THE ROADWAY IS CLOSED.




(B) TYPICAL APPLICATION - 3-LANE ONEWAY ROADWAY WHERE CENTER LANE IS CLOSED.

CHANNELIZING DEVICES

WHEN CONES ARE USED ON FREEWAYS AND MULTI-LANE HIGHWAYS, THEY SHALL BE 28" MIN. DURING HOURS OF DARKNESS, 28" CONES SHALL BE USED ON ALL ROADWAYS, AND SHALL BE REFLECTORIZED IN ACCORDANCE WITH THE M.U.T.C.D.



NOTE: FOR ALL ROAD CLOSURES, THE TYPE III BARRICADES SHALL BE OF SUFFICIENT LENGTH TO EXTEND ACROSS ENTIRE ROADWAY.




FLAG SHALL BE OF GOOD GRADE RED MATERIAL

TRAFFIC CONTROL DEVICES			
NON-INTERSTATE			
VERTICAL DIFFERENTIAL	LOCATION	TRAFFIC CONTROL	
		≤ 45 MPH	> 45 MPH
≤ 2"	CENTERLINE	W8-11 AND LANE STRIPING	W8-11 AND LANE STRIPING
> 2"	CENTERLINE	STANDARD LANE CLOSURE	STANDARD LANE CLOSURE
≤ 3"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-9, EDGE LINE STRIPING, AND VERTICAL PANELS	W8-9, EDGE LINE STRIPING, AND VERTICAL PANELS
> 3"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-17, EDGE LINE STRIPING, AND VERTICAL PANELS	W8-17, EDGE LINE STRIPING, AND VERTICAL PANELS
≤ 6"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS ⁽¹⁾	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS ⁽²⁾
> 6"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS ⁽¹⁾	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS ⁽²⁾
> 24"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	PRECAST CONCRETE BARRIER ⁽³⁾ & EDGE LINES	PRECAST CONCRETE BARRIER ⁽³⁾ & EDGE LINES

INTERSTATE		
VERTICAL DIFFERENTIAL	LOCATION	TRAFFIC CONTROL
≤ 2"	CENTERLINE	W8-11 AND LANE STRIPING
≤ 2"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-9, EDGE LINE STRIPING, AND TRAFFIC DRUMS ⁽²⁾
≤ 6"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS ⁽¹⁾
> 6"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	PRECAST CONCRETE BARRIER & EDGE LINES



INTERSTATE AND NON-INTERSTATE		
FORESLOPE	HEIGHT	TRAFFIC CONTROL
1:1	> 2 FT	PRECAST CONCRETE BARRIER
2:1	≤ 5 FT	TRAFFIC DRUMS
2:1	> 5 FT	PRECAST CONCRETE BARRIER
Flatter than 2:1	N/A	TRAFFIC DRUMS

GENERAL NOTES:
 1. WHEN THE SHOULDER AREA IS USED AS PART OF THE TRAVELED LANE AND THERE IS INSUFFICIENT WIDTH TO PLACE TRAFFIC DRUMS ON THE REMAINING SHOULDER WIDTH, THEN VERTICAL PANELS SHALL BE USED.
 2. WHEN THERE IS INSUFFICIENT WIDTH TO PLACE TRAFFIC DRUMS ON THE REMAINING SHOULDER WIDTH, A STABILIZED WEDGE SHALL BE USED. A STABILIZED WEDGE, W8-17 SIGN, EDGE LINE STRIPING, AND TRAFFIC DRUMS CAN BE USED IN LIEU OF PRECAST CONCRETE BARRIER WALL, IF AND WHERE DIRECTED BY THE ENGINEER.
 3. W21-5, W21-5a, AND/OR W21-5b SIGNS SHALL BE USED WHERE THE ROADWAY IS UNOBSTRUCTED IF AND WHERE DIRECTED BY THE ENGINEER.




STABILIZED WEDGE

NOTE: MATERIALS FOR THE STABILIZED WEDGE SHALL MEET THE REQUIREMENTS PROVIDED IN SECTION 603.02 OF THE STANDARD SPECIFICATIONS.




DATE	REVISION	FILED
11-07-19	REVISED NOTE 9, ADDED NOTE II	
7-25-19	REVISED TRAFFIC CONTROL DEVICES DETAILS	
9-2-15	REVISED NOTE 2 & REPLACED R2-5A WITH W3-5	
10-15-09	ADDED REFERENCE TO MASH	
11-20-08	REVISED SIGN DESIGNATIONS	
11-18-04	ADDED NOTE	
10-1-98	ADDED NOTE	
4-03-97	ADDED (SPI) TO W6-1 & REVISED TRAFFIC CONTROL DEVICES NOTE	
10-18-96	ADDED R55-1	
10-12-95	MOVED UPPER SPLICE	
6-8-95	REVISED SPLICE DETAIL, TEXT	6-8-95
2-2-95	REVISED PER PART VI, MUTCD, SEPT. 3, 1993	
8-15-91	DRAWN AND PLACED IN USE	










(C) TYPICAL APPLICATION - CONSTRUCTION OPERATIONS OF INTERMEDIATE TO LONG TERM DURATION ON A 4-LANE DIVIDED ROADWAY WHERE HALF OF THE ROADWAY IS CLOSED.

- KEY:
 ○○○ ARROW PANEL (IF REQUIRED)
 ■ CHANNELIZING DEVICE
 ● TRAFFIC DRUM
- GENERAL NOTES:
 1. A SPEED LIMIT REDUCTION MAY BE IMPLEMENTED ONLY WHEN DESIGNATED IN THE PLAN OR WHEN RECOMMENDED BY THE ROADWAY DESIGN DIVISION.
 2. WHEN THE EXISTING SPEED LIMIT IS 55MPH AND THE PLANS REQUIRE A SPEED LIMIT OF 45MPH, THE R2-1(K5) SHALL BE OMITTED AND THE W3-5 SHALL BE INSTALLED AT THAT LOCATION. ADDITIONAL R2-145MPH SPEED LIMIT SIGNS SHALL BE INSTALLED AT A MAXIMUM OF 1 MILE INTERVALS. AT THE END OF THE WORK AREA A R2-1(X) SHALL BE INSTALLED TO MATCH ORIGINAL SPEED LIMIT.
 3. WHEN THE EXISTING SPEED LIMIT IS 65MPH AND THE PLANS REQUIRE A SPEED LIMIT OF 55MPH, THE R2-1(K45) SHALL BE OMITTED. ADDITIONAL R2-155MPH SPEED LIMIT SIGNS SHALL BE INSTALLED AT A MAXIMUM OF 1 MILE INTERVALS. AT THE END OF THE WORK AREA A R2-1(X) SHALL BE INSTALLED TO MATCH ORIGINAL SPEED LIMIT.
 4. THE MAXIMUM SPACING BETWEEN CHANNELIZING DEVICES IN A TAPER SHOULD BE APPROXIMATELY EQUAL IN FEET TO THE SPEED LIMIT. BEYOND THE TAPER, MAXIMUM SPACING SHALL BE TWO TIMES THE SPEED LIMIT OR AS DIRECTED BY THE ENGINEER.
 5. WARNING LIGHTS AND/OR FLAGS MAY BE MOUNTED TO SIGNS OR CHANNELIZING DEVICES AT NIGHT AS NEEDED.
 6. PAVEMENT MARKINGS NO LONGER APPLICABLE WHICH MIGHT CREATE CONFUSION IN THE MINDS OF VEHICLE OPERATORS SHALL BE REMOVED OR OBLITERATED AS SOON AS PRACTICABLE.
 7. THE G20-1 SIGN WILL BE REQUIRED ON JOBS OF OVER TWO MILES IN LENGTH. WHEN THE LANE CLOSURE IS NOT AT THE BEGINNING OF THE PROJECT, THE G20-1 SIGN SHALL BE ERECTED 125' IN ADVANCE OF THE JOB LIMIT. ADDITIONAL W20-1 (1 MILE) SIGNS ARE NOT REQUIRED IN ADVANCE OF LANE CLOSURES THAT BEGIN INSIDE THE PROJECT LIMITS.
 8. FLAGGERS SHALL USE STOP/SLOW PADDLES FOR CONTROLLING TRAFFIC THROUGH WORK ZONES. FLAGS MAY BE USED ONLY FOR EMERGENCY SITUATIONS.
 9. ALL PLASTIC DRUMS AND CONES SHALL MEET THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH).
 10. TRAILER MOUNTED DEVICES SUCH AS ARROW PANELS AND PORTABLE CHANGEABLE MESSAGE SIGNS SHALL BE DELINEATED BY AFFIXING CONSPICUITY MATERIAL IN A CONTINUOUS LINE ON THE FACE OF THE TRAILER. WHEN PLACED ON OR ADJACENT TO THE SHOULDER AND NOT BEHIND A POSITIVE BARRIER, THESE DEVICES SHALL BE DELINEATED BY PLACING FIVE (5) TRAFFIC DRUMS, EQUALLY SPACED ALONG THE TRAFFIC SIDE OF THE DEVICE.
 11. ALL TRAILER MOUNTED DEVICES SUCH AS ARROW PANELS AND PORTABLE CHANGEABLE MESSAGE SIGNS SHALL MEET THE REQUIREMENTS OF THE MANUAL FOR ASSESSING SAFETY HARDWARE (MASH).




(D) TYPICAL APPLICATION - CLOSING MULTIPLE LANES OF A MULTILANE HIGHWAY.




REINFORCING BAR TABLE PER BARRIER UNIT			
MARK	LOCATION	BAR SIZE	(NO. BARS)
H-1	HORIZONTAL IN BARRIER TIED INSIDE V-1 BARS	#5	(6)
H-2	CENTERED ABOVE DRAIN SLOTS LONG. & TRANSVERSELY	#5	(6)
H-3	TIED ABOVE H-1 BARS TO SUPPORT H-2, TIED TO V-1	#4	(2)
S-1	OVER LIFT HOLES	#4	(2)
S-2	HORIZ. AROUND SLOTS BETWEEN V-1'S & DRAIN SLOTS	#4	(2)
V-1	VERTICAL IN BARRIER (3) EACH END & (2) AT EACH DRAIN SLOTS	#5	(16)



ROADWAY SECTION
 E 4" - CONCRETE PAVEMENT
 8" - ASPHALT PAVEMENT
 12" - SHOULDER AREAS



NOTE: THREADED INSERTS SHALL BE CAST IN PLACE FOR ALL NEW BRIDGE DECKS AND DRILLED AND GROUTED FOR EXISTING BRIDGE DECKS. INSERTS SHALL HAVE A MINIMUM ULTIMATE LOAD CAPACITY OF 8000 LBS. IN TENSION, AFTER REMOVAL OF BARRIER, BOLTS, AND ANGLES, THE INSERTS SHALL BE FILLED WITH APPROVED NON-SHRINK EPOXY.




DATE	REVISION	FILED
8-07-19	REVISED NOTE 3	
2-27-14	REVISED BARRIER STABILIZATION DETAIL	
10-15-09	ADDED REFERENCE TO MASH	
8-5-09	REV. NOTE 3 CONCERNING DRAIN SLOTS	
8-29-07	REVISED NOTE 3	
5-25-06	DELETED GENERAL NOTE 7	
1-18-04	REVISED BARRIER STABILIZATION DETAIL BRIDGE DECKS	
4-10-03	REVISED GENERAL NOTE 2	
8-22-02	ISSUED NEW DRAWING	

- GENERAL NOTES**
- THE CONTRACTOR SHALL FURNISH THE PRECAST CONCRETE BARRIER UNITS AND SHALL BE RESPONSIBLE FOR THE MANUFACTURE, SHIPMENT, STORAGE, PLACEMENT AND REMOVAL. AT THE COMPLETION OF THE PROJECT, THE PRECAST UNITS WILL REMAIN THE PROPERTY OF THE CONTRACTOR.
 - MATERIALS SHALL MEET THE FOLLOWING MINIMUM REQUIREMENTS:
 CONCRETE: 2500 PSI COMPRESSIVE STRENGTH AT 28 DAYS.
 REINFORCING STEEL: AASHTO M 31 OR M 53, GRADE 60
 STRUCTURAL STEEL: AASHTO M270 GRADE 36 SHALL BE USED FOR THE CONNECTION PIN, CONNECTION LOOPS, AND STABILIZATION PINS. A ONE PIECE PIN WITH A 3" ROUNDED TOP MAY BE USED IN PLACE OF THE DETAILED CONNECTION PIN.
 DELINEATORS: DELINEATORS SHALL BE MOUNTED AT 10' SPACING ON TOP OF PRECAST BARRIER.
 - IN APPLICATIONS WHERE BARRIER WALL IS WITHIN 6 FEET OF A TRAFFIC LANE, ADDITIONAL DELINEATORS SHALL BE PLACED ON THE BARRIER AT 10' SPACING APPROXIMATELY ONE (1) FOOT FROM THE TOP OF THE BARRIER. DELINEATORS SHALL BE ON THE AASHTO QUALIFIED PRODUCTS LIST FOR CONSTRUCTION CONCRETE BARRIER MARKERS. DELINEATOR COLOR SHALL BE IN ACCORDANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES. PAYMENT FOR DELINEATORS SHALL BE CONSIDERED INCLUDED IN THE PRICE BID PER LIN. FT. FOR "FURNISHING AND INSTALLING PRECAST CONCRETE BARRIER". THE CONTRACTOR SHALL CERTIFY TO THE ENGINEER THAT THE MATERIAL AND THE DESIGN USED IN THE PRECAST BARRIER UNITS MEETS THE REQUIREMENTS AS SHOWN ON THIS STANDARD DRAWING.
 - OTHER PRECAST CONCRETE BARRIERS THAT HAVE BEEN CRASH TESTED AND APPROVED BY THE FEDERAL HIGHWAY ADMINISTRATION TO MEET THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH) WILL BE ACCEPTED IN LIEU OF THE BARRIER SHOWN. DRAIN SLOTS SHALL BE PROVIDED AS NEEDED OR AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHALL FURNISH A CERTIFICATION OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH) COMPLIANCE FOR ANY OTHER TYPES OF PRECAST BARRIER TO BE USED. THE CERTIFICATION SHALL STATE THAT THE PRECAST CONCRETE BARRIER MEETS THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH). MIXING OF SHAPES WILL NOT BE ALLOWED IN A CONTINUOUS LINE OF UNITS.
 - DOWEL HOLES IN PAVEMENT OR BRIDGE SLABS THAT ARE TO REMAIN IN PLACE SHALL BE FILLED. HOLES IN CONCRETE PAVEMENT AND BRIDGE SLABS SHALL BE FILLED WITH AN APPROVED NON-SHRINK EPOXY GROUT. HOLES IN ASPHALT PAVEMENT SHALL BE FILLED WITH AN APPROVED ASPHALT JOINT FILLER. PAYMENT FOR DRILLING AND FILLING HOLES TO BE INCLUDED IN THE PRICE FOR VARIOUS BARRIER ITEMS.
 - ATTACH UNITS TO ROADWAY SURFACE WITH STABILIZATION PINS AND TO DECK SLABS USING BOLTS WHEN REQUIRED.
 - A 4" WHITE PVC SLEEVE MAY BE USED TO FORM THE LIFTING HOLE AND IF USED THE SLEEVE IS TO BE LEFT IN PLACE.

ARKANSAS STATE HIGHWAY COMMISSION
 STANDARD TRAFFIC CONTROLS
 FOR HIGHWAY CONSTRUCTION -
 TEMPORARY PRECAST BARRIER
 STANDARD DRAWING TC-4


(A) 4 feet or greater preferred. If less than 4 feet, Precast Units shall be connected to slab (SEE BARRIER STABILIZATION DETAIL-BRIDGE DECKS STD. DRWG. TC-4)



BARRIER PLACEMENT ALONG BRIDGE WITH OFFSET


No Scale

** Offset Distance for Two Way Traffic Only



SECTION J-J

No Scale



BARRIER PLACEMENT ALONG ROADWAY WITH OFFSET

No Scale


* Offset Distance (See Table)

** Offset Distance For Two Way Traffic Only

Offset Distance Table

Speed (MPH)	Offset Distance (FT.)
≤ 45	12
> 45	18

If offset distance is not attainable, then see 'Barrier Placement With Attenuator' Detail shown below.




SPECIAL END UNIT

No Scale

General Notes

When shown on the Plans, the ends of the Temporary Precast Concrete Barrier shall be protected with a Manual For Assessing Safety Hardware (MASH) approved Crash Cushion. Payment for Crash Cushions shall be made under the item of "Temporary Impact Attenuation Barrier."



BARRIER PLACEMENT WITH ATTENUATOR

No Scale


***Min. 3'-0" From Edge of Travel Lane to Nearest Edge of Attenuator

** Offset Distance For Two Way Traffic Only

ARKANSAS STATE HIGHWAY COMMISSION		
STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION - TEMPORARY PRECAST BARRIER		
STANDARD DRAWING TC-5		
8-07-19	REVISED NOTE	
10-15-09	ADDED REFERENCE TO MASH	
5-25-06	REVISED BARRIER PLACEMENT	
8-22-02	ISSUED NEW DRAWING	
DATE	REVISION	FILED


GENERAL NOTES

INSTALL A MINIMUM OF 2 UPSLOPE STAKES AND 4 DOWNSLOPE STAKES AT AN ANGLE TO WEDGE WATTLE TO BOTTOM OF DITCH.




WATTLE DITCH CHECK (E-1)

NUMBER OF SAND BAGS AND ARRANGEMENT VARIABLE WITH ON-SITE CONDITIONS. PLACE SAND BAGS AT BASE OF DITCH CHECK IN AREA OF OVERFLOW.




SAND BAG DITCH CHECK (E-5)




ROCK DITCH CHECK (E-6)


GENERAL NOTES
 GEOTEXTILE FABRIC (TYPE 4) IN ACCORDANCE WITH SECTION 625
 GEOTEXTILE FABRIC SHALL BE SPICED TOGETHER WITH A SEWN SEAM ONLY AT A SUPPORT POST OR TWO SECTIONS OF FENCE MAY BE OVERLAPPED INSTEAD. PAYMENT OF ADDITIONAL MATERIAL FOR OVERLAP WILL NOT BE MADE.



SILT FENCE (E-11)




DROP INLET SILT FENCE (E-7)




SILT FENCE ON R/W FENCE (E-4)

GENERAL NOTES
 1. STRAW BALES SHALL BE INSTALLED SO THAT THE BINDINGS ARE ORIENTED AROUND THE SIDES RATHER THAN ALONG THE TOPS AND BOTTOMS OF THE BALES. THE BALES SHALL BE A MINIMUM OF 36 INCHES IN LENGTH.
 2. NO GAPS SHALL BE LEFT BETWEEN BALES.
 3. BALED STRAW FILTER BARRIERS COMPLETED AND ACCEPTED WILL BE MEASURED BY THE BALE IN PLACE AS AUTHORIZED BY THE ENGINEER AND WILL BE PAID FOR AT THE CONTRACT UNIT PRICE BID PER BALE FOR BALED STRAW DITCH CHECKS.




BALED STRAW FILTER BARRIER (E-2)



FILTER SOCK ALONG SLOPE (E-3)

NOTES:
 1. FILTER SOCKS CAN BE PLACED AT THE TOP, ON THE FACE, AND AT THE TOE OF SLOPES AS SEDIMENT-TRAPPING DEVICES FOR SHEET FLOW RUNOFF.
 2. FILTER SOCKS ARE TYPICALLY SUPPLIED AND INSTALLED WITH 18 INCH DIAMETERS. DIAMETER TOLERANCE IS 2 INCHES, AS FILTER SOCKS TEND TO FLATTEN OUT WHEN PLACED.
 3. STEEL POSTS WILL BE USED AND SHALL BE ROLLED FROM HIGH CARBON STEEL AND HAVE A MINIMUM OF 1.25 LB./FT. POSTS SHALL BE HOT-DIPPED GALVANIZED OR PAINTED WITH HIGH-GRADE WEATHER RESISTANT BROWN OR BLACK STEEL PAINT. STEEL POSTS SHALL BE EQUIPPED WITH ANCHOR PLATE HAVING A MINIMUM AREA OF 14 SQUARE INCHES. POSTS SHALL BE STUDDED, EMBOSSED, OR PUNCHED. POSTS AND ANCHOR PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A702. NO ADDITIONAL PAYMENT WILL BE PROVIDED FOR STEEL POSTS, BUT PRICE WILL BE CONSIDERED SUBSIDIARY TO "FILTER SOCK (8\"/>




COMPOST FILTER SOCK DROP INLET PROTECTION (E-13)


NOTES:
 1. OVERLAP ENDS OF SOCK 0\"/>

8-16-17	ADDED FILTER SOCK E-3 AND E-13	
12-15-11	DELETED BALED STRAW DITCH CHECK & ADDED WATTLE DITCH CHECK	
1-18-98	ADDED NOTES	
07-02-98	ADDED BALED STRAW FILTER BARRIER (E-2)	
07-20-95	REVISED SILT FENCE E-4 AND E-11	7-20-95
07-15-94	REV. E-4 & E-11 MIN. 1 1/2\"/>	
06-02-94	REVISED E-1, 4, 7 & 8; DELETED E-2 & 3	6-2-94
04-01-93	REDRAWN	
10-01-92	REDRAWN	
08-02-76	ISSUED R.D.M.	298-7-28-76
DATE	REVISION	FILMED


ARKANSAS STATE HIGHWAY COMMISSION
 TEMPORARY EROSION CONTROL DEVICES
 STANDARD DRAWING TEC-1




SEDIMENT BASIN WITH RIPRAP OUTLET (E-9)




SEDIMENT BASIN WITH PIPE OUTLET (E-10)



DIVERSION DITCH (E-8)



SLOPE DRAIN (E-12)



SEDIMENT BASIN (E-14)

6-2-94	Revised E-8 & E-12; Added E-14 & Deleted E-13		
4-1-93	ISSUED		
DATE	REVISION		FILMED


ARKANSAS STATE HIGHWAY COMMISSION
 TEMPORARY EROSION CONTROL DEVICES
 STANDARD DRAWING TEC-2

CLEARING AND GRUBBING

CONSTRUCTION SEQUENCE

1. PLACE PERIMETER CONTROLS (I.E. SILT FENCES, DIVERSION DITCHES, SEDIMENT BASINS, ETC.)
2. PERFORM CLEARING AND GRUBBING OPERATION.

EXCAVATION



NOTE:
NUMBER OF PHASES WILL VARY.
THREE PHASES SHOWN FOR
ILLUSTRATION.


GENERAL NOTE

ALL CUT SLOPES SHALL BE DRESSED, PREPARED, SEEDED, AND MULCHED AS THE WORK PROGRESSES. SLOPES SHALL BE EXCAVATED AND STABILIZED IN EQUAL INCREMENTS NOT TO EXCEED 25 FEET, MEASURED VERTICALLY.

CONSTRUCTION SEQUENCE

1. EXCAVATE AND STABILIZE INTERCEPTOR AND/OR DIVERSION DITCHES.
2. PERFORM PHASE 1 EXCAVATION. PLACE PERMANENT OR TEMPORARY SEEDING.
3. PERFORM PHASE 2 EXCAVATION. PLACE PERMANENT OR TEMPORARY SEEDING.
4. PERFORM FINAL PHASE OF EXCAVATION. PLACE PERMANENT OR TEMPORARY SEEDING. STABILIZE DITCHES. CONSTRUCT DITCH CHECKS, DIVERSION DITCHES, SEDIMENT BASINS, OR OTHER EROSION CONTROL DEVICES AS REQUIRED.

EMBANKMENT



NOTE:
NUMBER OF PHASES WILL VARY.
THREE PHASES SHOWN FOR
ILLUSTRATION.

GENERAL NOTE

ALL EMBANKMENT SLOPES SHALL BE DRESSED, PREPARED, SEEDED, AND MULCHED AS THE WORK PROGRESSES. SLOPES SHALL BE CONSTRUCTED AND STABILIZED IN EQUAL INCREMENTS NOT TO EXCEED 25 FEET, MEASURED VERTICALLY.

CONSTRUCTION SEQUENCE

1. CONSTRUCT DIVERSION DITCHES, DITCH CHECKS, SEDIMENT BASINS, SILT FENCES, OR OTHER EROSION CONTROL DEVICES AS SPECIFIED.
2. PLACE PHASE 1 EMBANKMENT WITH PERMANENT OR TEMPORARY SEEDING. PROVIDE DIVERSION DITCHES AND SLOPE DRAINS IF EMBANKMENT CONSTRUCTION IS TO BE TEMPORARILY ABANDONED FOR A PERIOD OF GREATER THAN 21 DAYS.
3. PLACE PHASE 2 EMBANKMENT WITH PERMANENT OR TEMPORARY SEEDING. PROVIDE DIVERSION DITCHES AND SLOPE DRAINS IF EMBANKMENT CONSTRUCTION IS TO BE TEMPORARILY ABANDONED FOR A PERIOD OF GREATER THAN 21 DAYS.
4. PLACE FINAL PHASE OF EMBANKMENT WITH PERMANENT OR TEMPORARY SEEDING. PLACE DIVERSION DITCHES AND SLOPE DRAINS AND MAINTAIN UNTIL ENTIRE SLOPE IS STABILIZED.

ARKANSAS STATE HIGHWAY COMMISSION		
TEMPORARY EROSION CONTROL DEVICES		
STANDARD DRAWING TEC-3		
11-03-94	CORRECTED SPELLING	
6-2-94	Drawn & Issued	6-2-94
DATE	REVISION	FILMED