

EVALUATION OF BONDING/POSITIONING OF ELASTOMER  
JOINT SEALERS AND BRIDGE BEARING PADS

by

Ken Benson

Final Report

Highway Research Project TRC - 73

Conducted For

The Arkansas State Highway and Transportation Department

December 1985

EVALUATION OF BONDING/POSITIONING OF ELASTOMER  
JOINT SEALERS AND BRIDGE BEARING PADS

by

Ken Benson

Final Report

Highway Research Project TRC - 73

Conducted For

The Arkansas State Highway and Transportation Department

The opinions, findings, and conclusions are those of the author and not necessarily those of the Arkansas State Highway and Transportation Department.

December 1985

TRC-73 - "Evaluation of Bonding/Positioning of Elastomer Joint Sealers and Bridge Bearing Pads"

FINAL REPORT

Background

Elastomer pre-formed joint sealers and bearing pads have been used extensively by the Department for several years. There have been several cases where the sealers have moved out of position, although an adhesive was applied during placement. Some elastomer bearing pads have also experienced this same problem.

This project was begun as an effort to determine the most cost effective method of maintaining the positioning of pre-formed sealers and bearing pads through the use of better adhesives or mechanical devices or by improving construction techniques.

Literature Search

A thorough search of available literature was made. There are very few published documents which provide any data on this subject. In general, those few reports which were found indicated that if the preformed sealer was the proper size for the joint as-built, no mechanical devices were needed and the required adhesive strength was fairly low. Letter reports from several states indicated that they had experienced no problems with the adhesives used, and that the few problems with preformed joint sealers could be attributed to the sealer being too small for the joint in which it was used. Louisiana does not use an adhesive on bearing pads and Minnesota uses adhesives only in maintenance work; both states reported no problems with maintaining positioning of the sealers or pads.

## Tests and Inspections

Several adhesives were tested in the laboratory in August, September and October of 1981. The all purpose cement, XL-8, from R. H. Products, Inc., had an extremely low bond strength to both concrete and the elastomeric pads. This material appeared to be an ordinary rubber cement.

Of the four epoxy adhesives tested, two showed fair adhesion to the elastomer (Sika shx 370 from Sika Chemical and A-103 from Industrial Coatings). The other two (FX-762 and FX-763 from Fox Industries) showed good adhesion to the elastomer. All four showed excellent adhesion to both concrete and unpainted steel.

The other six adhesives tested (Delastiseal, Neolube, Prima-Lub, Betaseal 32-025 Bon-Lashe, and Scotch-Grip Rubber Adhesive 1300 and 2141) showed generally fair adhesion to the elastomer.

Tests were made in November, 1982, using various adhesives on "cyclized" polymer sealers. "Cyclizing" involves treating the neoprene seals with a paste prepared from silica powder and sulfuric acid. This was supposed to increase the bonding strength; however, the tests did not show any significant difference in bond strength between cyclized and untreated seals.

Several installations where failures had occurred were inspected. In most cases, the pre-formed sealer was narrower than the joint opening.

### Conclusions and Actions Taken

Based on the responses received from other states and the tests and inspections made during this study, it appears that the primary problem has been joints opening wider than the width of the pre-formed sealer. The sealers are not designed to stretch. They are intended to be under compression at all times. When, for whatever reason, the joint opens wider than the sealer, a failure is inevitable. The solution is simply to be sure that the sealer installed is wider than the maximum width to which the joint is expected to open.

No attempt was made to determine the cause of undersized sealers, although several possible explanations were noted. These include the possibility that the wrong size was furnished by the supplier, the joint was built wider than the plans called for, or the plans called for the wrong size.

During the progress of this project, the Bridge Design Division made some modifications in their procedures. Present policy calls for the anchor bolts to be installed through the bearing pads. This procedure keeps the bearing pads in place, without relying on any adhesive. The steel members which make the sides of the joints are required to be blocked at the fabricator's shop to the proper width. This insures that the joint is built at the proper width. They also eliminated the 5" and 6" joint widths, which had been the most likely to develop problems.

These modifications in policy and procedure have reduced the problem this project was intended to solve; therefore, work on this project has stopped and the project will be closed.

The Department is presently working on FHWA Evaluation Project No. 5, which is designed to evaluate the performance of various types of bridge deck joints in use. If the results of this project - or any other reports - indicate that the problem has not been solved, further study will be made.

BOMAG Demonstration Project  
Post Construction Report

Introduction

On July 11, 1985, in a meeting at District 8 headquarters, arrangements were made for a demonstration of a BOMAG machine in a shoulder stabilization. Mr. George Thweatt of Riffe Petroleum Company was the industry representative who was in charge of the demonstration.

The site selected for the demonstration was a section of outside shoulder of the westbound lanes of I-40 near mile marker 119. The Arkansas Highway and Transportation Department core-drilled and obtained samples of the existing shoulder for mix design purposes, and agreed to provide traffic control and purchase the asphalt emulsion to be used. In addition, AHTD would be responsible for sealing the treated shoulder after it was completed.

Mr. Thweatt was to prepare the mix design, furnish all needed equipment, materials, and labor necessary to process approximately 2000 L.F. of the 10' wide shoulder, except for the asphalt emulsion and traffic control.

The basic process involves scarifying the existing material to a specified depth, adding a designed amount of asphalt emulsion, mixing, spreading, shaping, and rolling the material in place. A wearing surface is applied after an appropriate curing period. The curing period can vary from 2 to 14 days, depending on the moisture content of the processed material and the temperature and humidity conditions.

### Existing Site Conditions

The shoulder was originally constructed in the 1960's as a compacted base course (SB-2) with a double bituminous surface treatment (DBST) for a wearing course. Several years ago, this section had been resealed with one additional BST course. Later, portions of the shoulder selected for BOMAG treatment had been patched with an asphalt cold mix and one short section had been repaired with an approximate 1 inch layer of ACHM.

The section which had only the three BST courses was in fair condition. There was some rutting and a few cracks evident and the outer edge was raveling. The area next to the PC slab (within 12-16 inches) was deeply rutted and generally in poor condition.

The areas which had been repaired with cold mix and hot mix were both in poor condition. The entire shoulder had severe random cracking and some mild rutting. The outer edge had only minor raveling. The area within 12-16 inches of the PC slab was rutted to nearly the same depth as the sealed section.

It was decided to process the top 4 inches of approximately 900 L.F. of the sealed section and 900 L.F. of the hot/cold mix patched area. Figure 1 shows the limits of the demonstration project.

Tests run by Riffe Petroleum on the samples obtained for mix design showed 2.5% moisture and a unit weight of 103.7 lb/ft<sup>3</sup>. An extraction analysis yielded a 3.0% AC content. Their test reports and mix design data sheets are included in the Appendix.






Figure 1. BOMAG Demonstration Site near IM 119, I-40

## Mix Design and Construction

Riffe Petroleum's mix design called for the addition of 4.9% SS-1 which had a 62.8% residue. This would be equivalent to an additional 3% AC residue or a total of 6% asphalt in the final mixture. This was based on a consolidated sample which included material from both the sealed section and the hot mix section. For the 4" depth, this called for 2.4 gallons of emulsion added per square yard.

The demonstration was conducted on August 29, 1985. The BOMAG machine processed a non-adjustable width of 6'-7"; therefore, two overlapping passes were required to process the 10-foot width. The first pass was made adjacent to the PC slab, adding 2.4 gallons per square yard of SS-1 at the same time. The loosened material was pulled away from the slab with a motor patrol before the second pass was made, adding SS-1 for the remaining 3'-5" width. Water was added to bring the total moisture content to approximately 10%, then a third pass was made to thoroughly mix the material. The material was windrowed by the motor patrol and a final mixing pass was made.

After mixing the material was spread and shaped to final crown profile and the compaction process began. The first rolling was done by a vibratory sheepsfoot roller, which covered the entire area twice. This was followed by a rubber-tired roller which provided a single coverage of the area. The final rolling was a double coverage with a static steel-wheel roller.

After the final rolling, a fog seal coat of dilute SS-1 was applied to hold the surface while the processed material cured. AHTD maintenance forces applied a single BST approximately two weeks later.

Samples of the processed material were taken from both the seal section and the hot/cold mix patched section. An extraction analysis showed 3.6% AC in the seal section and 5.4% AC in the patched section. The cause of the discrepancy between the actual AC content and the designed 6% AC content has not been determined. Proctor densities were run on samples from both sections, yielding a maximum dry density of 127.1 lb/cf with optimum moisture of 6.4% for the seal section and 125.1 lb/cf at 4.0% for the hot/cold mix section. Test reports are included in the Appendix. No density tests were made of the completed shoulder prior to the final seal coat application.

#### Post-Construction Testing

Nuclear density tests were made on October 17, 1985. The valves obtained included the seal coat, and therefore do not reflect the actual density of the underlying base. The new seal coat was extended beyond the limits of the BOMAG treated area on both ends, and densities were measured in these extended areas. The values obtained showed a slight increase (approximately 3%) in density in the seal section and a slight decrease (approximately 3%) in density in the hot/cold mix section. The test record is included in the Appendix.

On September 24, 1985, the shoulder was tested with the Falling Weight Deflectometer (FWD). The results of these tests showed a marginal increase in strength on the seal section and a slight decrease in the hot/cold mix section. These results correlate directly with the results of the density tests.

## Conclusions

The BOMAG machine does an excellent job of scarifying and mixing a material to a specific depth. The material was broken up into well-graded size particles, with a minimum of oversize chunks.

Nuclear density and FWD tests after construction reflect only a marginal improvement in the area where the existing shoulder was composed of base course and BST courses and a slight decrease in density and strength in those areas where the existing shoulder had been patched/repared with cold mix or ACHM. The changes noted are not significant. The size of differences fall within the limits of precision of the tests performed.

The compaction effort may have been insufficient. No tests were made to determine the degree of compaction obtained; however, the completed shoulder seemed to be soft, based only on a visual inspection of the material as the roller made its final pass. Additional rolling probably would have yielded a significant improvement in both density and strength.

It is too soon to determine whether any improvement has been made with respect to cracking and rutting.

## Cost

The cost of the processing was as follows:

BOMAG Machine	\$0.55	per square yard	
Asphalt Emulsion (SS-1)	1.92	" " "	(2.4 gal/sy)
Rollers & Motor patrol	0.40	" " "	
Total	\$2.87	per square yard	

These costs do not include traffic control nor the cost of sealing the shoulder.

Monitoring

This project will be monitored for one year. Visual inspections will be made, Falling Weight Deflectometer and other tests will be conducted as needed. A final report will be prepared at the end of this period.

A P P E N D I X



Riffe Petroleum Company  
5131 East 68th Street  
P.O. Box 470860  
Tulsa, Oklahoma 74147-0860  
Telephone 918-492-0952  
Telex 79-6087 RIFFE TUL

MEMORANDUM

TO: George Thweatt  
FROM: Bill Porter  
DATE: August 5, 1985  
RE: SS-1 MIX DESIGN OF SHOULDER MATERIAL (SOIL, AGGREGATE AND ASPHALT MIXTURE) FROM MILE MARKER 119 ON I-40 HIGHWAY, ARKANSAS HIGHWAY AND TRANSPORTATION DEPARTMENT. WR 85-195

We ran an extraction on the original material and a gradation on the recovered material. The extraction yielded 3% asphalt residue.

If SS-1 is used on this project we would recommend 4% moisture and 4.9% emulsion which would be equivalent to an additional 3% asphalt residue in the mix. This would mean that the total residue would be 6.0% asphalt in the final mix.

If CMS-2 is used on this project we would recommend 5 - 6% moisture and 4.3% emulsion which would be equivalent to an additional 3% asphalt residue in the mix which is the same as for the SS-1 mix.

The SS-1 coated 90 - 100% as compared with 75 - 80% for the CMS-2. The CMS-2 produced 1570 pound Marshall stability as compared with 1276 pounds stability for the SS-1. There was no difference in the moisture absorbed on the soak test.

All test data please find enclosed.

BP:je

attachment

c: John Huffman  
Bob Johnson  
C. V. Morgan



WR 85-195 **AGGREGATE TEST REPORT**

Type App. Soil-Agg. and asphalt mixture  
 Source mile Marker 119 I-40 (Shoulder Work) AHTD  
 Application Bomag Stabilization

Date Rec'd. 7/19/85  
 Date Sampled \_\_\_\_\_  
 Date Tested 7/22/85-7/23/85

Moisture as Rec'd. (C-566)(T-255) 2.5 %  
 Sand Equivalency (D-241B) 18  
 Agg. Specific Gravity (C-128)(T-84) \_\_\_\_\_  
 Agg. Specific Gravity (C-127)(T-85) \_\_\_\_\_  
 Unit Wt. (C-29)(T-18) 103.7 pcf  
 Moisture/Density (T-99) \_\_\_\_\_ % Opt. Moisture  
 Liquid Limit (T-89) \_\_\_\_\_ %  
 Plasticity Index (T-90) \_\_\_\_\_ %  
 Absorption (T-84, T-85) \_\_\_\_\_ %


Contractor \_\_\_\_\_  
 State Oklahoma County \_\_\_\_\_

ASPHALTIC CONCRETE EXTRACTION (D-2172 Method A)  
 Total Ash, g = G/(V'V'') \_\_\_\_\_  
 G = Ash in solvent tested, \_\_\_\_\_ g  
 V' = Total volume of solvent \_\_\_\_\_  
 V'' = Solvent minus that used for ash \_\_\_\_\_ ml

% Asphalt of dry sample =  $\frac{1144.6 - 110.8 - 338}{1144.6 - 110.8 - 338 + 1.3} \times 100 = 3.0\%$  AC

W' = Wt. of sample 1144.6  
 W'' = Wt. of water in sample 0  
 W''' = Wt. of extracted aggregate 1108.8 + .7 gms in filter  
 W'''' = Wt. of ash in extract 1.3 gms.

% H <sub>2</sub> O	Unit Wt.
A)	
B)	
C)	
D)	



**AGGREGATE BLENDS:**

Sieve Analysis (C-136)(T-27) Dry/washed				No. 1			No. 2			No. 3			No. 4			Total % in Blend	
Sieve	Cum. Wt.	% Retained	% Passing	Specifi-cations	% Pass x Blend	% of Blend	% in Blend	% Pass x Blend	% of Blend	% in Blend	% Pass x Blend	% of Blend	% in Blend	% Pass x Blend	% of Blend		% in Blend
No. 3/4	205.8	18.5	81.5														
No. 1/2	370.2	33.3	66.7														
No. 3/8	449.6	40.5	59.5														
No. 4	605.7	54.5	45.5														
No. 10	720.8	64.9	35.1														
No. 40	824.1	74.2	25.8														
No. 80	918.4	82.7	17.3														
No. 200	992.9	89.4	10.6														
Pan	1110.8																

Mix Design				Marshall stability (T-245) <input checked="" type="checkbox"/> Hveem stability (T-246) _____ Cured at <u>140</u> F for <u>15</u> Hrs. Min. TOTAL										
	Type A.E.	% H <sub>2</sub> O A.E.	Coating	Thick-ness	Factor	Load	Pounds Stability	Flow	Voids	Stability Value	Temp.	% Residue	Bulk Sp. Gr.	% Absorbed
A	SS-1	4-2.4		2 3/8"	1.09	1330.7	1450.5	13			140°F	4.5		
B	✓	4-2.4		2 7/16"	1.09	1135.0	1180.4	7			✓	4.5		
C	✓	4-2.4		2 7/16"	SOAK						✓	4.5	2.238	3.9
D	✓	4-3.2		2 7/16"	1.04	1104.0	1182.2	14			✓	5.0		
E	✓	4-3.2		2 1/2"	1.00	948.9	948.9	8			✓	5.0		
F	✓	4-3.2		2 1/2"	SOAK						✓	5.0	2.111	4.4
G	✓	4-4.0		2 1/2"	1.00	1033.4	1083.9	11			✓	5.5		
H	✓	4-4.0		2 1/2"	1.00	814.0	814.0	7			✓	5.5		
I	✓	4-4.0		2 1/2"	SOAK						✓	5.5	2.113	3.8
J	✓	4-4.9	90-100	2 5/16"	1.14	1000.7	1140.8	7			✓	6.0		
K	✓	4-4.9		2 5/16"	1.14	1233.1	1411.4	10			✓	6.0		
L	✓	4-4.9	✓	2 5/16"	SOAK						✓	6.0	2.196	1.6

Recommendation	Comments:
Type Emulsion - <u>SS-1</u> RES. <u>6.28%</u>	
% Moisture - <u>4.0</u>	
% Emulsion - <u>4.9</u>	
% Residue - <u>6.0 total</u>	

*Handwritten signature or initials*



AGGREGATE TEST REPORT

WR 15-195

Date Rec'd. 7/19/85

Type Agg. Soil - Agg., and Asphalt Mixture  
 Source Mile Marker 119 I-40 (Shoulder Work) AHTD

Date Sampled \_\_\_\_\_  
 Date Tested 7/22/85 - 7/29/85

Application Bonag Stabilization

- Moisture as Rec'd. (C-568)(T-255) \_\_\_\_\_ %
- Sand Equivalency (D-2419) \_\_\_\_\_
- Agg. Specific Gravity (C-128)(T-84) \_\_\_\_\_
- Agg. Specific Gravity (C-127)(T-85) \_\_\_\_\_
- Unit Wt. (C-29)(T-19) \_\_\_\_\_ #/ft. 3
- Moisture/Density (T-89) \_\_\_\_\_ % Opt. Moisture
- Liquid Limit (T-89) \_\_\_\_\_ %
- Plasticity Index (T-89) \_\_\_\_\_ %
- Absorption (T-84, T-85) \_\_\_\_\_ %


Contractor \_\_\_\_\_  
 State Arkansas County \_\_\_\_\_

ASPHALTIC CONCRETE EXTRACTION (D-2172 Method A) \_\_\_\_\_  
 Total Ash, g =  $G(V'/V')$  \_\_\_\_\_  
 G = Ash in solvent tested, \_\_\_\_\_ g  
 V' = Total volume of solvent \_\_\_\_\_  
 V'' = Solvent minus that used for ash \_\_\_\_\_ ml

% Asphalt of dry sample =  $[(W' - W) - (W'' + W''')(W' - W)] \times 100$  3.0% AC.

W' = Wt. of sample \_\_\_\_\_  
 W'' = Wt. of water in sample \_\_\_\_\_  
 W''' = Wt. of extracted aggregate \_\_\_\_\_  
 W'''' = Wt. of ash in extract \_\_\_\_\_

% H <sub>2</sub> O	Unit Wt.
A)	
B)	
C)	
D)	



AGGREGATE BLENDS:

Sieve	Cum. Wt.	% Retained	% Passing	Specifications	No. 1			No. 2			No. 3			No. 4			Total % in Blend
					% Pass	% of Blend	% in Blend	% Pass	% of Blend	% in Blend	% Pass	% of Blend	% in Blend	% Pass	% of Blend	% in Blend	
No.																	
No.																	
No.																	
No.																	
No.																	
No.																	
No.																	
No.																	
Pan																	

Mix Design				<input checked="" type="checkbox"/> Marshal stability (T-245)                    _____ Hveem stability (T-246)                    _____ Cured at 140°F for 15 Hrs. Min.											
Type A.E.	% H <sub>2</sub> O A.E.	Coating	Thick-ness	Factor	Load	Pounds Stability	Flow	Voids	Stability Value	Temp.	% Residue	Bulk Sp. Gr.	% Absorbed		
A	SS-1	4 - 5.6	2 3/8"	1.09	897.0	977.7	10			140°F	6.5				
B	✓	4 - 5.6	2 3/8"	1.09	1083.4	1181.0	13			✓	6.5				
C	✓	4 - 5.6	2 5/8"	SOAK						✓	6.5	2.163	1.2		
D															
E															
F															
G															
H															
I															
J															
K															
L															

Recommendation	Comments:
Type Emulsion - <u>SS-1</u> RES. 62.8%	
% Moisture - <u>4.0</u>	
% Emulsion - <u>4.9</u>	
% Residue - <u>6.0 total</u>	

Tested By: Jim Kealib

RIFFE PETROLEUM, TULSA, OK  
EMULSION ANALYSIS

WR 85-195

Date: 7/30/85

Purpose: OMS-2 for use with RAP on F-40 shoulder in Arkansas using Little Rock formulation.

TYPE:	OMS-2				
Formulation on Total:	0.3% AA-54-100				
(Based on 69% A.C.)	% Hd				
In soap tank →	10% Diesel				
pH	2.5 2V				
Base Asphalt	Ergon 120/150				
Solution Temp. °F(°C)	102				
Asphalt Temp. °F(°C)	270				
Discharge Temp. °F(°C)	171				
Flowmeter Setting	2 1/2				

EMULSION TEST RESULTS (D-244)

Sieve, wt. %					
Residue, wt. %	70.0				
Viscosity @ 77/122°F, SFS					
(E-70)					
Particle Charge					
Settlement _____ days, T					
Settlement _____ days, B					
Cement Mix, wt. %					
Demulsibility _____ ml. wt. %					
Classification Test					
API Gravity @ 60°F(15.6°C)					
Mixes: Aggregate, %H, O, %A.E.					

TESTS ON RESIDUE

Oil in Dist. by Volume (D-244), %					
Penetration (D-5), mm/10					
Float @ 140°F(60°C), (D-139), sec.					
R&B Softening Pt. (D-36), °F					
Residue by Dist. (D-244), wt. %					

Notes and Observations:

Copies to:

Tested by:

AGGREGATE TEST REPORT

WR 85-195

Date Rec'd. 7/19/85

Type Agg. Soil-Agg., and Asphalt Mixture (Extra mat.)

Date Sampled \_\_\_\_\_

Source Mile Marker 119, I-40 (Shoulder Work) AHTD

Date Tested 7/21/85 to 8/2/85

Application Borrow Stabilization

Moisture as Rec'd. (C-566)(T-255) \_\_\_\_\_ %  
 Sand Equivalency (D-2419) \_\_\_\_\_  
 Agg. Specific Gravity (C-128)(T-84) \_\_\_\_\_  
 Agg. Specific Gravity (C-127)(T-85) \_\_\_\_\_  
 Unit Wt. (C-29)(T-19) \_\_\_\_\_ #/ft. 3  
 Moisture/Density (T-99) \_\_\_\_\_ % Opt. Moisture  
 Liquid Limit (T-89) \_\_\_\_\_ %  
 Plasticity Index (T-90) \_\_\_\_\_ %  
 Absorption (T-84, T-85) \_\_\_\_\_ %

Contractor \_\_\_\_\_  
 State Ark. County \_\_\_\_\_

ASPHALTIC CONCRETE EXTRACTION (D-2172 Method A) \_\_\_\_\_

Total Ash, g = G(V/V')

G = Ash in solvent tested, \_\_\_\_\_ g

V' = Total volume of solvent \_\_\_\_\_

V = Solvent minus that used for ash \_\_\_\_\_ ml

% Asphalt of dry sample =  $[(W' - W) - (W' + W) / (W' - W)] \times 100$  3.0% ac


W' = WL of sample \_\_\_\_\_

W = Wt. of water in sample \_\_\_\_\_

W' = Wt. of extracted aggregate \_\_\_\_\_

W = Wt. of ash in extract \_\_\_\_\_

% H <sub>2</sub> O	Unit Wt.
A)	
B)	
C)	
D)	



AGGREGATE BLENDS:

Sieve Analysis (C-136)(T-27) Dry/ washed				No. 1			No. 2			No. 3			No. 4			Total % in Blend
Sieve	Cum. Wt.	% Retained	% Passing	Specifications	% Pass	% of Blend	% in Blend	% Pass	% of Blend	% in Blend	% Pass	% of Blend	% in Blend	% Pass	% of Blend	
No.																
No.																
No.																
No.																
No.																
No.																
No.																
No.																
Pan																

Mix Design

Marshal stability (T-245)  Hveem stability (T-246)  Cured at 140 °F for 15 Hrs. min

	Type A.E.	% H <sub>2</sub> O A.E.	Coating	Thick-ness	Factor x Load	Pounds Stability	Flow	Voids	Stability Value	Temp.	% Residue	Bulk Sp. Gr.	% Absorbed
1)	A	CMS-2	5.5-3.6	2 9/16	1.14	1505.1	1715.8	7		140°F	5.5		
2)	B		5.5-3.6	2 3/8	1.09	1104.0	1223.9	9		140°F	5.5		
3)	C		5.5-3.6	2 5/16							5.5	2. AB	2.3
4)	D		5.5-4.3	75-80	2 1/4	1.19	1330.7	1583.5	6	140°F	6.0		
5)	E		5.5-4.3		2 5/16	1.14	1371.7	1502.7	B	140°F	6.0		
6)	F		5.5-4.3		2 1/4						6.0	2.226	1.7
7)	G		5.5-5.0		2 5/16	1.14	1207.2	1376.2	8	140°F	6.5		
8)	H		5.5-5.0		2 1/4	1.19	1227.8	1461.1	7	140°F	6.5		
9)	I	✓	5.5-5.0		2 5/16						6.5	2.215	1.6
J													
K													
L													

Recommendation Res. 70-0%

Comments:

Type Emulsion - CMS-2

% Moisture - 5-6

% Emulsion - 4.3

% Residue - 6.0 total

ARKANSAS STATE HIGHWAY DEPARTMENT

DIVISION OF MATERIALS AND TESTS

LITTLE ROCK, ARKANSAS

9-4-85  
FOR INFORMATION ONLY

Riffe Petroleum  
(SPECIAL)

STATE JOB NO. \_\_\_\_\_  
REG. No. \_\_\_\_\_ P.O. \_\_\_\_\_  
F.A.P. No. \_\_\_\_\_  
PROJECT NAME \_\_\_\_\_

REPORT OF TESTS OF SS-1 EMULSIFIED ASPHALT

Lab. No. A-85-223 Tank No. \_\_\_\_\_ No. JV8 2 Batch No. \_\_\_\_\_  
Date Sampled 8-29-85 Date Received 8-29-85 Date Tested 8-30-85  
Material Source & Address RIFFE PETROLEUM, LITTLE ROCK, AR  
Quantity Represented \_\_\_\_\_  
Sampled From TANK 6 Submitted by KEN BENSON  
Type Construction BOMAB

AASHTO M-140

TEST RESULTS

SPECIFIC GRAVITY @ _____ °F: _____	ASPHALT CEMENT OR RESIDUE TESTS:
FUROL VISCOSITY @ _____ °F: _____ sec.	Ductility _____ cm
KINEMATIC VISCOSITY @ _____ °F: _____ Cs	Penetration @ 77°F. _____
ABSOLUTE VISCOSITY _____ poises	Penetration @ 32°F. _____
DISTILLATE (% of total distillate to 680°F):	Ash _____ %
to 374°F _____ % to 500°F _____ %	Float _____ sec.
to 437°F _____ % to 600°F _____ %	Flow _____ cm
RESIDUE FROM DISTILLATION TO <u>500</u> °F:	RESIDUE OF 100 PENETRATION _____ %
by volume _____ %	FLASH POINT _____ °F.
by weight <u>61.5</u> %	SOFTENING POINT _____ °F.
THIN-FILM OVEN RESIDUE TESTS:	SIEVE TEST _____ %
Loss on Heating _____ %	COATING TEST: Dry _____ %
Absolute Viscosity _____ poises	Wet _____ %
Ductility _____ cm	PARTICLE CHARGE _____
Penetration (% original) _____ %	MISCIBILITY WITH WATER _____
SOLUBLE IN TRICHLOROETHYLENE _____ %	CEMENT MIXING _____ %
SOLUBLE IN CARBON DISULFIDE _____ %	DEMULSIBILITY _____ %
INSOLUBLE IN BE-NAPHTHA _____ %	SETTLEMENT _____ %
SPOT TEST _____	OIL DISTILLATE _____ %

cc KEN BENSON, RESEARCH ✓

LABORATORY PROCTOR CURVE


Seal Section

JOB No. Research  
 LAB. No. AM-7  
 MATERIAL W. Price Shouder  
 SOURCE Shouder  
 DATE TESTED 9-6-85  
 TESTED BY Mechanica  
 MAX. DEN. 127.1 pcf  
 OPT. MOIST 6.4 %  
 MAX. DEN. (1pt.) \_\_\_\_\_ pcf  
 OPT. MOIST. (1pt.) \_\_\_\_\_ %

SIEVE SIZE	RETAINED, %
2"	
1½"	
1"	
¾"	
⅜"	
No. 4	
No. 10	
No. 40	
No. 80	
No. 200	
L.L.	
P.I.	
Sp.G., + No. 4	

EUGENE DIETZGEN CO.  
MADE IN U. S. A.

NO. 340R-10 DIETZGEN GRAPH PAPER  
10 X 10 PER INCH



weigh & shake 1 full pan  
 over  $\frac{3}{4}$  sieve. Calculate  
 percent retained on  $\frac{3}{4}$  sieve.

COMPACTION WORK SHEET

Job No. Research  
 Lab. No. AM-7  
 Material In Place Shoulder  
 Source Shoulder  
 Date \_\_\_\_\_

8000 gram sample

Factor - 0.0193

Trace  
 H<sub>2</sub>O

Moisture pan number	# 5	# 9	# 9A
Water added - cc	350	500	650
Weight of compacted sample - grams	6835	7022	6904
Wet weight of sample lbs. per Cu.Ft.	131.9	135.5	133.2
Wt. of pan & wet sample	7242	7464	7327
Wt. of pan & dry sample	6902	7014	6772
Water Weight	340	450	555
Wt. of pan & dry sample	6902	7014	6772
Pan weight	409	442	423
Dry weight of sample	6493	6572	6349
Percent moisture	5.2	6.8	8.7
Dry weight of sample-lbs. per Cu.Ft.	125.4	126.9	122.5

Sieve	Gradation	% Retained
2		
1 1/2		
1 1/4		
1		
3/4		
3/8		
4		
10		
40		
200		
LL		
PI		

4.4 / 126.4      6.3 / 127.5      8.1 / 123.3  
 Sample Blend

8000 gms Total sample  
 \_\_\_\_\_ lbs +  $\frac{3}{4}$  → x 11.2 Retained 3/4"  
 \_\_\_\_\_ lbs full pan      896 gms (- 3/4", + # 4)

8000 gms Total sample  
 896 gms (- 3/4" + # 4)  
 7104 gms (- 3/4")

Calculated by as

Checked by \_\_\_\_\_  
 Form MT-57

LABORATORY PROCTOR CURVE

Hof Mix Section.


JOB No. Resenach  
 LAB. No. AM-6  
 MATERIAL In. Above Shoulder  
 SOURCE Shovel  
 DATE TESTED 9-6-85  
 TESTED BY Mechanical  
 MAX. DEN. 125.1 pcf  
 OPT. MOIST 4.0 %  
 MAX. DEN. (1pt.) \_\_\_\_\_ pcf  
 OPT. MOIST. (1pt.) \_\_\_\_\_ %

SIEVE SIZE	RETAINED, %
2"	<i>No. Reg. returned</i>
1 1/2"	
1"	
3/4"	
3/8"	
No. 4	<i>No. Reg. returned</i>
No. 10	
No. 40	
No. 80	
No. 200	
L.L.	
P.I.	
Sp.G., + No. 4	

EUGENE DIETZGEN CO.  
MADE IN U. S. A.

NO. 34DR-10 DIETZGEN GRAPH PAPER  
10 X 10 PER INCH

128  
124  
120  
116  
112  
108



Weigh & shake 1 full pan over 3/4" sieve. Calculate percent retained on 3/4 sieve

Job No. RESEARCH  
 Lab. No. AM-6  
 Material In-Place Shoulder  
 Source Shoulder  
 Date \_\_\_\_\_

COMPACTION WORK SHEET

8000 gram sample

Factor - 0.0193

Slight Trace


Moisture pan number	#10	#17	#19	#1A
Water added - cc	350	500	200	50
Weight of compacted sample - grams	6668	6701	6654	5713
Wet weight of sample lbs. per Cu.Ft.	128.7	129.3	128.5	110.3
Wt. of pan & wet sample	7063	7104	7080	6065
Wt. of pan & dry sample	6753	6701	6853	6003
Water Weight	310	403	227	62
Wt. of pan & dry sample	6753	6701	6853	6003
Pan weight	395	403	424	352
Dry weight of sample	6358	6298	6429	5651
Percent moisture	4.9	6.4	3.5	1.1
Dry weight of sample-lbs. per Cu.Ft.	122.7	121.5	124.2	109.1

Gradation	% Retained
Sieve	
2	
1 1/2	
1 1/4	
1	
3/4	
3/8	
4	
10	
40	
200	
LL	
PI	

4.4 / 123.3      6.3 / 121.7      2.5 / 125.3      .625 / 109.6  
 Sample Blend

8000 gms Total sample  
 16s + 3/4" → Retained 3/4"  
 16s full pan  
 gms (- 3/4", + # 4)

8000 gms Total sample  
8000 gms (- 3/4" + # 4)  
 gms (- 3/4")



Calculated by AS

Checked by \_\_\_\_\_



**Arkansas State Highway and Transportation Department**  
**MATERIALS and RESEARCH DIVISION**  
 Little Rock, Arkansas

*Att. Research*

## Report of Tests of Bituminous Mixtures

Type of Mixture Hot Mix Seal Job No. SPECIAL  
 Bitumen in Mixture \_\_\_\_\_ Federal Aid Proj. No. \_\_\_\_\_  
 Aggregates in Mixture \_\_\_\_\_ Job Name \_\_\_\_\_  
 Submitted By Ken Benson  
 Sampled From Shoulders  
 Date Sampled 8-29-85 Date Received 8-29-85 Date Tested 9-5-85

**EXTRACTION ANALYSIS**

*Hot mix seal*

Laboratory Number	AM 6	AM 7					Specification
Station Number	LM 118.7	LM 119.1					
Location	I90-Shlds.	I90-Shlds.					
Total Ret. on 1 1/2" Sieve	%						
Total Ret. on 1 1/4" Sieve	%						
Total Ret. on 1 1/8" Sieve	%						
Total Ret. on 1" Sieve	%	0	0				
Total Ret. on 3/4" Sieve	%	11.1	1.9				
Total Ret. on 1/2" Sieve	%	18.7	13.5				
Total Ret. on 3/8" Sieve	%	23.7	23.4				
Total Ret. on No. 4 Sieve	%	41.1	43.3				
Total Ret. on No. 10 Sieve	%	55.1	57.5				
Total Ret. on No. 20 Sieve	%						
Total Ret. on No. 40 Sieve	%	69.7	69.4				
Total Ret. on No. 80 Sieve	%	82.4	79.7				
Total Ret. on No. 100 Sieve	%						
Total Ret. on No. 200 Sieve	%	90.3	88.8				
Bitumen	%	5.4	3.6				
Density	%						
Core Thickness							
Plan Qty., lbs. per sq. yd.							

SIEVE ANALYSIS BASED ON WEIGHT OF EXTRACTED AGGREGATE

REMARKS:

ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT  
MATERIALS AND RESEARCH DIVISION

NUCLEAR MOISTURE-DENSITY GAUGE ANALYSIS

JOB NO. \_\_\_\_\_ JOB NAME BOMAG Demonstration

GAUGE NO. \_\_\_\_\_ DENSITY COUNT RATIO RANGE \_\_\_\_\_ MOISTURE STANDARD RANGE \_\_\_\_\_

MATERIAL \_\_\_\_\_ MAX. DENSITY (A) \_\_\_\_\_ Lb/Ft.<sup>3</sup> OPT. MOISTURE \_\_\_\_\_ %

DATE	STATION	LOCATION	LIFT ELEVATION	PROBE DEPTH	DC		RATIO	MOIST. STD. MS	(B) DENSITY DD/WD	MOISTURE % M	[(B) ÷ (A)] X 100 % COMPACTION
					DC	DS					
10/17/85	East of processed section - new seal			4"				124.4	113.1	10.0	
"	ON BOMAG Section - original Seal			4"				128.5	116.4	10.4	
"	"			4"				129.7	117.2	10.7	
"	ON BOMAG Section - patched w/ cold mix / ACHM			4"				129.3	116.6	10.8	
"	"			4"				127.8	116.1	10.1	
"	West of processed section - on new seal over patched			4"				129.7	121.3	7.0	

