

Dampproofing and Membrane Waterproofing Materials

Asphalt For Mopping Above Ground

Supplier	Brand
-----------------	--------------

None Approved	
---------------	--

Asphalt For Mopping Below Ground

Supplier	Brand
-----------------	--------------

None Approved	
---------------	--

	NA
--	----

Asphalt Treated Cotton Fabric (ASTM D 173)

Supplier	Brand
-----------------	--------------

Brewer Company - Wickliffe Division Wickliffe, OH	
--	--

	Fortress 9400
--	---------------

	Identified by 94###, last three numbers are roll width and length codes.
--	--

Asphalt Treated Felt - ASTM D 226 - Type I - 15lb

Supplier	Brand
-----------------	--------------

Tarco North Little Rock, AR	
--------------------------------	--

	15 ASTM
--	---------

Asphalt Treated Felt (ASTM D 226 - Type II)

Supplier	Brand
-----------------	--------------

Tarco North Little Rock, AR	
--------------------------------	--

	30 ASTM
--	---------

Dampproofing and Membrane Waterproofing Materials

Other Approved Types

Supplier	Brand
W.R. Meadows, Inc. Hampshire, IL	Trowel-Mastic

Type C Polyethylene Laminated Asphalt Mastic Material

Supplier	Brand
Concrete Sealants, Inc. Tipp City, OH	ConSeal CS-212 (membrane)
GCP Applied Technologies Cambridge, MA	Bituthene 3000 Membrane Bituthene 4000 Membrane Bituthene Low Temperature Membrane
Polyguard Products Inc. Ennis, TX	Polyguard 650 (membrane)
W.R. Meadows, Inc. Hampshire, IL	Mel-Rol Waterproofing Membrane

Type D One-Part, Cold-Applied, Asphalt Modified Polyurethanes

Supplier	Brand
Carlisle Coatings & Waterproofing, Inc. Wylie, TX	CCW-525 V
Sonneborn / ChemRex, Inc. Shakopee, MN	HLM 5000 T

For Type C Polyethylene Laminated Asphalt Mastic Material, primer and mastic used shall be as specified by the manufacturer of the approved waterproofing membrane.

Dampproofing and Membrane Waterproofing Materials

Method of Documentation of Acceptance:

By brand and Source

Method of Approval:

- Suppliers/Manufacturers shall provide to the Materials Division the Manufacturer's certification for each material stating compliance with the appropriate stated specification and certifying that all materials supplied to Department projects will comply with the appropriate specifications.
- Sample(s), 3' by roll width, along with product literature shall be submitted to Materials Division for verification testing.
- When deemed necessary by the Materials Engineer and at a frequency determined by same, samples shall be taken and tested on a random basis on materials from each manufacturer.
- Material failure of random samples will be considered sufficient reason to discontinue acceptance of a material from a manufacturer by the Materials Engineer.

No information contained in these lists is to be used for promotional purposes.

The manufacturer of privately labeled products must be disclosed.