

## Retroreflectors for Plowable Pavement Markers

### Plowable Pavement Marker Retroreflectors

Supplier	Brand
3M St. Paul, MN	3M Series 190
Ennis-Flint, Inc. Thomasville, NC	Model 944 Stimsonite C40
Ray-O-Lite Division - PAC-TEC, Inc. Newark, OH	Ray-O-Lite 2004

#### Method of Documentation of Acceptance:

By brand and source.

#### Method of Approval:

- Prismatic retroreflectors for plowable pavement markers shall comply with the properties of Section 721. The plowable pavement marker retroreflectors must be standard size, nominal 2" x 4", and must be evaluated by the National Transportation Product Evaluation Program (NTPEP) as a Raised Pavement Marker. Approval will be based on NTPEP performance. NTPEP laboratory and final field results must be furnished to the Department. All reports shall include the manufacturer's name, address, and product name of the raised pavement markers.
- The manufacturer shall submit samples and product information, including printed instructions for application and safety data sheets.
- Destination samples will be taken as deemed necessary by the Materials Engineer to assure compliance with specifications.
- Failure of these samples either in the laboratory or in field applications is sufficient reason to reconsider acceptance of the material. Suspension of further use and/or removal from the QPL may occur until the Materials Engineer determines that the product is in compliance with applicable specifications and requirements.

No information contained in these lists is to be used for promotional purposes.

## **Retroreflectors for Plowable Pavement Markers**

**The manufacturer of privately labeled products must be disclosed.**